




FL112/DX.48V G5 19W T927

White LED strips



LIGHT TYPE	White
LED Qty	112 LEDs/m
CCT	2700K
CRI	CRI90
COLOR CONSISTENCY	3-Step MacAdam
PHOTOMETRIC	120° beam angle
LUMINOUS FLUX	2598 Lm/m (792 Lm/ft)
EFFICACY	135 Lm/W
LIFETIME	L70B10 > 50.000h
CONTROL	Dimmable
VOLTAGE	48 VDC
WATTAGE	19.2 W/m (5.85 W/ft)
CUTTING STEP	12,5 cm (4,92 in)
MAX RUN	11 m (36.1 ft)
PACKING	10 m, 50 m or customized length per reel
DIMENSIONS	Width: 8mm; Height: 1.58mm
TEMPERATURE	Tc max 75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)
STORAGE TEMP.	-25°C...+80°C (-13°F...176°F)

CE

ETL

MADE IN EUROPE

5 YEAR WARRANTY

3 STEP MACADAM

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.