



FL112/NX G5 09W T950

White LED strips



LIGHT TYPE	White
LED Qty	112 LEDs/m
CCT	5000K
CRI	CRI90
COLOR CONSISTENCY	3-Step MacAdam
PHOTOMETRIC	120° beam angle
LUMINOUS FLUX	1524 Lm/m (465 Lm/ft)
EFFICACY	159 Lm/W
LIFETIME	L90B10 > 60.000h
CONTROL	Dimmable
VOLTAGE	24 VDC
WATTAGE	9.6 W/m (2.93 W/ft)
CUTTING STEP	6,25 cm (2,46 in)
MAX RUN	9 m (29.5 ft)
PACKING	10 m, 50 m or customized length per reel
DIMENSIONS	Width: 8mm; Height: 1.62mm
TEMPERATURE	Tc max 75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)
STORAGE TEMP.	-25°C...+80°C (-13°F...176°F)

CE

ETL

MADE IN EUROPE

5 YEAR WARRANTY

3 STEP MACADAM

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.