



FL112S/NX G5 04W T965

White LED strips



|                   |                      |
|-------------------|----------------------|
| LIGHT TYPE        | White                |
| LED Qty           | 112 LEDs/m           |
| CCT               | 6500K                |
| CRI               | CRI90                |
| COLOR CONSISTENCY | 3-Step MacAdam       |
| PHOTOMETRIC       | 120° beam angle      |
| LUMINOUS FLUX     | 741 Lm/m (226 Lm/ft) |
| EFFICACY          | 154 Lm/W             |
| LIFETIME          | L90B10 > 60.000h     |

|         |          |
|---------|----------|
| CONTROL | Dimmable |
|---------|----------|

|         |                     |
|---------|---------------------|
| VOLTAGE | 24 VDC              |
| WATTAGE | 4.8 W/m (1.46 W/ft) |

|              |                                          |
|--------------|------------------------------------------|
| CUTTING STEP | 6,25 cm (2,46 in)                        |
| MAX RUN      | 13 m (42.7 ft)                           |
| PACKING      | 10 m, 50 m or customized length per reel |
| DIMENSIONS   | Width: 5mm; Height: 1.33mm               |

|                 |                                 |
|-----------------|---------------------------------|
| TEMPERATURE     | Tc max 75°C ( 167°F )           |
| OPERATING TEMP. | -25°C...+50°C ( -13°F...122°F ) |
| STORAGE TEMP.   | -25°C...+80°C ( -13°F...176°F ) |



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.