



FL112S/NX G5 19W 925

White LED strips



LIGHT TYPE	White
LED Qty	112 LEDs/m
CCT	2500K
CRI	CRI90
COLOR CONSISTENCY	3-Step MacAdam
PHOTOMETRIC	120° beam angle
LUMINOUS FLUX	1921 Lm/m (586 Lm/ft)
EFFICACY	100 Lm/W
LIFETIME	L90B10 > 60.000h

CONTROL	Dimmable
---------	----------

VOLTAGE	24 VDC
WATTAGE	19.2 W/m (5.85 W/ft)

CUTTING STEP	6,25 cm (2,46 in)
MAX RUN	5.5 m (18 ft)
PACKING	10 m, 50 m or customized length per reel
DIMENSIONS	Width: 5mm; Height: 1.33mm

TEMPERATURE	Tc max 75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)
STORAGE TEMP.	-25°C...+80°C (-13°F...176°F)

MADE IN EUROPE5 YEAR WARRANTY3 STEP MACADAM

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.