



FL175/NX G5 14W P50

White LED strips



|                   |                                          |
|-------------------|------------------------------------------|
| LIGHT TYPE        | White                                    |
| LED Qty           | 175 LEDs/m                               |
| CCT               | 5000K                                    |
| CRI               | Optisolis                                |
| COLOR CONSISTENCY | 3-Step MacAdam                           |
| PHOTOMETRIC       | 120° beam angle                          |
| LUMINOUS FLUX     | 1326 Lm/m (404 Lm/ft)                    |
| EFFICACY          | 92 Lm/W                                  |
| LIFETIME          | L90B10 > 60.000h                         |
| CONTROL           | Dimmable                                 |
| VOLTAGE           | 24 VDC                                   |
| WATTAGE           | 14.4 W/m (4.39 W/ft)                     |
| CUTTING STEP      | 4 cm (1,57 in)                           |
| MAX RUN           | 1.5 m (4.9 ft)                           |
| PACKING           | 10 m, 50 m or customized length per reel |
| DIMENSIONS        | Width: 5mm; Height: 1.8mm                |
| TEMPERATURE       | Tc max 75°C ( 167°F )                    |
| OPERATING TEMP.   | -25°C...+50°C ( -13°F...122°F )          |
| STORAGE TEMP.     | -25°C...+80°C ( -13°F...176°F )          |



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.