



Inground Radius - R0000

Outdoor

IngroundR E EOP H100 R0000 L0505 / RGB48/Nx G5 11W RGB_RGB_ / OR.T1x

CCT	RGB
CRI	RGB
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 110 Lm (R: 24, G: 71, B: 16 Lm) Light Source: 240 Lm (R: 52, G: 154, B: 35 Lm)
EFFICACY	Luminaire: 19 Lm/W Light Source: 42 Lm/W
LIFETIME	L90B10 > 60.000h
VOLTAGE	24VDC
LUMINAIRE POWER	5.75 W
CONTROL	Dimmable
COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10
DIMENSIONS	Height: 102 mm (4 in) Radius: R0000 mm Length: L0505 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
SEGMENT	End Endcap at the end only Input connector only, no output wire



Product Code Explanation

IngroundR E EOP H100 R0000 L0505 / RGB48/Nx G5 11W RGB_RGB_ / OR.T1x

E	End	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R0000	R0000, mm	Radius, mm
L0505	L0505, mm	Length, mm
RGB48/Nx	RGB48/Nx	LED strip model
G5	G5	LED strip generation
11W	11W (rounded)	Wattage, W/m
RGB_	RGB_	CRI
RGB_	RGB_	CCT

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.