



Inground Radius - R6100

Outdoor

IngroundR E EOP H100 R6100 L0382 / RGB48/Nx G5 11W RGB\_RGB\_ / OR.T1x

|                   |                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| CCT               | RGB                                                                                                                                   |
| CRI               | RGB                                                                                                                                   |
| COLOR CONSISTENCY | 3-Step MacAdam                                                                                                                        |
| LUMINOUS FLUX     | Luminaire: 83 Lm ( R: 18, G: 53, B: 12 Lm )<br>Light Source: 180 Lm ( R: 39, G: 115, B: 26 Lm )                                       |
| EFFICACY          | Luminaire: 19 Lm/W<br>Light Source: 42 Lm/W                                                                                           |
| LIFETIME          | L90B10 > 60.000h                                                                                                                      |
| VOLTAGE           | 24VDC                                                                                                                                 |
| LUMINAIRE POWER   | 4.3125 W                                                                                                                              |
| CONTROL           | Dimmable                                                                                                                              |
| COVER             | Opal Encapsulation ( EOP )                                                                                                            |
| HOUSING           | Stainless Steel ( Marine Grande 316L )                                                                                                |
| IP CLASS          | IP67                                                                                                                                  |
| IK RATE           | IK10                                                                                                                                  |
| DIMENSIONS        | Height: 102 mm ( 4 in )<br>Radius: R6100 mm<br>Length: L0382 mm<br>Width: 33 mm ( 1,3 in ) Light Area<br>Width: 73 mm ( 2,9 in ) Base |
| SEGMENT           | End<br>Endcap at the end only<br>Input connector only, no output wire                                                                 |



# Product Code Explanation

---

IngroundR E EOP H100 R6100 L0382 / RGB48/Nx G5 11W RGB\_RGB\_ / OR.T1x

|          |                    |                      |
|----------|--------------------|----------------------|
| E        | End                | Segment type         |
| EOP      | Opal Encapsulation | Cover type           |
| H100     | 102 mm             | Height, mm           |
| R6100    | R6100, mm          | Radius, mm           |
| L0382    | L0382, mm          | Length, mm           |
| RGB48/Nx | RGB48/Nx           | LED strip model      |
| G5       | G5                 | LED strip generation |
| 11W      | 11W (rounded)      | Wattage, W/m         |
| RGB_     | RGB_               | CRI                  |
| RGB_     | RGB_               | CCT                  |

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.