





Inground Radius - R2950

Outdoor

IngroundR | EOP H100 R2950 L0384 / RGB48/Nx G5 11W RGB_RGB_ / OR.T1x



CCT	RGB
CRI	RGB
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 83 Lm (R: 18, G: 53, B: 12 Lm) Light Source: 180 Lm (R: 39, G: 115, B: 26 Lm)
EFFICACY	Luminaire: 19 Lm/W Light Source: 42 Lm/W
LIFETIME	L90B10 > 60.000h
VOLTAGE	24VDC
LUMINAIRE POWER	4.3125 W
CONTROL	Dimmable
COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10
DIMENSIONS	Height: 102 mm (4 in) Radius: R2950 mm Length: L0384 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
SEGMENT	Individual Endcaps on both ends Input connector only, no output wire



Product Code Explanation

IngroundR I EOP H100 R2950 L0384 / RGB48/Nx G5 11W RGB_RGB_ / OR.T1x

I	Individual	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R2950	R2950, mm	Radius, mm
L0384	L0384, mm	Length, mm
RGB48/Nx	RGB48/Nx	LED strip model
G5	G5	LED strip generation
11W	11W (rounded)	Wattage, W/m
RGB_	RGB_	CRI
RGB_	RGB_	CCT

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.