



Inground Radius - R0272

Outdoor

IngroundR E EOP H100 R0272 L0404 / RGBW48/NN G5 09W RGB_RGB_T940 / OR.T1x




CCT	RGB + 4000K
CRI	RGB + CRI90 (White)
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 111 Lm (R: 11, G: 36, B: 7, W: 57 Lm) Light Source: 242 Lm (R: 24, G: 78, B: 16, W: 123 Lm)
EFFICACY	Luminaire: 31 Lm/W Light Source: 67 Lm/W
LIFETIME	L90B10 > 60.000h

VOLTAGE	24VDC
LUMINAIRE POWER	3.6 W
CONTROL	Dimmable

COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10

DIMENSIONS	Height: 102 mm (4 in) Radius: R0272 mm Length: L0404 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
------------	---

SEGMENT	End Endcap at the end only Input connector only, no output wire
---------	---



Product Code Explanation

IngroundR E EOP H100 R0272 L0404 / RGBW48/NN G5 09W RGB_RGB_T940 / OR.T1x

E	End	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R0272	R0272, mm	Radius, mm
L0404	L0404, mm	Length, mm
RGBW48/NN	RGBW48/NN	LED strip model
G5	G5	LED strip generation
09W	09W (rounded)	Wattage, W/m
RGB_	RGB_	LED 1 CRI
RGB_	RGB_	LED 1 CCT
T9	CRI90	LED 2 CRI
40	4000K	LED 2 CCT