




Inground Radius - R0000

Outdoor

IngroundR S EOP H100 R0000 L0505 / RGBW48/NN G5 09W RGB_RGB_922 / OR.T1x

CCT	RGB + 2200K
CRI	RGB + CRI90 (White)
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 118 Lm (R: 15, G: 48, B: 10, W: 45 Lm) Light Source: 257 Lm (R: 33, G: 104, B: 22, W: 99 Lm)
EFFICACY	Luminaire: 25 Lm/W Light Source: 53 Lm/W
LIFETIME	L90B10 > 60.000h
VOLTAGE	24VDC
LUMINAIRE POWER	4.8 W
CONTROL	Dimmable
COVER	Opal Encapsulation (EOP)
HOUSING	Stainless Steel (Marine Grande 316L)
IP CLASS	IP67
IK RATE	IK10
DIMENSIONS	Height: 102 mm (4 in) Radius: R0000 mm Length: L0505 mm Width: 33 mm (1,3 in) Light Area Width: 73 mm (2,9 in) Base
SEGMENT	Start Endcaps at the start only Input connector and output wire



Product Code Explanation

IngroundR S EOP H100 R0000 L0505 / RGBW48/NN G5 09W RGB_RGB_922 / OR.T1x

S	Start	Segment type
EOP	Opal Encapsulation	Cover type
H100	102 mm	Height, mm
R0000	R0000, mm	Radius, mm
L0505	L0505, mm	Length, mm
RGBW48/NN	RGBW48/NN	LED strip model
G5	G5	LED strip generation
09W	09W (rounded)	Wattage, W/m
RGB_	RGB_	LED 1 CRI
RGB_	RGB_	LED 1 CCT
9	CRI90	LED 2 CRI
22	2200K	LED 2 CCT