NetApp

Configure software
Cluster and storage switches

NetApp
January 19, 2024

Table of Contents

Configure software

Software install workflow for Cisco Nexus 9336C-FX2 storage switches

To install and configure software for a Cisco Nexus 9336C-FX2 switch, follow these steps:

1. Prepare to install NX-OS and RCF.
2. Install the NX-OS software.
3. Install the RCF config file.

   Install the RCF after setting up the Nexus 9336C-FX2 switch for the first time. You can also use this procedure to upgrade your RCF version.

Prepare to install NX-OS software and RCF

Before you install the NX-OS software and the Reference Configuration File (RCF), follow this procedure.

About the examples

The examples in this procedure use the following switch and node nomenclature:

- The names of the two Cisco switches are cs1 and cs2.
- The node names are cluster1-01 and cluster1-02.
- The cluster LIF names are cluster1-01_clus1 and cluster1-01_clus2 for cluster1-01 and cluster1-02_clus1 and cluster1-02_clus2 for cluster1-02.
- The `cluster1::*>` prompt indicates the name of the cluster.

About this task

The procedure requires the use of both ONTAP commands and Cisco Nexus 9000 Series Switches commands; ONTAP commands are used unless otherwise indicated.

Steps

1. If AutoSupport is enabled on this cluster, suppress automatic case creation by invoking an AutoSupport message: `system node autosupport invoke -node * -type all -message MAINT=x h`

   where x is the duration of the maintenance window in hours.

   > (i) The AutoSupport message notifies technical support of this maintenance task so that automatic case creation is suppressed during the maintenance window.

2. Change the privilege level to advanced, entering **y** when prompted to continue:

   ```
   set -privilege advanced
   ```

   The advanced prompt (`*>`) appears.

3. Display how many cluster interconnect interfaces are configured in each node for each cluster interconnect switch:

```
network device-discovery show -protocol cdp
```

Show example

```
cluster1::*> network device-discovery show -protocol cdp

Node/        Local  Discovered
Protocol     Port   Device (LLDP: ChassisID)  Interface
Platform
-----------  ------ ------------------------- ------------------
--------
cluster1-02/cdp
             e0a    cs1                            Eth1/2          N9K-
C9336C
             e0b    cs2                            Eth1/2          N9K-
C9336C
cluster1-01/cdp
             e0a    cs1                            Eth1/1          N9K-
C9336C
             e0b    cs2                            Eth1/1          N9K-
C9336C

4 entries were displayed.
```

4. Check the administrative or operational status of each cluster interface.

   a. Display the network port attributes:

   ```
   `network port show –ipspace Cluster`
   ```

Show example

```
cluster1::*> network port show -ipspace Cluster

Node: cluster1-02
                                         Speed(Mbps)
Health
Port      IPspace       Broadcast Domain Link MTU  Admin/Oper
Status
--------- ------------- ---------------- ---- ---- -----------
------
e0a       Cluster       Cluster          up   9000 auto/10000
healthy
e0b       Cluster       Cluster          up   9000 auto/10000
healthy

Node: cluster1-01
                                         Speed(Mbps)
Health
Port      IPspace       Broadcast Domain Link MTU  Admin/Oper
Status
--------- ------------- ---------------- ---- ---- -----------
------
e0a       Cluster       Cluster          up   9000 auto/10000
healthy
e0b       Cluster       Cluster          up   9000 auto/10000
healthy

4 entries were displayed.
```

b. Display information about the LIFs:

```
network interface show -vserver Cluster
```

Show example

```
cluster1::*> network interface show -vserver Cluster

          Logical              Status     Network
Current        Current Is
Vserver     Interface          Admin/Oper Address/Mask        Node
Port    Home
----------- ------------------ ---------- ------------------
------------- ------- ----
Cluster
          cluster1-01_clus1  up/up      169.254.209.69/16
cluster1-01   e0a      true
          cluster1-01_clus2  up/up      169.254.49.125/16
cluster1-01   e0b      true
          cluster1-02_clus1  up/up      169.254.47.194/16
cluster1-02   e0a      true
          cluster1-02_clus2  up/up      169.254.19.183/16
cluster1-02   e0b      true

4 entries were displayed.
```

5. Ping the remote cluster LIFs:

   ```
   cluster ping-cluster -node node-name
   ```

Show example

```
cluster1::*> cluster ping-cluster -node cluster1-02
Host is cluster1-02
Getting addresses from network interface table...
Cluster cluster1-01_clus1 169.254.209.69 cluster1-01     e0a
Cluster cluster1-01_clus2 169.254.49.125 cluster1-01     e0b
Cluster cluster1-02_clus1 169.254.47.194 cluster1-02     e0a
Cluster cluster1-02_clus2 169.254.19.183 cluster1-02     e0b
Local = 169.254.47.194 169.254.19.183
Remote = 169.254.209.69 169.254.49.125
Cluster Vserver Id = 4294967293
Ping status:

Basic connectivity succeeds on 4 path(s)
Basic connectivity fails on 0 path(s)

Detected 9000 byte MTU on 4 path(s):
    Local 169.254.19.183 to Remote 169.254.209.69
    Local 169.254.19.183 to Remote 169.254.49.125
    Local 169.254.47.194 to Remote 169.254.209.69
    Local 169.254.47.194 to Remote 169.254.49.125
Larger than PMTU communication succeeds on 4 path(s)
RPC status:
2 paths up, 0 paths down (tcp check)
2 paths up, 0 paths down (udp check)
```

6. Verify that the auto-revert command is enabled on all cluster LIFs:

```
network interface show -vserver Cluster -fields auto-revert
```

Show example

```
cluster1::*> network interface show -vserver Cluster -fields auto-
revert

          Logical
Vserver   Interface           Auto-revert
--------- ------------------- ------------
Cluster
          cluster1-01_clus1   true
          cluster1-01_clus2   true
          cluster1-02_clus1   true
          cluster1-02_clus2   true
4 entries were displayed.
```

7. For ONTAP 9.8 and later, enable the Ethernet switch health monitor log collection feature for collecting switch-related log files, using the commands:

`system switch ethernet log setup-password` and `system switch ethernet log enable-collection`

Show example

```
cluster1::*> system switch ethernet log setup-password
Enter the switch name: <return>
The switch name entered is not recognized.
Choose from the following list:
cs1
cs2

cluster1::*> system switch ethernet log setup-password

Enter the switch name: cs1
RSA key fingerprint is
e5:8b:c6:dc:e2:18:18:09:36:63:d9:63:dd:03:d9:cc
Do you want to continue? {y|n}::[n] y

Enter the password: <enter switch password>
Enter the password again: <enter switch password>

cluster1::*> system switch ethernet log setup-password

Enter the switch name: cs2
RSA key fingerprint is
57:49:86:a1:b9:80:6a:61:9a:86:8e:3c:e3:b7:1f:b1
Do you want to continue? {y|n}:: [n] y

Enter the password: <enter switch password>
Enter the password again: <enter switch password>

cluster1::*> system  switch ethernet log enable-collection

Do you want to enable cluster log collection for all nodes in the
cluster?
{y|n}: [n] y

Enabling cluster switch log collection.

cluster1::*>
```

ⓘ   If any of these commands return an error, contact NetApp support.

8. For ONTAP releases 9.5P16, 9.6P12, and 9.7P10 and later patch releases, enable the Ethernet switch health monitor log collection feature for collecting switch-related log files, using the commands:

`system cluster-switch log setup-password` and `system cluster-switch log enable-`

```
collection
```

Show example

```
cluster1::*> system cluster-switch log setup-password
Enter the switch name: <return>
The switch name entered is not recognized.
Choose from the following list:
cs1
cs2

cluster1::*> system cluster-switch log setup-password

Enter the switch name: cs1
RSA key fingerprint is
e5:8b:c6:dc:e2:18:18:09:36:63:d9:63:dd:03:d9:cc
Do you want to continue? {y|n}::[n] y

Enter the password: <enter switch password>
Enter the password again: <enter switch password>

cluster1::*> system cluster-switch log setup-password

Enter the switch name: cs2
RSA key fingerprint is
57:49:86:a1:b9:80:6a:61:9a:86:8e:3c:e3:b7:1f:b1
Do you want to continue? {y|n}:: [n] y

Enter the password: <enter switch password>
Enter the password again: <enter switch password>

cluster1::*> system cluster-switch log enable-collection

Do you want to enable cluster log collection for all nodes in the
cluster?
{y|n}: [n] y

Enabling cluster switch log collection.

cluster1::*>
```

ⓘ   If any of these commands return an error, contact NetApp support.

What's next?

Install the NX-OS software

Follow this procedure to install the NX-OS software on the Nexus 9336C-FX2 cluster switch.

Before you begin, complete the procedure in Prepare to install NX-OS and RCF.

Review requirements

What you'll need

- A current backup of the switch configuration.
- A fully functioning cluster (no errors in the logs or similar issues).
- Cisco Ethernet switch page. Consult the switch compatibility table for the supported ONTAP and NX-OS versions.
- Appropriate software and upgrade guides available on the Cisco web site for the Cisco switch upgrade and downgrade procedures. See Cisco Nexus 9000 Series Switches.

About the examples

The examples in this procedure use the following switch and node nomenclature:

- The names of the two Cisco switches are cs1 and cs2.
- The node names are cluster1-01, cluster1-02, cluster1-03, and cluster1-04.
- The cluster LIF names are cluster1-01_clus1, cluster1-01_clus2, cluster1-02_clus1, cluster1-02_clus2 , cluster1-03_clus1, cluster1-03_clus2, cluster1-04_clus1, and cluster1-04_clus2.
- The `cluster1::*>` prompt indicates the name of the cluster.

Install the software

The procedure requires the use of both ONTAP commands and Cisco Nexus 9000 Series Switches commands; ONTAP commands are used unless otherwise indicated.

Steps

1. Connect the cluster switch to the management network.
2. Use the ping command to verify connectivity to the server hosting the NX-OS software and the RCF.

   Show example

   This example verifies that the switch can reach the server at IP address 172.19.2.1:

   ```
   cs2# ping 172.19.2.1
   Pinging 172.19.2.1 with 0 bytes of data:

   Reply From 172.19.2.1: icmp_seq = 0. time= 5910 usec.
   ```

3. Copy the NX-OS software and EPLD images to the Nexus 9336C-FX2 switch.

Show example

```
cs2# copy sftp: bootflash: vrf management
Enter source filename: /code/nxos.9.3.5.bin
Enter hostname for the sftp server: 172.19.2.1
Enter username: user1

Outbound-ReKey for 172.19.2.1:22
Inbound-ReKey for 172.19.2.1:22
user1@172.19.2.1's password:
sftp> progress
Progress meter enabled
sftp> get   /code/nxos.9.3.5.bin  /bootflash/nxos.9.3.5.bin
/code/nxos.9.3.5.bin  100% 1261MB    9.3MB/s    02:15
sftp> exit
Copy complete, now saving to disk (please wait)...
Copy complete.


cs2# copy sftp: bootflash: vrf management

Enter source filename: /code/n9000-epld.9.3.5.img
Enter hostname for the sftp server: 172.19.2.1
Enter username: user1

Outbound-ReKey for 172.19.2.1:22
Inbound-ReKey for 172.19.2.1:22
user1@172.19.2.1's password:
sftp> progress
Progress meter enabled
sftp> get   /code/n9000-epld.9.3.5.img  /bootflash/n9000-
epld.9.3.5.img
/code/n9000-epld.9.3.5.img  100%  161MB    9.5MB/s    00:16
sftp> exit
Copy complete, now saving to disk (please wait)...
Copy complete.
```

4. Verify the running version of the NX-OS software:

```
show version
```

Show example

```
cs2# show version
Cisco Nexus Operating System (NX-OS) Software
TAC support: http://www.cisco.com/tac
Copyright (C) 2002-2020, Cisco and/or its affiliates.
All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under their
own
licenses, such as open source.  This software is provided "as is,"
and unless
otherwise stated, there is no warranty, express or implied,
including but not
limited to warranties of merchantability and fitness for a
particular purpose.
Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or
GNU General Public License (GPL) version 3.0  or the GNU
Lesser General Public License (LGPL) Version 2.1 or
Lesser General Public License (LGPL) Version 2.0.
A copy of each such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://opensource.org/licenses/gpl-3.0.html and
http://www.opensource.org/licenses/lgpl-2.1.php and
http://www.gnu.org/licenses/old-licenses/library.txt.

Software
  BIOS: version 08.38
  NXOS: version 9.3(4)
  BIOS compile time:  05/29/2020
  NXOS image file is: bootflash:///nxos.9.3.4.bin
  NXOS compile time:  4/28/2020 21:00:00 [04/29/2020 02:28:31]


Hardware
  cisco Nexus9000 C9336C-FX2 Chassis
  Intel(R) Xeon(R) CPU E5-2403 v2 @ 1.80GHz with 8154432 kB of
memory.
  Processor Board ID FOC20291J6K

  Device name: cs2
  bootflash:   53298520 kB
Kernel uptime is 0 day(s), 0 hour(s), 3 minute(s), 42 second(s)
```

```
Last reset at 157524 usecs after Mon Nov  2 18:32:06 2020
  Reason: Reset Requested by CLI command reload
  System version: 9.3(4)
  Service:

plugin
  Core Plugin, Ethernet Plugin

Active Package(s):


cs2#
```

5. Install the NX-OS image.

   Installing the image file causes it to be loaded every time the switch is rebooted.

Show example

```
cs2# install all nxos bootflash:nxos.9.3.5.bin

Installer will perform compatibility check first. Please wait.
Installer is forced disruptive

Verifying image bootflash:/nxos.9.3.5.bin for boot variable "nxos".
[####################] 100% -- SUCCESS

Verifying image type.
[####################] 100% -- SUCCESS

Preparing "nxos" version info using image bootflash:/nxos.9.3.5.bin.
[####################] 100% -- SUCCESS

Preparing "bios" version info using image bootflash:/nxos.9.3.5.bin.
[####################] 100% -- SUCCESS

Performing module support checks.
[####################] 100% -- SUCCESS

Notifying services about system upgrade.
[####################] 100% -- SUCCESS




Compatibility check is done:
Module  bootable        Impact      Install-type Reason
------  --------  ---------------  ------------  ------
   1      yes       disruptive         reset     default upgrade is
not hitless




Images will be upgraded according to following table:

Module   Image    Running-Version(pri:alt                        New-
Version          Upg-Required
------- --------- -----------------------------------------
------------------- ------------
   1      nxos     9.3(4)                                         9.3(5)
yes
   1      bios     v08.37(01/28/2020):v08.23(09/23/2015)
v08.38(05/29/2020)       yes
```

```
Switch will be reloaded for disruptive upgrade.

Do you want to continue with the installation (y/n)? [n] y

Install is in progress, please wait.

Performing runtime checks.
[####################] 100% -- SUCCESS

Setting boot variables.
[####################] 100% -- SUCCESS

Performing configuration copy.
[####################] 100% -- SUCCESS

Module 1: Refreshing compact flash and upgrading
bios/loader/bootrom.
Warning: please do not remove or power off the module at this time.
[####################] 100% -- SUCCESS

Finishing the upgrade, switch will reboot in 10 seconds.
```

6. Verify the new version of NX-OS software after the switch has rebooted:

```
show version
```

Show example

```
cs2# show version

Cisco Nexus Operating System (NX-OS) Software
TAC support: http://www.cisco.com/tac
Copyright (C) 2002-2020, Cisco and/or its affiliates.
All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under their
own
licenses, such as open source.  This software is provided "as is,"
and unless
otherwise stated, there is no warranty, express or implied,
including but not
limited to warranties of merchantability and fitness for a
particular purpose.
Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or
GNU General Public License (GPL) version 3.0  or the GNU
Lesser General Public License (LGPL) Version 2.1 or
Lesser General Public License (LGPL) Version 2.0.
A copy of each such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://opensource.org/licenses/gpl-3.0.html and
http://www.opensource.org/licenses/lgpl-2.1.php and
http://www.gnu.org/licenses/old-licenses/library.txt.

Software
  BIOS: version 05.33
  NXOS: version 9.3(5)
  BIOS compile time:  09/08/2018
  NXOS image file is: bootflash:///nxos.9.3.5.bin
  NXOS compile time:  11/4/2018 21:00:00 [11/05/2018 06:11:06]


Hardware
  cisco Nexus9000 C9336C-FX2 Chassis
  Intel(R) Xeon(R) CPU E5-2403 v2 @ 1.80GHz with 8154432 kB of
memory.
  Processor Board ID FOC20291J6K

  Device name: cs2
  bootflash:   53298520 kB
Kernel uptime is 0 day(s), 0 hour(s), 3 minute(s), 42 second(s)
```

```
Last reset at 277524 usecs after Mon Nov  2 22:45:12 2020
   Reason: Reset due to upgrade
   System version: 9.3(4)
   Service:

plugin
   Core Plugin, Ethernet Plugin

Active Package(s):
```

7. Upgrade the EPLD image and reboot the switch.

Show example

```
cs2# show version module 1 epld

EPLD Device                     Version
-----------------------------------------
MI   FPGA                         0x7
IO   FPGA                         0x17
MI   FPGA2                        0x2
GEM  FPGA                         0x2
GEM  FPGA                         0x2
GEM  FPGA                         0x2
GEM  FPGA                         0x2


cs2# install epld bootflash:n9000-epld.9.3.5.img module 1
Compatibility check:
Module        Type         Upgradable        Impact    Reason
------  -----------------  ----------------  --------- -----
    1          SUP          Yes       disruptive  Module Upgradable


Retrieving EPLD versions.... Please wait.
Images will be upgraded according to following table:
Module  Type  EPLD              Running-Version   New-Version  Upg-
Required
------- ------ ---------------- ----------------- ------------
------------
    1  SUP    MI FPGA          0x07              0x07        No
    1  SUP    IO FPGA          0x17              0x19        Yes
    1  SUP    MI FPGA2         0x02              0x02        No
The above modules require upgrade.
The switch will be reloaded at the end of the upgrade
Do you want to continue (y/n) ?  [n] y


Proceeding to upgrade Modules.


Starting Module 1 EPLD Upgrade


Module 1 : IO FPGA [Programming] : 100.00% (     64 of      64
sectors)
Module 1 EPLD upgrade is successful.
Module    Type  Upgrade-Result
-------- ----- --------------
    1   SUP    Success


EPLDs upgraded.


Module 1 EPLD upgrade is successful.
```

8. After the switch reboot, log in again and verify that the new version of EPLD loaded successfully.

Show example

```
cs2# show version module 1 epld

EPLD Device                     Version
----------------------------------------
MI   FPGA                       0x7
IO   FPGA                       0x19
MI   FPGA2                      0x2
GEM  FPGA                       0x2
GEM  FPGA                       0x2
GEM  FPGA                       0x2
GEM  FPGA                       0x2
```

9. Repeat steps 1 to 8 to install the NX-OS software on switch cs1.

What's next?

Install RCF config file.

Install the Reference Configuration File (RCF)

You can install the RCF after setting up the Nexus 9336C-FX2 switch for the first time. You can also use this procedure to upgrade your RCF version.

Before you begin, complete the procedure in Prepare to install NX-OS and RCF.

Review requirements

What you'll need

- A current backup of the switch configuration.
- A fully functioning cluster (no errors in the logs or similar issues).
- The current RCF file.
- A console connection to the switch, required when installing the RCF.

Suggested documentation

- Cisco Ethernet switch page Consult the switch compatibility table for the supported ONTAP and RCF versions. Note that there can be command dependencies between the command syntax in the RCF and that found in versions of NX-OS.
- Cisco Nexus 3000 Series Switches. Refer to the appropriate software and upgrade guides available on the Cisco web site for complete documentation on the Cisco switch upgrade and downgrade procedures.

Install the RCF

About the examples

The examples in this procedure use the following switch and node nomenclature:

- The names of the two Cisco switches are cs1 and cs2.

- The node names are cluster1-01, cluster1-02, cluster1-03, and cluster1-04.

- The cluster LIF names are cluster1-01_clus1, cluster1-01_clus2, cluster1-02_clus1, cluster1-02_clus2 , cluster1-03_clus1, cluster1-03_clus2, cluster1-04_clus1, and cluster1-04_clus2.

- The `cluster1::*>` prompt indicates the name of the cluster.

The examples in this procedure use two nodes. These nodes use two 10GbE cluster interconnect ports e0a and e0b. See the Hardware Universe to verify the correct cluster ports on your platforms.

> ⓘ The command outputs might vary depending on different releases of ONTAP.

About this task

The procedure requires the use of both ONTAP commands and Cisco Nexus 9000 Series Switches commands; ONTAP commands are used unless otherwise indicated.

No operational inter-switch link (ISL) is needed during this procedure. This is by design because RCF version changes can affect ISL connectivity temporarily. To ensure non-disruptive cluster operations, the following procedure migrates all of the cluster LIFs to the operational partner switch while performing the steps on the target switch.

> ⚠ Before installing a new switch software version and RCFs, you must erase the switch settings and perform basic configuration. You must be connected to the switch using the serial console. This task resets the configuration of the management network.

Step 1: Prepare for the installation

1. Display the cluster ports on each node that are connected to the cluster switches:

   `network device-discovery show`

Show example

```
cluster1::*> network device-discovery show
Node/       Local  Discovered
Protocol    Port   Device (LLDP: ChassisID)  Interface
Platform
----------- ------ ------------------------- ----------------
--------
cluster1-01/cdp
            e0a    cs1                        Ethernet1/7     N9K-
C9336C
            e0d    cs2                        Ethernet1/7     N9K-
C9336C
cluster1-02/cdp
            e0a    cs1                        Ethernet1/8     N9K-
C9336C
            e0d    cs2                        Ethernet1/8     N9K-
C9336C
cluster1-03/cdp
            e0a    cs1                        Ethernet1/1/1   N9K-
C9336C
            e0b    cs2                        Ethernet1/1/1   N9K-
C9336C
cluster1-04/cdp
            e0a    cs1                        Ethernet1/1/2   N9K-
C9336C
            e0b    cs2                        Ethernet1/1/2   N9K-
C9336C
cluster1::*>
```

2. Check the administrative and operational status of each cluster port.

   a. Verify that all the cluster ports are **up** with a healthy status:

   ```
   network port show -role cluster
   ```

```
cluster1::*> network port show -role cluster


Node: cluster1-01


Ignore
                                                            Speed(Mbps)
Health   Health
Port      IPspace       Broadcast Domain Link MTU  Admin/Oper
Status    Status
--------- ------------ --------------- ---- ---- -----------
-------- ------
e0a       Cluster       Cluster           up   9000  auto/100000
healthy false
e0d       Cluster       Cluster           up   9000  auto/100000
healthy false


Node: cluster1-02


Ignore
                                                            Speed(Mbps)
Health   Health
Port      IPspace       Broadcast Domain Link MTU  Admin/Oper
Status    Status
--------- ------------ --------------- ---- ---- -----------
-------- ------
e0a       Cluster       Cluster           up   9000  auto/100000
healthy false
e0d       Cluster       Cluster           up   9000  auto/100000
healthy false
8 entries were displayed.


Node: cluster1-03


   Ignore
                                                            Speed(Mbps)
Health   Health
Port      IPspace       Broadcast Domain Link MTU  Admin/Oper
Status    Status
--------- ------------ --------------- ---- ---- -----------
-------- ------
e0a       Cluster       Cluster           up   9000  auto/10000
healthy  false
e0b       Cluster       Cluster           up   9000  auto/10000
healthy  false
```

```
Node: cluster1-04

Ignore
                                            Speed(Mbps)
Health   Health
Port       IPspace       Broadcast Domain Link MTU  Admin/Oper
Status   Status
--------- ------------ ---------------- ---- ---- -----------
-------- ------
e0a       Cluster       Cluster           up   9000  auto/10000
healthy  false
e0b       Cluster       Cluster           up   9000  auto/10000
healthy  false
cluster1::*>
```

b. Verify that all the cluster interfaces (LIFs) are on the home port:

```
network interface show -role cluster
```

```
cluster1::*> network interface show -role cluster
            Logical              Status      Network
Current       Current Is
Vserver     Interface           Admin/Oper Address/Mask        Node
Port    Home
----------- ------------------ ---------- -----------------
------------ ------- ----
Cluster
            cluster1-01_clus1  up/up      169.254.3.4/23
cluster1-01  e0a     true
            cluster1-01_clus2  up/up      169.254.3.5/23
cluster1-01  e0d     true
            cluster1-02_clus1  up/up      169.254.3.8/23
cluster1-02  e0a     true
            cluster1-02_clus2  up/up      169.254.3.9/23
cluster1-02  e0d     true
            cluster1-03_clus1  up/up      169.254.1.3/23
cluster1-03  e0a     true
            cluster1-03_clus2  up/up      169.254.1.1/23
cluster1-03  e0b     true
            cluster1-04_clus1  up/up      169.254.1.6/23
cluster1-04  e0a     true
            cluster1-04_clus2  up/up      169.254.1.7/23
cluster1-04  e0b     true
8 entries were displayed.
cluster1::*>
```

c. Verify that the cluster displays information for both cluster switches:

```
system cluster-switch show -is-monitoring-enabled-operational true
```

Show example

```
cluster1::*> system cluster-switch show -is-monitoring-enabled
-operational true
Switch                          Type              Address
Model
--------------------------- ----------------- ----------------
-----
cs1                             cluster-network   10.233.205.90
N9K-C9336C
        Serial Number: FOCXXXXXXGD
         Is Monitored: true
               Reason: None
      Software Version: Cisco Nexus Operating System (NX-OS)
Software, Version
                      9.3(5)
       Version Source: CDP

cs2                             cluster-network   10.233.205.91
N9K-C9336C
        Serial Number: FOCXXXXXXGS
         Is Monitored: true
               Reason: None
      Software Version: Cisco Nexus Operating System (NX-OS)
Software, Version
                      9.3(5)
       Version Source: CDP
cluster1::*>
```

3. Disable auto-revert on the cluster LIFs.

Show example

```
cluster1::*> network interface modify -vserver Cluster -lif * -auto
-revert false
```

Step 2: Configure ports

1. On cluster switch cs2, shut down the ports connected to the cluster ports of the nodes.

Show example

```
cs2(config)# interface eth1/1/1-2,eth1/7-8
cs2(config-if-range)# shutdown
```

2. Verify that the cluster LIFs have migrated to the ports hosted on cluster switch cs1. This might take a few seconds.

```
network interface show -role cluster
```

Show example

```
cluster1::*> network interface show -role cluster
           Logical              Status     Network                  Current
Current Is
Vserver      Interface          Admin/Oper Address/Mask        Node
Port     Home
----------- ----------------- ---------- ------------------
------------- ------- ----
Cluster
           cluster1-01_clus1 up/up        169.254.3.4/23
cluster1-01   e0a      true
           cluster1-01_clus2 up/up        169.254.3.5/23
cluster1-01   e0a      false
           cluster1-02_clus1 up/up        169.254.3.8/23
cluster1-02   e0a      true
           cluster1-02_clus2 up/up        169.254.3.9/23
cluster1-02   e0a      false
           cluster1-03_clus1 up/up        169.254.1.3/23
cluster1-03   e0a      true
           cluster1-03_clus2 up/up        169.254.1.1/23
cluster1-03   e0a      false
           cluster1-04_clus1 up/up        169.254.1.6/23
cluster1-04   e0a      true
           cluster1-04_clus2 up/up        169.254.1.7/23
cluster1-04   e0a      false
8 entries were displayed.
cluster1::*>
```

3. Verify that the cluster is healthy:

```
cluster show
```

Show example

```
cluster1::*> cluster show
Node                    Health  Eligibility   Epsilon
--------------------    ------- ------------  -------
cluster1-01             true    true          false
cluster1-02             true    true          false
cluster1-03             true    true          true
cluster1-04             true    true          false
4 entries were displayed.
cluster1::*>
```

4. If you have not already done so, save a copy of the current switch configuration by copying the output of the following command to a text file:

```
show running-config
```

5. Clean the configuration on switch cs2 and perform a basic setup.

> ⚠️ When updating or applying a new RCF, you must erase the switch settings and perform basic configuration. You must be connected to the switch serial console port to set up the switch again.

   a. Clean the configuration:

Show example

```
(cs2)# write erase

Warning: This command will erase the startup-configuration.

Do you wish to proceed anyway? (y/n)  [n]  y
```

   b. Perform a reboot of the switch:

Show example

```
(cs2)# reload

Are you sure you would like to reset the system? (y/n) y
```

6. Copy the RCF to the bootflash of switch cs2 using one of the following transfer protocols: FTP, TFTP, SFTP, or SCP. For more information on Cisco commands, see the appropriate guide in the Cisco Nexus 9000 Series NX-OS Command Reference guides.

Show example

This example shows TFTP being used to copy an RCF to the bootflash on switch cs2:

```
cs2# copy tftp: bootflash: vrf management
Enter source filename: Nexus_9336C_RCF_v1.6-Cluster-HA-Breakout.txt
Enter hostname for the tftp server: 172.22.201.50
Trying to connect to tftp server......Connection to Server
Established.
TFTP get operation was successful
Copy complete, now saving to disk (please wait)...
```

7. Apply the RCF previously downloaded to the bootflash.

For more information on Cisco commands, see the appropriate guide in the Cisco Nexus 9000 Series NX-OS Command Reference guides.

Show example

This example shows the RCF file Nexus_9336C_RCF_v1.6-Cluster-HA-Breakout.txt being installed on switch cs2:

```
cs2# copy Nexus_9336C_RCF_v1.6-Cluster-HA-Breakout.txt running-
config echo-commands
```

8. Examine the banner output from the show banner motd command. You must read and follow these instructions to ensure the proper configuration and operation of the switch.

Show example

```
cs2# show banner motd

********************************************************************
**********
* NetApp Reference Configuration File (RCF)
*
* Switch   : Nexus N9K-C9336C-FX2
* Filename : Nexus_9336C_RCF_v1.6-Cluster-HA-Breakout.txt
* Date     : 10-23-2020
* Version  : v1.6
*
* Port Usage:
* Ports  1- 3: Breakout mode (4x10G) Intra-Cluster Ports, int
e1/1/1-4, e1/2/1-4
, e1/3/1-4
* Ports  4- 6: Breakout mode (4x25G) Intra-Cluster/HA Ports, int
e1/4/1-4, e1/5/
1-4, e1/6/1-4
* Ports  7-34: 40/100GbE Intra-Cluster/HA Ports, int e1/7-34
* Ports 35-36: Intra-Cluster ISL Ports, int e1/35-36
*
* Dynamic breakout commands:
* 10G: interface breakout module 1 port <range> map 10g-4x
* 25G: interface breakout module 1 port <range> map 25g-4x
*
* Undo breakout commands and return interfaces to 40/100G
configuration in confi
g mode:
* no interface breakout module 1 port <range> map 10g-4x
* no interface breakout module 1 port <range> map 25g-4x
* interface Ethernet <interfaces taken out of breakout mode>
* inherit port-profile 40-100G
* priority-flow-control mode auto
* service-policy input HA
* exit
*
********************************************************************
**********
```

9. Verify that the RCF file is the correct newer version:

```
show running-config
```

When you check the output to verify you have the correct RCF, make sure that the following information is correct:

- ◦ The RCF banner
- ◦ The node and port settings
- ◦ Customizations

  The output varies according to your site configuration. Check the port settings and refer to the release notes for any changes specific to the RCF that you have installed.

10. After you verify the RCF versions and switch settings are correct, copy the running-config file to the startup-config file.

    For more information on Cisco commands, see the appropriate guide in the Cisco Nexus 9000 Series NX-OS Command Reference guides.

    Show example

    ```
    cs2# copy running-config startup-config
    [########################################] 100% Copy complete
    ```

11. Reboot switch cs2. You can ignore the "cluster ports down" events reported on the nodes while the switch reboots.

    Show example

    ```
    cs2# reload
    This command will reboot the system. (y/n)?  [n] y
    ```

12. Verify the health of cluster ports on the cluster.

    a. Verify that e0d ports are up and healthy across all nodes in the cluster:

    ```
    network port show -role cluster
    ```

Show example

```
cluster1::*> network port show -role cluster

Node: cluster1-01

Ignore
                                                  Speed(Mbps)
Health   Health
Port      IPspace      Broadcast Domain Link MTU  Admin/Oper
Status   Status
--------- ------------ ---------------- ---- ---- -----------
-------- ------
e0a       Cluster      Cluster          up   9000 auto/10000
healthy  false
e0b       Cluster      Cluster          up   9000 auto/10000
healthy  false

Node: cluster1-02

Ignore
                                                  Speed(Mbps)
Health   Health
Port      IPspace      Broadcast Domain Link MTU  Admin/Oper
Status   Status
--------- ------------ ---------------- ---- ---- -----------
-------- ------
e0a       Cluster      Cluster          up   9000 auto/10000
healthy  false
e0b       Cluster      Cluster          up   9000 auto/10000
healthy  false

Node: cluster1-03

Ignore
                                                  Speed(Mbps)
Health   Health
Port      IPspace      Broadcast Domain Link MTU  Admin/Oper
Status   Status
--------- ------------ ---------------- ---- ---- -----------
-------- ------
e0a       Cluster      Cluster          up   9000 auto/100000
healthy false
e0d       Cluster      Cluster          up   9000 auto/100000
healthy false
```

```
Node: cluster1-04

Ignore
                                          Speed(Mbps)
Health   Health
Port      IPspace       Broadcast Domain Link MTU  Admin/Oper
Status   Status
--------- ------------ ---------------- ---- ---- -----------
-------- ------
e0a       Cluster      Cluster          up   9000  auto/100000
healthy false
e0d       Cluster      Cluster          up   9000  auto/100000
healthy false
8 entries were displayed.
```

b. Verify the switch health from the cluster (this might not show switch cs2, since LIFs are not homed on e0d).

Show example

```
cluster1::*> network device-discovery show -protocol cdp
Node/        Local  Discovered
Protocol     Port   Device (LLDP: ChassisID)  Interface
Platform
-----------  ------  -----------------------  -----------------
--------
cluster1-01/cdp
             e0a    cs1                       Ethernet1/7
N9K-C9336C
             e0d    cs2                       Ethernet1/7
N9K-C9336C
cluster01-2/cdp
             e0a    cs1                       Ethernet1/8
N9K-C9336C
             e0d    cs2                       Ethernet1/8
N9K-C9336C
cluster01-3/cdp
             e0a    cs1                       Ethernet1/1/1
N9K-C9336C
             e0b    cs2                       Ethernet1/1/1
N9K-C9336C
cluster1-04/cdp
             e0a    cs1                       Ethernet1/1/2
N9K-C9336C
             e0b    cs2                       Ethernet1/1/2
N9K-C9336C

cluster1::*> system cluster-switch show -is-monitoring-enabled
-operational true
Switch                        Type            Address
Model
----------------------------  --------------  ----------------
-----
cs1                           cluster-network  10.233.205.90
NX9-C9336C
     Serial Number: FOCXXXXXXGD
      Is Monitored: true
            Reason: None
  Software Version: Cisco Nexus Operating System (NX-OS)
Software, Version
                  9.3(5)
    Version Source: CDP

cs2                           cluster-network  10.233.205.91
```

```
  NX9-C9336C
        Serial Number: FOCXXXXXXGS
          Is Monitored: true
                Reason: None
      Software Version: Cisco Nexus Operating System (NX-OS)
  Software, Version
                        9.3(5)
        Version Source: CDP

  2 entries were displayed.
```

You might observe the following output on the cs1 switch console depending on the RCF version previously loaded on the switch:

```
2020 Nov 17 16:07:18 cs1 %$ VDC-1 %$ %STP-2-UNBLOCK_CONSIST_PORT:
Unblocking port port-channel1 on VLAN0092. Port consistency
restored.
2020 Nov 17 16:07:23 cs1 %$ VDC-1 %$ %STP-2-BLOCK_PVID_PEER:
Blocking port-channel1 on VLAN0001. Inconsistent peer vlan.
2020 Nov 17 16:07:23 cs1 %$ VDC-1 %$ %STP-2-BLOCK_PVID_LOCAL:
Blocking port-channel1 on VLAN0092. Inconsistent local vlan.
```

13. On cluster switch cs1, shut down the ports connected to the cluster ports of the nodes.

    Show example

    The following example uses the interface example output:

    ```
    cs1(config)# interface eth1/1/1-2,eth1/7-8
    cs1(config-if-range)# shutdown
    ```

14. Verify that the cluster LIFs have migrated to the ports hosted on switch cs2. This might take a few seconds.

    ```
    network interface show -role cluster
    ```

Show example

```
cluster1::*> network interface show -role cluster
          Logical               Status     Network            Current
Current Is
Vserver    Interface            Admin/Oper Address/Mask       Node
Port    Home
----------- ------------------ ---------- ------------------
------------------ ------- ----
Cluster
          cluster1-01_clus1  up/up      169.254.3.4/23
cluster1-01        e0d     false
          cluster1-01_clus2  up/up      169.254.3.5/23
cluster1-01        e0d     true
          cluster1-02_clus1  up/up      169.254.3.8/23
cluster1-02        e0d     false
          cluster1-02_clus2  up/up      169.254.3.9/23
cluster1-02        e0d     true
          cluster1-03_clus1  up/up      169.254.1.3/23
cluster1-03        e0b     false
          cluster1-03_clus2  up/up      169.254.1.1/23
cluster1-03        e0b     true
          cluster1-04_clus1  up/up      169.254.1.6/23
cluster1-04        e0b     false
          cluster1-04_clus2  up/up      169.254.1.7/23
cluster1-04        e0b     true
8 entries were displayed.
cluster1::*>
```

15. Verify that the cluster is healthy:

```
cluster show
```

Show example

```
cluster1::*> cluster show
Node                    Health   Eligibility   Epsilon
--------------------    --------  -------------  -------
cluster1-01             true      true           false
cluster1-02             true      true           false
cluster1-03             true      true           true
cluster1-04             true      true           false
4 entries were displayed.
cluster1::*>
```

16. Repeat steps 4 to 11 on switch cs1.

17. Enable auto-revert on the cluster LIFs.

Show example

```
cluster1::*> network interface modify -vserver Cluster -lif * -auto
-revert True
```

18. Reboot switch cs1. You do this to trigger the cluster LIFs to revert to their home ports. You can ignore the "cluster ports down" events reported on the nodes while the switch reboots.

Show example

```
cs1# reload
This command will reboot the system. (y/n)?  [n] y
```

Step 3: Verify the configuration

1. Verify that the switch ports connected to the cluster ports are **up**.

```
show interface brief
```

Show example

```
cs1# show interface brief | grep up
.
.
Eth1/1/1       1       eth  access up      none
10G(D) --
Eth1/1/2       1       eth  access up      none
10G(D) --
Eth1/7         1       eth  trunk  up      none
100G(D) --
Eth1/8         1       eth  trunk  up      none
100G(D) --
.
.
```

2. Verify that the expected nodes are still connected:

show cdp neighbors

Show example

```
cs1# show cdp neighbors

Capability Codes: R - Router, T - Trans-Bridge, B - Source-Route-
Bridge
                  S - Switch, H - Host, I - IGMP, r - Repeater,
                  V - VoIP-Phone, D - Remotely-Managed-Device,
                  s - Supports-STP-Dispute

Device-ID          Local Intrfce  Hldtme Capability  Platform
Port ID
node1              Eth1/1         133    H           FAS2980
e0a
node2              Eth1/2         133    H           FAS2980
e0a
cs2                Eth1/35        175    R S I s     N9K-C9336C
Eth1/35
cs2                Eth1/36        175    R S I s     N9K-C9336C
Eth1/36

Total entries displayed: 4
```

3. Verify that the cluster nodes are in their correct cluster VLANs using the following commands:

```
show vlan brief
```

```
show interface trunk
```

Show example

```
cs1# show vlan brief

VLAN Name                             Status    Ports
---- -------------------------------- ---------
--------------------------------
1    default                          active    Po1, Eth1/1, Eth1/2,
Eth1/3
                                                Eth1/4, Eth1/5,
Eth1/6, Eth1/7
                                                Eth1/8, Eth1/35,
Eth1/36
                                                Eth1/9/1, Eth1/9/2,
Eth1/9/3
                                                Eth1/9/4, Eth1/10/1,
Eth1/10/2
                                                Eth1/10/3, Eth1/10/4
17   VLAN0017                         active    Eth1/1, Eth1/2,
Eth1/3, Eth1/4
                                                Eth1/5, Eth1/6,
Eth1/7, Eth1/8
                                                Eth1/9/1, Eth1/9/2,
Eth1/9/3
                                                Eth1/9/4, Eth1/10/1,
Eth1/10/2
                                                Eth1/10/3, Eth1/10/4
18   VLAN0018                         active    Eth1/1, Eth1/2,
Eth1/3, Eth1/4
                                                Eth1/5, Eth1/6,
Eth1/7, Eth1/8
                                                Eth1/9/1, Eth1/9/2,
Eth1/9/3
                                                Eth1/9/4, Eth1/10/1,
Eth1/10/2
                                                Eth1/10/3, Eth1/10/4
31   VLAN0031                         active    Eth1/11, Eth1/12,
Eth1/13
                                                Eth1/14, Eth1/15,
Eth1/16
                                                Eth1/17, Eth1/18,
Eth1/19
                                                Eth1/20, Eth1/21,
Eth1/22
32   VLAN0032                         active    Eth1/23, Eth1/24,
Eth1/25
```

```
                                                      Eth1/26, Eth1/27,
Eth1/28
                                                      Eth1/29, Eth1/30,
Eth1/31
                                                      Eth1/32, Eth1/33,
Eth1/34
33   VLAN0033                         active   Eth1/11, Eth1/12,
Eth1/13
                                                      Eth1/14, Eth1/15,
Eth1/16
                                                      Eth1/17, Eth1/18,
Eth1/19
                                                      Eth1/20, Eth1/21,
Eth1/22
34   VLAN0034                         active   Eth1/23, Eth1/24,
Eth1/25
                                                      Eth1/26, Eth1/27,
Eth1/28
                                                      Eth1/29, Eth1/30,
Eth1/31
                                                      Eth1/32, Eth1/33,
Eth1/34

cs1# show interface trunk

--------------------------------------------------------
Port            Native  Status         Port
                Vlan                   Channel
--------------------------------------------------------
Eth1/1          1       trunking       --
Eth1/2          1       trunking       --
Eth1/3          1       trunking       --
Eth1/4          1       trunking       --
Eth1/5          1       trunking       --
Eth1/6          1       trunking       --
Eth1/7          1       trunking       --
Eth1/8          1       trunking       --
Eth1/9/1        1       trunking       --
Eth1/9/2        1       trunking       --
Eth1/9/3        1       trunking       --
Eth1/9/4        1       trunking       --
Eth1/10/1       1       trunking       --
Eth1/10/2       1       trunking       --
Eth1/10/3       1       trunking       --
Eth1/10/4       1       trunking       --
Eth1/11         33      trunking       --
```

```
Eth1/12        33        trunking       --
Eth1/13        33        trunking       --
Eth1/14        33        trunking       --
Eth1/15        33        trunking       --
Eth1/16        33        trunking       --
Eth1/17        33        trunking       --
Eth1/18        33        trunking       --
Eth1/19        33        trunking       --
Eth1/20        33        trunking       --
Eth1/21        33        trunking       --
Eth1/22        33        trunking       --
Eth1/23        34        trunking       --
Eth1/24        34        trunking       --
Eth1/25        34        trunking       --
Eth1/26        34        trunking       --
Eth1/27        34        trunking       --
Eth1/28        34        trunking       --
Eth1/29        34        trunking       --
Eth1/30        34        trunking       --
Eth1/31        34        trunking       --
Eth1/32        34        trunking       --
Eth1/33        34        trunking       --
Eth1/34        34        trunking       --
Eth1/35        1         trnk-bndl      Po1
Eth1/36        1         trnk-bndl      Po1
Po1            1         trunking       --


-------------------------------------------------------
Port            Vlans Allowed on Trunk
-------------------------------------------------------
Eth1/1          1,17-18
Eth1/2          1,17-18
Eth1/3          1,17-18
Eth1/4          1,17-18
Eth1/5          1,17-18
Eth1/6          1,17-18
Eth1/7          1,17-18
Eth1/8          1,17-18
Eth1/9/1        1,17-18
Eth1/9/2        1,17-18
Eth1/9/3        1,17-18
Eth1/9/4        1,17-18
Eth1/10/1       1,17-18
Eth1/10/2       1,17-18
Eth1/10/3       1,17-18
Eth1/10/4       1,17-18
```

```
Eth1/11          31,33
Eth1/12          31,33
Eth1/13          31,33
Eth1/14          31,33
Eth1/15          31,33
Eth1/16          31,33
Eth1/17          31,33
Eth1/18          31,33
Eth1/19          31,33
Eth1/20          31,33
Eth1/21          31,33
Eth1/22          31,33
Eth1/23          32,34
Eth1/24          32,34
Eth1/25          32,34
Eth1/26          32,34
Eth1/27          32,34
Eth1/28          32,34
Eth1/29          32,34
Eth1/30          32,34
Eth1/31          32,34
Eth1/32          32,34
Eth1/33          32,34
Eth1/34          32,34
Eth1/35          1
Eth1/36          1
Po1              1
..
..
..
..
..
```

> (i) For specific port and VLAN usage details, refer to the banner and important notes section in your RCF.

4. Verify that the ISL between cs1 and cs2 is functional:

```
show port-channel summary
```

Show example

```
cs1# show port-channel summary
Flags:  D - Down        P - Up in port-channel (members)
        I - Individual  H - Hot-standby (LACP only)
        s - Suspended   r - Module-removed
        b - BFD Session Wait
        S - Switched    R - Routed
        U - Up (port-channel)
        p - Up in delay-lacp mode (member)
        M - Not in use. Min-links not met
--------------------------------------------------------------------
------------
Group Port-        Type       Protocol  Member Ports      Channel
--------------------------------------------------------------------
------------
1     Po1(SU)      Eth        LACP      Eth1/35(P)        Eth1/36(P)
cs1#
```

5. Verify that the cluster LIFs have reverted to their home port:

   `network interface show -role cluster`

```
cluster1::*> network interface show -role cluster
           Logical              Status     Network                Current
Current Is
Vserver    Interface            Admin/Oper Address/Mask           Node
Port    Home
----------- ------------------ ---------- ------------------
------------------ ------- ----
Cluster
           cluster1-01_clus1  up/up      169.254.3.4/23
cluster1-01         e0d      true
           cluster1-01_clus2  up/up      169.254.3.5/23
cluster1-01         e0d      true
           cluster1-02_clus1  up/up      169.254.3.8/23
cluster1-02         e0d      true
           cluster1-02_clus2  up/up      169.254.3.9/23
cluster1-02         e0d      true
           cluster1-03_clus1  up/up      169.254.1.3/23
cluster1-03         e0b      true
           cluster1-03_clus2  up/up      169.254.1.1/23
cluster1-03         e0b      true
           cluster1-04_clus1  up/up      169.254.1.6/23
cluster1-04         e0b      true
           cluster1-04_clus2  up/up      169.254.1.7/23
cluster1-04         e0b      true
8 entries were displayed.
cluster1::*>
```

6. Verify that the cluster is healthy:

```
cluster show
```

Show example

```
cluster1::*> cluster show
Node                    Health  Eligibility   Epsilon
--------------------    -------  ------------- -------
cluster1-01             true    true          false
cluster1-02             true    true          false
cluster1-03             true    true          true
cluster1-04             true    true          false
4 entries were displayed.
cluster1::*>
```

7. Ping the remote cluster interfaces to verify connectivity:

```
cluster ping-cluster -node local
```

```
cluster1::*> cluster ping-cluster -node local
Host is cluster1-03
Getting addresses from network interface table...
Cluster cluster1-03_clus1 169.254.1.3 cluster1-03 e0a
Cluster cluster1-03_clus2 169.254.1.1 cluster1-03 e0b
Cluster cluster1-04_clus1 169.254.1.6 cluster1-04 e0a
Cluster cluster1-04_clus2 169.254.1.7 cluster1-04 e0b
Cluster cluster1-01_clus1 169.254.3.4 cluster1-01 e0a
Cluster cluster1-01_clus2 169.254.3.5 cluster1-01 e0d
Cluster cluster1-02_clus1 169.254.3.8 cluster1-02 e0a
Cluster cluster1-02_clus2 169.254.3.9 cluster1-02 e0d
Local = 169.254.1.3 169.254.1.1
Remote = 169.254.1.6 169.254.1.7 169.254.3.4 169.254.3.5 169.254.3.8
169.254.3.9
Cluster Vserver Id = 4294967293
Ping status:
............
Basic connectivity succeeds on 12 path(s)
Basic connectivity fails on 0 path(s)
................................................
Detected 9000 byte MTU on 12 path(s):
    Local 169.254.1.3 to Remote 169.254.1.6
    Local 169.254.1.3 to Remote 169.254.1.7
    Local 169.254.1.3 to Remote 169.254.3.4
    Local 169.254.1.3 to Remote 169.254.3.5
    Local 169.254.1.3 to Remote 169.254.3.8
    Local 169.254.1.3 to Remote 169.254.3.9
    Local 169.254.1.1 to Remote 169.254.1.6
    Local 169.254.1.1 to Remote 169.254.1.7
    Local 169.254.1.1 to Remote 169.254.3.4
    Local 169.254.1.1 to Remote 169.254.3.5
    Local 169.254.1.1 to Remote 169.254.3.8
    Local 169.254.1.1 to Remote 169.254.3.9
Larger than PMTU communication succeeds on 12 path(s)
RPC status:
6 paths up, 0 paths down (tcp check)
6 paths up, 0 paths down (udp check)
```