

ASSIGNMENT 5 DESIGN DOCUMENT

Chris Moon

February 2023

1 Goal

Implement the Lempel-Ziv method of file compression and decompression, utilizing tries and words ADTs.

2 Pseudocode

TRIES

- WHAT IS A TRIE:

- tree type data structure, made up of connected individual nodes
- first letter is the parent, all other letters following are children
- ex: A is a parent, N and T are children, for the words AN and AT
- each node is a struct, containing an array and a value
- the value is referred to as a code
- the array contains pointers to 256 nodes, one per ASCII character

- HOW TO IMPLEMENT CONSTRUCTION AND DELETION:

- trie create uses struct syntax (arrows for parameters)
- should allocate memory for the node first, and then the array, using malloc
- takes a code value as a parameter, and sets the code of the node using arrow syntax
- trie node delete should free the array pointer first, and then the pointer to the node
- create a root first, which is a node with an empty code

- TREE FUNCTIONS

- implement the function, trie create, which will just use the trie constructor with the given EMPTY CODE value as the code parameter

- this will create the root node of the trie tree

- trie delete should take a node, and clear that node and all its children

- recursively call trie node delete here, starting from the lowest children, and working up, as to not lose the ability to reference lower children

- trie reset should delete the trie starting at the root node

- call trie delete(root)

WORDS

- allows translation of codes to symbols

- word type contains a list of symbols and a length

- also has a constructor and delete function

- an array of words, or a word table, can also be created