# 【OGG】OGG 的下载和安装篇

# 1.1 **BLOG 文档结构图**

i	[00	GG】OGG的下载和安装篇
Г	1.	1 BLOG 文档结构图
- 4	1.	2 前言部分
	1.2.1 导读	
		1.2.2 实验环境介绍
		1.2.3 本文简介
4	1.	3 gg <del>安装</del>
	4	1.3.1 Downloading Oracle GoldenGate software.
		1.3.1.1 第一种: http://edelivery.oracle.com
		1.3.1.2 第二种: http://www.oracle.com
		1.3.2 Setting ORACLE_HOME and ORACLE_SID
		1.3.3 Setting library paths for dynamic builds
		1.3.4 Installing the Oracle GoldenGate software
		1.3.5 GoldenGate Directories
	1.	4 系统要求
4	1.	5 自己的安装例子
		1.5.1 配置环境变量
		1.5.2 解压
		1.5.3 安装
	1.	6 总结
	1.	7 About Me

#### 1.2 前言部分

### 1. 2. 1 导读

各位技术爱好者,看完本文后,你可以掌握如下的技能,也可以学到一些其它你所不知道的知识,~O(N\_N)O~:

① OGG 的下载和安装

注意:本篇 BLOG 中代码部分需要特别关注的地方我都用黄色背景和红色字体来表示,比如下边的例子中,thread 1 的最大归档日志号为 33,thread 2 的最大归档日志号为 43

#### 是需要特别关注的地方。

Lis	st of Arc	chived Logs	in backup set 11		
Thr	rd Seq	Low SCN	Low Time	Next SCN	Next Time
1	32	1621589	2015-05-29 11:09	:52 1625242	2015-05-29 11:15:48
1	33	1625242	2015-05-29 11:15	:48 1625293	2015-05-29 11:15:58
2	42	1613951	2015-05-29 10:41	:18 1625245	2015-05-29 11:15:49
2	43	1625245	2015-05-29 11:15	:49 1625253	2015-05-29 11:15:53

本文如有错误或不完善的地方请大家多多指正,ITPUB 留言或 QQ 皆可,您的批评指正是我写作的最大动力。

# 1.2.2 实验环境介绍

11.2.0.3 RHEL6.5

# 1. 2. 3 本文简介

有个同事喊我解决 OGG 不能同步的问题,汗颜啊,我也就之前学过安装和简单的配置,当时是成功的,结果帮同事搭建的时候数据死活不能同步。于是下决心这几天好好再研究一下 OGG 的内容。

# 1.3 **gg 安装**

在 Linux 上安装 OGG 很简单,总体分为以下几个部分:

- 1. Downloading Oracle GoldenGate software.
- 2. Setting ORACLE\_HOME and ORACLE\_SID
- 3. Setting library paths for dynamic builds
- 4. Installing the Oracle GoldenGate software

#### 1. 3. 1 Downloading Oracle GoldenGate software.

#### 第一步,下载 gg 软件,可以有2种途径直接下载


# 1.3.1.1 第一种: http://edelivery.oracle.com

- 1. On a browser, go to http://edelivery.oracle.com
- 2. Welcome page:
  - Select language
  - Continue
- 3. Export Validation:
  - Enter your name, company, email, country
  - Accept Trial License (even if you have permanent license)
  - Accept Export Restrictions
  - Continue
- 4. Media Pack Search:

Select a Product Pack: Oracle Fusion Middleware

Select a platform from the drop-down list

Go



#### 5. Results:

Select the Oracle GoldenGate Media Pack you want Continue

0	Oracle GoldenGate on Oracle Media Pack for Microsoft Windows (32-bit)	n/a	B56876-01	NOV-09-2009	3 / 37M
0	Oracle GoldenGate on IBM DB2 Media Pack for Microsoft Windows (32-bit)	n/a	B56892-01	NOV-09-2009	2 / 28M
0	Oracle GoldenGate on SQL SERVER Media Pack for Microsoft Windows (32- bit)	n/a	B56896-01	NOV-09-2009	2 / 29M
0	Oracle GoldenGate on Sybase Media Pack for Microsoft Windows (32-bit)	n/a	B56924-01	NOV-09-2009	3 / 37M


Oracle GoldenGate on Oracle v11.2.1  Media Pack for Linux x86-64	11.2.1.0.1	B68070-03	JAN-22-2014	3 / 262M
--	------------	-----------	-------------	-------------

- 6. View Readme
- 7. Download software
- 8. Download documentation


Oracle Golden Windows (32-b	Gate on SQL SERVER Media Pack v1 for Microsoft oit)		
Readme	/iew Digest		
Select	Name	Part Number	Size (Bytes)
Download	Oracle GoldenGate V10.4.0.x for Windows 2000, XP, 2003 on SQL Server 2000, 2003, 2008 (delivery only)	V18174-01	8.3M
Download	Oracle GoldenGate Documentation	V18423-01	20M
Total: 2			

# 1. 3. 1. 2 **第二种:http://www.oracle.com**

1. 登录 www.oracle.com ,选择 Middleware 下的 See All



#### 2. 选择 GoldenGate





#### 注意选择好对应的版本及平台:



#### 不用详细说明了吧,所以最终的下载地址:

英文: http://www.oracle.com/technetwork/middleware/goldengate/downloads/index.html

中文: http://www.oracle.com/technetwork/cn/middleware/goldengate/downloads/index.html

### 1. 3. 2 Setting ORACLE HOME and ORACLE SID

Set the environment variables in your .bash profile (Bash)

ORACLE BASE=/u01

# ORACLE\_HOME=\$ORACLE\_BASE/oracle ORACLE SID=ggsource

PATH=\$ORACLE\_BASE/gg11:\$ORACLE\_HOME/bin:\$PATH
LD LIBRARY PATH=\$ORACLE BASE/gg11:\$ORACLE HOME/lib:\$LD LIBRARYPATH

export ORACLE\_BASE ORACLE\_HOME ORACLE\_SID export PATH LD LIBRARY PATH

#### 自己:

export ORACLE\_BASE=/u01/app/oracle
export ORACLE\_HOME=\$ORACLE\_BASE/product/11.2.0/dbhome\_1
export OGG\_HOME=/u01/gg11
export PATH=\$OGG\_HOME:\$ORACLE\_HOME/bin:\$PATH
export LD\_LIBRARY\_PATH=\$OGG\_HOME:\$ORACLE\_HOME/lib:\$LD\_LIBRARYPATH

stty erase ^h alias ggsci='rlwrap ggsci'

#### 1. 3. 3 Setting library paths for dynamic builds

Platform	Environment variables
IBM AIX	
IBM z/OS	
HP-UX	SHLIB_PATH
Solaris	
HP Tru64	LD_LIBRARY_PATH
Linux	

# 1. 3. 4 Installing the Oracle GoldenGate software

Use the gzip and tar options appropriate for your system. If you are installing GoldenGate into a cluster environment, make certain that the GoldenGate binaries and files are installed on a file system that is available to all cluster nodes. After installing GoldenGate, make certain to configure the GoldenGate Manager process within the cluster application, as directed by the vendor's documentation, so that GoldenGate will fail over properly with the other applications. The Manager process is the master control program for all GoldenGate operations. A GoldenGate instance is a single installation of GoldenGate.

- Unzip the Oracle GoldenGate media pack .zip file on a Windows system. This produces a .tar file.
- FTP the .tar file in binary mode to the system and directory where you want GoldenGate to be installed.
- Extract the .tar file into the current directory:

tar -xvof <filename>.tar

Run the command shell and change directories to the new GoldenGate directory.
 GGSCI> CREATE SUBDIRS

#### 1. 3. 5 GoldenGate Directories

Directory	Contents
dirchk	GoldenGate checkpoint files
dirdat	GoldenGate trail and extract files
dirdef	Data definitions produced by DEFGEN and used to translate heterogeneous data
dirpcs	Process status files
dirprm	Parameter files
dirrpt	Process report files
dirsql	SQL scripts
dirtmp	Temporary storage for transactions that exceed allocated memory

a. dirchk: 存放检查点文件

b. dirdat:存放 Trail 文件

c. dirdef:存放通过 DEFGEN 工具生成的源或目标端数据定义文件

d. dirpcs:存放进程状态文件

e. dirprm: 存放配置参数文件

f. dirrpt: 存放进程报告文件

g. dirsql:存放 sql 脚本文件

h. dirtmp: 当食物所需要的内存超过已分配内存时,默认存储在这个目录。

# 1.4 系统要求

- 1. 一个 0GG 实例最多支持 300 个并发 extract 和 replicat 进程,每个进程需要 25-55M 内存。
- 2. GGSCI, view report, 找到 PROCESS VM AVAIL FROM OS, 大约就是系统所需 要的 swap space 大小
- 3. 磁盘空间每个实例 50-150M, 外加 trail 等等,至少给 1G。trail 所需空间 的预估方法是: [log volume in one hour] x [number of hours downtime] \* 0.4
- 4. /tmp 空间,默认是 dirtmp 目录,可以通过 CACHEMGR 参数的 CACHEDIRECTORY 选项指定

- 5. 安装 OGG 的用户必须属于 ORACLE 数据库实例的组,通常就是 dba。
- 6. 要想支持 RAC 里的 RMAN log retention 特性,得在 add extract 之前安装 patch BUGFIX 11879974


#### 1.5 自己的安装例子

source 和 target 端的安装过程是一样的。

#### 1.5.1 配置环境变量

```
| Gene learned | The "S ving env. sh |
| Gene learned | The "S ving env. sh |
| Gene learned | The "S ving env. sh |
| export ORALE BASE-NOI/app/oracle |
| export DAIDMANY_PATH-Noi/actil:SOMACLE_BASE/product/il.2.0/dbhome_1
| export DAIDMANY_PATH-Noi/actil:SOMACLE_BASE/product/il.2.0/dbhome_1
| stiy erase "h |
| alias genetic riverap genetic |
| foraclearned | The "S wid" | yu0/gg11 |
| foraclearned | The "S wid" | yu0/gg11 |
| foraclearned | The "S wid" | yu0/gg11 |
| foraclearned | The "S wid" | yu0/gg11 |
| foraclearned | The "S wid" | yu0/gg11 |
| foraclearned | The "S wid" | yu0/gg11 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | The "S wid" | yu0/gg10 |
| foraclearned | yu0/gg10 |
| forac
```

#### 1.5.2 解压



#### 1.5.3 安装

- 1. 这里确保 gg11 目录的用户为 Oracle,如果不是执行: chown -R oracle:oinstall gg11
- 2. 安装的时候进入 gg11 目录,不然会安装在当前登录的目录下边

# 1.6 总结

OGG 的安装相对于 ORACLE 的安装来说是非常简单的,其实也就是配置环境变量,然后解压一下,最后创建目录即可。

#### 1.7 About Me

本文作者:小麦苗,只专注于数据库的技术,更注重技术的运用

ITPUB BLOG: http://blog.itpub.net/26736162

本文地址: http://blog.itpub.net/26736162/viewspace-1693241/

本文pdf版: http://yunpan.cn/QCwUAI9bn7g7w 提取码:af2d

QQ:642808185 若加 QQ 请注明你所正在读的文章标题

创作时间地点: 2015-06-09 10:00~ 2015-06-09 19:00 于外汇交易中心

<版权所有,文章允许转载,但须以链接方式注明源地址,否则追究法律责任!>

.....