# $btctweets\_sentiment\_prediction-cnn-lstm-05312020$

June 21, 2020

# 1 Bitcoin Tweets Sentiment Analysis Prediction – CNN-LSTM


```
[1]: # Data analysis and wrangling
     import pandas as pd
     import numpy as np
     import os
     import string
     import csv
     # Visualization
     %matplotlib inline
     import matplotlib.pyplot as plt
     import seaborn
     from wordcloud import WordCloud
     # Sentiment prediction
     import re
     import nltk
     from sklearn.model_selection import train_test_split
     from keras.preprocessing.text import Tokenizer
     from keras.preprocessing import sequence
     from tensorflow.keras import backend, models, layers
     from tensorflow.keras.models import Model, Sequential
     from tensorflow.keras.layers import Dense, Embedding, Conv1D, MaxPooling1D,
     →Dropout, LSTM
     from sklearn.metrics import accuracy_score, confusion_matrix,
      →classification_report
```

Using TensorFlow backend.

```
usecols=[2,5])
     df.head()
[2]:
                                                clean_text sentiment
       goldman sachs hosting client call bitcoin gold...
                                                           neutral
                       ok president trump endorsing tommy positive
     1
     2 bitcoin day nwhen btc first used commercial tr... positive
       great icle nif way could avoided know like min... positive
     4
                            bitcoin btc current price gbp
[3]: df.tail()
[3]:
                                                   clean_text sentiment
     2015 xrp xrpcommunity btc bitcoin eth ltc vet oh ye... positive
     2016 yes world global pandemic world going recessio...
                                                              neutral
     2017 last days grayscale bitcoin trust bought bitco...
                                                              neutral
     2018 pretty incredible imho nwe need creativity lik... positive
     2019
                                         drop sachs nget sats
                                                                neutral
    1.1 Exploratory Data Analysis
[4]: df.info()
    <class 'pandas.core.frame.DataFrame'>
    RangeIndex: 2020 entries, 0 to 2019
    Data columns (total 2 columns):
    clean_text
                  2020 non-null object
    sentiment
                  2020 non-null object
    dtypes: object(2)
    memory usage: 31.7+ KB
[5]: df.describe()
[5]:
                        clean_text sentiment
     count
                              2020
                                         2020
     unique
                              1391
                                            3
     top
             tick tock less blocks
                                     neutral
                                          964
     freq
                                36
[6]: tweets_count = df['sentiment'].value_counts()
     tweets_count
[6]: neutral
                 964
    positive
                 788
                 268
    negative
    Name: sentiment, dtype: int64
```

```
[7]: # Plot sentiment mood count
seaborn.countplot(x='sentiment', data=df)
plt.title('Bitcoin Sentiment Analysis - 2020')
plt.ylabel('Total Counts')
```

[7]: Text(0, 0.5, 'Total Counts')



```
[8]: # add text length column
      df['text_length'] = df['clean_text'].apply(len)
 [9]: df.head()
 [9]:
                                                clean_text sentiment text_length
      O goldman sachs hosting client call bitcoin gold...
                        ok president trump endorsing tommy positive
                                                                                34
      2 bitcoin day nwhen btc first used commercial tr... positive
                                                                              87
        great icle nif way could avoided know like min... positive
                                                                              68
                             bitcoin btc current price gbp
                                                             neutral
                                                                                29
[10]: df.tail()
```

```
[10]:
                                                   clean_text sentiment text_length
     2015 xrp xrpcommunity btc bitcoin eth ltc vet oh ye... positive
                                                                                96
      2016 yes world global pandemic world going recessio...
                                                                                56
                                                              neutral
      2017 last days grayscale bitcoin trust bought bitco...
                                                              neutral
                                                                                70
      2018 pretty incredible imho nwe need creativity lik... positive
                                                                                68
      2019
                                         drop sachs nget sats
                                                                neutral
                                                                                  20
```


#### [11]: df['text\_length'].describe()

```
[11]: count
               2020.000000
                  61.235149
      mean
                 27.054467
      std
      min
                  4.000000
      25%
                 39.000000
      50%
                 66.500000
      75%
                 83.000000
      max
                 117.000000
```

Name: text\_length, dtype: float64


## [12]: df['text\_length'].hist(bins=30)

[12]: <matplotlib.axes.\_subplots.AxesSubplot at 0x1d95e61ac08>



```
[13]: plot = seaborn.FacetGrid(df,col='sentiment')
plot.map(plt.hist,'text_length')
```

#### [13]: <seaborn.axisgrid.FacetGrid at 0x1d95f9a6748>




```
[14]: # visualization using wordcloud for the Neutral tweets

tweets_neutral = df[df['sentiment']=='neutral']
words = ' '.join(tweets_neutral['clean_text'])

wordcloud = WordCloud(background_color='blue').generate(words)

plt.figure(1,figsize=(15, 12))
plt.imshow(wordcloud)
plt.axis('off')
plt.show()
```




```
[15]: # visualization using wordcloud for the Positive tweets

tweets_positive = df[df['sentiment']=='positive']
words = ' '.join(tweets_positive['clean_text'])

wordcloud = WordCloud(background_color='orange').generate(words)

plt.figure(1,figsize=(15, 12))
plt.imshow(wordcloud)
plt.axis('off')
plt.show()
```




```
[16]: # visualization using wordcloud for the Negative tweets

tweets_negative = df[df['sentiment']=='negative']
words = ' '.join(tweets_negative['clean_text'])

wordcloud = WordCloud(background_color='green').generate(words)

plt.figure(1,figsize=(15, 12))
plt.imshow(wordcloud)
plt.axis('off')
plt.show()
```



#### 1.2 Training and Testing sets

[17]: # Encode Categorical Variable for Deep Learning

(1616,) (404,) (1616, 3) (404, 3)

#### 1.2.1 Tokenize Text


```
[19]: # Tokenize Text

# Define max number of words in dictionary
max_features = 20000
```

```
tokenizer = Tokenizer(num_words=max_features, lower=True)
tokenizer.fit_on_texts(list(x_train))

x_train = tokenizer.texts_to_sequences(x_train)
x_test = tokenizer.texts_to_sequences(x_test)
```

```
[20]: totalNumWords = [len(feature) for feature in x_train]
   plt.hist(totalNumWords,bins = 30)
   plt.show()
```



```
[21]: # Based on the plot histogram, setting feature maxWords
maxWords = 20

x_train = sequence.pad_sequences(x_train, maxlen=maxWords)
x_test = sequence.pad_sequences(x_test, maxlen=maxWords)
print(x_train.shape,x_test.shape)
```

(1616, 20) (404, 20)

#### 1.3 Model – CNN Long Short-Term Memory Network (CNN LSTM)

```
[22]: # Build a CNN-LSTM Model
backend.clear_session()
```

```
embedding_size = 300
epoch = 25
batch_size = 64
model = models.Sequential()
model.add(Embedding(max_features, embedding_size, input_length=x_train.
\hookrightarrowshape [1]))
model.add(Conv1D(filters=32, kernel_size=3, padding='same', activation='relu'))
model.add(MaxPooling1D(pool_size=2))
model.add(Conv1D(filters=32, kernel_size=3, padding='same', activation='relu'))
model.add(MaxPooling1D(pool_size=2))
model.add(LSTM(96, dropout=0.15, recurrent_dropout=0.15))
model.add(Dense(num_classes * 4, activation='relu'))
model.add(Dropout(0.2))
model.add(Dense(num_classes * 2, activation='relu'))
model.add(Dropout(0.2))
# Output layer
model.add(Dense(num_classes, activation='softmax'))
# Compile the model
model.compile(optimizer = 'adam',
               loss = 'categorical_crossentropy',
               metrics = ['accuracy'])
print(model.summary())
# Train the model
history = model.fit(x_train,
                    y_train,
                    epochs = epoch,
                    batch_size = batch_size,
                    validation_data=(x_test, y_test),
                    verbose = 1)
history_dict = history.history
loss_values = history_dict['loss']
val_loss_values = history_dict['val_loss']
acc_values = history_dict['acc']
val_acc_values = history_dict['val_acc']
epochs = range(1, len(history_dict['acc']) + 1)
hist = pd.DataFrame(history.history)
print(hist.head())
```

```
plt.plot(epochs, loss_values, 'b', label = 'Training loss')
plt.plot(epochs, val_loss_values, 'r', label = 'Validation loss')
plt.title('Training and Validation loss')
plt.xlabel('Epochs')
plt.ylabel('Loss')
plt.legend()
plt.show()
plt.plot(epochs, acc_values, 'b', label = 'Training accuracy')
plt.plot(epochs, val_acc_values, 'r', label = 'Validation accuracy')
plt.title('Training and Validation accuracy')
plt.xlabel('Epochs')
plt.ylabel('Accuracy')
plt.legend()
plt.show()
results = model.evaluate(x_test, y_test)
print(model.metrics_names)
print(results)
```

WARNING:tensorflow:From C:\cuong\lib\site-

packages\tensorflow\python\ops\resource\_variable\_ops.py:435: colocate\_with (from tensorflow.python.framework.ops) is deprecated and will be removed in a future version.

Instructions for updating:

Colocations handled automatically by placer.

WARNING:tensorflow:From C:\cuong\lib\site-

packages\tensorflow\python\keras\backend.py:4010: calling dropout (from tensorflow.python.ops.nn\_ops) with keep\_prob is deprecated and will be removed in a future version.

Instructions for updating:


Please use `rate` instead of `keep\_prob`. Rate should be set to `rate = 1 - keep\_prob`.


Layer (type)	Output Shape	Param #
embedding (Embedding)	(None, 20, 300)	6000000
conv1d (Conv1D)	(None, 20, 32)	28832
max_pooling1d (MaxPooling1D)	(None, 10, 32)	0
conv1d_1 (Conv1D)	(None, 10, 32)	3104
max_pooling1d_1 (MaxPooling1	(None, 5, 32)	0
lstm (LSTM)	(None, 96)	49536

```
dense (Dense)
              (None, 12)
                           1164
          (None, 12)
dropout (Dropout)
_____
dense_1 (Dense)
              (None, 6)
_____
dropout_1 (Dropout)
           (None, 6)
-----
dense_2 (Dense) (None, 3)
                            21
______
Total params: 6,082,735
Trainable params: 6,082,735
Non-trainable params: 0
None
Train on 1616 samples, validate on 404 samples
WARNING:tensorflow:From C:\cuong\lib\site-
packages\tensorflow\python\ops\math_ops.py:3066: to_int32 (from
tensorflow.python.ops.math_ops) is deprecated and will be removed in a future
Instructions for updating:
Use tf.cast instead.
Epoch 1/25
0.3886 - val_loss: 1.0004 - val_acc: 0.3911
Epoch 2/25
0.4158 - val_loss: 0.9701 - val_acc: 0.4777
Epoch 3/25
0.4783 - val_loss: 0.9305 - val_acc: 0.5025
Epoch 4/25
0.4691 - val loss: 0.9334 - val acc: 0.5619
Epoch 5/25
0.5136 - val_loss: 0.8856 - val_acc: 0.6213
Epoch 6/25
0.6572 - val_loss: 0.7892 - val_acc: 0.7054
Epoch 7/25
0.8521 - val_loss: 0.9438 - val_acc: 0.7871
Epoch 8/25
0.9146 - val_loss: 1.0719 - val_acc: 0.7871
Epoch 9/25
```

```
0.9270 - val_loss: 1.2080 - val_acc: 0.7723
Epoch 10/25
0.9437 - val_loss: 1.4904 - val_acc: 0.7698
Epoch 11/25
0.9449 - val_loss: 1.6264 - val_acc: 0.7723
Epoch 12/25
0.9406 - val_loss: 1.6331 - val_acc: 0.7748
Epoch 13/25
0.9431 - val_loss: 1.6162 - val_acc: 0.7723
Epoch 14/25
0.9425 - val_loss: 1.5931 - val_acc: 0.7673
Epoch 15/25
0.9394 - val_loss: 1.6905 - val_acc: 0.7698
Epoch 16/25
0.9400 - val_loss: 1.6773 - val_acc: 0.7723
Epoch 17/25
0.9474 - val_loss: 1.7794 - val_acc: 0.7673
Epoch 18/25
0.9412 - val_loss: 1.6707 - val_acc: 0.7847
Epoch 19/25
0.9449 - val_loss: 1.7929 - val_acc: 0.7550
Epoch 20/25
0.9468 - val_loss: 1.6023 - val_acc: 0.7748
Epoch 21/25
0.9474 - val_loss: 1.8945 - val_acc: 0.7748
Epoch 22/25
0.9363 - val_loss: 1.8327 - val_acc: 0.7797
Epoch 23/25
0.9443 - val_loss: 1.9289 - val_acc: 0.7797
Epoch 24/25
0.9387 - val_loss: 1.8335 - val_acc: 0.7921
Epoch 25/25
```

```
0.9474 - val_loss: 1.8239 - val_acc: 0.7970
             acc val_loss
                         val_acc
     loss
0 1.063406 0.388614 1.000369 0.391089
1 1.008457
         0.415842 0.970121
                        0.477723
2 0.953958
         0.478342 0.930459
                        0.502475
3 0.852168
         0.469059 0.933353
                        0.561881
4 0.780665
         0.513614  0.885603  0.621287
```





#### 1.4 Model Prediction/Evaluation

```
#confusion matrix
confmatrix = confusion_matrix(np.argmax(y_test,axis=1), y_pred_test)

fig, ax = plt.subplots(figsize=(4, 4))
ax.matshow(confmatrix, cmap=plt.cm.Blues, alpha=0.3)

for i in range(confmatrix.shape[0]):
    for j in range(confmatrix.shape[1]):
        ax.text(x=j, y=i, s=confmatrix[i, j], va='center', ha='center')

plt.xlabel('Predicted label')
plt.ylabel('True label')
plt.tight_layout()
```

### [24]: print(model\_evaluation())

Accuracy: 79.7%

	precision	recall	f1-score	support
0	0.83	0.55	0.66	53
1	0.79	0.85	0.82	193
2	0.80	0.81	0.80	158
accuracy			0.80	404
macro avg	0.81	0.74	0.76	404
weighted avg	0.80	0.80	0.79	404

None

