CS 4900

Project: Blacktop TPS Report 11/18//2019

Team:	Skyler Sheler	skyler.j.sheler@wmich.edu	(616) 438-3527
	Erron Johnson	erron.d.johnson@wmich.edu	(269) 547-8933
	Allin Kahrl	f.allin.kahrl@wmich.edu	(207) 522-4859
	Tyler Henniges	tyler.m.henniges@wmich.edu	(269) 330-4229
Client:	WMU Computer Club	colin.c.maccreery@wmich.edu	(269) 276-3106
Contact:	Colin MacCreery	colin.c.maccreery@wmich.edu	(269) 276-3106
Project Lead	Allin Kahrl	f.allin.kahrl@wmich.edu	(207) 522-4859

Task	Who will complete	Time	Risk 1-10	% complete	Actual time	review
T1	SS	1 hour	1	100%	1 hour	AK TH EJ
T2	SS AK TH EJ	1 hour or less	1	100%	1 hour	AK SS TH
ТЗ	SS AK TH EJ	5 hours	3	20%	TBD	TBD
T4	SS AK TH EJ	10 hours	3	50%	TBD	TBD
T5	SS AK TH EJ	10 hours	6	30%	TBD	TBD
Т6	SS AK TH EJ	10 hours	6	30%	TBD	TBD

T1: Write the requested deliverables for the week

Write the TPS Report and Stories for the week

T2: Install the toolchain for the MSP 430.

The toolchain necessary to use the board will have to be installed before any circuit prototypes can be tested.

- T3: Test the board to see if it can handle all of the peripherals being turned on at once

 The maximum current load of the board must be determined, and if turning on all

 peripherals exceeds that load a failsafe must be developed to prevent the board from
 breaking.
- T4: Begin breadboarding a prototype board.

The components will have to be socketed into a breadboard and tested for full functionality. This is currently the largest portion of the project to overcome and time specifications will have to be further analyzed.

- T5: Develop drivers using SPI to interface with the on-board EEPROM

 Drivers must be developed using a serial peripheral interface to transfer data from the main board to the on-board EEPROM
- T6: Develop the CAD files for the production circuit board

 The circuit board must be designed via KiCAD before a prototype board can be ordered