



wild**tag**.ai

Automated species identification for camera trap images -
powered by AI, designed for ecologists.

USER MANUAL - BETA 1 - JUNE 2026

1. Overview

wildtag.ai processes folders of camera trap images automatically - detecting animals, classifying species, and organising results for review. It runs entirely on your computer with no internet connection required after installation.

The workflow has four stages:

- 1 Run**
Point wildtag at an image folder, choose a model, and let it detect and classify everything.
- 2 Validate**
Browse AI predictions as a gallery, correct any mistakes, and mark batches as complete.
- 3 Distribute**
Package species folders as zips for volunteer validators, and collect their corrections when returned.
- 4 Summary**
Review detection statistics and a species breakdown for your survey.

2. Getting Started

1 Download and unzip

Download the zip from the link provided. Right-click and select "Extract All". Choose a permanent location with around 5 GB of free space. Do not run wildtag from inside the zip file.

2 Launch the app

Open the unzipped folder and double-click `wildtag.bat`. A brief console window appears, then the wildtag interface opens.

3 Organise your images

wildtag works on a folder of JPEGs. Subfolders are supported - all images are found automatically. Each run should correspond to one survey site or session.

wildtag never modifies your original images. All outputs are written to new files in a `validation\` subfolder.

3. Running the Pipeline

Run wildtag

Select your image folder

Click Browse and navigate to your camera trap image folder. wildtag counts all JPEG images found inside, including subfolders.

Choose a detector and classifier

Setting	Recommended choice
Detector	MegaDetector v5a - the global standard for camera trap animal detection
Classifier	DeepFaune v1.4 for European surveys; SpeciesNet Global for broader geographic coverage

When SpeciesNet is selected it runs its own internal detector. The MegaDetector setting is ignored.

Set confidence thresholds

- **Detection threshold** - images where no detection exceeds this value are recorded as `empty`. Default: 0.1.
- **Species confidence** - detections below this threshold are labelled `low_confidence`. Default: 0.6. Lower this to see more predictions; raise it for stricter results.

Geographic filter

Select a region to filter out implausible species predictions. For UK surveys, select GBR. This removes predictions like wolverine or raccoon and replaces them with the next most plausible UK species. Select None to use raw model predictions.

Performance options

- **Processing device** - CPU is always available. NVIDIA GPU (CUDA) appears automatically if detected and dramatically speeds up classification.
- **CPU threads** - defaults to one less than your total CPU count, leaving one core free for the rest of your computer.

Output options

- **Generate IDs** - adds unique `image_id` and `detection_id` columns to the CSV.
- **Prepare validation folder** - creates downscaled annotated images organised by species, ready for the Validate tab.

Running

Click Run wildtag. The log panel shows live progress. A 38-image folder takes 3-10 minutes on CPU depending on the model chosen. SpeciesNet takes longer as it runs a full internal pipeline.

4. Validating Results

Validate

Validation is where you review AI predictions and correct any errors. wildtag presents images as a gallery, one species folder at a time.

Opening a validation folder

Click Browse and select your project folder or the `validation\` folder inside it - wildtag finds it automatically. The species dropdown shows only folders with images still needing review.

Reviewing images

Images appear in a grid with the AI confidence score below each one and a bounding box drawn around the detected animal. Click any image to open the correction dialog.

- If the label is correct, click **Correct**
- If wrong, select the right species from the dropdown and click **Apply correction**

The correction dropdown is ordered: *unidentifiable* first, then species alphabetically, then broad groups such as mustelid or lagomorph, then special labels.

Completing a batch

Once you have reviewed all images in a folder, click **Mark batch complete**. This writes your corrections to the validation CSV. The folder will not appear again in the dropdown once fully validated.

Images containing humans are automatically pixelated in the validation folder. Original images are never modified.

How validation updates the master CSV

As you validate, wilddtag writes corrections to `validation.csv` files inside each species folder. When you distribute or export, these corrections are merged into the master `results_with_ids.csv`, populating the `correct_label` and `human_verified` columns. Your master CSV always reflects your latest validation work.

5. Distributing and Collecting

Distribute

The Distribute tab has two parts: packaging validation folders to send to volunteer validators, and collecting their corrections when they are returned.

Part A - Prepare packages for validators

Select your validation folder and click **Prepare zip packages**. wildtag creates one zip file per species folder containing the annotated images, the validation spreadsheet, the wildtag app, and instructions. Each zip goes into a `distribute\` folder next to your validation folder.

Send the relevant zip to each volunteer. You might assign one species to each person, or send multiple zips to the same person for different species.

Zips only include species folders that have unvalidated images. If everything is already validated, no zips are created.

What the volunteer does

- 1 Unzip the file and double-click `wildtag.bat`
- 2 Click Browse in the Validate tab and select the unzipped folder
- 3 Review images, correct labels, click Mark batch complete
- 4 Zip up the folder and return it

Part B - Collect returned validated zips

When validators return their zips, drop them into the `collect\` folder inside your project folder. Then click **Merge all returned validations**. wildtag will:

- Show you a preview of all corrections across all returned zips

- Ask you to confirm before merging
- Update your master validation CSVs and `results_with_ids.csv`
- Move processed zips to `collect\processed\` so you know what has been handled

The first time you click Merge, wildtag creates the `collect\` folder if it does not exist and tells you where to drop the zips.

6. Understanding the CSV Output

wildtag produces a CSV with one row per detection - not one row per image. An image with two animals produces two rows; an empty image produces one row with `NA` for species fields.

Core columns

Column	Description
<code>image_id</code>	Unique identifier for the source image. Consistent across runs on the same image.
<code>detection_id</code>	Unique identifier for this specific detection.
<code>relative_path</code>	Path to the image relative to the survey folder root.
<code>label</code>	Final species label: <code>empty</code> , <code>human</code> , <code>vehicle</code> , <code>low_confidence</code> , or a species name.
<code>confidence</code>	Classifier confidence score (0-1). <code>NA</code> for empty images.
<code>correct_label</code>	Correction entered during validation. Empty if the AI label was accepted.
<code>human_verified</code>	<code>TRUE</code> once a detection has been reviewed in the Validate tab.

Detection detail columns

Column	Description
<code>detector_label</code>	What the detector found: <code>animal</code> , <code>human</code> , or <code>vehicle</code> .
<code>detector_confidence</code>	Detector confidence score.
<code>cv_label</code>	

	Raw species label from the classifier before geofencing or thresholding.
<code>cv_confidence</code>	Classifier confidence for <code>cv_label</code> .
<code>cv_model</code>	Name of the classifier used, e.g. <code>deepfaune-v1.4</code> .
<code>bbox_left</code> , <code>bbox_top</code> , <code>bbox_right</code> , <code>bbox_bottom</code>	Bounding box coordinates. Normalised (0-1) when <code>bbox_normalised = 1</code> .

EXIF columns

wildtag automatically extracts camera metadata including

`DateTimeOriginal`, `Make`, `Model`, GPS coordinates, `ExposureTime`, and `ISOSpeedRatings`.

For analysis, use `correct_label` where populated, falling back to `label` where not. This gives the best available identification for every detection.

7. Privacy and GDPR

Camera traps occasionally capture people. wildtag handles this in two ways:

- **Detection labelling** - MegaDetector identifies humans and vehicles separately from animals, labelled `human` or `vehicle` in the CSV.
- **Automatic pixelation** - validation copies of human detections are heavily pixelated. Faces and bodies are unrecognisable. Original images are never modified.

wildtag pixelates validation copies only. Original images remain unmodified and you remain responsible for their storage and access controls under applicable data protection law.

Appendix A: AI Models

MegaDetector v5a

Developed by Microsoft AI for Earth. A YOLOv5-based detector trained on millions of camera trap images worldwide. Identifies three categories: animal, human, and vehicle, with bounding boxes. Does not identify species.

- Architecture: YOLOv5x, 140M parameters, 1280px input
- Weight file: 280 MB

DeepFaune v1.4

Developed by CNRS (France). A vision transformer classifier trained on European camera trap images. Classifies animal crops into 38 classes covering the full range of European wildlife.

- Architecture: ViT-Large with DINOv2 backbone, 182px crop
- Classes: 38 including domestic animals and birds as a group
- Weight file: 1.1 GB
- Best for: European surveys, ungulates and carnivores

SpeciesNet Global (Google, v4.0.3a)

Developed by Google. A complete end-to-end pipeline combining its own internal MegaDetector with a global species classifier and geofencing. Outputs taxonomy-aware predictions that roll up to family or order level when species-level confidence is insufficient.

- Architecture: EfficientNetV2-M classifier with internal MegaDetector
- Classifier weight file: 224 MB
- Best for: global surveys or when taxonomy-level rollup is needed

For UK and European surveys, DeepFaune v1.4 with the GBR geofence is faster and well-calibrated for local species. SpeciesNet

is better for international datasets or when you want taxonomy-level predictions such as "cervidae family" rather than a forced species-level guess.

Appendix B: Geographic Filtering

The geographic filter reduces false positives by removing species predictions that are implausible for your study region. When GBR is selected, wildtag checks each prediction against a curated list of UK species. If the top prediction is not on the list, wildtag uses the next most confident plausible prediction instead.

UK species list includes

- **Deer:** red deer, roe deer, fallow deer, sika deer, Chinese water deer, muntjac
- **Carnivores:** red fox, badger, otter, stoat, weasel, polecat, pine marten, mink, wildcat
- **Rodents:** red squirrel, grey squirrel, water vole, bank vole, field vole, wood mouse, dormouse, brown rat
- **Lagomorphs:** rabbit, brown hare, mountain hare
- **Other:** hedgehog, mole, wild boar, all shrews, domestic livestock, dog, cat, bird

Broad group labels such as mustelid, lagomorph, and bird always pass the geofence since they are plausible anywhere. Select None to disable geofencing entirely.