

# Fitting Models to Data in Ecology and Evolution

CMEE Masters

Samraat Pawar

**Imperial College**  
London


November 18, 2016

# MECHANISTIC VS. PHENOMENOLOGICAL MODELS


- Mechanistic models aim to explain the PROCESSES underlying observed patterns
- Empirical or phenomenological models show relationships between observed data (e.g. population size as a function of temperature or rainfall), but provide no insights into why they are related

# MECHANISTIC VS. PHENOMENOLOGICAL MODELS

- Mechanistic models aim to explain the PROCESSES underlying observed patterns
- Empirical or phenomenological models show relationships between observed data (e.g. population size as a function of temperature or rainfall), but provide no insights into why they are related




# WHAT ARE MECHANISMS?




- Ecological studies often focus on explaining phenomena using somewhat phenomenological models.

# WHAT ARE MECHANISMS?




- Ecological studies often focus on explaining phenomena using somewhat phenomenological models.
- For example, insect invasions, outbreaks and spread  
([http://www.sandyliebhold.com/pubs/science\\_DC1/](http://www.sandyliebhold.com/pubs/science_DC1/)) — papers in your Readings directory; (<http://www.imperial.ac.uk/qmee-cdt/supervisors/>)

# WHAT ARE MECHANISMS?




- Ecological studies often focus on explaining phenomena using somewhat phenomenological models.
- For example, insect invasions, outbreaks and spread  
([http://www.sandyliebhold.com/pubs/science\\_DC1/](http://www.sandyliebhold.com/pubs/science_DC1/)) — papers in your Readings directory; (<http://www.imperial.ac.uk/qmee-cdt/supervisors/>)
  - Why the cycles?, Why the travelling waves?

# WHAT ARE MECHANISMS?



- Ecological studies often focus on explaining phenomena using somewhat phenomenological models.
- For example, insect invasions, outbreaks and spread  
([http://www.sandyliebhold.com/pubs/science\\_DC1/](http://www.sandyliebhold.com/pubs/science_DC1/)) — papers in your Readings directory; (<http://www.imperial.ac.uk/qmee-cdt/supervisors/>)
  - Why the cycles?, Why the travelling waves?

# WHAT ARE MECHANISMS?



- Ecological studies often focus on explaining phenomena using somewhat phenomenological models.
- For example, insect invasions, outbreaks and spread  
([http://www.sandyliebhold.com/pubs/science\\_DC1/](http://www.sandyliebhold.com/pubs/science_DC1/)) — papers in your Readings directory; (<http://www.imperial.ac.uk/qmee-cdt/supervisors/>)
  - Why the cycles?, Why the travelling waves? What mechanisms operate? (budmoth/parasitoid interaction? (budmoth/food quality interaction?) Are these truly mechanisms?
- Another example, disease outbreaks (Papers in your Readings directory)



# WHAT ARE MECHANISMS?

- Somewhat subjective!

# WHAT ARE MECHANISMS?

- Somewhat subjective!
- For example, the Ricker model can be thought of as mechanistic:

$$N_{t+1} = N_t e^{r\left(1 - \frac{N_t}{K}\right)} \quad (1)$$

# WHAT ARE MECHANISMS?

- Somewhat subjective!
- For example, the Ricker model can be thought of as mechanistic:

$$N_{t+1} = N_t e^{r\left(1 - \frac{N_t}{K}\right)} \quad (1)$$

- What is the mechanism? — Density dependence through scramble competition (Brannstrom & Sumpter 2005)

# WHAT ARE MECHANISMS?

- Somewhat subjective!
- For example, the Ricker model can be thought of as mechanistic:

$$N_{t+1} = N_t e^{r\left(1 - \frac{N_t}{K}\right)} \quad (1)$$

- What is the mechanism? — Density dependence through scramble competition (Brannstrom & Sumpter 2005)
- If the Ricker model and another model with contest competition were compared with data — some would call it mechanistic modelling because one is trying to get at the underlying mechanism, scramble or contest competition

# WHAT ARE MECHANISMS?

- Somewhat subjective!
- For example, the Ricker model can be thought of as mechanistic:

$$N_{t+1} = N_t e^{r\left(1 - \frac{N_t}{k}\right)} \quad (1)$$

- What is the mechanism? — Density dependence through scramble competition (Brannstrom & Sumpter 2005)
- If the Ricker model and another model with contest competition were compared with data — some would call it mechanistic modelling because one is trying to get at the underlying mechanism, scramble or contest competition
- But is this REALLY mechanistic? What are  $r$  and  $k$  really?

# WHAT ARE MECHANISMS?


- Somewhat subjective!
- For example, the Ricker model can be thought of as mechanistic:

$$N_{t+1} = N_t e^{r(1 - \frac{N_t}{k})} \quad (1)$$

- What is the mechanism? — Density dependence through scramble competition (Brannstrom & Sumpter 2005)
- If the Ricker model and another model with contest competition were compared with data — some would call it mechanistic modelling because one is trying to get at the underlying mechanism, scramble or contest competition
- But is this REALLY mechanistic? What are  $r$  and  $k$  really?
- Many (including yours truly!) now argue that we have not progressed far enough because the first level has been ignored!


# AN EXAMPLE OF A FUNDAMENTAL MECHANISM: METABOLISM

# AN EXAMPLE OF A FUNDAMENTAL MECHANISM: METABOLISM





# AN EXAMPLE OF A FUNDAMENTAL MECHANISM: METABOLISM



$$B = B_0 \boxed{e^{-\frac{E}{kT}}} f(T, T_{pk}, E_D)$$

$T$  = temperature (K)

$k$  = Boltzmann constant ( $\text{eV K}^{-1}$ )


$E$  = Activation energy (eV)

$T_{pk}$  = Temperature of peak performance

$E_D$  = Deactivation energy (eV)

(J H van't Hoff 1884, S Arrhenius 1889)

# AN EXAMPLE OF A FUNDAMENTAL MECHANISM: METABOLISM



$$B = B_0 \boxed{e^{-\frac{E}{kT}}} f(T, T_{pk}, E_D)$$

$T$  = temperature (K)

$k$  = Boltzmann constant ( $\text{eV K}^{-1}$ )

$E$  = Activation energy (eV)


$T_{pk}$  = Temperature of peak performance

$E_D$  = Deactivation energy (eV)

(J H van't Hoff 1884, S Arrhenius 1889)

- Surely there is more to thermal responses?
  - Oxygen limitation
  - Complexity of metabolic network
  - Hormonal regulation

# AN EXAMPLE OF A FUNDAMENTAL MECHANISM: METABOLISM



$$B = B_0 \boxed{e^{-\frac{E}{kT}}} f(T, T_{pk}, E_D)$$

$T$  = temperature (K)

$k$  = Boltzmann constant ( $\text{eV K}^{-1}$ )

$E$  = Activation energy (eV)

$T_{pk}$  = Temperature of peak performance

$E_D$  = Deactivation energy (eV)

(J H van't Hoff 1884, S Arrhenius 1889)


- Surely there is more to thermal responses?
  - Oxygen limitation
  - Complexity of metabolic network
  - Hormonal regulation
- *What about alternative models?*

# MODELLING, AND FITTING MODELS TO DATA: WHAT'S THE BIG IDEA?

- If possible, use biological knowledge to construct models
- See if the models “agree well” with data
- Whichever model “agrees best” is most likely to have the right mechanisms
- That's the one that's best for predictions (e.g. population cycles), estimating rates (e.g. growth rates), etc.
- Don't use models you already know have the wrong mechanisms!
- Phenomenological models often perform better than mechanistic ones

# MODELS: HOW TO BUILD THEM?

- It's an art, take practice (look at Levins' paper on the strategy of model building in biology)
- Build models one mechanism at a time — in biology, it means start at the right level of organization!
- Always consider a alternative that is more parsimonious, even if it is phenomenological (the TPC example: Sharpe-Schoolfield, or Polynomial?)!



# MODELS: HOW TO BUILD THEM?

- For example, the Boltzmann-Arrhenius model is a good first try describe and uncover mechanisms underlying individual level rates
- The next step would be to include high-temperature effects (e.g., the Schoolfield model)
- The next step would be to include species interactions with temperature dependence of individuals (or go in an evolutionary direction!)

**Next: A primer on mechanistic model fitting**

**Next: A primer on mechanistic model fitting**

But first: A preview of the Miniproject (back to Notes)



# FITTING MODELS TO DATA

Two common ways to do it:

- One-step forecasting (appropriate for discrete models)
- Ensemble fitting (appropriate for full time series or responses) – this is what you will be doing in NLLS

# ENSEMBLE FITTING

There include maximum likelihood, bayesian methods, and Non-linear least squares (NLLS) optimization or fitting. Many of you will use NLLS. Basically, this is how it works:

- 1 Start with an initial value for each parameter in the model

# ENSEMBLE FITTING

There include maximum likelihood, bayesian methods, and Non-linear least squares (NLLS) optimization or fitting. Many of you will use NLLS. Basically, this is how it works:

- 1 Start with an initial value for each parameter in the model
- 2 Generate the curve defined by the initial values

# ENSEMBLE FITTING

There include maximum likelihood, bayesian methods, and Non-linear least squares (NLLS) optimization or fitting. Many of you will use NLLS. Basically, this is how it works:

- 1 Start with an initial value for each parameter in the model
- 2 Generate the curve defined by the initial values
- 3 Calculate the residual sum-of-squares (rss)

# ENSEMBLE FITTING

There include maximum likelihood, bayesian methods, and Non-linear least squares (NLLS) optimization or fitting. Many of you will use NLLS. Basically, this is how it works:

- 1 Start with an initial value for each parameter in the model
- 2 Generate the curve defined by the initial values
- 3 Calculate the residual sum-of-squares (rss)
- 4 Adjust the parameters to make the curve come closer to the data points. This the tricky part — you will use the Levenberg-Marquardt algorithm in the `lmfit` package in `python`

# ENSEMBLE FITTING

There include maximum likelihood, bayesian methods, and Non-linear least squares (NLLS) optimization or fitting. Many of you will use NLLS. Basically, this is how it works:

- 1 Start with an initial value for each parameter in the model
- 2 Generate the curve defined by the initial values
- 3 Calculate the residual sum-of-squares (rss)
- 4 Adjust the parameters to make the curve come closer to the data points. This the tricky part — you will use the Levenberg-Marquardt algorithm in the `lmfit` package in `python`
- 5 Adjust the parameters again so that the curve comes even closer to the points (rss decreases)

# ENSEMBLE FITTING

There include maximum likelihood, bayesian methods, and Non-linear least squares (NLLS) optimization or fitting. Many of you will use NLLS. Basically, this is how it works:

- 1 Start with an initial value for each parameter in the model
- 2 Generate the curve defined by the initial values
- 3 Calculate the residual sum-of-squares (rss)
- 4 Adjust the parameters to make the curve come closer to the data points. This the tricky part — you will use the Levenberg-Marquardt algorithm in the `lmfit` package in `python`
- 5 Adjust the parameters again so that the curve comes even closer to the points (rss decreases)
- 6 Repeat 4–5

# ENSEMBLE FITTING

There include maximum likelihood, bayesian methods, and Non-linear least squares (NLLS) optimization or fitting. Many of you will use NLLS. Basically, this is how it works:

- 1 Start with an initial value for each parameter in the model
- 2 Generate the curve defined by the initial values
- 3 Calculate the residual sum-of-squares (rss)
- 4 Adjust the parameters to make the curve come closer to the data points. This the tricky part — you will use the Levenberg-Marquardt algorithm in the `lmfit` package in `python`
- 5 Adjust the parameters again so that the curve comes even closer to the points (rss decreases)
- 6 Repeat 4–5
- 7 Stop simulations when the adjustments make virtually no difference to the rss



# ENSEMBLE FITTING

Once the algorithm has converged (hopefully – but you may be surprised how well it usually works),

- Report the best-fit results, including sums of deviations of the data from the final model fit

# ENSEMBLE FITTING

Once the algorithm has converged (hopefully – but you may be surprised how well it usually works),

- Report the best-fit results, including sums of deviations of the data from the final model fit
- Then compare multiple models (e.g., Schoolfield vs. cubic)

# ENSEMBLE FITTING

Once the algorithm has converged (hopefully – but you may be surprised how well it usually works),

- Report the best-fit results, including sums of deviations of the data from the final model fit
- Then compare multiple models (e.g., Schoolfield vs. cubic)

# ENSEMBLE FITTING

Once the algorithm has converged (hopefully – but you may be surprised how well it usually works),

- Report the best-fit results, including sums of deviations of the data from the final model fit
- Then compare multiple models (e.g., Schoolfield vs. cubic)

The precise parameter values you obtain will depend in part on the initial values chosen and the stopping criteria –

# ENSEMBLE FITTING

Once the algorithm has converged (hopefully – but you may be surprised how well it usually works),

- Report the best-fit results, including sums of deviations of the data from the final model fit
- Then compare multiple models (e.g., Schoolfield vs. cubic)

The precise parameter values you obtain will depend in part on the initial values chosen and the stopping criteria – so different programs will not always give exactly the same results

# COMPARING MODELS

- It's all about the “Likelihood” of a model:
- That is, the likelihood of a set of parameter values (of a model),  $\theta$ , given outcomes  $x$ , equals the probability of those observed outcomes given those parameter values, that is,

$$\mathcal{L}(\theta|x) = P(x|\theta)$$

# COMPARING MODELS

The easiest thing to do for you is to use information theory (including AIC and BIC) to compare models.

*Both use estimated likelihoods of a model*

# COMPARING MODELS

The easiest thing to do for you is to use information theory (including AIC and BIC) to compare models.

*Both use estimated likelihoods of a model*

The lower the AIC or BIC, the better. This is how you calculate them (using python syntax):



# COMPARING MODELS

The easiest thing to do for you is to use information theory (including AIC and BIC) to compare models.

*Both use estimated likelihoods of a model*

The lower the AIC or BIC, the better. This is how you calculate them (using python syntax):

- $\text{residuals} = \text{Observations} - \text{Predictions}$
- $\text{rss} = \text{sum}(\text{residuals} ** 2)$
- Then, AIC is  $n * \log((2 * \pi) / n) + n + 2 + n * \log(\text{rss}) + 2 * k$   
(*what is n and k?*)
- And BIC is  $n + n * \log(2 * \pi) + n * \log(\text{rss} / n) + (\log(n)) * (k + 1)$
- For both AIC and BIC, If model **A** has AIC lower by 2-3 or more than model **B**, it's better — Differences of less than 2-3 don't really matter

# COMPARING MODELS

The easiest thing to do for you is to use information theory (including AIC and BIC) to compare models.

*Both use estimated likelihoods of a model*

The lower the AIC or BIC, the better. This is how you calculate them (using python syntax):

- $\text{residuals} = \text{Observations} - \text{Predictions}$
- $\text{rss} = \text{sum}(\text{residuals} ** 2)$
- Then, AIC is  $n * \log((2 * \pi) / n) + n + 2 + n * \log(\text{rss}) + 2 * k$   
(*what is n and k?*)
- And BIC is  $n + n * \log(2 * \pi) + n * \log(\text{rss} / n) + (\log(n)) * (k + 1)$
- For both AIC and BIC, If model **A** has AIC lower by 2-3 or more than model **B**, it's better — Differences of less than 2-3 don't really matter

Also note that:

- $R^2 = 1 - (\text{rss}/\text{tss})$ , where tss is total sum of squares:  
 $\text{tss} = \text{sum}((\text{Observations} - \text{mean}(\text{Predictions})) ** 2)$   
(a useful measure of goodness of fit – you should report it)

# READINGS

- Levins, R. 1966 The strategy of model building in population biology. *Am. Sci.* 54, 421–431.
- Johnson, J. B. & Omland, K. S. 2004 Model selection in ecology and evolution. *Trends Ecol. Evol.* 19, 101–108.
- For the suggested fitting TPCs project: Papers in the `Temperature_response_papers` directory, but especially Schoolfield, R. M., Sharpe, P. J. & Magnuson, C. E. 1981 Non-linear regression of biological temperature-dependent rate models based on absolute reaction-rate theory. *J. Theor. Biol.* 88, 719–31.