

Headers

h1 Heading

h2 Heading

h3 Heading

h4 Heading

h5 Heading

h6 Heading

Alternatively, for H1 and H2, an underline-ish style:

Alt-H1

Alt-H2

```
# h1 Heading 8-)
## h2 Heading
### h3 Heading
#### h4 Heading
#####
##### h5 Heading
#####
##### h6 Heading
```

Alternatively, for H1 and H2, an underline-ish style:

Alt-H1

=====

Alt-H2

=====

Emphasis

Emphasis, aka italics, with **asterisks** or **underscores**.

Strong emphasis, aka bold, with **asterisks** or **underscores**.

Combined emphasis with **asterisks and underscores**.

Strikethrough uses two tildes. ~~Scratch this.~~

This is bold text

This is bold text

This is italic text

This is italic text

~~Strikethrough~~

Emphasis, aka italics, with ***asterisks*** or **_underscores_**.

Strong emphasis, aka bold, with ****asterisks**** or **__underscores__**.

Combined emphasis with ****asterisks and _underscores_****.

Strikethrough uses two tildes. ~~Scratch this.~~~~

****This is bold text****

This is bold text

This is italic text

This is italic text

~~~~Strikethrough~~~~

# Extended emphasis

19<sup>th</sup>

H<sub>2</sub>O

Inserted text

## Marked text

```
19^th^  
H~2~O  
++Inserted text++  
==Marked text==
```

# Lists

1. First ordered list item
2. Another item
  - Unordered sub-list.
    1. Actual numbers don't matter, just that it's a number
      1. Ordered sub-list
  - 4. And another item.

You can have properly indented paragraphs within list items. Notice the blank line above, and the leading spaces (at least one, but we'll use three here to also align the raw Markdown).

To have a line break without a paragraph, you will need to use two trailing spaces. Note that this line is separate, but within the same paragraph. (This is contrary to the typical GFM line break behaviour, where trailing spaces are not required.)

- Unordered list can use asterisks
  - Or minuses
  - Or pluses
1. Make my changes
    1. Fix bug
    2. Improve formatting
      - Make the headings bigger
  2. Push my commits to GitHub
  3. Open a pull request

3.
  - Describe my changes
  - Mention all the members of my team
    - Ask for feedback
  - Create a list by starting a line with +, -, or \*
  - Sub-lists are made by indenting 2 spaces:
    - Marker character change forces new list start:
      - Ac tristique libero volutpat at
      - Facilisis in pretium nisl aliquet
      - Nulla volutpat aliquam velit
  - Very easy!

1. First ordered list item
2. Another item
  - \* Unordered sub-list.
    1. Actual numbers don't matter, just that it's a number
      1. Ordered sub-list
  - 4. And another item.

You can have properly indented paragraphs within list items. Notice the blank line above, and the leading spaces (at least one, but we'll use three here to also align the raw Markdown).

To have a line break without a paragraph, you will need to use two trailing spaces.

Note that this line is separate, but within the same paragraph.  
(This is contrary to the typical GFM line break behaviour, where trailing spaces are not required.)

- \* Unordered list can use asterisks
- Or minuses
- + Or pluses

1. Make my changes
  1. Fix bug
  2. Improve formatting
    - Make the headings bigger
2. Push my commits to GitHub
3. Open a pull request
  - \* Describe my changes

- \* Mention all the members of my team
  - \* Ask for feedback
- + Create a list by starting a line with `+`, `-`, or `\*`
- + Sub-lists are made by indenting 2 spaces:
  - Marker character change forces new list start:
    - \* Ac tristique libero volutpat at
    - + Facilisis in pretium nisl aliquet
    - Nulla volutpat aliquam velit
- + Very easy!

## Task lists

- Finish my changes
  - Push my commits to GitHub
  - Open a pull request
  - @mentions, #refs, [links](#), **formatting**, and <del>tags</del> supported
  - list syntax required (any unordered or ordered list supported)
  - this is a complete item
  - this is an incomplete item
- 
- [x] Finish my changes
  - [ ] Push my commits to GitHub
  - [ ] Open a pull request
  - [x] @mentions, #refs, [links](), \*\*formatting\*\*, and <del>tags</del> supported
  - [x] list syntax required (any unordered or ordered list supported)
  - [x] this is a complete item
  - [ ] this is an incomplete item

## Ignoring Markdown formatting

You can tell GitHub to ignore (or escape) Markdown formatting by using \ before the Markdown character.

Let's rename \*our-new-project\* to \*our-old-project\*.

```
Let's rename \*our-new-project\* to \*our-old-project\*.
```

# Links

[I'm an inline-style link](#)

[I'm an inline-style link with title](#)

[I'm a reference-style link](#)

[I'm a relative reference to a repository file](#)

[You can use numbers for reference-style link definitions](#)

Or leave it empty and use the [link text itself](#).

URLs and URLs in angle brackets will automatically get turned into links.<http://www.example.com> or <http://www.example.com> and sometimes [example.com](http://www.example.com) (but not on Github, for example).

Some text to show that the reference links can follow later.

```
[I'm an inline-style link] (https://www.google.com)
```

```
[I'm an inline-style link with title] (https://www.google.com "Google's Homepage")
```

```
[I'm a reference-style link] [Arbitrary case-insensitive reference text]
```

```
[I'm a relative reference to a repository file] (.../blob/master/LICENSE)
```

```
[You can use numbers for reference-style link definitions] [1]
```

Or leave it empty and use the [link text itself].

URLs and URLs in angle brackets will automatically get turned into links. <http://www.example.com> or <<http://www.example.com>> and sometimes [example.com](http://www.example.com) (but not on Github, for example).

Some text to show that the reference links can follow later.

```
[arbitrary case-insensitive reference text]: https://www.mozilla.org  
[1]: http://slashdot.org
```

[link text itself]: <http://www.reddit.com>

---

# Images



Inline images:



Inline-style:



Reference-style:



Like links, Images also have a footnote style syntax



200 × 200

With a reference later in the document defining the URL location:

---

Inline images:

Inline-style:

```
![48x48 image] (https://placehold.co/48.jpg "Logo Title Text 1")
```

Reference-style:

```
![48x48 image] [logo]
```

```
[logo]: https://placehold.co/48.jpg "Logo Title Text 2"
```

```
![200x200 image] (https://placehold.co/200.jpg)
```

```
![200x200 image with title] (https://placehold.co/200.jpg "The title")
```

Like links, Images also have a footnote style syntax

```
![200x200 image with reference] [id]
```

With a reference later in the document defining the URL location:

```
[id]:https://placehold.co/200.jpg "The title"
```

## Code and Syntax Highlighting

Inline code has back-ticks around it.

```
Inline `code` has `back-ticks around` it.
```

```

var text =
@"# Hello, world!
*Greetings* from **markdown**!
> Hello, back!";

var document = Document.Create(container =>
{
    container.Page(page =>
    {
        page.Margin(20);
        page.Content().Markdown(text);
    });
});

```

# Tables

Colons can be used to align columns.

| Tables        | Are           | Cool   |
|---------------|---------------|--------|
| col 3 is      | right-aligned | \$1600 |
| col 2 is      | centered      | \$12   |
| zebra stripes | are neat      | \$1    |

There must be at least 3 dashes separating each header cell. The outer pipes (|) are optional, and you don't need to make the raw Markdown line up prettily. You can also use inline Markdown.

| Markdown     | Less                           | Pretty        |
|--------------|--------------------------------|---------------|
| <i>Still</i> | renders                        | <b>nicely</b> |
| 1            | 2                              | 3             |
| First Header | Second Header                  |               |
| Content Cell | Content Cell                   |               |
| Content Cell | Content Cell                   |               |
| Command      | Description                    |               |
| git status   | List all new or modified files |               |

|          |                                                |
|----------|------------------------------------------------|
| git diff | Show file differences that haven't been staged |
|----------|------------------------------------------------|

| Command    | Description                                           |
|------------|-------------------------------------------------------|
| git status | List all <i>new or modified</i> files                 |
| git diff   | Show file differences that <b>haven't been</b> staged |

| Left-aligned | Center-aligned | Right-aligned |
|--------------|----------------|---------------|
| git status   | git status     | git status    |
| git diff     | git diff       | git diff      |

| Name     | Character |
|----------|-----------|
| Backtick | '         |
| Pipe     |           |

Colons can be used to align columns.

|               |               |        |  |
|---------------|---------------|--------|--|
| Tables        | Are           | Cool   |  |
| -----         | -----:        | ----:  |  |
| col 3 is      | right-aligned | \$1600 |  |
| col 2 is      | centered      | \$12   |  |
| zebra stripes | are neat      | \$1    |  |

There must be at least 3 dashes separating each header cell.  
 The outer pipes (|) are optional, and you don't need to make the raw Markdown line up prettily. You can also use inline Markdown.

```
Markdown | Less | Pretty
--- | --- | ---
*Still* | `renders` | **nicely**
1 | 2 | 3
```

|              |               |  |
|--------------|---------------|--|
| First Header | Second Header |  |
| -----        | -----         |  |
| Content Cell | Content Cell  |  |
| Content Cell | Content Cell  |  |

|         |             |  |
|---------|-------------|--|
| Command | Description |  |
|---------|-------------|--|

|                                                                 |              |                |               |
|-----------------------------------------------------------------|--------------|----------------|---------------|
| ---   ---                                                       |              |                |               |
| git status   List all new or modified files                     |              |                |               |
| git diff   Show file differences that haven't been staged       |              |                |               |
|                                                                 | Command      | Description    |               |
| ---   ---                                                       |              |                |               |
| `git status`   List all *new or modified* files                 |              |                |               |
| `git diff`   Show file differences that **haven't been** staged |              |                |               |
|                                                                 | Left-aligned | Center-aligned | Right-aligned |
| :---                                                            | :---:        | ---:           |               |
| git status                                                      | git status   | git status     |               |
| git diff                                                        | git diff     | git diff       |               |
|                                                                 | Name         | Character      |               |
| ---                                                             | ---          |                |               |
| Backtick                                                        | `            |                |               |
| Pipe                                                            | \            |                |               |

## Blockquotes

Blockquotes are very handy in email to emulate reply text. This line is part of the same quote.

Quote break.

This is a very long line that will still be quoted properly when it wraps. Oh boy let's keep writing to make sure this is long enough to actually wrap for everyone. Oh, you can put **Markdown** into a blockquote.

Blockquotes can also be nested...

...by using additional greater-than signs right next to each other...

...or with spaces between arrows.

```
> Blockquotes are very handy in email to emulate reply text.
> This line is part of the same quote.
```

Quote break.

```
> This is a very long line that will still be quoted properly when it
wraps. Oh boy let's keep writing to make sure this is long enough to
actually wrap for everyone. Oh, you can *put* **Markdown** into a
blockquote.
```

```
> Blockquotes can also be nested...
>> ...by using additional greater-than signs right next to each other...
> > > ...or with spaces between arrows.
```

---

## Inline HTML

```
<dl><dt>Definition list</dt><dd>Is something people use sometimes.</dd>
<dt>Markdown in HTML</dt><dd>Does not work very well. Use HTML <em>tags</em>.</dd></dl>
```

```
<dl>
  <dt>Definition list</dt>
  <dd>Is something people use sometimes.</dd>

  <dt>Markdown in HTML</dt>
  <dd>Does *not* work **very** well. Use HTML <em>tags</em>.</dd>
</dl>
```

---

## Horizontal Rules

Three or more...

---

Hyphens

---

Asterisks

---

Underscores

```
Three or more...
```

---

Hyphens

\*\*\*

Asterisks

—

## Underscores

---