

Web Portfolio Template Setup Guide

This guide explains how to set up the web-portfolio project locally and connect it to a Supabase database. Follow these steps to deploy your custom instance of the portfolio.

1. Prerequisites & Local Installation

Ensure you have Node.js installed before starting.

1. **Install Node.js:** Download and install the LTS version of Node.js from nodejs.org.
2. **Open the Project Terminal:** Open a command prompt or terminal and change directory into the root of the cloned repository:

```
cd web-portfolio
```

3. **Install Node Dependencies:** Run npm install to download React, Next.js, and required dependencies:

```
npm install
```

2. Supabase Database Integration Setup

The portfolio fetches all resume details, project screenshots, skills, and certifications dynamically from a Supabase PostgreSQL backend.

Step A: Create a Supabase Project

- Go to supabase.com, sign up or log in, and click **New Project**.
- Assign your project a name, safe database password, and choose a host region close to you.
- Wait 2–3 minutes for the database instance to provision.

Step B: Set Up Schema & Seed Mock Data

- In your Supabase dashboard, click on the **SQL Editor** tab (represented by a console terminal icon on the left navigation sidebar).
- Click **New Query** to open a blank editor console.
- Locate the `supabase_schema.sql` file in the `docs/` folder of the project codebase. Copy all of its SQL contents and paste it into your Supabase SQL editor.
- Click **Run** in the bottom right corner of the page. This SQL command will:
 - Generate all tables (`profile` , `skills` , `projects` , `certifications` , `seminars` , `experience` , `education`).
 - Enable Row Level Security (RLS) policies allowing public read access, while restricting modify/write access to authenticated dashboard users.
 - Populate initial mock items so the portfolio is pre-loaded with templates.

Step C: Configure Next.js Environment Variables

- In your Supabase dashboard, go to **Project Settings** (gear icon in the sidebar) -> **API**.
- Copy the **Project URL** and the **anon public API key** (starts with `eyJ...`).
- In your local project folder, create a file named `.env.local` and paste the keys in this exact format:

```
NEXT_PUBLIC_SUPABASE_URL=paste_your_project_url_here
NEXT_PUBLIC_SUPABASE_ANON_KEY=paste_your_anon_public_key_here
```

Security Note

Never push your `.env.local` file or database keys to Github. This file is already excluded via `.gitignore`.

3. Launching and Running the Project

Once configuration is complete, you can launch the app locally.

1. Start the development server:

```
npm run dev
```

2. Open your browser and navigate to **http://localhost:3000** to see the website running.
3. To manage database records, go to **http://localhost:3000/admin** to log in and make live updates directly from the admin dashboard GUI.

4. Customizing Asset Files

- Store custom profile photos, favicon icons, and resume PDFs inside the `public/` folder.
- Replace default files like `/Formal_Picture.jpg` and `/resume.pdf` with your own files or edit the URLs on your Admin Profile settings page.