How to Change the Database Connection String (Encrypted)

Overview

The application stores the database connection string encrypted inside appsettings.json. If you need to change the database server or database name, you must generate a new encrypted connection string and update the configuration.

Step 1 — Prepare the new connection string

Create the new connection string you want to use.

Example:

```
Server=.;Database=LuftBornTaskDb;Trusted_Connection=True;TrustServerCertificate=True
```

Step 2 — Temporarily enable encryption in Program.cs

Open Program.cs and uncomment the encryption code:

```
var encrypted = EncryptionHelper.Encrypt(

"Server=.;Database=LuftBornTaskDb;Trusted_Connection=True;TrustServerCertificate=True");


Console.WriteLine(encrypted);
```

Step 3 — Run the application

Run the project. The console will output an encrypted value. Copy the generated encrypted string.

Step 4 — Update appsettings.json

Open appsettings.json and replace the DefaultConnection value with the encrypted string.

Example:

```
"ConnectionStrings": {

  "DefaultConnection": "PASTE_ENCRYPTED_VALUE_HERE"

}
```

Important rules:

- Do not modify the encrypted string

- Do not add spaces or line breaks

Step 5 — Comment the encryption code again

After generating the encrypted value, comment the encryption code again in Program.cs.
The application should only decrypt the connection string at runtime.

Step 6 — Run the application again

Run the application to verify:

- The application starts successfully

- The database connection works

- No Base64 or decryption errors occur

Final Flow

New Connection String -> Encrypt once -> Copy encrypted value -> Paste in appsettings.json -> Application decrypts at runtime