

MSP Report Builder

Setup Guide · August 2026

Per-tenant Microsoft Entra ID app registration and Graph API permission setup.

Overview

The MSP Report Builder pulls live data from Microsoft Graph API on behalf of each client tenant. To do this securely, an App Registration must be created in each client's Microsoft Entra ID tenant, granting 12 read-only Graph API permissions. This guide walks through that setup step by step for a brand new tenant.

Once configured, the client's Tenant ID, Client ID, and Client Secret are entered into the report builder at <https://integricitymsp.netlify.app>. This is a one-off setup per client — once complete, generating a report each month takes only a few minutes.

Estimated time: 10-15 minutes per tenant. Requires Global Administrator access to the client's Microsoft 365 tenant for at least the admin consent step.

Prerequisites

- Access level: Global Administrator or Privileged Role Administrator in the client's tenant. Admin consent (Step 6) specifically requires Global Administrator.
- Microsoft 365 licences: the client must have Microsoft 365 Business Premium, E3, or E5 (or Intune standalone)
- Intune: Microsoft Intune must be active with enrolled devices present in the tenant
- Browser: any modern browser with access to entra.microsoft.com

Step-by-Step Setup

Step 1 — Sign in to Microsoft Entra admin centre

Navigate to entra.microsoft.com and sign in with a Global Administrator account for the client tenant.

Step 2 — Create a new App Registration

Go to Applications → App registrations → New registration, and fill in the form:

- Name: Integricity MSP Report Builder (or any recognisable name)
- Supported account types: Accounts in this organisational directory only (Single tenant)
- Redirect URI: leave blank — not required for the client credentials flow

Click Register.

Step 3 — Note your Tenant ID and Client ID

After registering, you land on the app's Overview page. Note down:

- Application (client) ID — this is the Client ID
- Directory (tenant) ID — this is the Tenant ID

Step 4 — Create a Client Secret

Go to Certificates & secrets → Client secrets → New client secret.

- Description: Integricity MSP Report Builder
- Expires: choose 12 or 24 months (set a calendar reminder to renew before expiry)

Click Add.

Copy the secret Value immediately after creation. It will not be shown again. The Secret ID is not what you need — copy the Value column.

Step 5 — Add API permissions

Go to API permissions → Add a permission → Microsoft Graph → Application permissions, and search for and add each of the following:

Permission	Used for	Status
DeviceManagementManagedDevices.Read.All	Device inventory, compliance, patch status, encryption, disk space, device types	Required
DeviceManagementConfiguration.Read.All	Compliance policies	Required
DeviceManagementApps.Read.All	App protection (MAM) policies	Required
Policy.Read.All	Conditional Access policies, security defaults, authentication methods	Required
SecurityEvents.Read.All	Microsoft Secure Score	Required
IdentityRiskyUser.Read.All	Entra ID Protection — risky user accounts	Required
AuditLog.Read.All	User last sign-in dates, sign-ins from outside AU/NZ/MY	Required
User.Read.All	User list, guest count, licence assignments, shared mailboxes, inactive accounts	Required
RoleManagement.Read.Directory	Admin role holders and their role names	Required
Reports.Read.All	SharePoint usage — site count, storage used, inactive sites	Required
Organization.Read.All	Licence subscriptions — used vs available counts	Required
Group.Read.All	Microsoft 365 Group and Security Group counts	Required

Step 6 — Grant admin consent

Click the Grant admin consent for [Tenant Name] button, then confirm the dialog. All 12 permissions should show a green tick with status "Granted for [Tenant Name]".

If you do not see the "Grant admin consent" button, you do not have sufficient privileges. Ask a Global Administrator to complete this step.

Step 7 — Test the connection

Open <https://integricitymsp.netlify.app> and enter the three values from Steps 3 and 4:

Field	Where to find it
Tenant ID	App registration Overview page → Directory (tenant) ID
Client ID	App registration Overview page → Application (client) ID
Client Secret	Certificates & secrets → Client secrets → Value (copied in Step 4)

Enter the client's display name, click Save & continue, then click Pull data. If the setup is correct, KPI cards will populate within a few seconds across every section. If any section is blank, see the Troubleshooting table below.

Saved credentials are stored in the browser's local storage on the device you are using — not on Integricity's servers, and not synced between devices. If you set up a client on your laptop, those saved credentials will not appear if you open the report builder on a different computer or in a different browser.

Security Notes

- Application permissions, not delegated: the app registration operates as a service identity — no user needs to be signed in when data is pulled.
- Credentials are session-only: Tenant ID, Client ID, and Client Secret are held in browser memory (and optionally browser local storage, per the note above) — never sent to or stored on Integricity's servers.
- All permissions are read-only: no write permissions are requested. The app cannot modify any data in the client tenant.
- Secret rotation: client secrets expire after the period chosen at creation. Set a recurring calendar reminder 2 weeks before expiry.
- Principle of least privilege: only the 12 permissions listed above are required. Do not grant additional permissions.
- Audit trail: every API call made by the app registration appears in the client's own Entra ID sign-in logs, attributed to the app name.

Troubleshooting

Client Secret Renewal

Client secrets expire after the period chosen at creation (12 or 24 months). When a secret expires, the report builder will return an authentication error. To renew:

- 1. Sign in to entra.microsoft.com for the client tenant
- 2. Go to App registrations → Integricity MSP Report Builder → Certificates & secrets
- 3. Click New client secret, set description and expiry, click Add
- 4. Copy the new Value immediately
- 5. Update your secure record for this client's credentials
- 6. Delete the old expired secret (optional but recommended)

Symptom	Fix
Authentication failed	Check the Tenant ID, Client ID, and Client Secret are correct. Ensure the secret has not expired. Try generating a new secret.
Secure Score not showing	Requires SecurityEvents.Read.All. Verify admin consent was granted for this permission.
Licence count shows no available total	Requires Organization.Read.All with admin consent. Without it, only the assigned count is shown (e.g. "73") with no available total or progress bar.
SharePoint data unavailable	Requires Reports.Read.All. Confirm admin consent is granted. Data can take up to 48 hours to populate in new tenants.
Risky users not showing	Requires IdentityRiskyUser.Read.All, and the tenant must have Microsoft Entra ID P2 or Microsoft 365 E5 licences.
Sign-in logs empty	Requires AuditLog.Read.All. Logs are retained 30 days on most tiers (90 days with Entra ID P2). No overseas sign-ins in the period also results in an empty list.
User data not showing	Requires User.Read.All with admin consent granted.
Shared mailbox count seems too low or high	Shared mailboxes are detected as enabled, non-guest, mail-enabled accounts with no licence assigned — this is an inferred count, not a Graph API mailbox type flag.
Admin roles not showing	Requires RoleManagement.Read.Directory with admin consent granted.
Licence names showing as GUIDs	Requires User.Read.All (for subscribedSkus). If still showing GUIDs after granting consent, regenerate the report.
M365 Group / Security Group counts missing	Requires Group.Read.All with admin consent granted.
Forbidden on all data	Admin consent has not been granted. Return to API permissions and click Grant admin consent for [Tenant Name].
Saved credentials missing on a different computer	Expected — saved credentials live in that browser's local storage on that device only. Re-enter the three values on the new device.