Solution of Exercise Sheet 2

Exercise 1 (Classifications of Operating Systems)

1. At any given moment, only a single program can be executed. What is the technical term for this operation mode?

Singletasking.

2. What are half multi-user operating systems?

Different users can work with the system only one after the other, but the data and processes of the different users are protected from each other.

3. What is the difference between 8 bit, 16 bit, 32 bit and 64 bit operating systems?

The bit number indicates the memory address length, with which the operating system works internally.

4. What are the essential criteria of real-time operating systems?

Response time (short latency) and deadlines must be met.

5. Name the two types of real-time operating systems.

Hard real-time operating systems and soft real-time operating systems.

6. Name four typical application areas of real-time operating systems and assign each application area to one of the categories of subtask 5.

Typical application areas of real-time operating systems: Welding robot, reactor control, Anti-lock braking system (ABS), aircraft flight control, monitoring systems of an intensive care unit,...

Typical applications of soft real-time operating systems: Telephone system, parking ticket vending machine, ticket machine, multimedia applications such as audio/video on demand,...

7. Describe the structure of a thin kernel.

The operating system kernel itself runs as a process with lowest priority. The real-time kernel does the scheduling. Real-time processes have the highest priority \Longrightarrow minimum reaction time (latency).

8. Describe the structure of a nano kernel.

In addition to the real-time kernel, any number of kernels of other operating systems may be executed.

Content: Topics of slide set 2 Page 1 of 10

9. Describe the structure of a monolithic kernel.

Monolithic kernels contain functions for...

- memory management
- process management
- interprocess communication
- hardware management (drivers)
- file systems

Outside the kernel are the user processes.

10. Describe the structure of a microkernel.

The kernel contains only...

- essential functions for memory management and process management
- functions for process synchronization and interprocess communication
- essential drivers (e.g. for system start)

Device drivers, file systems, and services (servers) are located outside the kernel and run equal to the user applications in user mode.

11. Describe the structure of a hybrid kernel.

- Grown stability

• Drawbacks:

Hybrid kernels are a tradeoff between monolithic kernels and microkernels. They contain for performance reasons some components, which are never located inside microkernels. It is not specified which additional components are located inside hybrid kernels.

12.	GNU HURD implements a				
	\Box monolithic kernel	\boxtimes microkernel	\Box hybrid kernel		
13.	Linux implements a				
	\boxtimes monolithic kernel	\square microkernel	\Box hybrid kernel		
14.	MacOS X implements a				
	\square monolithic kernel	\square microkernel	\boxtimes hybrid kernel		
15.	Windows NT4/Vista/XP/	7/8/10 implements a.			
	\square monolithic kernel	\square microkernel	\boxtimes hybrid kernel		
16.	Name one advantage and o	one drawback of mono	lithic kernels.		
	• Advantages: - Fewer context sw.	$itching \Longrightarrow better per$	rformance		

Content: Topics of slide set 2 Page 2 of 10

- Crashed components can not be started separately in the kernel and may cause the entire system to crash
- Kernel extensions cause a high development effort, because for each compilation of the extension, the complete kernel need to be recompiled
- 17. Name one advantage and one drawback of microkernels.
 - Advantages:
 - Components can be exchanged easily
 - Best stability and security in theory, because fewer functions run in kernel mode
 - Drawbacks:
 - Slower because of more context switches
 - Development of a new (micro)kernel is a complex task
- 18. Name one advantage and one drawback of hybrid kernels.
 - Advantages:
 - Better performance as with microkernels (because fewer context switching)
 - The stability is (theoretically) better as with monolithic kernels
 - Drawbacks:
 - Development of a new (hybrid)kernel is a complex task
- 19. Your colleague recommends you to relocate frequently used server daemons, such as web server, email server, SSH server and FTP server, from user mode to kernel mode. How do you feel about this idea? Give reasons for your answer. Name a benefit and a drawback.

One advantage would be that the operating system and the server daemons overall perform better, because in the scenario described, fewer context switches between user mode and kernel mode are required.

More serious, however, is the resulting drawback. There is a security risk. Complex software such as server daemons should not run in kernel mode. Bugs in the server daemons may cause system crashes or allow attackers to gain complete control of the system.

20. What means Single System Image?

Users and their applications do not know that the services they use run on multiple computers.

Exercise 2 (Basic Linux/UNIX commands)

Which command is used to...

Content: Topics of slide set 2 Page 3 of 10

1.	check the man pages?
	man
2.	print out the present working directory in the shell?
	pwd
3.	create a new directory?
	mkdir
4.	navigate to a directory?
	cd
5.	print out the content a directory in the shell?
	ls
6.	create an empty file?
	touch
7.	try to determine the content of a file?
	file
8.	concatenate the content of files with other files and can also be used to prin out the content of a file?
	cat
9.	print out lines from the end of a file in the shell?
	tail
10.	print out lines from the beginning of a file in the shell?
	head
11.	copy files or directories to a different location?
	cp
12.	move files or directories to a different location?
	mv
13.	delete files or directories?
	rm
14.	delete an empty directory?

```
rmdir
15. place a string in the shell?
   echo
16. modify the permissions of the file or directory?
   chmod
17. change the password of a user?
   passwd
18. terminate a session (and thus shell) and allows to specify the return value of
   she shell script?
   exit
19. reboot the system?
   reboot or alternatively shutdown
20. shut the system down?
   halt or alternatively shutdown
21. create a new user?
   adduser
22. delete a user?
   deluser
23. modify a user?
    usermod
24. print out the group memberships of a user?
   groups
25. create a new group?
   groupadd
26. delete a group?
   groupdel
```

27. change a group?

groupmod

28.	change the user (\Longrightarrow ownership) which is associated with a file or directory?
	chown
29.	change the group which is associated with a file or directory?
	chgrp
30.	create a link?
	ln
31.	search a file for lines which contain a search pattern?
	grep
32.	print out a list of running processes in the shell?
	ps
33.	bring a process, running in the backgrund of the shell, into foreground?
	fg
34.	bring a process into the background of the shell?
	bg
35.	kill (terminate) a process?
	kill
36.	kill (terminate) a group of processes?
	killall
37.	specify the priority of a new process?
	nice
38.	modify the priority of an existing process?
	renice

39. print out the process tree in the shell?

pstree

Exercise 3 (Permissions / Access Rights)

The source of this tutorial is:

http://www.ws.afnog.org/afnog2012/unix-intro/presos/permissions-exercises.pdf

Notes

- Commands preceded with \$ imply that you should execute the command as a general user an not as root.
- Commands preceded with # imply that you should working as root with sudo imply that you are executing commands on remote equipment, or within another program.

REFERENCE

If you look at files in a directory using ls -al you will see the permissions for each file and directory. Here is an example:

```
drwxrwxr-x 3 bnc bnc 4096 Feb 25 09:49 directory -rwxr--r- 12 bnc bnc 4096 Feb 16 05:02 file
```

The left column is important. You can view it like this:

Туре	User	Group	Other	Links	Owner	Group	Size	Date	Hour	Name
d	rwx	rwx	r-x	3	bnc	bnc	4096	Feb 25	09:49	directory
-	rwx	r	r	12	bnc	bnc	4096	Feb 16	05:02	file

The directory has r (read), w (write), x (execute) access for the User (= Owner) and Group. For Other it has r (read) and x (execute) access.

The file has r (read), w (write), x (execute) access for User and r (read) only access for everyone else (Group and Other).

You can change permissions with the chmod command. chmod uses a base eight (octal) system to configure permissions. Or, you can use an alternate form to specify permissions by column (User/Group/Other) at a time.

Permissions have values like this:

Permission	Value				
read	4				
write	2				
execute	1				
none	0				
	read write execute				

Content: Topics of slide set 2

Thus you can give permissions to a file using the sum of the values for each permission you wish to give for each column. Here is an example:

Letter	Permission	Value
=======		=====
	none	0
X	execute	1
-M-	write only (rarely used)	2
-MX	write and execute (rare)	3
r	read only	4
r-x	read and execute	5
rw-	read and write	6
rwx	read, write, and execute	7

This is just one column. Since we have three areas of permissions (User, Group, Other), it looks like this, if you want to specify all 3 sets:

Permissions	Numeric equivalent	Description
-rw	600	User has read & execute permission.
-rw-rr	644	User has read & execute. Group and Other have read permission.
-rw-rw-rw-	666	Everyone (User, Group, Other) has read & write permission (dangerous?)
-rwx	700	User has read, write, execute permission.
-rwxr-xr-x	755	User has read, write, execute permission. Rest of the world (Other) has read & execute permission (typical for web pages or 644).
-rwxrwxrwx	777	Everyone has full access (read, write, execute).
-rwxxx	711	User has read, write, execute permission. Group and world have execute permission.
drwx	700	User only has access to this directory. Directories require execute permission to access.
drwxr-xr-x	755	User has full access to directory. Everyone else can see the directory.
drwxxx	711	Everyone can list files in the directory, but Group and Other need to know a filename to do this.

1.) CHANGING FILE PERMISSIONS

If you are logged in as the root user on your machine please do the following to become a normal user.

exit

Your prompt should change and now include a \$ sign.

\$

Please check your username with the command whoami:

\$ whoami

Please create a file and set permissions of the file in various ways.

```
$ cd
$ echo "test file" > working.txt
$ chmod 444 working.txt
```

What does that look like?

\$ ls -lah working.txt

Because the file has no write permission for the owner, the owner can still change the file's permissions. This way, the owner can change the permissions of the file at any time to have write access again.

\$ chmod 644 working.txt

Or, you can do this by using this form of chmod:

\$ chmod u+w working.txt

Note: When you type these commands you should be able to use the tab key for command completion once you've typed the w in the file name working.txt. This will save you a lot of time. It's highly recommended!

To remove the read permission of a file for the user you would do

\$ chmod u-r working.txt

Or, you can do something like this:

\$ chmod 344 working.txt

You probably noticed that you can use the - (minus) sign to remove permissions from a file. Try reading your file:

\$ cat working.txt

Now you cannot read your own file. Please make the file readable again by you with the chmod command. Look at your reference at the start of these tutorial to figure out what permissions are required.

2.) PROGRAM EXECUTION, PRIVILEGES AND SUDO

As a general user you can see that there is a file called /etc/shadow:

\$ ls /etc/shadow

But, you cannot see its contents:

\$ less /etc/shadow

Figure out the permissions of this file.

As a general user, however, you can see the content of the /etc/shadow file if you do the following:

\$ sudo less /etc/shadow

What is sudo? Read about it:

\$ man sudo

Content: Topics of slide set 2 Page 10 of 10