


9th Slide Set
Operating Systems

Prof. Dr. Christian Baun

Frankfurt University of Applied Sciences
(1971–2014: Fachhochschule Frankfurt am Main)
Faculty of Computer Science and Engineering
christianbaun@fb2.fra-uas.de

- At the end of this slide set You know/understand. . .
 - what **critical sections** and **race conditions** are
 - what **synchronization** is
 - how **signaling** influences the execution order of the processes
 - how critical sections can be secured via **blocking**
 - what problems (**starvation** and **deadlocks**) may arise from blocking
 - how **deadlock detection with matrices** works
 - different options to implement **communication** between processes:
 - **Shared memory, Message queues, Pipes, Sockets**
 - different options to implement **cooperation** between processes
 - how critical sections can be protected via **semaphores** (and **mutex**)

Operating Systems



Exercise sheet 9 repeats the contents of this slide set which are relevant for these learning objectives



Interprocess Communication (IPC)

- Processes do not only carry out read and write operations on data, but also:
 - call each other
 - wait for each other
 - coordinate with each other
 - In short: They must **interact** with each other
- Important questions regarding **interprocess communication** (IPC):
 - How can a process transmit information to others?
 - How can multiple processes access shared resources?

Question: What is the situation here with threads?

- For threads, the same challenges and solutions exist as for interprocess communication with processes
- Only the communication between the threads of a process is no problem because they operate in the same address space

Critical Sections – Example: Print Spooler



- The spooling directory is consistent
 - But the entry of **process Y** was overwritten by **process X** and got lost
- Such a situation is called **race condition**

Therac-25: Race Condition with tragic Result (1/2)

- Therac-25 is a linear particle accelerator for the radiation therapy of cancer tumors
- Mid-1980s: In the United States some accidents happened because of poor programming and quality assurance
 - Some patients got an up to 100 times increased radiation dose



Image source: Google image search.
Frequently shown picture in this context.
(author and license: unknown)

An Investigation of the Therac-25 Accidents. Nancy Leveson, Clark S. Turner. IEEE Computer, Vol. 26, No. 7, July 1993, S.18-41
http://courses.cs.vt.edu/~cs3604/lib/Therac_25/Therac_1.html

- A race condition („Texas-Bug“) led to incorrect settings of the device and consequently to increased radiation doses.
 - The control process did not synchronize correctly with the user interface process
 - The error occurred only during a quick input correction (time window: 8 seconds) by the user
 - During testing the error did not occur because experience (routine) was required to operate the device this fast

<https://www.bugsnag.com/blog/bug-day-race-condition-therac-25>

„Once the data entry phase was marked complete, the magnet setting phase began. However, if a specific sequence of edits was applied in the Data Entry phase during the 8 second magnet setting phase, the setting was not applied to the machine hardware, due to the value of the completion variable. The UI would then display the wrong mode to the user, who would confirm the potentially lethal treatment.“


Other interesting sources

Killer Bug. Therac-25: Quick-and-Dirty: <https://www.viva64.com/en/b/0438/>

Killed by a machine: The Therac-25: <https://hackaday.com/2015/10/26/killed-by-a-machine-the-therac-25/>

Cooperation


(= access to common data)



- _____

Signal and Wait

- Better concept: Blocking of process P_B until process P_A has finished section **X**
 - Advantage: No CPU resources are wasted
 - Drawback: Only a single process can wait
 - In literature, this technique is also called **passive waiting**




One way to specify in Linux an execution order with passive waiting, is by using the function `sigsuspend`. Thereby a process blocks itself until another process sends it an appropriate signal (usually `SIGUSR1` or `SIGUSR2`) with the command `kill` (or the system call of the same name) and in this way signals that it should continue working.

Alternative system calls and function calls by which a process can block itself until it is woken up again by a system call are **pause** and **sleep**




-
- The diagram illustrates the implementation of a semaphore using two mutexes and two condition variables. It is divided into three parts:
- Process 1 and Process 2:** Two processes, Process 1 and Process 2, are shown. Each process has a vertical timeline with a light blue shaded region representing its critical section. Process 1's critical section is labeled 'X' and Process 2's is labeled 'Y'. Both processes have a `lock(s)` operation before entering the critical section and an `unlock(s)` operation after exiting. Arrows indicate that both processes can acquire either of the two mutexes.
 - Reset Operation:** A sequence of operations for the `reset s` function:
 - Call `unlock(s)` (indicated by a horizontal line).
 - Dashed line labeled `reset s`.
 - Decision: `process waiting?`
 - If **yes**, call `deblock process`.
 - If **no**, proceed to the next step.
 - Lock Operation:** A sequence of operations for the `lock(s)` function:
 - Call `lock(s)` (indicated by a horizontal line).
 - Dashed line labeled `is s set?`.
 - If **yes**, call `block process` and loop back to `is s set?`.
 - If **no**, call `set s`.

- Prof. Dr. Christian Baun – 9th Slide Set Operating Systems – Frankfurt University of Applied Sciences – WS22/23 14/76

Process 1



Process 2



sigsuspend, kill, pause and sleep

- Alternative 1: Implementation of locking with the signals SIGSTOP (No. 19) and SIGCONT (No. 18)
 - With SIGSTOP another process can be stopped
 - With SIGCONT another process can be reactivated

Locking and Unlocking Processes in Linux (2/2)

- Alternative 2: A local file serves as a locking mechanism for mutual exclusion
 - Each process verifies before entering its critical section whether it can open the file exclusively
 - e.g. with the system call `open` or the standard library function `fopen`
 - If this is not the case, it must pause for a certain time (e.g. with the system call `sleep`) and then try again (**busy waiting**).
 - Alternatively, it can pause itself with `sleep` or `pause` and hope that the process that has already opened the file unblocks it with a signal at the end of its critical section (**passive waiting**)


Summary: Difference between Signaling and Blocking

- **Signaling** specifies the execution order
Example: Execute section X of process P_A before section Y of P_B
- **Blocking / Locking** secures critical sections
The execution order of the critical sections of the processes is not specified! It is just ensured that the execution of critical sections does not overlap

- **Starvation**

- If a process does never remove a lock, the other processes need to wait infinitely long for the release

- If several processes wait for resources, locked by each other, they lock each other mutually
- Because all processes, which are involved in the deadlock, must wait forever, no one can initiate an event that resolves the situation




Source: <https://i.redd.it/vvu6v8pxvue11.jpg>
(author and license: unknown)

Conditions for Deadlock Occurrence

System Deadlocks. E. G. Coffman, M. J. Elphick, A. Shoshani. Computing Surveys, Vol. 3, No. 2, June 1971, P.67-78
http://people.cs.umass.edu/~mcorner/courses/691J/papers/TS/coffman_deadlocks/coffman_deadlocks.pdf

- A deadlock situation can arise if these conditions are all fulfilled
 - **Mutual exclusion**
 - At least 1 resource is occupied by exactly 1 process or is available
 \implies non-sharable
 - **Hold and wait**
 - A process, which currently occupies at least 1 resource, requests additional resources which are being held by another process
 - **No preemption**
 - Resources, which are occupied by a process can not be deallocated by the operating system, but on released by the holding process voluntarily
 - **Circular wait**
 - A cyclic chain of processes exists
 - Each process requests a resource that the next process in the chain occupies.
- If one of these conditions is not fulfilled, no deadlock can occur

- The relations of processes and resources can be visualized using directed graphs
- In this way, deadlocks can also be modeled
 - The nodes of a resource graph are:
 - **Processes:** Are shown as circles
 - **Resources:** Are shown as rectangles
 - An edge from a process to a resource means:
 - The process is blocked because it waits for the resource
 - An edge from a resource to a process means:
 - The process occupies the resource




A good description of resource graphs provides the book **Betriebssysteme – Eine Einführung**, Uwe Baumgarten, Hans-Jürgen Siegart, 6th Edition, Oldenbourg Verlag (2007), Chapter 6

Deadlock Detection with Matrices

- One drawback of deadlock detection with resource graphs is that only individual resources can be represented with it
 - If multiple copies (instances) of a resource exist, then graphs are not suited for the visualisation and detection of deadlocks
 - If multiple copies of a resource exist, a matrices-based algorithm can be used, which requires 2 vectors and 2 matrices
- We specify 2 vectors
 - **Existing resource vector**
 - Indicates the number of existing resources of each class
 - **Available resource vector**
 - Indicates the number of free resources of each class
- Additionally 2 matrices are required
 - **Current allocation matrix**
 - Indicates, which resources are currently occupied by the processes
 - **Request matrix**
 - Indicates, which resource the processes would like to occupy


- Shared Memory
- Message Queues
- Pipes
- Sockets



Shared Memory


- Interprocess communication via a shared memory is also called **memory-based communication**
- **Shared memory segments** are memory areas, which can be accessed by multiple processes
 - These memory areas are located in the address space of multiple processes
- The processes need to coordinate the access operations by themselves and ensure that their memory requests are mutually exclusive
 - A receiver process, cannot read data from the shared memory, before the sender process has finished its current write operation
 - If access operations are not coordinated carefully \implies inconsistencies

In all other forms of interprocess communication, the operating system takes care about the synchronization of the access operations



Shared Memory in Linux/UNIX

- Linux/UNIX operating systems contain a **shared memory table**, which contains information about the existing shared memory segments
 - This information includes: Start address in memory, size, owner (username and group) and privileges



- Advantage: A shared memory segment which is not attached to a process, is not erased by the operating system automatically

When the operating system is rebooted, the shared memory segments and their contents are lost

Working with Shared Memory (System V vs. POSIX)

Linux/UNIX operating systems provide 4 system calls for working with shared memory

- `shmget()`: Create a shared memory segment or access an existing one
- `shmat()`: Attach a shared memory segment to a process
- `shmdt()`: Detach a shared memory segment from a process
- `shmctl()`: Request status information (e.g. privileges) of a shared memory segment, modify or erase it
- The command `ipcs` provides information about existing shared memory segments (System V)

One example of working with shared memory segments in Linux can be found on the website of this course

- Some developers prefer the System V API and Others the POSIX API. ...

C function calls for working with POSIX shared memory segments (some defined in the header file `mman.h`)

- `shm_open()`: Create a shared memory segment or access an existing one
- `ftruncate()`: Specify the size of a shared memory segment
- `mmap()`: Attach a shared memory segment to a process
- `munmap()`: Detach a shared memory segment from a process
- `close()`: Close the descriptor of a shared memory segment Speichersegmente schließen
- `shm_unlink()`: Erase a segment
- In Linux, POSIX shared memory segments can be found in the `/dev/shm` directory

One example of working with POSIX shared memory segments in Linux can be found on the website of this course

1. *Journal of the American Medical Association*, 1997; 277: 1001-1005.

Attach a (System V) Shared Memory Segment (in C)

```

1 #include <sys/types.h>
2 #include <sys/ipc.h>
3 #include <sys/shm.h>
4 #include <stdio.h>
5 #define MAXMEMSIZE 20
6
7 int main(int argc, char **argv) {
8     int shared_memory_id = 12345;
9     int returncode_shmget;
10    char *sharedmempointer;
11
12    // Create shared memory segment or access an existing one
13    returncode_shmget = shmget(shared_memory_id, MAXMEMSIZE, IPC_CREAT | 0600);
14    ...
15
16    // Attach shared memory segment
17    sharedmempointer = shmat(returncode_shmget, 0, 0);
18    if (sharedmempointer==(char *)-1) {
19        printf("Unable to attach the shared memory segment.\n");
20        perror("shmat");
21    } else {
22        printf("The shared memory segment has been attached %p\n", sharedmempointer);
23    }
24 }
25 }

```

```
$ ipcs -m
```

```
----- Shared Memory Segments -----
```

key	shmid	owner	perms	bytes	nattch	status
0x00003039	56393780	bnc	600	20	1	

1. *Journal of Management Studies*, 1997, 34, 1, 1-14.

Prof. Dr. Christian Baun – 9th Slide Set Operating Systems – Frankfurt University of Applied Sciences – WS2223 30/76

Detach a (System V) Shared Memory Segment (in C)

```

1 #include <sys/types.h>
2 #include <sys/ipc.h>
3 #include <sys/shm.h>
4 #include <stdio.h>
5 #define MAXMEMSIZE 20
6
7 int main(int argc, char **argv) {
8     int shared_memory_id = 12345;
9     int returncode_shmget;
10    int returncode_shmdt;
11    char *sharedmempointer;
12
13    // Create shared memory segment or access an existing one
14    returncode_shmget = shmget(shared_memory_id, MAXMEMSIZE, IPC_CREAT | 0600);
15    ...
16
17    // Attach the shared memory segment
18    sharedmempointer = shmat(returncode_shmget, 0, 0);
19    ...
20
21    // Detach the shared memory segment
22    returncode_shmdt = shmdt(sharedmempointer);
23    if (returncode_shmdt < 0) {
24        printf("Unable to detach the shared memory segment.\n");
25        perror("shmdt");
26    } else {
27        printf("The shared memory segment has been detached.\n");
28    }
29 }
30 }

```

Erase a (System V) Shared Memory Segment (in C)


```

1 #include <sys/types.h>
2 #include <sys/ipc.h>
3 #include <sys/shm.h>
4 #include <stdio.h>
5 #define MAXMEMSIZE 20
6
7 int main(int argc, char **argv) {
8     int shared_memory_id = 12345;
9     int returncode_shmget;
10    int returncode_shmctl;
11    char *sharedmempointer;
12
13    // Create shared memory segment or access an existing one
14    returncode_shmget = shmget(shared_memory_id, MAXMEMSIZE, IPC_CREAT | 0600);
15    ...
16
17    // Erase shared memory segment
18    returncode_shmctl = shmctl(returncode_shmget, IPC_RMID, 0);
19    if (returncode_shmctl == -1) {
20        printf("Unable to erase the shared memory segment.\n");
21        perror("semctl");
22    } else {
23        printf("The shared memory segment has been erased.\n");
24    }
25 }
26 }

```


Message Queues

- Are linked lists with messages
- Operate according to the FIFO principle
- Processes can store data inside and pick them up from there
- Benefit: Even after the termination of the process, which created the message queue, the data inside the message queue stays available



Linux/UNIX operating systems provide 4 system calls for working with message queues (System V)

- `msgget()`: Create a message queue or access an existing one
- `msgsnd()`: Write message into message queues (\Rightarrow send operation)
- `msgrcv()`: Read message from message queues (\Rightarrow receive operation)
- `msgctl()`: Request status information (e.g. privileges) of a message queue, modify or erase it
- The command `ipcs` provides information about existing System V message queues

34/76

```

1 #include <stdlib.h>
2 #include <sys/types.h>
3 #include <sys/ipc.h>
4 #include <stdio.h>
5 #include <sys/msg.h>
6 #include <string.h>                                // This header file is required for strcpy()
7
8 struct msgbuf {                                    // Template of a buffer for msgsnd and msgrcv
9     long mtype;                                    // Message type
10    char mtext[80];                                // Send buffer
11 } msg;
12
13 int main(int argc, char **argv) {
14     int returncode_msgget;
15
16     // Create message queue or access an existing one
17     returncode_msgget = msgget(12345, IPC_CREAT | 0600);
18     ...
19
20     msg.mtype = 1;                                  // Specify the message type
21     strcpy(msg.mtext, "Testnachricht");             // Write the message into the send buffer
22
23     // Write a message into the message queue
24     if (msgsnd(returncode_msgget, &msg, strlen(msg.mtext), 0) == -1) {
25         printf("Unable to write the message into the message queue.\n");
26         exit(1);
27     }
28 }

```

- 35/76

Result of writing a Message into a Message Queue

- Before...

```
$ ipcs -q
----- Message Queues -----
key          msqid          owner          perms          used-bytes      messages
0x00003039  98304          bnc            600            0                0
```

- Afterwards...

```
$ ipcs -q
----- Message Queues -----
key          msqid          owner          perms          used-bytes      messages
0x00003039  98304          bnc            600            80             1
```

Pick a Message from a (System V) Message Queue (in C)

```

1 #include <stdlib.h>
2 #include <sys/types.h>
3 #include <sys/ipc.h>
4 #include <stdio.h>
5 #include <sys/msg.h>
6 #include <string.h>           // This header file is required for strcpy()
7 struct msgbuf {              // Template of a buffer for msgsnd and msgrcv
8     long mtype;               // Message type
9     char mtext[80];           // Send buffer
10 } msg;
11
12 int main(int argc, char **argv) {
13     int returncode_msgget, returncode_msgrcv;
14     msg receivebuffer;        // Create a receive buffer
15
16     // Create message queue or access an existing one
17     returncode_msgget = msgget(12345, IPC_CREAT | 0600)
18
19     msg.mtype = 1;            // Pick the first message of type 1
20     // MSG_NOERROR => The message will be truncated when it is too long
21     // IPC_NOWAIT  => Do not block the process if no message exists
22     returncode_msgrcv = msgrcv(returncode_msgget, &msg, sizeof(msg.mtext), msg.mtype,
23                               MSG_NOERROR | IPC_NOWAIT);
24     if (returncode_msgrcv < 0) {
25         printf("Unable to pick a message from the message queue.\n");
26         perror("msgrcv");
27     } else {
28         printf("This message was picked from the message queue: %s\n", msg.mtext);
29         printf("The received message is %i characters long.\n", returncode_msgrcv);
30     }
31 }

```

Erase a (System V) Message Queue (in C)

```

1 #include <stdlib.h>
2 #include <sys/types.h>
3 #include <sys/ipc.h>
4 #include <stdio.h>
5 #include <sys/msg.h>
6
7 int main(int argc, char **argv) {
8     int returncode_msgget;
9     int returncode_msgctl;
10
11     // Create message queue or access an existing one
12     returncode_msgget = msgget(12345, IPC_CREAT | 0600);
13     ...
14
15     // Erase message queue
16     returncode_msgctl = msgctl(returncode_msgget, IPC_RMID, 0);
17     if (returncode_msgctl < 0) {
18         printf("Unable to erase the message queue with the ID %i.\n", returncode_msgget);
19         perror("msgctl");
20         exit(1);
21     } else {
22         printf("The message queue with the ID %i has been erased.\n", returncode_msgget);
23     }
24     exit(0);
25 }

```

One example of working with System V message queues in Linux can be found on the website of this course

Message Queues in Linux (System V vs. POSIX)

- The functions described so far for working with message queues are part of the **System V** interface
- Some developers prefer the System V API and Others the POSIX API... ㄟ(ˊ)ㄏ


C function calls for POSIX message queue specified in the header file `mqueue.h`

- `mq_open()`: Create a message queue or access an existing one
- `mq_send()`: Write (send) a message into a message queue. Blocking operation
- `mq_timedsend()`: Write (send) a message into a message queue. Blocking operation with a timeout
- `mq_receive()`: Read (receive) a message from a message queue. Blocking operation
- `mq_timedreceive()`: Read (receive) a message from a message queue. Blocking operation with a timeout
- `mq_getattr()`: Request the attributes of a message queue. These are: number of messages in the queue, maximum message size, maximum number of messages...
- `mq_setattr()`: Modify the attributes of a message queue
- `mq_notify()`: Notify the process as soon as a message is available
- `mq_close()`: Close a message queue
- `mq_unlink()`: Erase a message queue
- POSIX message queues are created In Linux in the folder `/dev/mqueue`

One example of working with POSIX message queues in Linux can be found on the website of this course

Anonymous Pipes (1/2)

- Pipes can be **anonymous pipes** or **named pipes** (see slide 44)
- An **anonymous pipe**...
 - is a buffered unidirectional communication channel between 2 processes
 - If communication in both directions shall be possible at the same time, 2 pipes are necessary – one for each communication direction
 - operates according to the FIFO principle
 - has a limited capacity
 - Pipe = filled \implies the writing process gets blocked
 - Pipe = empty \implies the reading process gets blocked
 - is created with the system call `pipe()`
 - During this process, the kernel of the operating system creates an Inode (\implies slide set 6) and 2 file descriptors (*handles*)
 - Processes access the access identifiers with `read()` and `write()` system calls (or standard library functions) for reading data from or writing data into the pipe



Anonymous Pipes (2/2)

- When child processes are created with `fork()`, the child processes also inherit access to the file descriptors
- **Anonymous pipes** allow process communication only between closely related processes
 - Only processes, which are closely related via `fork()` can communicate with each other via anonymous pipes
 - If the last process, which has access to an anonymous pipe, terminates, the pipe gets erased by the operating system

Overview of the pipes in Linux/UNIX: `lsuf` | `grep pipe`

Anonymous Pipe Example (in C) – Part 1/2

You can monitor the anonymous pipe in Linux/UNIX via `ls -n -P | grep <PID>` and inside the directory `/proc/<PID>/fd`

```

1  #include <stdio.h>
2  #include <unistd.h>
3  #include <stdlib.h>
4
5  void main() {
6      int pid_of_child;
7      // Create handles for the pipe to read (testpipe[0]) and write (testpipe[1])
8      int testpipe[2];
9
10     // Create anonymous pipe testpipe
11     if (pipe(testpipe) < 0) {
12         printf("Unable to create the anonymous pipe.\n");
13         // Terminate process
14         exit(1);
15     } else {
16         printf("Created the anonymous pipe testpipe.\n");
17     }
18
19     // Create a child process
20     pid_of_child = fork();
21
22     if (pid_of_child < 0) {
23         perror("Unable to create the child process!\n");
24         // Terminate process
25         exit(1);
26     }

```

```

27 // Parent process
28 if (pid_of_child > 0) {
29     printf("Parent process: PID: %i\n", getpid());
30     // Block the read channel of the anonymous pipe testpipe
31     close(testpipe[0]);
32     char message[] = "Testnachricht";
33     // Write the message into the write channel of the anonymous pipe
34     write(testpipe[1], &message, sizeof(message));
35 }
36
37 // Child process
38 if (pid_of_child == 0) {
39     printf("Child process: PID: %i\n", getpid());
40     // Block the write channel of the anonymous pipe testpipe
41     close(testpipe[1]);
42     // Create a receive buffer (80 bytes capacity)
43     char puffer[80];
44     // Read the message from the read channel of the anonymous pipe
45     read(testpipe[0], puffer, sizeof(puffer));
46     printf("Received: %s\n", puffer);
47 }
48 }

```

43/76

Named Pipes

- Processes, which are not closely related with each other, can communicate via **named pipes**
 - These pipes can be accessed by using their names
 - They are created in C by: `mkfifo("<pathname>", <permissions>)`
 - Any process, which knows the name of a pipe, can use the name to access the pipe and communicate with other processes
- The operating system ensures **mutual exclusion**
 - At any time, only a single process can access a pipe
- Named pipes are not erased automatically by the operating system (unlike anonymous pipes)

Named Pipe Example (in C) – Part 1/4

```

1  #include <stdio.h>
2  #include <unistd.h>
3  #include <stdlib.h>
4  #include <fcntl.h>
5  #include <sys/stat.h>
6
7  void main() {
8      int pid_of_child;
9
10     // Create named pipe
11     if (mkfifo("testfifo", 0666) < 0) {
12         printf("Unable to create the named pipe.\n");
13         exit(1);
14     } else {
15         printf("Created the named pipe testfifo.\n");
16     }
17
18     // Create a child process
19     pid_of_child = fork();
20
21     if (pid_of_child < 0) {
22         perror("Unable to create the child process!\n");
23         exit(1);
24     }

```

The function call creates a file system entry named `testfifo` in the current directory. The first letter in the output of the `ls` command shows that `testfifo` is a named pipe.

```
$ ls -la testfifo
```

```
prw-r--r-- 1 bnc bnc 0 1. Feb 10:15 testfifo
```

Named Pipe Example (in C) – Part 2/4

```
25 // Parent process
26 if (pid_of_child > 0) {
27     printf("Parent process: PID: %i\n", getpid());
28
29     // Create the file descriptor (handle) for the pipe
30     int fd;
31
32     // Specify the message to be transferred
33     char message[] = "Testnachricht";
34
35     // Open the named pipe for writing
36     fd = open("testfifo", O_WRONLY);
37
38     // Write the message into the pipe
39     write(fd, &message, sizeof(message));
40
41     // Close the named pipe
42     close(fd);
43 }
```

```

44 // Child process
45 if (pid_of_child == 0) {
46     printf("Child process: PID: %i\n", getpid());
47
48     // Create the file descriptor (handle) for the pipe
49     int fd;
50     // Create a receive buffer
51     char puffer[80];
52
53     // Open the named pipe for reading
54     fd = open("testfifo", O_RDONLY);
55
56     // Read the message from the pipe
57     read(fd, puffer, sizeof(puffer));
58     printf("Received: %s\n", puffer);
59
60     // Close the named pipe
61     close(fd);
62
63     // Erase the named pipe
64     if (unlink("testfifo") < 0) {
65         printf("Unable to erase the named pipe.\n");
66         exit(1);
67     } else {
68         printf("The named pipe has been erased.\n");
69     }
70 }
71 }

```


Named Pipe Example (in C) – Part 4/4

```
$ gcc named_pipe_example.c -o named_pipe_example
$ ./named_pipe_example
Created the named pipe testfifo.
Parent process: PID: 395415
Child process: PID: 395416
Received: Testnachricht
The named pipe has been erased.
```

You can monitor the named pipe in Linux/UNIX via `ls -l | grep <PID>` and inside the directory `/proc/<PID>/fd`

Sockets

- Full duplex-ready alternative to pipes and shared memory
 - Allow interprocess communication in distributed systems
- An user process can request a socket from the operating system and afterwards send and receive data via the socket
 - The operating system maintains all used sockets and the related connection information



- Ports are used for the communication via sockets
 - Port numbers are randomly assigned during connection establishment
 - Port numbers are assigned randomly by the operating system
 - Exceptions are port numbers of well-known applications, such as HTTP (80) SMTP (25), Telnet (23), SSH (22), FTP (21),...
- Sockets can be used in a blocking (synchronous) and non-blocking (asynchronous) way

Different Types of Sockets

- **Connectionless sockets (= datagram sockets)**
 - Use the Transport Layer protocol UDP
 - Advantage: Better data rate as with TCP
 - Reason: Lesser overhead for the protocol
 - Drawback: Segments may arrive in wrong sequence or may get lost
- **Connection-oriented sockets (= stream sockets)**
 - Use the Transport Layer protocol TCP
 - Advantage: Better reliability
 - Segments cannot get lost
 - Segments always arrive in the correct sequence
 - Drawback: Lower data rate as with UDP
 - Reason: More overhead for the protocol


Using Sockets

- Almost all major operating systems support sockets
 - Advantage: Better portability of applications
- Functions for communication via sockets:
 - Creating a Socket:
`socket()`
 - Binding a socket to a port number and making it ready to receive data:
`bind()`, `listen()`, `accept()` and `connect()`
 - Sending/receiving messages via the socket:
`send()`, `sendto()`, `recv()` and `recvfrom()`
 - Closing eines Socket:
`shutdown()` or `close()`

Overview of the sockets in Linux/UNIX: `netstat -n` or `lsof | grep socket`

Examples of Interprocess communication via sockets (TCP and UDP) in Linux can be found on the website of this course

Connection-less Communication via Sockets – UDP



• Client

- Create socket (`socket`)
- Send (`sendto`) and receive data (`recvfrom`)
- Close socket (`close`)

• Server

- Create socket (`socket`)
- Bind socket to a port (`bind`)
- Send (`sendto`) and receive data (`recvfrom`)
- Close socket (`close`)


Connection-oriented Communication via Sockets – TCP

• Client

- Create socket (`socket`)
- Connect client with server socket (`connect`)
- Send (`send`) and receive data (`recv`)
- Close socket (`close`)

• Server

- Create socket (`socket`)
- Bind socket to a port (`bind`)
- Make socket ready to receive (`listen`)
 - Set up a queue for connection requests.
Specifies the number of connection requests, which can be stored in the queue
- Server accepts connections (`accept`)
 - Fetch the first connection request from the queue
- Send (`send`) and receive data (`recv`)
- Close socket (`close`)




Sockets via UDP – Example (Server)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <string.h>
4  #include <sys/socket.h>
5  #include <netinet/in.h>
6  #include <unistd.h>
7  #include <arpa/inet.h>
8
9  int main(int argc, char *argv[]) {
10     int sd, adresse_laenge;
11     char puffer[1024] = { 0 };
12     struct sockaddr_in adresse, client_adresse;
13     memset(&adresse, 0, sizeof(adresse));
14     memset(&client_adresse, 0, sizeof(client_adresse));
15     adresse.sin_family = AF_INET;
16     adresse.sin_addr.s_addr = INADDR_ANY;
17     adresse.sin_port = htons(atoi(argv[1]));
18
19     sd = socket(AF_INET, SOCK_DGRAM, 0);
20     bind(sd, (struct sockaddr *) &adresse, sizeof(adresse));
21     adresse_laenge = sizeof(client_adresse);
22     rcvfrom(sd, (char *)puffer, sizeof(puffer), 0,
23             (struct sockaddr *) &client_adresse, &adresse_laenge);
24     printf("Empfangene Nachricht: %s\n", puffer);
25     char antwort[]="Server: Nachricht empfangen.\n";
26     sendto(sd, (const char *)antwort, sizeof(antwort), 0,
27            (struct sockaddr *) &client_adresse, adresse_laenge);
28     close(sd);
29     exit(0);
30 }

```



```

$ gcc udp_server.c -o udp_server
$ ./udp_server 50002


```

Sockets via UDP – Example (Client)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <string.h>
4  #include <sys/socket.h>
5  #include <netinet/in.h>
6  #include <unistd.h>
7  #include <arpa/inet.h>
8
9  int main(int argc, char *argv[]) {
10     int sd, adresse_laenge;
11     char puffer[1024] = { 0 };
12     struct sockaddr_in adresse;
13     memset(&adresse, 0, sizeof(adresse));
14     adresse.sin_family = AF_INET;
15     adresse.sin_port = htons(atoi(argv[2]));
16     adresse.sin_addr.s_addr = inet_addr(argv[1]);
17
18     sd = socket(AF_INET, SOCK_DGRAM, 0);
19     printf("Bitte Nachricht eingeben: ");
20     fgets(puffer, sizeof(puffer), stdin);
21     adresse_laenge = sizeof(adresse);
22     sendto(sd, (const char *)puffer, strlen(puffer), 0,
23           (struct sockaddr *) &adresse, adresse_laenge);
24     memset(puffer, 0, sizeof(puffer));
25     recvfrom(sd, (char *)puffer, sizeof(puffer), 0,
26            (struct sockaddr *) &adresse, &adresse_laenge);
27     printf("%s\n", puffer);
28     close(sd);
29     exit(0);
30 }

```



```

$ gcc udp_client.c -o udp_client
$ ./udp_client 127.0.0.1 50002
Bitte Nachricht eingeben: Test
Server: Nachricht empfangen.

```

```

$ ./udp_server 50002
Empfangene Nachricht: Test


```

Sockets via TCP – Example (Server)

```

1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <string.h>
4 #include <sys/socket.h>
5 #include <netinet/in.h>
6 #include <unistd.h>
7 #include <arpa/inet.h>
8
9 int main(int argc, char *argv[]) {
10     int sd, fd, adresse_laenge;
11     char puffer[1024] = { 0 };
12     struct sockaddr_in adresse;
13     memset(&adresse, 0, sizeof(adresse));
14     adresse.sin_family = AF_INET;
15     adresse.sin_addr.s_addr = INADDR_ANY;
16     adresse.sin_port = htons(atoi(argv[1]));
17
18     sd = socket(AF_INET, SOCK_STREAM, 0);
19     bind(sd, (struct sockaddr *) &adresse, sizeof(adresse));
20     listen(sd, 5);
21     adresse_laenge = sizeof(adresse);
22     fd = accept(sd, (struct sockaddr *) &adresse, &adresse_laenge);
23     read(fd, puffer, sizeof(puffer));
24     printf("Empfangene Nachricht: %s\n", puffer);
25     char antwort[] = "Server: Nachricht empfangen.\n";
26     write(fd, antwort, sizeof(antwort));
27     close(fd);
28     close(sd);
29     exit(0);
30 }

```




```
$ gcc tcp_server.c -o tcp_server
$ ./tcp_server 50003
```


Sockets via TCP – Example (Client)

```

1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <string.h>
4 #include <sys/socket.h>
5 #include <netinet/in.h>
6 #include <unistd.h>
7 #include <arpa/inet.h>
8
9 int main(int argc, char *argv[]) {
10     int sd;
11     char puffer[1024] = { 0 };
12     struct sockaddr_in adresse;
13     memset(&adresse, 0, sizeof(adresse));
14     adresse.sin_family = AF_INET;
15     adresse.sin_port = htons(atoi(argv[2]));
16     adresse.sin_addr.s_addr = inet_addr(argv[1]);
17
18     sd = socket(AF_INET, SOCK_STREAM, 0);
19     connect(sd, (struct sockaddr *) &adresse, sizeof(adresse));
20
21     printf("Bitte Nachricht eingeben: ");
22     fgets(puffer, sizeof(puffer), stdin);
23     write(sd, puffer, strlen(puffer));
24     memset(puffer, 0, sizeof(puffer));
25     read(sd, puffer, sizeof(puffer));
26     printf("%s\n", puffer);
27
28     close(sd);
29     exit(0);
30 }

```



```
$ gcc tcp_client.c -o tcp_client
$ ./tcp_client 127.0.0.1 50003
Bitte Nachricht eingeben: Test
Server: Nachricht empfangen.
```

```
$ ./tcp_server 50003
Empfangene Nachricht: Test
```


- Semaphore
- Mutex

The diagram shows two separate components, Process 1 and Process 2, each containing a data object (Data 1 and Data 2). A directed arrow labeled 'copy' points from Data 1 to Data 2, indicating a directed relationship between the two data objects.

The diagram shows two processes, Process 1 and Process 2, each with an arrow pointing to a data block. Process 1 points to 'Data 1' and Process 2 points to 'Data 2'. The two data blocks overlap, with the overlapping region labeled 'common part'. Below the diagram, the text '(symmetric relationship)' is written.

Semaphore

- In order to protect (lock) critical sections, not only the already discussed locks can be used, but also **semaphores**
- 1965: Published by Edsger W. Dijkstra
- A semaphore is a counter lock **S** with operations **P(S)** and **V(S)**
 - **V** comes from the dutch *verhogen* = raise
 - **P** comes from the dutch *proberen* = try (to reduce)
- The **access operations are atomic** \implies can not be interrupted (indivisible)
- May allow multiple processes accessing the critical section
 - In contrast to semaphores, can locks (\implies slide 14) only be used to allow a single process entering the critical section at the same time

Cooperating sequential processes. *Edsger W. Dijkstra* (1965)

<https://www.cs.utexas.edu/~EWD/ewd01xx/EWD123.PDF>

Semaphore Access Operations (1/3)

A Semaphore consists of 2 Data Structures

- **COUNT:** An **integer, non-negative counter variable**.
Specifies how many processes can pass the semaphore now without getting blocked
 - A waiting room for the processes, which **wait** until they are allowed to pass the semaphore
The processes are in blocked state until they are transferred into ready state by the operating system when the semaphore allows to access the critical section
-
- **Initialization:** First, a new semaphore is created or an existing one is opened
 - For a new semaphore, the counter variable is initialized at the beginning with a non-negative initial value

```
1 // apply the INIT operation on semaphore SEM
2 SEM.INIT(unsigned int init_value) {
3
4     // initialize the variable COUNT of Semaphor SEM
5     // with a non-negative initial value
6     SEM.COUNT = init_value;
7 }
```

Image Source: Carsten Vogt

- ```
1 SEM.P() {
2 // if the counter variable = 0, the process becomes blocked
3 if (SEM.COUNT == 0)
4 < block >
5
6 // if the counter variable is > 0, the counter variable
7 // is decremented immediately by 1
8 SEM.COUNT = SEM.COUNT - 1;
9 }
```





Image Source: Carsten Vogt


- If processes are in the waiting room, one process gets deblocked
- The process, which just got deblocked, continues its P operation and first reduces the counter variable

```
1 SEM.V() {
2 // counter variable = counter variable + 1
3 SEM.COUNT = SEM.COUNT + 1;
4
5 // if processes are in the waiting room, one gets deblocked
6 if (< SEM waiting room is not empty >)
7 < deblock a waiting process >
8 }
```




# Producer/Consumer Example (1/3)

- A producer sends data to a consumer
- A buffer with limited capacity is used to minimize the waiting times of the consumer
- Data is placed into the buffer by the producer and the consumer removes data from the buffer
- Mutual exclusion is mandatory in order to avoid inconsistencies
- Buffer = full  $\implies$  producer must be blocked
- Buffer = empty  $\implies$  consumer must be blocked





Michael Vigneri



Fill in the blanks

<http://www.ccs.neu.edu/home/kenb/tutorial/example.gif>





Image Source: Carsten Vogt

- 
- Diagram illustrating the structure of a semaphore table:
- The **Semaphore table** is indexed by **Group number** (0, 1, 2, 3, ..., n).
  - Each entry in the table points to a **Semaphore group**.
  - The **Semaphore group** contains individual semaphores, indexed by **Semaphore number within the group** (0, 1, 2, 3, 4, 5).
  - Examples of semaphore groups:
    - Group 0:  $S_{00}, S_{01}, S_{02}, S_{03}, S_{04}, S_{05}$
    - Group 1:  $S_{10}, S_{11}$
    - Group 2:  $S_{20}, S_{21}, S_{22}$
    - Group 3:  $S_{30}, S_{31}, S_{32}, S_{33}, S_{34}$
  - The entry for group  $n$  is labeled **empty**.

- `semget()`: Create new semaphore or a group of semaphores or open an existing semaphore
- `semctl()`: Request or modify the value of an existing semaphore or of a semaphore group or erase a semaphore
- `semop()`: Carry out P and V operations on semaphores
- Information about existing semaphores (**System V**) provides the command `ipcs`

This program creates a child process. The parent process and the child process both try to print characters in the command line interface (critical section). Each process may print only one character at a time. Two semaphores are used to ensure mutual exclusion

Helpful documentation of `semget`

69/76

```

25 // Neue Semaphoregruppe 54321 mit einer Semaphore erstellen
26 returncode_semget2 = semget(sem_key2, 1, IPC_CREAT | IPC_EXCL | 0600);
27 if (returncode_semget2 < 0) {
28 printf("Die Semaphoregruppe %i konnte nicht erstellt werden.\n", sem_key2);
29 perror("semget");
30 exit(1);
31 }
32
33 // P-Operation definieren. Wert der Semaphore um eins dekrementieren
34 struct sembuf p_operation = {0, -1, 0};
35
36 // V-Operation definieren. Wert der Semaphore um eins inkrementieren
37 struct sembuf v_operation = {0, 1, 0};
38
39 // Erste Semaphore der Semaphoregruppe 12345 initial auf Wert 1 setzen
40 returncode_semctl = semctl(returncode_semget1, 0, SETVAL, 1);
41
42 // Erste Semaphore der Semaphoregruppe 54321 initial auf Wert 0 setzen
43 returncode_semctl = semctl(returncode_semget2, 0, SETVAL, 0);
44
45 // Initialen Wert der ersten Semaphore der Semaphoregruppe 12345 zur Kontrolle ausgeben
46 output = semctl(returncode_semget1, 0, GETVAL, 0);
47 printf("Wert der Semaphore mit ID %i und Key %i: %i\n", returncode_semget1, sem_key1, output);
48
49 // Initialen Wert der ersten Semaphore der Semaphoregruppe 54321 zur Kontrolle ausgeben
50 output = semctl(returncode_semget2, 0, GETVAL, 0);
51 printf("Wert der Semaphore mit ID %i und Key %i: %i\n", returncode_semget2, sem_key2, output);

```

Helpful documentation of `semctl`

<https://www.nt.th-koeln.de/fachgebiete/inf/diplom/semwork/unix/semctl/semctl.html>

```

52 // Einen Kindprozess erzeugen
53 pid_des_kindess = fork();
54
55 // Kindprozess
56 if (pid_des_kindess == 0) {
57 for (int i=0;i<5;i++) {
58 semop(returncode_semget2, &p_operation, 1); // P-Operation Semaphore 54321
59 // Kritischer Abschnitt (Anfang)
60 printf("B");
61 sleep(1);
62 // Kritischer Abschnitt (Ende)
63 semop(returncode_semget1, &v_operation, 1); // V-Operation Semaphore 12345
64 }
65 exit(0);
66 }
67
68 // Elternprozess
69 if (pid_des_kindess > 0) {
70 for (int i=0;i<5;i++) {
71 semop(returncode_semget1, &p_operation, 1); // P-Operation Semaphore 12345
72 // Kritischer Abschnitt (Anfang)
73 printf("A");
74 sleep(1);
75 // Kritischer Abschnitt (Ende)
76 semop(returncode_semget2, &v_operation, 1); // V-Operation Semaphore 54321
77 }
78 }

```

Helpful documentation of `semop`

<https://www.nt.th-koeln.de/fachgebiete/inf/diplom/semwork/unix/semop/semop.html>

## Simple Semaphore Example (in C) – Part 4/5

```

79 // Warten auf die Beendigung des Kindprozesses
80 wait(NULL);
81
82 printf("\n");
83
84 // Semaphoregruppe 12345 entfernen
85 returncode_semctl = semctl(returncode_semget1, 0, IPC_RMID, 0);
86 if (returncode_semctl < 0) {
87 printf("Die Semaphoregruppe %i konnte nicht entfernt werden.\n", returncode_semget1);
88 exit(1);
89 } else {
90 printf("Die Semaphoregruppe mit ID %i und Key %i wurde entfernt.\n", returncode_semget1, sem_key1);
91 }
92
93 // Semaphoregruppe 54321 entfernen
94 returncode_semctl = semctl(returncode_semget2, 0, IPC_RMID, 0);
95 if (returncode_semctl < 0) {
96 printf("Die Semaphoregruppe %i konnte nicht entfernt werden.\n", returncode_semget2);
97 exit(1);
98 } else {
99 printf("Die Semaphoregruppe mit ID %i und Key %i wurde entfernt.\n", returncode_semget2, sem_key2);
100 }
101
102 exit(0);
103 }

```

One example of working with semaphores in Linux can be found on the website of this course



```
$ gcc semaphore_beispiel_systemv.c -o semaphore_beispiel_systemv
$./semaphore_beispiel_systemv
Wert der Semaphore mit ID 98362 und Key 12345: 1
Wert der Semaphore mit ID 98363 und Key 54321: 0
ABABABABAB
Die Semaphorgruppe mit ID 98362 und Key 12345 wurde entfernt.
Die Semaphorgruppe mit ID 98363 und Key 54321 wurde entfernt.
```

```
$ printf "%d\n" 0x00003039 # Convert from hexadecimal to decimal
12345
$ printf "%d\n" 0x0000d431
54321
```

- 73/76

# Semaphores in Linux (System V vs. POSIX)

- The concept of protecting critical sections described so far is also called **system V semaphores** in the literature
- Some developers prefer the System V API and Others the POSIX API... 🤔

C function calls of the POSIX semaphores specified in the header file `semaphore.h`

- `sem_init()`: Create a new **unnamed** semaphore and thereby specify the initial value
- `sem_open()`: Create a new **named** semaphore and thereby specify the initial value
- `sem_post()`: Increment the value of a semaphore (V operation)
- `sem_wait()`: Decrement the value of a semaphore (P operation). Blocking operation
- `sem_trywait()`: Decrement the value of a semaphore (P operation). Non-blocking operation
- `sem_timedwait()`: Decrement the value of a semaphore (P operation). Blocking operation but with a timeout
- `sem_getvalue()`: Request the value of a semaphore
- `sem_destroy()`: Erase an **unnamed** semaphore
- `sem_close()`: Close a **named** semaphore
- `sem_unlink()`: Erase a **named** semaphore
- Named POSIX semaphores are created in Linux in the folder `/dev/shm` with names of the form `sem.<name>`

One example of working of working with named POSIX semaphores in Linux can be found on the website of this course

# Mutexes

- If the Semaphore-feature of counting is not required, a simplified alternative, the mutex can be used instead
  - **Mutexes** (derived from **Mutual Exclusion**) are used to protect critical sections, which are allowed to be accessed by only **a single process** at any given moment
    - Mutexes can only have 2 states: **occupied** and **not occupied**
    - Mutexes have the same functionality as **binary semaphores**

Several implementations of the mutex concept exist

- **C standard library:** `mtx_init`, `mtx_unlock („V operation“)`, `mtx_lock („P operation“)`, `mtx_trylock`, `mtx_timedlock`, `mtx_destroy`
- **POSIX threads:** `pthread_mutex_init`, `pthread_mutex_unlock`, `pthread_mutex_lock`, `pthread_mutex_trylock`, `pthread_mutex_timedlock`, `pthread_mutex_destroy`
- **C standard library (Sun/Oracle Solaris):** `mutex_init`, `mutex_unlock`, `mutex_lock`, `mutex_trylock`, `mutex_destroy`

- Focus: Cooperation of threads of a process (intra-process synchronization)
  - Cooperation of processes (inter-process synchronization) is not always possible and if, then via a shared memory segment (System V or POSIX)

## Monitor and erase IPC Objects

- Information about existing (**System V**) shared memory segments, (**System V**) message queues and (**System V**) semaphores provides the command `ipcs`
- The easiest way to erase such shared memory segments, message queues and semaphores from the command line is the command `ipcrm`

```
ipcrm [-m shmids] [-q msgids] [-s semids]
 [-M shmkeys] [-Q msgkeys] [-S semkeys]
```

- **POSIX** memory segments and **POSIX** semaphores can be inspected and manually erased in the directory `/dev/shm`
- **POSIX** message queues can be inspected and manually erased in the directory `/dev/mqueue`