

Analyses: Classification with MLP

03/01/2024

Description

Load Packages

If the libraries are not installed yet, you need to install them using, for example, the command: `install.packages("ggplot2")`. For the Hrate package this is different, since it comes from github. The devtools library needs to be installed, and then the `install_github()` function is used.

```
# install the latest version of neuralnet with bug fixes: devtools::install_github("bips-hb/neuralnet")
library(neuralnet)
library(sigmoid)
library(caret)
```

Load Data

Load data table with estimated feature values per sequence.

```
# load feature value estimations
estimations.df <- read.csv("~/Github/UpperPalCombinatorics/results/features/features_combined.csv")
head(estimations.df)
```

```
##      subcorpus      sequence num.char huni.chars hrate.chars  ttr.chars
## 1 Aurignacien ||| /////1 _ V      12  1.8962406   1.5295563  0.4166667
## 2 Aurignacien      vvvvv          5  0.0000000   0.5711903  0.2000000
## 3 Aurignacien      vvvv vvvv       9  0.5032583   0.9060047  0.2222222
## 4 Aurignacien vvvvvvvvvvvvvvv      14  0.0000000   0.6379550  0.07142857
## 5 Aurignacien      |||           3  0.0000000   0.4308271  0.3333333
## 6 Aurignacien      |||           4  0.0000000   0.5070802  0.2500000
##      rm.chars
## 1 0.6363636
## 2 1.0000000
## 3 0.7500000
## 4 1.0000000
## 5 1.0000000
## 6 1.0000000
```

Choose subcorpora for binary classification.

```
# choose subcorpora to compare: "Aurignacien", "TeDDi", "Cuneiform (Uruk V)",
# "Cuneiform (Uruk IV)", "Cuneiform (Uruk III)".
subcorpus1 <- "Aurignacien"
subcorpus2 <- "Cuneiform (Uruk V)"
selected <- c(subcorpus1, subcorpus2)
estimations.subset <- estimations.df[estimations.df$subcorpus %in% selected, ]
```

Remove NAs (whole row)

```
estimations.subset <- na.omit(estimations.subset)
```

Center and scale the data

```
# first three columns are meta information, the others are the feature values  
# be aware that this needs to be changed in case of other table format  
estimations.scaled <- cbind(estimations.subset[, c("subcorpus", "sequence", "num.char")],  
                             scale(estimations.subset[, c("huni.chars", "hrate.chars",  
                                                           "ttr.chars", "rm.chars")]))
```

Create Training and Test Sets

```
# Generating seed  
set.seed(1234)  
# Randomly generating our training and test samples with a respective ratio of 2/3 and 1/3  
datasample <- sample(2, nrow(estimations.scaled), replace = TRUE, prob = c(0.67, 0.33))  
# Generate training set (select rows randomly by using datasample vector)  
train <- estimations.scaled[datasample == 1, 1:ncol(estimations.scaled)]  
# Generate test set  
test <- estimations.scaled[datasample == 2, 1:ncol(estimations.scaled)]
```

Implement MLP classifier

This is partly based on code given at http://uc-r.github.io/ann_classification (last accessed 18.01.2023). The activation function (tanh), error function (SSE), and backpropagation algorithm (rprop+) are here chosen according to the best model performance reported in Bentz (2023).

```
# Generate list of hidden unit architectures (number of layers and units)  
# Choose number of random architectures  
arch.no <- 100  
# initialize empty list of hidden unit architectures  
hidden.list <- vector(mode = "list", length = arch.no)  
set.seed(09012020)  
# run loop to generate number of layers and hidden units randomly  
for (i in 1:arch.no) {  
  layer.no <- round(runif(1, min = 1, max = 4), 0)  
  hidden.units <- round(runif(layer.no, min = 1, max = 5), 0)  
  hidden.list[[i]] <- hidden.units  
}  
  
# Manual list of hidden layer structures (for plotting and experimenting)  
# hidden.list <- list(c(4,4))  
  
# initialize dataframe to append results to  
results.df <- data.frame(hidden.structure = character(0),  
                           hidden.size = numeric(0), hidden.depth = numeric(0),  
                           err.fct = character(0), act.fct.name = character(0),
```

```

        algorithm = character(0), baseline = numeric(0),
        accuracy = numeric(0), accuracy.pvalue = numeric(0),
        precision = numeric(0), recall = numeric(0),
        f1 = numeric(0)
    )

# Custom activation function
# Note that this function only works with err.fct = 'sse'
softplus <- function(x) log(1 + exp(x))

# set random seed for reproducibility
set.seed(123)
# counter
counter <- 0
# start time
start_time <- Sys.time()
for (hidden in hidden.list) {
  # Training
  # choose error function
  err.fct = 'sse' # options: 'sse', 'ce'
  # choose activation function
  act.fct = 'tanh' # options: 'logistic', 'tanh', softplus, relu,
  # beware: the last two options have to be written without quotes ''
  # note: softplus, relu, and tanh only work properly with sse as err.fct
  act.fct.name = 'tanh' # make sure to give name as character string (for later storage)
  # choose algorithm
  algorithm = 'rprop+' # options: 'rprop+', 'rprop-', 'backprop', 'sag', 'slr'
  # train classifier with neuralnet() function
  try({ # if the processing fails for a certain file, there will be no output for this file,
    # but the try() function allows the loop to keep running
    classifier.mlp <- neuralnet(subcorpus == subcorpus1 ~ .,
      data = train[, c("subcorpus",
        "huni.chars",
        "hrate.chars",
        "ttr.chars",
        "rm.chars")],
      hidden = hidden,
      threshold = 0.1, # defaults to 0.01
      rep = 1, # number of reps in which new initial values are used,
        # (essentially the same as a for loop)
      stepmax = 100000, # defaults to 100K
      linear.output = FALSE,
      algorithm = algorithm, # defaults to "rprop+",
        # i.e. resilient backpropagation
      # learningrate = 0.1,
      err.fct = err.fct,
      act.fct = act.fct,
      likelihood = TRUE,
      lifesign = 'minimal')

    classifier.mlp
    # results matrix (each column represents one repetition)
    classifier.mlp$result.matrix
  })
}

```

```

# Prediction
# Get prediction using the predict() function
mlp.predictions <- predict(classifier.mlp, test,
                           rep = which.min(classifier.mlp$result.matrix[1,]), # Predict response values
                           # based on the "best" repetition (epoche), i.e. the one with the lowest error
                           all.units = FALSE)
# assign a label according to the rule that the label is the label of subcorpus1
# if the prediction probability is >0.5, else assign label of subcorpus2.
mlp.predictions.rd <- ifelse(mlp.predictions > 0.5, subcorpus1, subcorpus2)

# Model Evaluation
# creating a dataframe from known (true) test labels
test.labels <- data.frame(test$subcorpus)
# combining predicted and known classes
class.comparison <- data.frame(mlp.predictions.rd, test.labels)
# giving appropriate column names
names(class.comparison) <- c("predicted", "observed")
# inspecting our results table
head(class.comparison)
# get confusion matrix
cm <- confusionMatrix(as.factor(class.comparison$predicted),
                      reference = as.factor(class.comparison$observed))
#print(cm)
# get performance metrics from the output list of confusionMatrix()
baseline <- cm$overall['AccuracyNull']
accuracy <- cm$overall['Accuracy']
accuracy.pvalue <- cm$overall['AccuracyPValue']
f1 <- cm[["byClass"]][["F1"]]
recall <- cm[["byClass"]][["Recall"]]
precision <- cm[["byClass"]][["Precision"]]

# unname and round resulting values
baseline <- round(unname(baseline), 2)
accuracy <- round(unname(accuracy), 2)
accuracy.pvalue <- round(unname(accuracy.pvalue), 2)
f1 <- round(unname(f1), 2)
recall <- round(unname(recall), 2)
precision <- round(unname(precision), 2)

# append results to dataframe
hidden.structure <- paste(unlist(hidden), collapse = ",")
hidden.size <- sum(unlist(hidden))
hidden.depth <- length(hidden)
local.df <- data.frame(hidden.structure, hidden.size,
                      hidden.depth, err.fct, act.fct.name, algorithm,
                      baseline, accuracy, accuracy.pvalue,
                      precision, recall, f1)
results.df <- rbind(results.df, local.df)
})
counter <- counter + 1
print(counter)
}

```

```
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
```

```

## requires numeric/complex matrix/vector arguments
## [1] 1
## [1] 2
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
## requires numeric/complex matrix/vector arguments
## [1] 3
## [1] 4
## [1] 5
## [1] 6
## [1] 7
## [1] 8
## [1] 9
## [1] 10
## [1] 11
## [1] 12
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
## requires numeric/complex matrix/vector arguments
## [1] 13
## [1] 14
## [1] 15
## [1] 16
## [1] 17
## [1] 18
## [1] 19
## [1] 20
## [1] 21
## [1] 22
## [1] 23
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
## requires numeric/complex matrix/vector arguments
## [1] 24
## [1] 25
## [1] 26
## [1] 27
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
## requires numeric/complex matrix/vector arguments
## [1] 28
## [1] 29
## [1] 30
## [1] 31
## [1] 32
## [1] 33
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
## requires numeric/complex matrix/vector arguments
## [1] 34
## [1] 35
## [1] 36
## [1] 37
## [1] 38
## [1] 39
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
## requires numeric/complex matrix/vector arguments
## [1] 40
## [1] 41

```

```

## [1] 42
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
##   requires numeric/complex matrix/vector arguments
## [1] 43
## [1] 44
## [1] 45
## [1] 46
## [1] 47
## [1] 48
## [1] 49
## [1] 50
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
##   requires numeric/complex matrix/vector arguments
## [1] 51
## [1] 52
## [1] 53
## [1] 54
## [1] 55
## [1] 56
## [1] 57
## [1] 58
## [1] 59
## [1] 60
## [1] 61
## [1] 62
## [1] 63
## [1] 64
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
##   requires numeric/complex matrix/vector arguments
## [1] 65
## [1] 66
## [1] 67
## [1] 68
## [1] 69
## [1] 70
## [1] 71
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
##   requires numeric/complex matrix/vector arguments
## [1] 72
## [1] 73
## [1] 74
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
##   requires numeric/complex matrix/vector arguments
## [1] 75
## [1] 76
## [1] 77
## [1] 78
## [1] 79
## [1] 80
## [1] 81
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
##   requires numeric/complex matrix/vector arguments
## [1] 82
## [1] 83

```

```
## [1] 84
## [1] 85
## [1] 86
## [1] 87
## [1] 88
## [1] 89
## Error in cbind(1, pred) %*% weights[[num_hidden_layers + 1]] :
##   requires numeric/complex matrix/vector arguments
## [1] 90
## [1] 91
## [1] 92
## [1] 93
## [1] 94
## [1] 95
## [1] 96
## [1] 97
## [1] 98
## [1] 99
## [1] 100
```

```
end_time <- Sys.time()
proc.time <- end_time - start_time
print(proc.time)
```

```
## Time difference of 4.732942 mins
```

Safe label predictions of the last run alongside the other columns in the test data set.

```
mlp.predictions.df <- cbind(test, mlp.predictions.rd)
```

Write to file.


```
# classification results summaries
write.csv(results.df, file = paste(c("~/Github/UpperPalCombinatorics/results/classifier/MLP/performance",
                                     act.fct.name, "_",
                                     err.fct, "_",
                                     algorithm, "_",
                                     subcorpus1, "_",
                                     subcorpus2, "_",
                                     ".csv"
                                   ), collapse = ""),
          row.names = F)

# predictions for post-hoc analyses
write.csv(mlp.predictions.df, file = paste(c("~/Github/UpperPalCombinatorics/results/classifier/MLP/pre",
                                             act.fct.name, "_",
                                             err.fct, "_",
                                             algorithm, "_",
                                             subcorpus1, "_",
                                             subcorpus2, "_",
                                             ".csv"
                                           ), collapse = ""),
          row.names = F)
```

Visualize the NN

Visualize the NN with the best weights after training. Note this is the last run of the for loop through different architectures.

```
mlp.plot <- plot(classifier.mlp, rep = 'best', show.weights = F)
```



```
mlp.plot
```

```
## NULL
```

```
#References Bentz, Christian (2023). The Zipfian Challenge: Learning the statistical fingerprint of natural languages. CoNLL, Singapore. https://aclanthology.org/2023.conll-1.3/
```