

Estimations of Quantitative Features for Cuneiform Tablets

27/02/2024

Description

This file contains the code for estimating the feature values (TTR, unigram entropy, entropy rate, repetition rate) per sign sequence on cuneiform tablets from CDLI.

Load libraries

If the libraries are not installed yet, you need to install them using, for example, the command: `install.packages("ggplot2")`. For the Hrate package this is different, since it comes from github. The devtools library needs to be installed, and then the `install_github()` function is used.

```
library(stringr)
library(entropy)
library(gsubfn)
```

```
## Loading required package: proto
```

```
#library(devtools)
#install_github("dimalik/Hrate")
library(Hrate)
```

Load files

Load the files with the cleaned sequences.

```
# choose period (UrukIII, UrukIV, UrukV)
period <- "UrukV"

# cuneiform data from CDLI
cunei.data <- read.csv(paste("~/Github/UpperPalCombinatorics/data/CDLI/",
                             paste(period, "/signs_clean.csv", sep = ""),
                             sep = ""))
# remove rows with empty sign codings
cunei.data <- cunei.data[-which(cunei.data$signs.orig.vec == ""), ]
```

Cuneiform Estimations

Estimations of quantitative features for the cuneiform data from CDLI.

```
# set counter
counter = 0
# initialize dataframe to append results to
```

```

estimations.df <- data.frame(tablet.id = character(0), num.char = numeric(0),
                             huni.chars = numeric(0), hrate.chars = numeric(0),
                             ttr.chars = numeric(0), rm.chars = numeric(0))

# start time
start_time <- Sys.time()
for (i in 1:nrow(cunei.data)){
  try({ # if the processing fails for a certain row, there will be no output for this row,
    # but the try() function allows the loop to keep running

    # collect info from row
    tablet.id <- cunei.data$tablet.id[i]
    coding.sample <- as.character(cunei.data$signs.expand.vec[i])

    # split strings into cuneiform sign types
    chars <- unlist(strsplit(coding.sample, " "))

    # get overall number of signs on tablet
    num.char <- length(chars)

    # preprocess the signs with bag-of-words normalization
    # note: this is an important step! Without it, entropy rate estimation will fail
    # to yield realistic results due to issues with processing special characters.
    chars <- PreprocessText(chars)

    # unigram entropy estimation
    # calculate unigram entropy for characters (note that this is the same
    # for random ordering of chracter strings)
    chars.df <- as.data.frame(table(chars))
    # print(chars.df)
    huni.chars <- entropy(chars.df$Freq, method = "ML", unit = "log2")

    # entropy rate estimation
    # the values chosen for max.length and every.word will crucially
    # impact processing time. In case of "max.length = NULL" the length is n units
    # here use the try() function since entropy rate estimation can fail when particular
    # special characters are in the strings
    hrate.chars <- try(get.estimate(text = chars, every.word = 1, max.length = NULL))
    if (class(hrate.chars) == "numeric") {
      hrate.chars <- hrate.chars
    } else {
      hrate.chars = "NA"
    }

    # calculate type-token ratio (ttr)
    # note that this is the same for random ordering of strings
    ttr.chars <- nrow(chars.df)/sum(chars.df$Freq)

    # calculate repetition measure according to Sproat (2014)
    # note that this is the same for random ordering of strings
    # the maximum number of adjacent repetitions "R" possible is the sum of frequency counts minus 1.
    R <- sum(chars.df$Freq)-1
    # calculate the number of adjacent repetitions "r"
    r = 0
  })
}

```

```

if (length(chars) > 1){
  for (i in 1:(length(chars)-1)){
    if (chars[i] == chars[i+1]){
      r = r + 1
    } else {
      r = r + 0
    }
  }
  # calculate the repetition measure
  rm.chars <- r/R
} else {
  rm.chars <- "NA"
}

# append results to dataframe
local.df <- data.frame(tablet.id, num.char, huni.chars, hrate.chars,
                        ttr.chars, rm.chars)
estimations.df <- rbind(estimations.df, local.df)
}) # end of try()
# counter
counter <- counter + 1
# print(counter)
}
end_time <- Sys.time()
end_time - start_time

```

Time difference of 0.2003758 secs

#estimations.df

Merge estimations with original file

```
cunei.data.est <- merge(cunei.data, estimations.df, by = "tablet.id")
```

Save outputs to file.

```

write.csv(cunei.data.est, paste("~/Github/UpperPalCombinatorics/results/cuneiform_",
                                paste(period, "_features.csv", sep = ""),
                                sep = ""), row.names = F)

```