

CUSTOM KEYCARD PRINTING GUIDELINES

Artwork Specifications & Production Guide

1. CARD SPECIFICATIONS & DIMENSIONS

- Standard Card Size: CR80 Standard (85.6 mm x 54.0 mm)
- Thickness: 0.84 mm (+/- 0.04 mm)
- Design Artwork Bleed: 89.6 mm x 58.0 mm (Include 2 mm bleed on all 4 sides)
- Safe Margin: Keep all essential text, logos & icons at least 3 mm inside the cut line

2. ACCEPTED FILE FORMATS & ARTWORK REQUIREMENTS

- Supported Formats: Adobe Illustrator (.AI), Vector PDF (.PDF), CorelDraw (.CDR)
- Vector Requirement: All fonts MUST be converted to outlines / curves
- Embedded Images: Min 300 DPI resolution embedded in the vector file
- Color Profile: CMYK Color Mode (Do not use RGB to prevent color shifts)

3. CHIP & TECHNOLOGY OPTIONS

- Mifare 1K (13.56 MHz): Standard HF chip for smart hotel locks & PMS access
- Temic T5577 (125 kHz): LF chip for legacy hotel lock systems
- Mifare Ultralight / NTAG: High-density NFC chip options for guest interaction

4. FINISHING OPTIONS & ORDERING INFORMATION

- Surface Finishing: Glossy PVC, Matte Doff, Frosted Translucent, Eco Wooden, Gold Metallic Foil
- Special Effects: Embossed Numbering, Magnetic Stripe (HiCo/LoCo), QR Code / Barcode
- Minimum Order Quantity (MOQ): 500 pcs per custom design
- Lead Time: 7 - 10 Business Days after digital proofing approval