

ANSI MORTISE SS304 SERIES

Technical Datasheet - Smart Hotel Lock System

1. OVERVIEW & DESCRIPTION

Product Name: ANSI Mortise SS304 Series Smart Hotel Lock
Application: Star Hotels, Resorts, Luxury Apartments, Modern Access Control
Material: Premium Stainless Steel 304 (Corrosion & Scratch Resistant)
Finish Options: Satin Stainless Steel, PVD Matte Black, Brushed Gold

2. HARDWARE & MECHANISM

Mortise Standard: ANSI 5-Latch Heavy-Duty Mortise (Grade 2 Certified)
Latch Features: Anti-Friction Latchbolt, 1-Inch Stainless Steel Deadbolt
Dimensions: Height 280 mm | Width 68 mm | Depth 72 mm
Door Thickness Compatibility: 38 mm - 65 mm (Standard European/ANSI door cutout)
Handle Mechanism: Free-Vane Clutch Handle System (Anti-Panic Release inside)

3. ACCESS CONTROL & ELECTRONICS

RFID Technology: High-Frequency 13.56 MHz Mifare 1K (ISO 14443 Type A)
Reading Distance: 10 mm - 30 mm (Instant keycard recognition < 0.3s)
Mechanical Backup: Concealed High-Security Dimple Mechanical Key Cylinder
Power Supply: 4x AA Alkaline Batteries (6V DC)
Battery Life: 12 - 18 Months (Approx. 10,000 unlock operations)
Emergency Power: External Micro-USB / USB-C Emergency Power Port
Audit Trail: Memory stores last 800 audit events (timestamps, card IDs, mechanical keys)

4. OPERATING ENVIRONMENT & CERTIFICATIONS

Operating Temperature: -10 C to 55 C
Operating Humidity: 15% - 90% RH (Non-condensing)
Certifications: ANSI/BHMA A156.13, CE Mark, FCC Part 15, RoHS Compliant, ISO 9001
Warranty: 3-Year Full Replacement & Technical Support Warranty