

---

SAARLAND UNIVERSITY

Faculty of Natural Sciences and Technology I  
Department of Computer Science  
Related Work Summary



## Interactive technology in slackline training

Christian Murlowski  
November 2017

---



**Main advisors:**

Prof. Dr. Antinio Krüger  
German Research Center for Artificial Intelligence  
Saarland Informatics Campus  
Saarbrücken, Germany

**Advisors:**

Felix Kosmalla  
German Research Center for Artificial Intelligence  
Saarland Informatics Campus  
Saarbrücken, Germany

Dr. Florian Daiber  
German Research Center for Artificial Intelligence  
Saarland Informatics Campus  
Saarbrücken, Germany

Handed in on 23/03/2017

Saarland University  
Faculty of Natural Sciences and Technology I  
Department of Computer Science  
Campus - Building E1.1  
66123 Saarbrücken  
Germany

### **Eidesstattliche Erklärung**

Ich erkläre hiermit an Eides Statt, dass ich die vorliegende Arbeit selbständig verfasst und keine anderen als die angegebenen Quellen und Hilfsmittel verwendet habe.

### **Statement in Lieu of an Oath**

I hereby confirm that I have written this thesis on my own and that I have not used any other media or materials than the ones referred to in this thesis.

November 2017

### **Einverständniserklärung**

Ich bin damit einverstanden, dass meine (bestandene) Arbeit in beiden Versionen in die Bibliothek der Informatik aufgenommen und damit veröffentlicht wird.

### **Declaration of Consent**

I agree to make both versions of my thesis (with a passing grade) accessible to the public by having them added to the library of the Computer Science Department.

Saarbrücken, 14th January, 2016

## Acknowledgements

Thanks to:

- Prof
- Advisors
- Tobias Walter
- Family
- Everyone else
- Maybe avarteq

Thank for:

- Help regarding research
- Be able to write the thesis in here
- Organizing and getting hardware and stuff for thesis
- Supporting me in all things regarding conceptual, design related, technical and reviewing stuff
- Mental and pushing me forward
- Avarteq for letting me have time to write the thesis

## **Abstract**

TEXTTEXT

- Kinect v2
- Slackline
- No interactive system
- Just learning by doing
- No real-time feedback to clarify if something is wrong
- System gives this feedback
- Measure learn progress
- In here user will be guided through exercises
- If such an interactive system can be used to learn user to go on a slackline
- If such a system is at least comparable with a human trainer (maybe also video training) or even better
- Feasibility study with experts
- User study with beginners in 2-3 groups and 2 sessions
- In 2. session all will train with the system
- -
- Problem
- Current approaches to solve the problem
- Problems with solutions, what would be better, what can't you do with these
- Solution approach of thesis to make everything better, What will be better
- Developed prototype, Used techniques, prototype design to motivate user
- Pre-study / Feasibility study -> Why doing this? What evaluate?
- Solve occurring problems, which exercises can be implemented + good trackable
- Main study -> what will be tested?, number of exercises and tiers/stages and exercise levels
- Final results, What was good, What was bad, Usability of system
- Assumed hypothesis true or false

---

# Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	Motivation . . . . .	3
1.2	Research Goals . . . . .	3
1.2.1	Hypothesis . . . . .	4
1.3	Outline . . . . .	4
<b>2</b>	<b>Related Work</b>	<b>5</b>
2.1	Slackline specific training and effects to the human body . . . . .	5
2.1.1	Exercises during slackline training . . . . .	6
2.1.2	Slackline specific training effects and application scenarios	8
2.2	Interactive technology . . . . .	9
2.2.1	Comparison of tracking technologies . . . . .	9
2.2.2	Accuracy of the Microsoft Kinect . . . . .	10
2.2.3	Implementation in balance training scenarios . . . . .	12
2.3	Feedback and interaction methods . . . . .	13
2.3.1	Restricting cognitive load . . . . .	14
2.3.2	Motivating factors for skill acquisition . . . . .	15
2.3.3	Approaches and techniques for providing feedback . . . . .	16
2.4	User interface design . . . . .	18
2.4.1	User interface design for appropriate feedback . . . . .	18
2.4.2	Kinect for Windows - Human Interface Guidelines . . . . .	19
2.5	Conclusion . . . . .	23
<b>3</b>	<b>Slacklining and slacklining learning techniques</b>	<b>25</b>
3.1	Introduction into slacklining . . . . .	25
3.2	Slacklining variations and categorization . . . . .	26
3.3	Slackline learning techniques . . . . .	29
3.3.1	Methods for slackline skill acquisition . . . . .	29
3.3.2	Stages and exercises of learning slacklining . . . . .	32

3.4	Conclusion . . . . .	33
<b>4</b>	<b>Concept</b>	<b>35</b>
4.1	General Information . . . . .	35
4.1.1	Ten heuristic principles for interaction design . . . . .	36
4.1.2	System specific basics . . . . .	37
4.2	Interaction . . . . .	37
4.3	Stages . . . . .	38
4.4	Exercises . . . . .	38
4.5	Feedback system . . . . .	39
4.6	Scenario . . . . .	40
4.7	Conclusion . . . . .	40
<b>5</b>	<b>System integration</b>	<b>41</b>
5.1	Technical feasibility . . . . .	41
5.1.1	General setup . . . . .	42
5.1.2	Testing scenario . . . . .	42
5.1.3	Best positioning for beginner learning purposes . . . . .	44
5.2	Gesture Construction . . . . .	44
5.2.1	Visual gesture builder . . . . .	45
5.2.2	Building gestures workflow . . . . .	45
5.3	System architecture . . . . .	46
5.3.1	Hardware and software components . . . . .	46
5.3.2	Software implementation . . . . .	46
5.4	User Interface . . . . .	51
<b>6</b>	<b>Study</b>	<b>53</b>
<b>7</b>	<b>Conclusion and Outlook</b>	<b>55</b>
	Bibliography . . . . .	56

While the following examples, arguments, and descriptions apply equally to both genders, for the sake of ease of reading, only the female pronouns are used in this thesis.



---

---

# **Chapter 1**

## **Introduction**

### **1.1 Motivation**

- Mostly skill acquisition is done with a professional who already knows how to act on the line and where particular attention must be paid. In contrast to such a human personal trainer this thesis will elaborate an interactive slackline learning system with real-time feedback.
- Interactive real time feedback system in other sports
- more exergames realeasing in past decades
- Exergames in general
- No comparable work regarding slacklining
- Support slackline beginners with such a system

### **1.2 Research Goals**

- Investigate related system
- Requirement analysis
- Conceptual design of an interactive feedback system for slacklining
- User interface design
- Integration
- Investigation of the system

### 1.2.1 Hypothesis

- Provide supportive feedback
- Show if an interactive real time feedback system is usable for this kind of sport
- If the learning progress is comparable with other training methods like human trainer
- If such a system motivates user for slackline exercises

## 1.3 Outline

The thesis is structured as follows: As a groundwork the **Related Work** chapter involves basics of **Slackline specific training and effects to the human body**, a number of possible interactive tracking devices that will be compared in the section **Interactive technology**, and **Feedback and interaction methods**.

- **Further chapters**

A List of ??, ??, ?? and the ?? can be found at the end of the thesis.

---

---

## **Chapter 2**

## **Related Work**

This section presents related work to a slacklining assistance system with an interactive technology approach. It provides exercises and feedback for beginners on a slackline with the Microsoft Kinect v2 as a tracking device. Hence it is necessary to provide instructive teaching methods for beginners. Therefore existing approaches and studies have been elaborated to build an appropriate foundation and point out several application scenarios. Also the user interface should motivate the slacker for the training scenario and lead to a proper user experience.

First related concepts regarding slacklining show how to build learning techniques for beginners, the efficacy of it in balance training, and areas of application. Next current tracking technologies have to be compared for tracking the human body on the slackline and why the Microsoft Kinect v2 seems like the appropriate tracking device. The system has also be aware of the cognitive load and motivating aspects, which can be challenging with repetitive exercises. Several applications show where problems occur with different feedback and interaction methods. Lastly design opportunities for guiding the user through the learning process are demonstrated by various approaches.

### **2.1 Slackline specific training and effects to the human body**

As in other sport activities it is important to have a concrete baseline about what exercises and tips are useful for very beginners. Mainly to have a good knowledge of the basics, which results in a faster learning process, but also to prevent injuries from the beginning. In the following several slackline learning techniques will be discussed, which can then be implemented in the assistance

system. Prior research indicates the applicability of slackline training for areas like sport medicine and rehabilitation training. It shows why slacklining could be used as an alternative to classical balance training and how the body swift affect these. Donath et al. [9] found in his meta-analysis significant improvements in the postural control after slackline training, which indicates the efficacy of this training method. This subsection shows several application scenarios in which a slackline can be implemented and improve the training effect.

### 2.1.1 Exercises during slackline training

For beginners it is difficult to walk or even stay on a slackline. The uncontrollable swift of the narrow line result in unfamiliar movements that cannot be handled at the very beginning. Therefore they should learn to concentrate, build up motoric basics and trust into the line, as well as manage their body behaviour.

Thoman [44] differentiate two basic methods for the learning process on a slackline. Teaching a slackline beginner, further called slacker, without any help or with systematic external assistance. The investigation of Kroiß [24] resulted in no significant difference between both methods. But there is a trend regarding providing methodological aid, like human support or physical objects as nordic walking sticks or a bar, can help to improve the learning effect (Figure 2.1). Therefore it is a good advise for beginners to learn the fundamentals of standing and walking on the slackline to build up a groundwork. Several basic techniques and tips are useful to support her in this way. For example focusing on a specific point, stretching out the arm, raising the hands over the shoulder level, turning the palms to the top, going slightly in the knees, have the feet straight with the line, and so on [23, 24].




Figure 2.1: Supportive exercises [24]

With further progress, the external help, if given, should be reduced. The slacker can now try to stay and walk on the line on her own. It is recommended to begin with the practice of a basic start, to stay with both feet, and one feet on the slackline since these are basic techniques (Figure 2.2). Staying with both feet seems easier in the beginning but only the hips and hands can be used for

balancing. With just one feet on the line, the slacker can use the other one as an additional extremity for balancing purposes.




Figure 2.2: Basic exercises [24]

Advanced training should be practiced in a more dynamical way [44]. Like seen in several research works [7, 8, 14, 22, 33] this can be from crossover start (Figure 2.3a), turning on the line, hands on hips or behind the back (Figure 2.3b), walk sideways or backwards up to catch and pass a pall, kicking a football, bouncing a basketball, or a kneel down on the slackline (Figure 2.3c).




Figure 2.3: Advanced techniques [24]

Additional cognitive load is caused by unfamiliar exercises and simultaneous balancing on the line. This conjunction can lead to impairments. Even more difficult exercises can be carried out in further sessions like standing up from a sitting position, juggling, two people on the same line, reading a newspaper, closing eyes while balancing, vertical jumps, or rope skipping. Due to the higher difficulty of constraints, it results in a more unstable movement of the line.

Changes directly on the slackline itself, like varying the tension and length, have also an influence on the stability of the human body on the line [22, 33, 34]. A short and tight line results in a relatively small vibrating area, where the slacker has to outbalance short unpredictable movements on point. Given a longer and loose line, it results in a more swinging behaviour that she has to counteract [24].

The slacklining assistance system should mainly train and support slacker to walk on the slackline. With those approaches in mind a foundation is set to build helpful exercises for the system. Because the focus relies especially on beginners, this information serves as an inspiration for supporting them with effective and efficient methods. Now is the question, what effect has slackline on the human body and where can it be applied? This is part of the next subsection.

### 2.1.2 Slackline specific training effects and application scenarios

Donath et al. [7] elaborated the effects of slackline training on regular balancing, jump performance, and muscle activity with young children in school sport. The slackline specific balance has improved. Also the dynamic sway and muscle activity for the lower limb is reduced. But there were no effects regarding jump performance. The children enjoyed the slackline training. In comparison to classical balance training it can be more fun for the children and at the same time an effective training method.

Another study of Donath et al. [8] investigated slackline training with seniors from an age between 59 to 69 to measure effects on slackline specific balance and neuromuscular performance. They found significant differences between pre- and posttests during all slackline stance conditions. In addition the trunk and limb muscle activity were reduced after the training phase. With this in mind slacklining can be provided as an alternative balance training method for seniors. Regular balance training can help to reduce the fall risk, which can be an useful therapy for seniors when keeping in mind that 30% of seniors suffer from fall injuries once a year.

Keller et al. [22] examined the improvement of the postural control regarding the Hoffmann-Reflex after slackline training and whether adaptations can be found regarding classical balance training. The H-Reflex (Hoffmann-Reflex) is used to assess and quantify stretch-reflex responses due to electrical stimulation. The measurements show that these were significantly reduced as well as slackline specific balance were improved. Therefore slackline training and classical balance training have at least similar effects on the postural control.

Pfusterschmied et al. [33] found significant effects regarding stable stance after slackline training and even more effects were found for perturbed leg stance. This is because slacklining is a high dynamic movement activity and there is more need of regaining equilibrium as in perturbed stance than for maintaining balance as in a stable leg stance condition. The velocity in medio-lateral and anterior-posterior center of gravity, knee and hip joint is reduced as well as the range motion in knee and hip joint. No changes in medio lateral direction for the stable surface or joint kinematics for both have been found.

Another study of Pfusterschmied et al. [34] shows effects on lower limb joint motion and muscle activation. They found a decrease in platform velocity and

improvements in corrective action in the knee joint. Also enhanced activation of the muscle activity in rectus femoris (upper leg) was measured.

Granacher et al. [14] investigated the impact of slackline training for balance and strength promotion and found contradictory results compared with the studies described above. Static and dynamic postural control were analysed as well as the isometric and dynamic muscle strength. There were no effects regarding the postural control, maximal torque, and jumping height. The results can be explained due to the assessment of other recorded variables, usage of different methods for analysing the data, and the relatively short slackline training time than in other studies [33]. Therefore this study can be seen as an exceptional case.

Those investigations show that slacklining is indeed an effective method for improving the postural control. Hence many application scenarios can be thought of to implement a slacklining assistance system. For example it can be used as a training approach in school sport, preventative activity for seniors, and rehabilitation alternative. Furthermore it can be used as a supportive training method for athletes in sport activities like skiing or skating, that require a good body balance. Interactive technologies can be used to support training in such scenarios. The next section provides an overview about state of the art technologies, compares them, and show several implementations in balance scenarios.

## 2.2 Interactive technology

To build a real time feedback assistance system, a tracking device is needed that supports the slacker in an appropriate way and won't interrupt her. The Microsoft Kinect v2 seems like a suitable tracking system in this context, because the user don't need any further devices to be tracked. But it should be compared with other tracking technologies like the Nintendo Wii, Playstation Move, and motion capture systems, to justify its usage. In the following advantages and drawbacks of these systems will be discussed. Further several studies show how accurate and precise the Microsoft Kinect v2 is, if it can be applied for balancing purposes, give the user appropriate feedback, or useful analysis data for specialist like therapist.

### 2.2.1 Comparison of tracking technologies

The Nintendo Wii consists of a sensor bar with infrared sensors that estimates the position of the Wiimote controller in 3D. Further an accelerometer is integrated in the Wiimote to detect its motion. Thus the user can interact with the console, based on predefined gestures [4, 42]. Gesture recognition is an essential aspect of the slacklining assistance system for giving appropriate feedback regarding the executed exercise. Schröder et al. [40] analysed the gesture recognition of the Wii and found an error rate between 5% and 15%.

A similar approach with a handheld controller is followed by the PlayStation Move. It contains an RGB camera called Move Eye that is used for tracking the 3D position of a lighting sphere attached on the handheld device named Move wand. The controller contains an accelerometer, gyro sensor and geomagnetic sensor to track the rotation and also support position tracking. In this way more accurate tracking is possible than with the Nintendo Wii [4, 42].

Both systems are good devices if the controller itself can be replicated as a virtual device like for example in golf or tennis. But they do not track the body movement and the user is bound to her handheld devices to interact with the system. In the slacklining system they could disturb user standing on the slackline. Moreover accurate feedback from the whole body is wanted and thus it should be the actual controlling device. Therefore they seem not to be appropriate devices for the slacklining system.

With a motion capture suit, like *Xsens MVN* [28] or *OptiTrack* [31], markers have to be attached on the user's body for tracking her body motion and rotational data. This makes it the best device for high accuracy and precision body tracking. Problems with the suite are that it is very expensive and the setup takes relatively long time because of the marker attachment and the positioning of the tracking cameras. The biggest drawback is the uncomfortable bulky equipment that could interfere the user during the performance [4, 5, 30]. This makes it an inappropriate device for user tracking on a slackline.

The Microsoft Kinect is a static device that includes a RGB camera and depth sensor. Because the body joints and player position are recognised by these, the user is free in her movement without any further controller. Another advantage is the low price in comparison to the motion control suite, and the low setup time because only the device itself is needed. Problems occur with occlusion of body parts that results in glitches and flawed tracking [20, 43]. To the user they can be hidden, e.g. by only showing the output of the depth cam [18]. This problem can also occur in the slacklining case because of overlaying feet. Therefore a feasibility study should be realised to show if this is a bigger problem or can be neglected.

With this in mind, the Microsoft Kinect v2 seems like the most suitable device. The recognition of the whole body, freedom of movement, short setup time, and relatively low cost makes it the best system out of the stated devices.

### 2.2.2 Accuracy of the Microsoft Kinect

In the field of balance training it is necessary to give appropriate feedback for the patient that reveals errors in the performance and support a proper execution. With this in mind user tracking should be good enough to fulfil this criteria. Since Microsoft Kinect is used as the tracking device the accuracy and precision should be assessed.

Lim et al. [26] assessed the accuracy of the Kinect with a 3D motion capture system as a reference system. For further understanding please review Figure 2.4 regarding expressions to body planes and anatomical directional references. The participants had to execute balance training with complex aperiodic movements in the body planes (Figure 2.4a). Similar characterization of movements are provided by the Kinect in comparison to the 3D motion capture system. The correlation analysis showed that the Kinect and the 3D motion capture system are highly correlated for the flexion and extensions in the medio-lateral-axis (x-axis) but not on the anterior-posterior-axis (y-axis) and the cranial-caudal-axis (z-axis) (Figure 2.4b). This is because the Kinect determine joint locations based on the depth image data and the data input is limited to the depth camera view. Therefore recognition of joint angles in the sagittal and transverse plane is not optimal (Figure 2.4a). Also the primary goal of the Kinect is to measure the dynamic movements in the coronal (frontal) plane for gaming reasons. It is indeed an effective system to characterize changes in center of mass and movements in the frontal plane during balance training. But it would not be suitable in balance training that require in-depth analyses of joint motions, which is not needed with the slackline assistance.




Figure 2.4: Anatomical terms of location [48]

Chang et al. [5] focuses mainly on the tracking performance of the Microsoft Kinect as a rehabilitation device in comparison with a high fidelity motion capture system called OptiTrack. In their application the user has to move objects from one side of the screen to the other. Five correct and incorrect movements have been realised and both systems successfully identified them. In trajectory comparison the results of the hand and elbow by the Kinect are very close to the OptiTrack system. Tracking of the shoulder movements are moderate because it involves rotation that the device does not recognizes well. The timing perfor-

mance comparison shows that the OptiTrack system is negligible faster than the Kinect.

Woolford [56] compared the accuracy and precision of the Kinect v2 with the Qualisys motion capture system for the usage in healthcare applications. He describes that accuracy is the amount of how close a measured quantity to the actual value is. Precision is the similarity of repeated measurements (Figure 2.5). For example the Kinect skeleton tracking methods are accurate because the average joint position data is very close to the actual physical position. Regarding his definition of precision, the joint position data is not always precise because the data spreads in its position of the frame. The results show that the Kinect V2 is accurate but imprecise for body parts whose center of mass cannot be easily identified like the shoulder. For smaller body parts as well as between two body parts such as elbow or wrist the accuracy and precision is very high.




Figure 2.5: Definition of accuracy and precision [56]

The Microsoft Kinect v2 can indeed be compared with high performance tracking devices. If no detailed analysis is needed, it provides reliable and appropriate data. For the assistance system it should provide sufficient data to track the user and give useful feedback

### 2.2.3 Implementation in balance training scenarios

Like already stated Chang et al. [5] not only assessed the accuracy of the Microsoft Kinect but also if it could fit as an alternative training device in rehabilitation

training. The results show that it provides enough usable feedback to the therapists to be an appropriate device for medical uses. Woolford [56] state that the Microsoft kinect is a useful device for monitoring such exercises. The set-up is relatively easy and the tracking is appropriate for exercises in a healthcare environment. Lim et al. [26] investigated the usage of Microsoft Kinect in the field of falling risk. They tracked characterizing movements and found that it is an useful device for balance training. Ustinova et al. [46] used the Kinect to improve the postural control as well as coordination deficits from chronic traumatic brain injury patients. It resulted in improvements of postural stability, movement performance and motoric coordination. The participants were also very satisfied whereas normal exercises have been stated as boring. Pisan et al. [35] used the device to investigate the prediction of the loss of balance for elderly users with a step training program. The user preferred doing exercises with the system and the tests matched also the expectation of the researcher. An integration in promoting the postural control for parkinson disease with

Kinect games were elaborated by Pompeu et al. [36, 37]. The results affirm that the patients improve in balance purposes and motoric movements with this help.

Furthermore Estapa et al. [10] and Freitas et al. [12] collected data of execution from patients for medical reviews. Both developed a motor rehabilitation game. It is used to support therapeutic exercises and evaluate biomechanics of the patients. This allows subsequent analysis of the performance data for the therapist.

This approach of data analysis was also integrated by Garrido et al. [13] but in addition they elaborate if the Kinect can serve as a rehabilitation home assistance. Many patients are thrown out of their daily life environment for accessing traditional rehabilitation training in a medical center. Here the patient incorporate the system into their daily life and avoid such trips. The medical stuff gets all relevant parameters due to the transmission of the recordings from the exercises to the medical center. Beside this they get more time because nobody has to observe the training.

Keeping the stated results in mind shows that the Microsoft Kinect is a promising system for balance exercises that provides sufficient accurate and usable feedback. It can be embedded in a variation of fields as rehabilitation system, home assistance, or preventative technique. The aspect to motivate patients with an exergame approach and enjoyable user interface can also lead to successful exercise execution, which is part of the next section.

## 2.3 Feedback and interaction methods

Cognitive load plays an important role if skill acquisition is a major factor. In slacklining the user has to focus on multiple things simultaneously that increases the mental pressure. Several studies show why and how the cognitive load should be restricted. Another important fact is that repetitive exercises can

lead to a boring and demotivating user experience. For that reason several methods, systems and game approaches can be used as an inspiration to build a system with a motivating and joyful environment. At last the integration and visualisation of feedback and interaction methods should be well thought out. Various techniques have been elaborated on how to provide this appropriately.

### 2.3.1 Restricting cognitive load

As a baseline Paas et al. [32] describes that the acquisition of new skills is in conjunction with cognitive load. By adjusting this the learning effect can be eased or hardened. Three types of cognitive loads exists that handle the working memory of a person regarding the learning process. Intrinsic load is the inherent complexity that is caused by the topic itself. It is also important in which manner information is given to the user. If this is unnecessary, repetitive, or interferes her it is called an extraneous cognitive load and increases the burden of the user. The last type is germane cognitive load, which describes also how information is given to the user but by supporting the him in that way. This is brought by activating and automating already existing patterns or generating new ones in the working memory to enhance a learning process. Regarding this several applications have been evaluated that are also relevant to the slacklining supporting system.

Van der Spek [47] evaluated how to deal with the right complexity in serious games. He describes in his mental model construction (Figure 2.6) that interference can be avoided by information regulation and focus attention. Improving is encouraged by predictability and reflection of the tasks. The attention of the user should be focused to relevant material by regulating the information given to him. Since a serious game like approach should be developed this is an important reference for building an effective learning process to the user.




Figure 2.6: Guideline for enhancing the cognitive load [47]

Pisan et al. [35] evaluates the user risk of falling with cognitive loading exercises. They executed two stroop tests, where the participant had to name the correct color of the word. High and low cognitive load can be measured by differentiating the meaning and color of a word. In the next challenge she has to answer different maths problems provided by the system. The results show that the reaction time due to cognitive load is much larger with users that have a higher risk of falling than for users that have a lower risk. This could be explainable due to the fact that user with higher falling risk are not that good in terms of switching the cognitive focus from the balancing action into other actions.

Training on a slackline provides cognitive load to the user because of several simultaneously things she has to be aware of. Hence feedback given on how to behave in a situation should be provided in an appropriate manner to support the slacker. The system has to be aware of this and restrict the cognitive capability in the right way. Next to cognitive load the system has to ensure that the user stays motivated for the training, which is part of the following subsection.

### 2.3.2 Motivating factors for skill acquisition

Several rehabilitation and sport training programs can be elaborated for motivating factors because the skill acquisition in slacklining resemble with them. The training procedure is a process of repetitive exercise execution. For mastering new skills and extend himself a user must have the willingness and commitment for practicing, which can be described as motivation. The self-determination theory by Ryan et al. [38, 39] describes several types of motivational factors. First the intrinsic motivation, which is caused by interest to an action and satisfies the own psychological needs for self-determined behaviour. This is the fundamental stimulus for high valuable learning and practicing. Second the extrinsic motivation that is performing an activity because of an external output. The user can hereby feel externally propelled due to compliance with external regulations or she can be self-endorsed due to willingness and acceptance by the value of the practice.

Johnson et al. [19] stated regarding rehabilitation training that if exercises and the user himself provide negative factors like boredom, repetition or long execution time it results in a discouragement. Enhancing the interaction with this trainings can lead to effective training. Pisan et al. [35] says that video games can help to motivate the patients through their physical training. The participants in his user tests found the games that he developed engaging. They preferred doing the exercises with the system.

Several researchers involved the motivational aspect of video games in their system. Ustinova et al. [46] developed four custom virtual video games to elaborate the efficacy for postural deficits. First a virtual teacher where the subject has to copy its movements strictly. Second a virtual challenger that is divided into a skateboard, courtyard and an octopus game with specific exercises

in which the movements of the user are more flexible. Successfully completed performance will be rewarded with a number of points. Overall the user were strongly satisfied with the gaming part of the therapy and moderate with the virtual teacher part.

Freitas et al. [12] focused on user centred development of a physiotherapeutic game that supports motor rehabilitation exercises. A plane represented the user and she has to fly through rings in the air and avoid obstacles. The patients were strongly satisfied with the game. An important factor here is the good user interface that affects the user motivation, visually presented scenario and playing technique in a positive way.

Estepa et al. [10] evaluates three developed exergames involving different psychophysical rehabilitation exercises. A virtual avatar represents the patient and orders are giving via an auditive or visual stimuli. The first two games are a series of coming balls placed at desired angles that the patient has to avoid with her trunk or, in the second game, with her feet. In the third exercise she has to step forward to a colored line between starting and goal position. All games were easy to understand and provide necessary feedback. The patients had a considerable interest to use the system.

Kajastila and Hämäläinen [20] encourages monotonous parts of climbing training by adding goals and supporting the social collaboration of the participants. Hence they are making it overall more enjoyable. Six prototypes were developed. Prototypes that rely more on a training part are an easy route builder, automatic route generator and instant video feedback. For the user those were the most useful ones. The exercises that consists of a more playful part, such as a chasing animated saw that the climber has to avoid, shifted the focus away from the training part.

With this in mind a useful training device should be considered that includes an enjoyable virtual environment. A good balance between these both is the key for successful and motivating skill acquisition. Another part of the system should also provide useful feedback to the slacker. What methods can be used for this will be discussed in the following.

### **2.3.3 Approaches and techniques for providing feedback**

Several technological advances like video feedback, virtual environments and auditive information can be applied for providing feedback in sport activities. Liebermann et al. [25] evaluated those regarding their field of application. With video information costs are relatively low, it is easy accessible, and portable. It can be repetitively replayed in real-time or superposition of two video. Training in 3D virtual environments can help to improve or to familiarize with a real world skill acquisition. The user can pre-practice a skill in simulated unknown conditions like pilots in a simulated airplane. Providing appropriate auditive information can also have a relatively high impact on performance enhancement.

Also the Microsoft HCI-Guidelines state that implementing audio is a good way if the user need to be notified, and to indicate states of changing behaviour [6]. For example in balance training a warning signal can indicate that the current pose is not the desired one. If the user corrects his posture in the right way, the signal should then transform into an more comfortable signal. All of these allow qualitative and meaningful feedback in their application context. The user can review the execution, pre practice in a virtual environment, or be supported by audio warning signals. WIth this she can discover failure in her performance.

Feedback has to be provided in an appropriate manner for improving new motor skill acquisition. Especially for starting to learn a new technique it is important to have immediate feedback sources on which the user can rely on [17, 55]. Therefore it should be easy to understand for enhancing the learning process.

Hämäläinen [16] developed applications for a camera output in front of the user. An automated motion controlled approach starts and stops the recording if the motion exceeds a certain threshold. Second a speech and last a gesture control prototype. Both consists of four commands to record, play, stop and delay the recording. The user test ranked the automatisation the worst because it reacted to unintentional motions, which ends in unwanted command recognition. The speech system ranked the best but only worked well if the participant speaks near the microphone. Some mentioned that the gesture approach were more intuitive and natural, which could be a good compromise out of the three approaches.

Holsti et al. [18] investigated delayed video feedback and a platform jumping game in trampoline sport. The former records the performance execution and shows it repetitive to the user. In the second the player has to jump back- and forwards on virtual platforms. They tested it with athletes and beginner. The delayed video feedback was ranked useful for nearly all athletes. Overall the platform jumping game was ranked the best.

Kajastila and Hämäläinen [20] project graphics on an artificial climbing wall. A feasibility study showed that graphic information is best located near holds where the focus of the climber goes naturally. This can be adapted to slacklining since the slacker has to focus usually a specific point in front of her. It would be useful to provide information in the peripheral view. Next to other prototypes he has implemented an instant delayed video feedback. This is rated as one of the most useful ones because the user can immediately analyse her performance. Also a gaming approach is developed as an animated saw that chases the climber and has to be avoided. User state that it moves the focus away from the training, but it could be an enjoyable alternative to kids for getting them used to the sport.

Based on the results of the last paper Kajastila et al. [21] developed two games and a route creation application. User emphasize the versatility and excitement of the games. They also forget the fear of heights due to time limits and forcing them to focus and achieve a goal. User stated that playing and spectating is also more fun due to implemented sound and visual effects.

Like seen a delayed video feedback is a good approach to learn new skills. Combining this with a gaming approach can simultaneously lead to a joyful experience with training aspects. Also adding audio signals can further improve this experience for the user as well as for spectators. A well suited interaction mechanism and a good looking environment can help to create an effective system and motivate the user for training purposes.

## 2.4 User interface design

The user interacts with the system through the provided interface. This should contain all relevant information, which are necessary to achieve a specific goal and support her on the way to reach this goal. General user interface approaches from exergame like related work approaches should be compared. Therefore the subsection *User interface design for appropriate feedback* gives an overview on which elements can be used for guiding the user through the system and how feedback can be visualized properly. After that in subsection *Kinect for Windows - Human Interface Guidelines* shows how to enhance the user experience on a kinect application with guidelines provided by Microsoft.

### 2.4.1 User interface design for appropriate feedback

Important feedback information during the exercise should be placed surrounding the focus point in the peripheral view of the user. Directing the user for correcting her movement can be done in several ways. Basic information about the execution should be given prior to the user for exercise preparation. Surrounding objects can be displayed as arrows, flashing notifications or weighting scale like seen by Garrido et al. [13] in Figure 2.7a. Additional informations like




Figure 2.7: Interface of a rehabilitation training application [13]

the current exercise and the state can be displayed outside of the focus space. They should be designed to not distract the user. A feedback summary after the execution can give an useful recap about the exercise for reflection (Figure 2.7b).

Another method is to show the user itself or an avatar that demonstrates the correct performance of the current exercises like in Figure 2.8 and 2.9. Holsti et al. [18] implemented such a user integration and in user testing they endorse to see themself performing in real time.




Figure 2.8: 3D Model as avatar [10]



Figure 2.9: Rail-time user representation [18]

The task about the execution has to be clarified. Chang et al. [5] provides real time feedback on the performance quality due to a visualised path. If the performance is correct the path will turn green. But if she moves outside the range the path turns red and an arrows guides him into the correct position. Instructions and highlighting objects can help to complete an exercise successfully (Figure 2.10). If she performs something wrong during the performance e.g. in the slacklining case corresponding body parts could be highlighted.



(a) Instruction to the game



(b) Green indicator for correct performance

Figure 2.10: User interface of a rehabilitational application [5]

## 2.4.2 Kinect for Windows - Human Interface Guidelines

Microsoft itself offers Human-Interface-Guidelines (HIG) for developer and designer that describes several techniques of certain areas for developing a kinect application [6]. It provides a quick introduction into the Kinect itself, design principles for interactions regarding gesture and voice, techniques on teaching complex gestures, and how to visualize appropriate feedback. Also which interactions should be used for a specific action. Therefore developer may follow this

general standard to support their end-user. In the following general principles of the guideline will be discussed on which the interactive slackline system will rely on to enhance the user experience.

### Basic design principles

Context-awareness delivers the best user experience e.g. controls should be placed where user would expect them to be and interactions should be appropriate for the environment. It is important that the user feel confident by designing interactions simple and easy to learn. User will choose an input that take the least effort for the given goal. Therefore the input method should match its purpose, be reliable, consistent, and convenient. Conducting user test helps to improve the system. Not each person will use the system the same way and minor adjustments can make a huge difference in the understanding of the usage.

### Visual and audio feedback

Giving the user constant feedback helps her to know what is happening. In general appropriate feedback should show if the sensor is ready, she is visible and engaging with the Kinect, and so on (Figure 2.11a). Regarding this a combination of visual as well as audio feedback results in a better experience, e.g. clicking a button changes its visual state and provides an audio signal (Figure 2.11b).




Figure 2.11: Feedback methods [6]

The most important part for complex gestures is the progress indicator described in this guideline. It supports the user if she has to hold a position, as well as if an amount of frequent repetitions have to be performed. Clear and prominent visuals should be used to show the entire progression (Figure 2.12a). If a user has to copy a specific movement an avatar or animation can be shown, before or during the movement, like in Figure 2.12b.

### Clarification

The user may interpret interactions with the system differently from others. Therefore the system should explain clearly what the user has to do, e.g. "Raise




Figure 2.12: Feedback indicator and movement visualization as an avatar [6]

*one hand above your head*" instead of just "*Raise your hand*". The cognitive load of the user should be kept low and not exceed a number of six gestures, such that she easily remembers the actions. The system has a set of three basic interaction techniques, which fits in this range.

### User viewer

A small scene viewer shows the range in which the user can move and is recognized by the Kinect. It displays a mirror like view in which the user can see a silhouette of herself and the constraints of the Kinect device, like in figure 2.13.




Figure 2.13: User Viewer on top [6]

### Learning interaction methods

The application should teach the user how to proper interact with it right from the beginning with an introduction tutorial. An interaction itself should rely on

the real world, which can help the user to be more familiar with the product, than learning unknown gestures (Figure 2.14). Also bilateral interaction support should be applied to cover both possibilities for left- and right-handed people.




Figure 2.14: Direct manipulation of a slider with intuitive interaction [6]

### Teaching complex gestures / exercises

Executing gestures is a core functionality in the slacklining assistance system. For new gestures, especially complex ones, the application should provide a tutorial that teaches and shows the user on how to execute or accomplish the gesture properly. When performing the gesture a visual indicator (a hint, animation, or notification) should acknowledge if the gesture is executed and when it is completed. (Figure 2.15).




Figure 2.15: Teaching new gestures [6]

### Element sizing

The system will rely on the guidelines and match the button sizing regarding the screen resolution to keep reliability on interaction. This is a size of 208 by 208px in a resolution of 1920x1080 pixel. As recommended a tile button style will be used which are a good baseline where the user can hit them accurately and read the button text.

### Physical interaction zone

This zone ensures that the user is able to reach anything in a comfortable range. In the application it is constrained by the joints of the shoulders to the hips of

the opposite site of the interaction hand. It is designed like seen in figure 2.16 to have a better understanding.




Figure 2.16: Physical interaction zone [6]

Summarizing the user interface should not distract the slacker but support him. Only necessary and useful information have to be displayed during the exercise. Providing an introduction and useful tips can help to give an understanding of the exercise. An avatar or animation is a good alternative to make clear how to perform an exercise. The system should also rely on Microsoft human interface guidelines, which provides design tips and serves as a reference to build user friendly applications.

## 2.5 Conclusion

With the stated related work a foundation is given to build a slacklining assistance system. For teaching beginners on a slackline it is important get familiar with it. The assistance system should provide the given exercises and tips for beginners which build a foundation for further training. Several application scenarios show that slacklining can replace balance training in rehabilitation environment, as prevention system, in school sport or as an home assistance. This can be combined with interactive technology, which helps patients to fulfil their exercises and provide the medical stuff with sufficient analysis data.

As interaction device the Microsoft Kinect v2 seems like the best choice out of the available technologies. It provides sufficient useful and accurate data analysis, if no in-depth analysis is needed. More advantages are the low cost, short setup time and the freedom of the movements for the user. Several studies indicate also that the Kinect can be embedded in balance training scenarios and increases the training efficacy while motivate patients.

A problem that occurs with more complexity in the exercises is the raising cognitive load. The system should therefore provide appropriate feedback and be aware of the cognitive load of the slacker. Motivating the slacker for further exercise execution can be done with a well defined interaction mechanism, an enjoyable but challenging virtual training environment, and an user friendly

interface. This can be realised especially with the help of human interface guidelines provided by Microsoft, which include several design tips for developing a Kinect application.

With the help of this foundation a concept for the slacklining assistance system has been created, which can be seen in the next chapter.

---

---

# **Chapter 3**

## **Slacklining and slacklining learning techniques**

The following chapter *Introduction into slacklining* gives an understanding of the evolution, philosophy and basics of this sport activity. Further an overview about the diversity of slacklining and application scenarios can be found in section *Slacklining variations and categorization*. The last section *Slackline learning techniques* elaborates teaching methods and exercises, which will be used as a basement for designing the concept of the system.

### **3.1 Introduction into slacklining**

The term slackline has its origin in the 1980's. Some climbers balanced on a tubular webbing in contrast to the existing balance activity tightrope, where you balance on a steel rope. Therefore they used the term *slack wire* that later transformed into *Slackline*, which means loose line [57, 2, 27].

Hence slacklining comes from the climbing sport and can be compared with ropedancing in a broader sense [23]. The line itself is made out of a nylon ribbon. Unlike in ropedancing the ribbons width is between 2.5 and 5 cm and very flat. It has to be tensed between two stable fixation points like trees, stable pillars, fixation systems on the ground, so called *A-Frames*, or on a rock with a bolt hanger and carabiner. Mostly this is done with a tension device, which is in general a ratchet or pulleys depending on the fix points [23]. Because of the nylon texture the line will expand under pressure if someone stays on it. Given this elasticity makes it very dynamic and the slacker has to outbalance every sway [24]. To be in control of her body behaviour she has to act very calm, which makes slacklining a quiet and meditative sport activity. Besides walking one can also e.g. bounce,

bob, or swing on the line. As a result various application scenarios arose from this variability, which is further described seen in the next section.

## 3.2 Slacklining variations and categorization

Depending on the length, tension and/or height several slackline variations originated [27, 23, 45]. Regarding the height one can differentiate between a *lowline* (Figure 3.1a) and a *highline* (Figure 3.1b). Almost all lines match in the category lowline because it describes a height in which one can safely jump off the line. On a highline this is not possible. Here you have to make safety provisions like e.g. a separate system in which the person can hook herself in this system above or under the regular line [23].



(a) Common lowline



(b) Highline between mountains [50]

Figure 3.1: Main categories of slacklines

The following terms describe some fine granular variations as well as categorizations of the slackline in different application scenarios. They are not strict, which means they can differ in its scenario or can be combined each other. A common slackline is also named *trickline* (Figure 3.2a). It is tensioned a bit loose in about the height of the knees and has a length up to 30 m. A *jumpline* (Figure 3.2b) is more tightly tensioned to simplify jumps on the line. It has a length of 8 - 14 m and is a bit higher than the trickline. With a *rodeoline* the line is more slacked and has the highest amplitude, like seen in figure 3.2c. It is a relatively short line with a length of 5 - 8 m and the fixation points are in about 2 m such that if a person stands in the mid of the line it is just about above the ground and can swing on it. Slacklines beyond 30 m are called *longline* (Figure 3.2d). The goal here is to walk as far as possible without falling off the line.

Beside these there exist some terms that describe a categorization or environment where a slackline can be applied. For example a *waterline* is simply a line tensed

over a pool, sea or a river like in figure 3.3a. *Urbanlining* can be found in urban areas, where manmade buildings or structures are used to tense the line between, like in figure 3.3b.



(a) Handstand on a trickline [51]



(b) Backflip on a jumpline [23]



(c) Rodeoline [52]



(d) Longline [49]

Figure 3.2: Slackline variations



Figure 3.3: Categorization of slacklining

The disadvantage of these lines is the inevitable usage of static fixation points. In the case of the slackline learning system this would result in a constraint of variability for developing, testing, and study purposes. For feasibility reasons and since the focus of the study lies mainly on beginners the slackline doesn't have to be very long. Therefore the choice fell on a mobile slackline device namely *alpidex POWER-WAVE 2.0*<sup>1</sup>. It provides the needed mobility and independency due to its comparatively short length of three meters. The included slackline is tensed around brackets at both ends of the device. The middle rail is divided into two parts and needs to be put together. Hence it is possible to set it up indoors as well as move it in different positions with a minimum of effort 3.4.

Figure 3.4: Mobile slackline *alpidex POWER-WAVE 2.0* [1]

<sup>1</sup><http://www.alpidex.com/fitness/slacklines/slackline-gestell-in-2-laengen-power-wave-2-0-inklusive-slackline/a-10288/>

### 3.3 Slackline learning techniques

Section *Exercises during slackline training* showed that systematic help is not essentially necessary to learn slacklining. The user of the interactive learning system should therefore be able to learn it by herself without any further external help. Therefore section *Methods for slackline skill acquisition* differentiates between two learning concepts on which the interactive learning system relies. Further section *Stages and exercises of learning slacklining* describes the categorization of specific slackline exercises in the system, which structures at the same time the learning flow of the user.

#### 3.3.1 Methods for slackline skill acquisition

##### Methodical routine

A methodical routine can be integrated in almost every sport activity. It consists of a series of exercises, whose difficulty increases with further practice. The selected exercises should base on methodical principals that can be scaled by e.g. easy to difficult, known to unknown, or simple to complex [11]. Größing [15] describes the general procedure as follows: at the beginning of a methodical routine the trainee will perform warm up exercises. This is useful to prepare her for the training. After that preliminary exercise will be provided, which are more specific regarding the actual exercises. With this she will learn the general motoric basics and train the movements needed to perform the activity. Further it ensures a smooth transition for the main exercises.

Thomann [44] designed a methodical routine as well as a dynamical methodic for slacklining skill acquisition. His methodical routine inherits various approaches with different elements to reach the goal of learning slacklining. However the integration of these elements are more strict to guide the trainee through a constructive exercise procedure (Figure 3.5). At first an introduction and preliminary exercises can be integrated. This follows by material and security where the lines dynamic, how to jump off, and controlling of the line is covered. Further the learning of the oscillation behaviour should be implemented with or without methodical help. Afterwards the user can decide to execute balance training with or without help. With help the trainee can directly balance on the line, which includes external support. Without any further help she can decide to first sit, step on the line, or balance independently. Continuing the trainee can decide if she wants to train the static or dynamic balance, which follows by the possibility for more variable exercise execution like walking forwards on the line, walking backwards, with eye closed, etc. Before going to train some tricks on the line, which is on the very end of the routine, the trainee has to learn first staying across the line with her feet. This is a necessary part for several tricks and has to be learned before.




Figure 3.5: Methodical routine [44]

### Differential methodic

The differential or dynamic methodic follows another approach. It is in coherence with an open learning situation [44]. This means it depends on several factors, which in slacklining would be line type and length, tension, environment, etc. Considering the interplay of these factors each trainee can construct her own training set. A dynamic methodic is a practical usage for this [3, 41]. This inherits the model of stepping stones. In general it describes that many possibilities can lead to the same goal. Each potential way has therefore its own difficulty level. This results in a more modular way to reach a specific goal. In comparison to the methodical routine it results in bigger differences in stimulus and provide more variability in the movement execution, like compared in figure 3.6.




Figure 3.6: Comparison methodical routine vs. differential method [44]

To make use of the principle of differential learning the trainee can follow a methodical principle like seen in methodical routine. If she reaches a certain threshold of skill level more dynamic procedures can then be involved in the actual learn process.

The usage in slacklining can be integrated like described and visualized by Thomann [44] (Figure 3.7). He divided exercises into five learning stages and its coordinative demand and complexity. The main goal is to master controlled and complex movements on the line. The trainee has to choose an amount of various exercise of all stages. Each more complex exercise can either be supported by methodical help or the trainee can return to the lower stage to learn the movement for the specific exercise. Each trainee can therefore create her individual path. Modification and integration of more useful exercises are allowed. A structured examples can be seen in figure 3.7. The purple arrows visualize a way for people that are more coordinative, more venturesome, or have background knowledge. In contrast the green arrows visualize a path for people that are less coordinate, less venturesome, or have no background knowledge in slacklining.




Figure 3.7: Dynamic methodic in slacklining [44]

For proper user training with the system the trainee should follow a clear workflow. Therefore the methodical routine is the better choice as a learning concept in this interactive learning system. She learns right from the beginning essential aspects of slacklining that are relevant and build up on each other. Because it follows a strict linear sequence stages and exercises can be designed as levels. The next subsection *Stages and exercises of learning slacklining* will therefore cover a clear workflow integration of exercises for this learning system.

### 3.3.2 Stages and exercises of learning slacklining

Now that an overview about slacklining and its learning techniques are given several practical exercises have to be considered. Repetitive trials are one approach of learning to walk on the line. However this could result in dangerous situations and frustration of the slacker because of her missing skills. Therefore an exercise set is elaborated that teach and guide the slacker. The teaching goal should be that the slacker can balance with a controlled manner on the line, stay on it for a few seconds, and be able to walk a few steps. In general one has to acquire three core skills to achieve this goal [24]. At first the slacker should be able to stay on one foot. This is essential because most of the time the slacker has a standing foot on the line and the other one servers as balance component. Second the balancing on a narrow surface since the slackline exists of a limited width. Lastly managing the height is also important due to the fact that the slackline is mostly tensed around the knee height and above.

As a groundwork the elaborated exercises are based on Kroiß [24]. He elicited learning exercises for beginners on a slackline within a school class, which gives a good basic on the exercise integration. Further several other references [2, 7, 8, 14, 22, 23, 33, 44] have been researched to elaborate exercises that fit the best in this system. Each exercise is therefore categorized in one of four tiers, which represent the fundamental basis of the exercises routine. In the following each tier is introduced, its goal clarified, and the learning aspects described:

#### Tier I - Preliminary exercises

The first tier serves as a preparation for the subsequent exercises. Hence just exercises on the ground will be executed. This is to train and strengthen the persons general physical balance. In general it is recommended to train barefoot or with socks to get a better foot feeling. The knees should be bent to have a better initial position for movement compensation. Keeping the head up and setting a focus point can help to calm the visual sense of balance. In almost all exercises of this tier the arms have to be stretched to the side, be over the shoulder, and bent in about 135 degree. This is the biggest balance function overall because you have freedom in all directions and the slacker can shift her body's center of gravity. Further all exercises should be executed slowly and controlled to master the body behaviour.

**Tier II - First contact with the line**

Mastering the general physical balancing leads the slacker to her first experience with the slackline. The goal is to get a feeling for the slackline and to be able to get up on the line as well as hold herself for a short amount of time. For this the slacker has to become familiar with the line, feel the imbalance, how her body wants to behave, and get a feeling for counterbalancing unpredictable movements. Therefore starting at the sweet spot, that's about 1/3 of the line, can help. It's an area with a comfortable vibration characteristic. The foot should also be always in alignment with the slackline to have the biggest amount of surface of your foot covered with the line, which results in more contact area of the foot. If the slacker has problems with holding her hands over the shoulder, she can turn the palms to the top and the hands will then raise automatically up. A relaxed but straight upper body can help to hold the right position.

**Tier III - Static exercises**

More difficult exercises come in this tier. The slacker is now familiar with the line and able to stand for a short amount of time on it. The goal is that the slacker should stay confidently on the line. Further it serves as preparation for walking on the line. All prior learned techniques have to be directly applied. The non standing leg now comes more into action. It serves as an additional balancing parameter to both of the arms. If the slacker has problems with going up on the line, she can keep the balancing leg vertically in line with the standing leg while going up and then move it to the side. The pressure is mostly around the ball of the foot.

**Tier IV - Dynamic exercises**

This is the last tier and it involves the dynamical part for the slackline. The slacker should now be able to stay confidently on the line with one foot and both feet. The goal is to learn how to make the first steps as a result for walking on the line. In general it is applying static exercises together. While staying on the line and when the slacker wants to make a step she can guide her balancing foot to the side of the line and shift it then forwards. Letting the knees together when making a step forward helps because the legs can support each other. Making small steps won't shift the body's center of gravity that much forward, which results in more control.

## 3.4 Conclusion

Slacklining can be compared with ropedancing but with a wider and more flat ribbon. It is a sport activity that claims a certain amount of balancing skills.

Therefore two methods exists for skill acquisition, which are the methodical routine and dynamic methodic. The interactive learning system will focus on the methodical routine because it follows a clear workflow and its structured routine can be easily implemented into the system as a prototype. With the help of Kroiß [24] and other research papers a set of exercises have been elaborated that fit in this routine and train beginners appropriately.

---

---

# Chapter 4

## Concept

This chapter describes with the help of chapter *Related Work* and *Slacklining and slacklining learning techniques* the conceptual analysis of an interactive slackline learning system with real-time feedback. The idea of this system is to provide helpful information, appropriate exercises, and feedback techniques to the user for learning slacklining with the given application. One main feature is the autonomous interaction with the system. This gives the opportunity to be independent of other human help and therefore it can only be controlled by the user that is currently interacting with the system. It responds to the actions of the user and provides several feedback indicators for the current exercise execution to help her with exercise execution. Therefore in the following a conceptual analysis will elaborate the requirements of the system. Section *General Information* describes basic requirements of the entire system. This is followed by the more specific sections *Interaction*, *Stages*, *Exercises* that describe how to interact with the system and how exercises are properly structured. Another main component is how to provide properly feedback to the user, which is part of section *Feedback system*. Lastly section *Scenario* gives a good overview about the workflow of the particular components.

### 4.1 General Information

In general the system should be easy to understand, to learn, and to interact. To achieve this it should provide proper user experience. Usability heuristics are useful to identify or to prevent problems in a system. Therefore the concept will rely on the interaction design principles by Nielsen [29] described in subsection *Ten heuristic principles for interaction design*. Beside this certain tasks have to be

considered that are more related to this system. An overview about these can be found in section *System specific basics*.

#### 4.1.1 Ten heuristic principles for interaction design

Nielsen designed his ten heuristics by comparing several sets of usability heuristics with existing usability problems from certain projects. Hence he was able to determine what heuristics identify usability problems the best and therefore creating a set of them. To prevent that a system results in having such problems they can also be used as a guideline for designing and developing a user friendly system. The interactive slackline system will follow these principles, which are described in the following:

##### **Visibility of system status**

The system should always keep the user informed about the current state through appropriate feedback in an adequate time.

##### **Match between system and the real world**

The system should provide the user with familiar terms and information. Using technical terms with which she is not familiar can lead to confusion. Therefore proper information should be natural and in a meaningful order.

##### **User control and freedom**

If the user clicks accidentally on something she should be able to leave this state without any troubles.

##### **Consistency and standards**

It should follow a clear design standard and provide consistency. The user should not be confused whether different terms or elements mean the same.

##### **Error prevention**

Conditions and actions that could easily result in errors should be prevented. Another option is to inform the user about the consequences that the action may have and which she has to actively confirm.

##### **Recognition rather than recall**

The users memory load has to be minimized. She should not remember every action or information. Elements, actions, and options should be visible and instructions about the usage must be easy to retrieve.

##### **Flexibility and efficiency of use**

Providing quick options and allowing to skip certain steps can speed up the interaction for more familiar users. Hence the system should take care of both

novice and experienced users.

### Aesthetic and minimalistic design

Information should just contain aspects that are relevant to the user and that she really needs. Every irrelevant data decreases the intelligibility.

### Help users recognize, diagnose, and recover from errors

Error messages should accurately indicate the ongoing problem such that the user knows what is wrong. Providing a constructive solution helps the user to solve the problem.

### Help and documentation

Optimally the system can be used without any further documentation. It may be the case to provide help and documentation. If it cannot be circumvented it should be easy to find it and clearly show the relevant steps.

#### 4.1.2 System specific basics

One person at a time should be able to interact with the system. This is because mostly just one person can stay on the slackline especially for beginners. However it should provide the ability to have multiple user profiles. One can switch between those such that several persons can have a profile on the same application. For proper user training the system should follow a clear workflow. Therefore two methods have been discussed in section *Methods for slackline skill acquisition*. A methodical routine will be used with which stages and exercises can be designed as levels. These should be locked at the beginning and the user can unlock them by successfully executing the prior exercise. Another important part is the user tracking. The system should be able to track the user in an appropriate accuracy such that it can match the users movement with the actual exercise. This is in correlation with properly providing real-time feedback, which is further discussed in section *Feedback system*. All relevant recorded data should be immediately saved when it is needed, e.g. when successfully accomplishing an exercise.

## 4.2 Interaction

The interaction can be seen as a bigger part of the system since it is autonomous. The user should be able to navigate through the system by herself with her hands as input for the interaction. A cursor should always be visualized to navigate through the systems interface. If the user initially starts the system, there should be an engagement gesture to convey that the system initially recognises and

responds to a user action. Further a small tutorial should be given in which the user will be trained on how to use the interaction possibilities with the system (*cf. Recognition rather than recall*). To make her familiar with these, she should directly apply these techniques in the tutorial. The current state of the interaction should be properly visualized, such that the user knows if she is in default mode or in progress of an interaction regarding an element (*cf. Visibility of system status*). To be able to interact with elements, the user should stay in the right position, so that the system knows if the user is ready to start. This could be useful before starting the actual exercise. Interaction will also play a role in exercise execution. In here the user interacts with the system by trying to match the predefined exercise. She should then get appropriate feedback, which is further explained in section *Feedback system*.

### 4.3 Stages

The system covers predefined exercises, which are subdivided in stages that have been elaborated in section *Stages and exercises of learning slacklining*. These are designed as levels, which the user has to unlock. With this a slightly exergame like approach is followed to motivate the user for unlocking the next level. Therefore a menu should exist for all available stages as well as for all exercises within a stage. To give her a starting position, the very first stage and exercise should be interactable. She can then unlock the next stage by accomplishing all exercises in the last one. Hence it can be assured that the user is able to encounter with more difficult exercises in the next stage. An introduction into each stage should inform the user about the purpose and goals of it, as well as general information about the exercise within that stage. Lastly a summary gives an overview of her performance for the entire stage.

### 4.4 Exercises

Each exercise is part of one stage. It is divided into two body sides, which consists of several repetitions (Figure 4.1). Every exercise is locked except the first one to provide a starting point, like with the stages. The next exercise should be unlocked by accomplishing both sides of the current one. Similarly a side will be completed if all repetitions have been finished. Like for the stage, each exercise should be instructed for the user such that she can successfully perform it. The system will also recognise if the user is ready to start with the exercise. During the execution she should get real time feedback about her current performance. An exercise summary should then show the performance of the execution with several performance parameters regarding the given exercise.




Figure 4.1: Exercise structure

## 4.5 Feedback system

Feedback is the main and most powerful component of the interactive learning system. Since the user should interact on her own with the system one has to assume that no other person interfere with her and the system. With this in mind the feedback of the system should designed in a way, that the user knows at any time what she has to do or has done (cf. *Aesthetic and minimalistic design*). In general audio and visual feedback will be provided to the user. Regarding the interaction with the system, e.g. clicking a button, the system should respond with an audio signal as well as change the elements visual state accordingly.

Real-time feedback supports the trainee during her performance and enhances the learning effect more than with post feedback methods (cf. *Approaches and techniques for providing feedback*). Hence the overall exercise execution as well as its accomplishment can be improved by providing appropriate real-time feedback. The system should therefore response to the user with helpful information. This can be seen in several other sport applications like *EA SPORTS Active 2*<sup>2</sup> or *Nike +*<sup>3</sup>. The provided feedback should mainly indicate if the current execution is performed correctly or not, visualize the the performance of the user regarding the predefined exercises, and show the execution progress. The user should also see herself mirrored in an appropriate environment to see her current execution and if she is in detection range of the tracking device. With this a baseline is built for appropriate real time feedback.

<sup>2</sup><https://www.ea.com/de-de/news/ea-sports-active-2-bringt-fitnessfans-in-die-form-ihres-lebens>

<sup>3</sup><https://news.nike.com/news/introducing-nike-kinect-training>

## 4.6 Scenario

To have a better understanding regarding the interplay of the several components a generic scenario workflow will be given from a users point of view. The users name is Bob and he is 21 years old. While climbing with friends in a climbing hall he noticed a new interactive learning system that they provide to visitors for trying and learning slacklining. He heard once of this activity by friends but never had the chance to try it. So he decides to test it and wants to execute some exercises. To engage with the system he has to stay in front of it, which recognizes him immediately. At the beginning it introduces him regarding the interaction possibilities. After that he selects a tier and is further informed about the goal and basics of this stage. Once confirming that he read everything it leads him to the first available exercise. The system shows him how to execute it properly. Right after starting the exercise he gets helpful real time feedback to correct himself for a successful accomplishment of the execution. After he finished the exercise Bob gets an overview about his performance.

## 4.7 Conclusion

The interactive slackline system should be able to teach and support user how to slackline with predefined exercises. For proper realization a few things have to be considered. The system should comprise an appropriate amount of user experience. By following and respecting Nielsens ten usability heuristics it provides an overall standard of usability. Further some system specific groundwork should be integrated. This involves for example autonomous interaction, proper user tracking, and supportive real-time feedback. More specifically the stages and exercises should be designed as a level like integration that can be unlocked by successfully completing exercises. Each of the exercises should be introduced to the user to give her an understanding of the correct execution. Lastly the feedback system is one of the biggest component. It involves audiovisual real-time feedback for the user interaction as well as exercise execution, and general feedback for rating her performance regarding an exercise or the entire stage. The next chapter *System integration* relies on this concept and elaborates the development process.

---

---

# Chapter 5

## System integration

This chapter shows the implementation of the interactive learning system with real-time feedback regarding the conceptual elaboration. Like seen in subsection *Comparison of tracking technologies* the Microsoft Kinect v2 will be used as tracking technology. Hence before going into the implementation detail section *Technical feasibility* clarifies the feasibility and the performance of tracking persons on a slackline with the Kinect. Further section *Gesture Construction* describes the recording and training of predefined gestures for the exercises in the system. After this section *System architecture* describes the general system architecture which involves the interplay of the Kinect SDK with Unity3D as game engine. Further it involves more specific how the data management, engagement, interaction components, gesture integration, and real-time feedback are implemented. Finally section *User Interface* covers the design process of the application including scribbles, mockups and the final integration.

### 5.1 Technical feasibility

Now having the concept and system integration, this section clarifies questions regarding the technical feasibility. First if it is possible to track a human body on the slackline with the Kinect v2. Is the answer positive than the second question should be how good is the tracking behaviour of the device and can it therefore be used to track a human body on a slackline.

As seen in several movement scenarios, in the area of balance training, the user were successfully trackable by the tracking device [CITE]. Hence the expectation is that the Microsoft Kinect v2 should be able to track the human body on a slackline with an appropriate accuracy and precision. But the range of the slackline, the movement of the line itself, unpredictable movements of the user,

and his balancing actions could also possibly disturb the tracking ability. This can then lead to imprecise and inaccurate tracking data that negate the stated findings of other tracking balancing scenarios. With this in mind multiple angles, positions of the camera, as well as the slackline positioning have been tested.

### 5.1.1 General setup

Like seen in *Introduction into slacklining* a mobile slackline device is the best solution for the learning system. This makes it easy to test it for the best position regarding the tracking camera, which is an essential part of the experiment.

In slacklining the user should be free in his movement and match predefined gestures. Therefore the low-cost tracking camera Kinect v2 is used as tracking device. As discussed in **Interactive technology** this is the most appropriate one out of the available user tracking devices. A mentionable role plays the detection range of Kinect's depth sensor regarding the length of the slackline. The sensors range lies between **0.5 up to 4.5 meters [CITE]**. Since a mobile slackline is used with a length up to 3.5 meters, it would fit entirely in the tracking range. To track user for further training on a longer slackline, the depth range is not sufficient. This could be solved by using more than one Kinect device to have a larger the range.

Generally a major point for tracking the user is the interplay between positioning the tracking device and slackline. The coherence of angle and height of the Kinect v2 is essential for the depth range, which varies by changing these parameters. This will be discussed in the following.

### 5.1.2 Testing scenario

The study took place in the laboratory of the research group in the *german reasearch center for artificial intelligence*. A big advantage of this is the large space to place the slackline in different variations. The slackline can therefore be easily moved and is faced in three positions to the Kinect - frontal (0 Degree), diagonal (45 Degree) and sideways (90 Degree) (**Figure X**). Each of this positions is tested regarding three different height level of the Kinect v2. Therefore it is attached on a tripod like seen in **Figure X**. At the end nine different combinations are covered to track a user on a slackline, which gives a good coherence of the camera height position to the slackline direction. In the following the results discuss the feasibility of the coherence. With this a good overview is given to find appropriate tracking positions.

#### Slackline positioning

##### *Sideways*

Here is the slackline positioned sideways, in 90 Degree rotated to the Kinect v2. The advantage of this is that the whole body on the slackline is in a constant line within the tracking area of the Kinect v2. With this no interference regarding the tracking distance can happen (**Figure X**). But the result show that regardless of the Kinect height the user tracking is very bad. This is because many body parts overlay and the Kinect v2 has problems to detect the body joints with appropriate accuracy and precision, which can be seen in **Figure X**. Therefore this seems not like the appropriate slackline position.

### *Diagonal*

The slackline stays diagonal in 45 Degrees to the camera view. Because of this there is now a distance between front and end point of the slackline. This is not a problem because it fits well in the tracking range (**Table X and Figure X**). This could even result in a better trackability in matter of the depth field range, since the distance in the front shrunked and is therefore closer to the Kinect depth view. Another advantage is that many body party doesn't occlude entirely here because of the angle to the camera. Therefore a better tracking ability is given than positioning the slackline sideways.

But this problem is not entirely solved. It occurs with occluding joints of the slacker at the end of the line due to the angle the arms and the body **occlude/interfere** with each other. Also the whole leg occludes the other one while stepping forwards (**Figure X**). This results in a not entirely perfect joint tracking and can lead to detection problems, depending on the executed exercise.

### *Frontal*

In the last positioning the slackline stays frontal in line with the user facing towards to the Kinect camera. The distance takes almost the whole range from the Kinect's depth field up to the edge of it (**Table X**). The advantage is the user tracking ability which is here the best out of the three positioning. The camera can see the full body and have nearly no problems with occlusions.

One problem could occur with overlaying feets if the slacker stay with both feet on the line, which is in this case independent to the Kinect height (**Figure X**). But testings regarding this problem have not shown any critical detection problems. The Kinect can calculate the location of an occluded joint with a certain tolerance due to its own algorithms [**CITE**].

### **Kinect height**

Three main height levels were used to show the main differences of the tracking behaviour from the Kinect. It is mounted on a tripod and covers the heights seen in **Table X**, within the range of 0.80 meters up to 2.40 meters from the ground.

Beginning with a height of 2.40 meters the Kinect has a very steep angle to track the slackers body on the full range of the slackline. Because of this the depth range shifts into the front like seen in **Figure X**. Therefore if the slacker begins

at the starting position on the slackline, he immediately reaches the end of the tracking area which can cause tracking problems. Because of this steep angle the joints will occlude other, the further he walks to the end of the line.

A step lower with a height of 1.60 meters the entire body is fully visible in almost all ranges. The Kinect is now on a level with the users shoulder and has therefore a relatively flat angle. Because of this the slackline has to be positioned a little bit further away as former to be fully visible for the Kinect view. This results in a more homogeneous depth range view like seen in [Figure X](#).

Problems can occur at the very end of the slackline depending on the slacker's height. It could be the case that his head or more will be cropped. Therefore the slackline has to be slightly further away from the Kinect camera than on other heights. But for beginner training purposes this is not relevant.

A height of 0.8 m results in an even more flat ground perspective. The Kinect is now a little above the level as the slackline. Like in the last one the whole body is in the entire line good visible, but here also at the very start of the line. Problems can occur here with the tracking ability at the starting point. This is because the full tracking range is used ([Figure X](#)). Therefore at the very end

Overall a range of 0.80 m up to 1.60 m seems like the best height for the Kinect for tracking a slacker. The tracking and view is more homogeneous and the angle is flatter with which the full depth range can be used.

### 5.1.3 Best positioning for beginner learning purposes

The frontal positioning has the only big problem with the depth range at the starting position of the slackline. Since only beginners are the main focus of this study, the starting position of the slackline plays an important role. Therefore for tracking purposes it is better to move the slackline closer to the camera. With this the last quarter of the slackline is cropped out of the view but the slacker can be tracked with a higher confidence ([Figure X](#)). The Kinect height should be between 0.8 and 1.8 meters. With a higher attachment the angle will be too steep and the available space is cropped, or occlusion of body parts can occur.

**table**

## 5.2 Gesture Construction

The system should provide predefined exercise on which the user is guided for learning slacklining. To give feedback in an appropriate manner the exercises are represented as custom gestures. There are two approaches of creating custom gestures. The first is one is to do heuristics, which means manually tracking the position of each joint and write code according to the action that should happen if the joints exceed a threshold or are in a defined range. This is used and implemented for simple gestures like raising the hand over the head. For

more complex gestures, the developer must have a good understanding about how the human body behaves and moves. In the most cases developer have not the appropriate expertise. Hence for complex gestures like the specific slackline exercises the second approach is to use the Visual gesture builder (VGB) provided by Microsoft.

### 5.2.1 Visual gesture builder

This tool relies on machine learning and looks at the data given by the developer via pre recorded clips. With these it builds a database that can then be used to track the actual gesture in an application. The more data is provided to it the better the detection by the Kinect. Another advantage is that environmental factors are not that complex to handle as in comparison to heuristics. For example if the sensor is set too high or too low the developer has to consider this in his code and it can blow up managing and maintaining such factors in code. With the VGB the developer just records data with the sensor on the appropriate height and let the machine learning algorithm learn it. The cons are the huge file size of the recorded clips which can take very much disk space. Also setting the keyframes for parts that the builder should detect is time consuming whereas on the other hand it is simple and user friendly.

### 5.2.2 Building gestures workflow

The workflow looks like in figure [figure workflow note pad](#). First clips have to be recorded with Kinectstudio. This is a monitor and recording software for the kinect. The clip must be recorded in raw data to have the necessary information about the streams. Like seen in figure [figurename](#) several streams can be selected as well as recording audio and so on. The most important for the VGB are the [infrared, body, bodyindex?](#). After finishing with this a new project can be built with the VGB. This can be done either manually in one screen or with a wizard that guides the user through the process. In here the developer considers on which parts of the body the gestures relies on. After that she has to choose if it is a discrete or a progress gestures [explain both](#). Discrete gestures area more of static ones, like staying on one leg or punching. Progress gestures can have multiple steps like switching the standing leg. Figure [VGB project hierarchy](#) shows the project hierarchy. In part A of figure [VGB project hierarchy](#) the actual training data, the recorded clip of Kinect studio, is inserted. With this the developer has to set keyframes that define the gesture movement to track. If it is a progress gesture more fine granular keyframes, e.g. for turning a steering wheel from the right side to the left are possible. After finishing this the database can be built and then analyzed via the live preview that can be seen in figure [figure live prev](#) or with other recorded clips in the analyze area. With this the VGB sets its own keyframes on the clip regarding the database it is tested. The developer can then accept these, adjust it, and move it into training clips if necessary.

The database can then be implemented in the application for gesture detecting. The structuring of the systems architecture is part of the next section.

## 5.3 System architecture

In the following several components of the general system architecture will be described that are necessary for the functionality of the interactive learning system with real-time feedback and for the study afterwards. An overview can be seen in figure [systemarchitecture](#).

### 5.3.1 Hardware and software components

As slackline the mobile *alpidex POWER-WAVE 2.0* is used. It is placed in front of the *Microsoft Kinect v2*, which is used as tracking device. The Kinect itself is attached on a [modell](#) tripod with a height of about [height, hüfthöhe?](#). A *Steambox PC* [footnote specs](#) served as development device that fulfilled the recommended specs of the Kinect: [kinect specs](#). To give the user a more immersive feeling a projector [modell](#) with a resolution of 1920x1080 was attached on a traverse system. With this a projection screen with a size of [2x3m](#) is used.

For software realization the cross-platform game engine *Unity3D* by *Unity Technologies* is used. This is a game engine which is mostly used for developing Applications developed with this can be deployed for several platforms on desktop, mobile, web, console, TV, VR, and AR (e.g. Windows, macOS, Android, iOS, Oculus Rift, Windows Mixed Reality and so on). It is widely used for developing games but has also very high compatibility with devices like *VR Head Mounted Display, Leap Motion*, or the Kinect.

For accessing the data stream of the Kinect the *Microsoft Kinect SDK v2.0*<sup>4</sup> has to be installed on the PC. Microsoft offers also a *Kinect for Windows Unity package*<sup>4</sup>, which delivers all required scripts to manage the data stream in Unity for creating a Kinect based unity application. Since *Unity 5* it can be used with the free personal edition, whereas before it could be only used with the pro version. Also the *Kinect v2 Examples with MS-SDK*<sup>5</sup> by Rumen Filkov were used for making data access and interaction implementation more simple as well as getting an idea on how to handle incoming data from the Kinect.

### 5.3.2 Software implementation

The software development process consists of the interplay of two system components (figure [image unity and kinect sdk](#)). First Unity itself, which is used to display and manage actions by the user on the interface. Second the Kinect

---

<sup>4</sup><https://developer.microsoft.com/de-de/windows/kinect/tools>

<sup>5</sup><https://www.assetstore.unity3d.com/en/#!/content/18708>

SDK plugin for accessing the users action recognized by the Kinect device. In the following the data structure and management, interaction integration, and feedback implementation of the system are further described.

### Data management

The data will be stored in JSON files, which is more human-readable and makes accessing and updating data simple in Unity via the JSON serialization feature<sup>6</sup>. For each object containing key-value pairs a class is generated, i.e. for Users, Tier, Exercise, Sides, and Repetitions. In listing [ref c# code example](#) an example for the *Tier* object can be seen. A class must be marked as serializable to work with the JSON serializer. It contains variables, which match the JSON structure on listing [ref json code. c# code example and json file](#)

With this an instance of the class can be created and the value accessed for adjustments (listing [ref img class instance](#)). This can then be serialized into a JSON object. Line [In number](#) shows how existing JSON data can be converted back into an object instance. This is needed to fetch user data that already exists.

#### [img class instance](#)

In the system a default exercise JSON file was created that is used as reference for all users. Each user has therefore the same basement regarding the exercises right from the beginning. For proper data management a internal exercise and user editor was created in Unity (figure [ref editor window](#)). The data files can be managed and adjusted more easily for testing purposes.

#### [img editor window](#)

The files are stored within the *StreamingAssets* folder of unity. It serves as location where files that should be accessed via path name of the target machines file system should be stored. The overall data structure can be seen in figure [img ref data structure](#).

#### [image of data structure](#)

### Engagement gesture

The engagement gesture is the very first interaction with the system. The user raises her hand, such that she initially knows that the system recognizes her actions. An example on how to access the Kinect and manage this gesture can be seen in the code snipped in listing 5.1. The *KinectManager* exists as an empty *GameObject* in the scene and has to be referenced in the script. The *KinectInterop* class delivers several utility and interop function and calls the sensor interfaces. Here it is used to assign the proper joint type for tracking them. For the functionality the script has to assure that the Kinect is initialized, a user has been detected, and the relating joints are recognized. In line 29 the condition checks if

---

<sup>6</sup><https://docs.unity3d.com/Manual/JSONSerialization.html>

the current vertical position of the right hand is greater than the current position of the head joint. If this is the case, the next scene is loaded. This is actually part of the script for the first scene in the application, in which the user has to engage with the Kinect by doing the described movement.

Listing 5.1: C# example code for tracking a raising hand

```

1 public KinectManager KinectManager;
2 private KinectManager _kinectManager;
3 private KinectInterop.JointType _jointHandRight, _jointHead;

5 void Start ()
6 {
7     _jointHandRight = KinectInterop.JointType.HandRight;
8     _jointHead = KinectInterop.JointType.Head;
9 }
10 void Update ()
11 {
12     if (KinectManager == null) return;
13     _kinectManager = KinectManager.GetComponent<KinectManager>();

15     if (_kinectManager &&
16         _kinectManager.IsInitialized() &&
17         _kinectManager.IsUserDetected())
18     {
19         long uId = _kinectManager.GetPrimaryUserID();

21         if ((_kinectManager.IsJointTracked(uId, (int) _jointHandRight) &&
22             _kinectManager.IsJointTracked(uId, (int) _jointHead))
23         {
24             Vector3 jointPosHandRight =
25                 _kinectManager.GetJointKinectPosition(uId, (int) _jointHandRight);
26             Vector3 jointPosHead =
27                 _kinectManager.GetJointKinectPosition(uId, (int) _jointHead);

29             if (jointPosHandRight.y > jointPosHead.y)
30                 SceneManager.LoadScene("Tutorial");
31         }
32     }
33 }
```

## Starting position

After engaging with the system the user is introduced in how to stay in the proper starting position. This is required by some actions like just before starting the exercise execution. It ensures the user is ready and to get her initial joint positions for primarily calculating the y-axis of the joint (cf. [section Feedback integration](#)). This initial joint position can differ if the user stands closer or more far away from the sensor because of the Kinects angel regarding its height. Hence the z-axis joint position of the left and right feet will be compared with each other to have

the same value with a little tolerance. Hereby the user has to stand with both feets in line and in front to the Kinect like in figure [ref illustration](#).

[illustration feets parallel](#)

### Hand cursor interaction

To be more familiar with the system the user interacts with her own hands. With this she is in constant system interaction and gets more used to it. A cursor visualizes where the user currently is and with this she can interact with other interface elements. As interaction gesture four different approaches were tested. First hovering with the hand over elements (Figure [interaction variation A](#)). This gesture is a good approach specific small elements should be selectable. The problem was that relatively big and many interaction elements exists. Therefore the user accidentally hovers over elements which resulted in unwanted misclicks. The second one is interacting by closing the hand to a fist (Figure [interaction variation B](#)). In testing periods many user accidentally triggered a click although they thought they did nothing wrong. Problems exist here concerning the users anatomical behaviour. The difficulty was that the users hand, closes automatically during hand movement. No user will stretch and spread her hand out because it is uncomfortable. Hence they tend to close the hand a little bit, which is more comfortable and results in a misclick recognition of the Kinect, which is fortified by the enlarged standing position of the user (Figure [comparison default & target](#)). A better interaction gesture is the *V-sign*. The user makes simply a pointing gesture with the index as well as the middle finger (Figure [interaction variation C](#)). The event is triggered when the user releases into the default hand state. It clearly distinguished from the fist gesture and will be accurately recognized. To give the user appropriate feedback the state is visualized like in (Figure [img handcursorPointing](#)). The last gesture is pushing the hand towards the Kinect. This is related to the real world like pushing a button down and therefore the most intuitive gestures (Figure [interaction variation D](#)). Since in this gesture the hand has to move from point a to point b in the z-axis the progress is visualized by a filling circle like seen in figure 5.1.

The pushing gesture is implemented as the main interaction technique because of its natural movement and real world reference. A fallback gestures is also implemented if something went wrong or the user feels uncomfortable with the pushing gesture. The *V-sign* is the next best technique for this, since there were less problems than with the remaining gestures.

[img interaction varations A - Hover&wait, B - fist, C - pointing, D - push](#)

### User selection

The user profile are created by the developer. In the user selection the trainee should select the right profile by herself to cover the condition of multiple user




Figure 5.1: Progress of handcursor (Left: Default, Middle: In progress, Right: Finished)

that can train with the system. When selecting a user the system checks if the JSON file has any data. If no data is available the default exercise JSON file will be copied. The users name and id are saved in as *PlayerPrefs*. This is a class in Unity that provides the possibility to be globally accessible in the application. The respective code for setting and getting the values can be seen in listing [ref listing playerprefs](#). This is needed to find the correct path for the JSON files to save the data.

[listing playerprefs](#)

### Tier & exercise menu

The tier and exercise menus are designed as levels the user has to accomplish. A locked tier can be unlocked by executing all exercises of the previous one. This is done by storing a boolean variable named *accomplished* for every tier and its exercises. The structure already seen in section 4.4 is adapter for storing the corresponding information for the tier, exercise, side, or repetition.

### Exercise execution, providing feedback

The most functionality is implemented in the exercise execution. Feedback indicators provide the user with information about the current exercise in real time. This should support the user to successfully accomplish the exercise performance. In the slackline system the following feedback indicators are integrated:

- Correct performance of an exercise
- How good the exercise is currently performed, namely the confidence
- Elapsed time the user is performing the exercise
- When the repetition was successful (i.e. minimum time has been reached)
- When a repetition attempt was not successful
- Amount of repetitions in general, finished, and left

- Checklist about key elements of an exercise (hands up, foot stretched, etc.)

After each successful exercise execution the user is lead to a summary screen. Here she gets an overview about her performance. It shows parameters about the execution time, attempts, and the confidence for each repetition as well as an average value for the accomplished side. A similar summary screen exists also for the entire stage with the same parameters but only the average value for the entire exercises.

## 5.4 User Interface

The user should be introduced to the stage. In here the purpose, goal, and helpful techniques should be given, such that the user becomes an overview about the exercises. At last a summary scene shows several performance parameter for the exercises in this stage.

The user starts with an engagement gesture like raising her hand over the head to convey that the system initially recognises and responds to a user action. After that a tutorial about the interaction with the system will be given that covers clicking and scrolling techniques. Now she's confident with the system interaction and can select a profile in the user select to train. This loads the profile which leads to the stage selection menu. In here she can select a stage, whereas initially the first one is can be selected and the others have to be unlocked by successfully accomplishing all exercises in the preview stage. Selecting a stage leads to the exercise menu. In here she has to read initially the stage introduction to become a basic understanding about the exercises in here. After reading this, it unlocks the first exercise. Selecting an exercise leads to the side selection, where the user has to choose the side she wants to train for this exercise. This is followed by an introduction of the exercise, in which is explained how to perform it correctly. If the user is ready, she should stay in a starting position to be able to start the exercise execution. In here she find all relevant elements to perform the exercise, like indicators for the time, repetitions, confidence and a checklist, which helps her to correctly execute the exercise. After successfully executing the exercise, a summary is shown which summarizes the user performance. Then she can return to the main menu or directly approach the next exercise. A stage summary gives an overview about all exercises with average performance parameters.

replace figure with directional flow




Figure 5.2: Scenario workflow

---

---

## **Chapter 6**

### **Study**



---

---

## **Chapter 7**

### **Conclusion and Outlook**



---

## Bibliography

- [1] ALPIDEX. Slackline Gestell in 2 Längen Power Wave 2.0 inklusive Slackline, 2014. [Online; accessed 13-March-2017].
- [2] BALCOM, SOTT. *Walk the Line: The Art of Balance and the Craft of Slackline*. Slack Daddy Press, 2005.
- [3] BECK, FRIEDER. Sportmotorik und Gehirn : Differenzielles Lernen aus der Perspektive interner Informationsverarbeitungsvorgänge. *German Journal of Exercise and Sport Research* 38, 4 (2008), pp. 423–450.
- [4] BOGDANOVYCH, ANTON AND STANTON, CHRISTOPHER. A Novel Approach to Sports Oriented Video Games with Real-time Motion Streaming. In *Proceedings of the 7th ACM SIGCHI Symposium on Engineering Interactive Computing Systems* (2015), EICS '15, ACM, pp. 64–73.
- [5] CHANG, CHIEN-YEN; LANGE, B.; ZHANG, MI; KOENIG, S.; REQUEJO, P.; SOMBOON, N.; SAWCHUK, A. A. AND RIZZO, A. A. Towards pervasive physical rehabilitation using Microsoft Kinect. In *6th International Conference on Pervasive Computing Technologies for Healthcare (PervasiveHealth) and Workshops* (2012), pp. 159–162.
- [6] CORPORATION, MICROSOFT. Kinect for Windows | Human Interface Guidelines v2.0, 2014. [Online; accessed 13-March-2017].
- [7] DONATH, L.; ROTH, R.; RUEEGGE, A.; GROPPA, M.; ZAHNER, L. AND FAUDE, O. Effects of Slackline Training on Balance, Jump Performance & Muscle Activity in Young Children. *International Journal of Sports Medicine* 34, 12 (2013), pp. 1093–1098.
- [8] DONATH, L.; ROTH, R.; ZAHNER, L. AND FAUDE, O. Slackline training and neuromuscular performance in seniors: A randomized controlled trial. *Scandinavian Journal of Medicine & Science in Sports* 26, 3 (2016), pp. 275–283.
- [9] DONATH, LARS; ROTH, RALF; ZAHNER, LUKAS AND FAUDE, OLIVER. Slackline Training (Balancing Over Narrow Nylon Ribbons) and Balance Performance: A Meta-Analytical Review. *Sports Medicine* (2016), pp. 1–12.
- [10] ESTEPA, A.; PIRIZ, S. SPONTON; ALBORNOZ, E. AND MARTÍNEZ, C. Development of a Kinect-based exergaming system for motor rehabilitation in neurological disorders. *Journal of Physics: Conference Series* 705, 1 (2016), p. 012060.

- [11] FETZ, FRIEDRICH. *Allgemeine Methodik der Leibesübungen*. ÖBV Pädagogischer Verl., 1996.
- [12] FREITAS, DANIEL Q.; DA GAMA, ALANA E. F.; FIGUEIREDO, LUCAS; CHAVES, THIAGO M.; MARQUES-OLIVEIRA, DÉBORAH; TEICHRIEB, VERONICA AND ARAÚJO, CRISTIANO. Development and Evaluation of a Kinect Based Motor Rehabilitation Game. In *Proceedings of SBGames 2012* (2012), pp. 144–153.
- [13] GARRIDO, JUAN ENRIQUE; MARSET, IRMA; PENICHE, VÍCTOR M. R. AND LOZANO, MARÍA D. Balance Disorder Rehabilitation Through Movement Interaction. In *7th International Conference on Pervasive Computing Technologies for Healthcare and Workshops* (2013), PervasiveHealth '13, ICST (Institute for Computer Sciences, Social-Informatics and Telecommunications Engineering), pp. 319–322.
- [14] GRANACHER, U.; ITEN, N.; ROTH, R. AND GOLLHOFER, A. Slackline training for balance and strength promotion. *International Journal of Sports Medicine* 31 (2010), pp. 717–723.
- [15] GRÖSSING, STEFAN. *Einführung in die Sportdidaktik*. Limpert, 1997.
- [16] HÄMÄLÄINEN, PERTTU. Interactive Video Mirrors for Sports Training. In *Proceedings of the 3rd Nordic Conference on Human-computer Interaction* (2004), NordICHI '04, ACM, pp. 199–202.
- [17] HODGES, NICOLA J. AND FRANKS, IAN M. Modelling coaching practice: the role of instruction and demonstration. *Journal of Sports Sciences* 20, 10 (2002), pp. 793–811.
- [18] HOLSTI, LEO; TAKALA, TUUKKA; MARTIKAINEN, AKI; KAJASTILA, RAINE AND HÄMÄLÄINEN, PERTTU. Body-controlled Trampoline Training Games Based on Computer Vision. In *CHI '13 Extended Abstracts on Human Factors in Computing Systems* (2013), CHI EA '13, ACM, pp. 1143–1148.
- [19] JOHNSON, D.A.; ROSE, ED; RUSHTON, S.; PENTLAND, B. AND ATTREE, E.A. Virtual Reality: A New Prostheses for Brain Injury Rehabilitation. *Scottish Medical Journal* 43, 3 (1998), pp. 81–83.
- [20] KAJASTILA, RAINE AND HÄMÄLÄINEN, PERTTU. Augmented Climbing: Interacting with Projected Graphics on a Climbing Wall. In *Proceedings of the Extended Abstracts of the 32Nd Annual ACM Conference on Human Factors in Computing Systems* (2014), CHI EA '14, ACM, pp. 1279–1284.
- [21] KAJASTILA, RAINE; HOLSTI, LEO AND HÄMÄLÄINEN, PERTTU. The Augmented Climbing Wall: High-Exertion Proximity Interaction on a Wall-Sized Interactive Surface. In *Proceedings of the 2016 CHI Conference on Human Factors in Computing Systems* (2016), CHI '16, ACM, pp. 758–769.

- [22] KELLER, M.; PFUSTERSCHMIED, J.; BUCHECKER, M.; MÜLLER, E. AND TAUBE, W. Improved postural control after slackline training is accompanied by reduced H-reflexes. *Scandinavian Journal of Medicine & Science in Sports* 22, 4 (2012), pp. 471–477.
- [23] KLEINDL, REINHARD. *Slackline: Die Kunst des modernen Seiltanzens*. Meyer & Meyer, 2011.
- [24] KROISS, ANDREAS. Der Trendsport Slackline und seine Anwendungsmöglichkeiten im Schulsport. Master's thesis, TU München, 2007.
- [25] LIEBERMANN, DARIO G.; KATZ, LARRY; HUGHES, MIKE D.; BARTLETT, ROGER M.; MCCLEMENTS, JIM AND FRANKS, IAN M. Advances in the application of information technology to sport performance. *Journal of Sports Sciences* 20, 10 (2002), pp. 755–769.
- [26] LIM, DOHYUNG; KIM, CHOONGYEON; JUNG, HOHYUN; JUNG, DUKYOUNG AND CHUN, KEYOUNG JIN. Use of the Microsoft Kinect system to characterize balance ability during balance training. *Clinical Interventions in Aging* 10 (2015), pp. 1077–1083.
- [27] MILLER, FRITZ; MAUSER, DANIEL. *Slackline - Tipps Tricks Technik*. Panico Alpinverlag, 2012.
- [28] MVN, XSENS. - Motion capture suit. [Online; accessed 07-October-2017].
- [29] NIELSEN, JAKOB. Enhancing the Explanatory Power of Usability Heuristics. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems* (1994), CHI '94, ACM, pp. 152–158.
- [30] NUSMAN, DAAN. Real-time full-body motion capture in virtual worlds. Master's thesis, June 2006.
- [31] OPTITRACK. - Optical motion capture system. [Online; accessed 07-October-2017].
- [32] PAAS, FRED; RENKL, ALEXANDER AND SWELLER, JOHN. Cognitive Load Theory and Instructional Design: Recent Developments. *Educational Psychologist* 38 (2003), pp. 1–4.
- [33] PFUSTERSCHMIED, JÜRGEN; BUCHECKER, MICHAEL; KELLER, MARTIN; WAGNER, HERBERT; TAUBE, WOLFGANG AND MÜLLER, ERICH. Supervised slackline training improves postural stability. *European Journal of Sport Science* 13, 1 (2013), pp. 49–57.
- [34] PFUSTERSCHMIED, JÜRGEN; STÖGGL, THOMAS; BUCHECKER, MICHAEL; LINDINGER, STEFAN; WAGNER, HERBERT AND MÜLLER, ERICH. Effects of 4-week slackline training on lower limb joint motion and muscle activation. *Journal of Science and Medicine in Sport* 16, 6 (2013), pp. 562 – 566.

- [35] PISAN, YUSUF; MARIN, JAIME GARCIA AND NAVARRO, KARLA FELIX. Improving Lives: Using Microsoft Kinect to Predict the Loss of Balance for Elderly Users Under Cognitive Load. In *Proceedings of the 9th Australasian Conference on Interactive Entertainment: Matters of Life and Death* (2013), IE '13, ACM, pp. 29:1–29:4.
- [36] POMPEU, J.E.; ARDUINI, L.A.; BOTELHO, A.R.; FONSECA, M.B.F.; POMPEU, S.M.A.A.; TORRIANI-PASIN, C. AND DEUTSCH, J.E. Feasibility, safety and outcomes of playing Kinect Adventures!™ for people with Parkinson's disease: a pilot study. *Physiotherapy* 100, 2 (2014), pp. 162 – 168.
- [37] POMPEU, JOSÉ EDUARDO; TORRIANI-PASIN, CAMILA; DONÁ, FLÁVIA; GANANÇA, FERNANDO FREITAS; DA SILVA, KEYTE GUEDES AND FERRAZ, HENRIQUE BALLALAI. Effect of Kinect Games on Postural Control of Patients with Parkinson's Disease. In *Proceedings of the 3rd 2015 Workshop on ICTs for Improving Patients Rehabilitation Research Techniques* (2015), REHAB '15, ACM, pp. 54–57.
- [38] RYAN, R. AND DECI, E. Self-determination theory and the facilitation of intrinsic motivation, social development, and well-being. *American Psychologist* 55, 1 (2000), pp. 68–78.
- [39] RYAN, RICHARD M. AND DECI, EDWARD L. Intrinsic and Extrinsic Motivations: Classic Definitions and New Directions. *Contemporary Educational Psychology* 25, 1 (2000), pp. 54 – 67.
- [40] SCHLÖMER, THOMAS; POPPINGA, BENJAMIN; HENZE, NIELS AND BOLL, SUSANNE. Gesture Recognition with a Wii Controller. In *Proceedings of the 2nd International Conference on Tangible and Embedded Interaction* (2008), TEI '08, ACM, pp. 11–14.
- [41] SCHÖLLHORN, WOLFGANG. Individualität - ein vernachlässigter Parameter? *Leistungssport* 29, 2 (1999), pp. 5–12.
- [42] TANAKA, KAZUMOTO; PARKER, JIM; BARADOY, GRAHAM; SHEEHAN, DWAYNE; HOLASH, JOHN R AND KATZ, LARRY. A comparison of exergaming interfaces for use in rehabilitation programs and research. *Loading* 6, 9 (2012), pp. 69–81.
- [43] TANG, RICHARD; YANG, XING-DONG; BATEMAN, SCOTT; JORGE, JOAQUIM AND TANG, ANTHONY. Physio@Home: Exploring Visual Guidance and Feedback Techniques for Physiotherapy Exercises. In *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems* (2015), CHI '15, ACM, pp. 4123–4132.
- [44] THOMANN, ANDREAS. Methodik im Slacklinesport - Wie geht guter Slacklineunterricht?, 2013.

- [45] THOMANN, ANDREAS. *Die Entwicklung der Trendsportart Slackline im urbanen Raum*. PhD thesis, 2017.
- [46] USTINOVA, K. I.; PERKINS, J.; LEONARD, W. A. AND HAUSBECK, C. J. Virtual reality game-based therapy for treatment of postural and co-ordination abnormalities secondary to TBI: A pilot study. *Brain Injury* 28, 4 (2014), pp. 486–495.
- [47] VAN DER SPEK, ERIK D. COgnition-based DEsign Rules Enhancing Decisionmaking TRaining In A Game Environment (Code Red Triage): Doctoral Consortium Paper. In *Proceedings of the 28th Annual European Conference on Cognitive Ergonomics* (2010), ECCE '10, ACM, pp. 319–322.
- [48] WIKIPEDIA. Anatomical terms of location — Wikipedia, The Free Encyclopedia. [Online; accessed 05-October-2017].
- [49] WIKIPEDIA. <https://commons.wikimedia.org/wiki/File:Slackline2.jpg>. [Online; accessed 12-March-2017].
- [50] WIKIPEDIA. Slacklining - Picture — Wikipedia, The Free Encyclopedia. [Online; accessed 12-March-2017].
- [51] WIKIPEDIA. Slacklining - Picture — Wikipedia, The Free Encyclopedia. [Online; accessed 12-March-2017].
- [52] WIKIPEDIA. Slacklining - Picture — Wikipedia, The Free Encyclopedia. [Online; accessed 12-March-2017].
- [53] WIKIPEDIA. Slacklining - Picture — Wikipedia, The Free Encyclopedia. [Online; accessed 12-March-2017].
- [54] WIKIPEDIA. Slacklining - Picture — Wikipedia, The Free Encyclopedia. [Online; accessed 12-March-2017].
- [55] WINSTEIN, CAROLEE J. AND SCHMIDT, RICHARD A. Reduced frequency of knowledge of results enhances motor skill learning. *Journal of Experimental Psychology: Learning, Memory, and Cognition* 16, 4 (1990), pp. 677–691.
- [56] WOOLFORD, KIRK. Defining Accuracy in the Use of Kinect V2 for Exercise Monitoring. In *Proceedings of the 2nd International Workshop on Movement and Computing* (2015), MOCO '15, ACM, pp. 112–119.
- [57] ZAK, HEINZ. *Slackline: das Praxisbuch*. blv, 2011.