Wood Surface Defect Detection Under Severe Long-Tail Imbalance: A Comparative Benchmark of Cascade R-CNN, YOLO26, and RF-DETR

Christian Raul Mestas Zegarra[1*], Luis Gustavo Sequeiros Condori[1], Yenaro Joel Noa Camino[1], Mariel Alison Jara Mamani[1], Yasiel Pérez Vera[1]

[1*]Systems Engineering Professional Program, Universidad Nacional de San Agustín, Arequipa, 04001, Arequipa, Peru.

*Corresponding author(s). E-mail(s): cmestasz@unsa.edu.pe;
Contributing authors: lsequeiros@unsa.edu.pe; ynoa@unsa.edu.pe; mjarama@unsa.edu.pe; yperezv@unsa.edu.pe;

Abstract

Automated inspection of surface defects in wood faces challenges arising from severe long-tail class imbalance and high intra-class variability of organic anomalies. This article presents a comparative benchmark evaluating three object-detection paradigms, one-stage, two-stage, and transformers, and four data augmentation strategies: no augmentation, Albumentations with class balancing, BoxAug with noise transformations, and BoxAug with neural harmonization via LibCom. The study uses a dataset of 4,000 images with 8,888 annotations across 8 defect categories and employs a reproducible five-stage pipeline with step caching. Experimental results demonstrate that RF-DETR achieves the highest ranking precision with mAP@0.5 of 0.717 under per-model calibrated confidence thresholds. At the same time, Cascade R-CNN with BoxAug LibCom reaches the best operating-point F1 of 0.798. Augmentation effects are paradigm-specific: BoxAug LibCom improves Cascade R-CNN by +0.033 mAP@0.5, whereas all three augmentation strategies leave YOLO26 at or below its unaugmented baseline (0.592 to 0.604 versus 0.618). Per-class analysis at AP@0.5 shows marrow reaching 0.910 while quartzite peaks at 0.550, confirming that visual distinguishability interacts with class frequency. The calibrated-threshold protocol and the paradigm-dependent augmentation response are discussed, and future directions are proposed, including extended training budgets and diffusion-based augmentation.

Keywords: defect detection, computer vision, deep learning, wood processing, comparative benchmark

1 Introduction

Modern industrial manufacturing depends on automated quality control systems to maintain operational efficiency and reduce costs in supply chains [1]. The integration of computer vision and machine learning technologies has transformed industrial inspection processes, enabling anomaly detection at speeds and precision levels that surpass manual methods [2]. Quality inspection automation has become an essential component of Industry 4.0, particularly in sectors where natural material variability hinders the standardization of production processes [3]. The wood industry is a significant global economic sector, where wood is a renewable

resource of high structural and commercial importance [4]. Wood processing involves multiple stages from sawing to final finishing, and in each stage material quality directly determines its value and applicability [5]. Total wood utilization in production processes reaches only 50% to 70% of volume because defects must be identified and removed [5]. This waste rate highlights the urgent need for more efficient inspection systems that maximize resource utilization [6]. Integrating these systems into automated plants, coordinated with robotic arms and autonomous material-handling cells, is essential [7].

Automated recognition of surface defects in wood presents specific technical challenges that distinguish it from other object detection applications [8]. Surface anomalies encompass live knots, dead knots, drying cracks, resin pockets, fungal stains, and mechanical damage [5]. The high intra-class variance of defects, where the same anomaly type can look very different, is a major obstacle [9]. The low contrast between certain defects and healthy wood grain hinders precise segmentation of anomalous regions [10]. Variable lighting conditions in sawmill environments, combined with production line speeds up to 9.6 m/s, impose strict requirements on detection-algorithm inference times [9]. Additionally, industrial datasets suffer from severe long-tail class imbalance, where rare defects such as marrow or missing knots are underrepresented compared to the high prevalence of standard knots [9]. These factors converge into a research problem that requires specialized algorithmic solutions with high spatial localization and low latency [11].

Historically, wood defect inspection relied on trained personnel who visually examined surfaces for imperfections [6]. This manual approach presents significant limitations in terms of speed, consistency, and scalability [6]. Operator visual fatigue, subjectivity in evaluation, and inability to process large volumes of material in real time are recurring problems that affect process reliability [6]. Previous studies have demonstrated that manual inspection rarely exceeds 70% accuracy in high-speed industrial environments [9]. To address these limitations, the state of the art has evolved from systems based on optoelectronic sensors and classical computer vision [12]. Classical approaches used image processing techniques such as gray-level co-occurrence matrices, local binary patterns, and oriented gradient descriptors (HOG) [13], combined with support vector machine (SVM) classifiers [14, 15]. The Viola-Jones framework [16] represented a pioneering advance in real-time object detection using Haar-like features [17] and AdaBoost cascade classifiers [18]. Image matching evolved from handcrafted descriptors (SIFT, SURF, HOG) to deep hierarchical representations [19]. However, while these classical methods offer interpretability, they are severely limited in handling the high natural variability and low contrast of organic surface defects in wood [11].

The transition to deep convolutional neural networks (CNNs) has enabled automatic extraction of hierarchical features that capture complex spatial patterns [20]. The contemporary technological ecosystem offers frameworks for developing high-performance deep detectors [21]. Deep convolution-based architectures evolved through two-stage region detectors such as Faster R-CNN [22] and Mask R-CNN [23], as well as anchor-based one-stage detectors such as Single Shot MultiBox Detector (SSD) [24] and Feature Pyramid Networks (FPN) [25]. Anchor-free models include FCOS [26]. The YOLO family drove real-time detection from its early versions YOLOv1 [27], YOLOv2 [28], Scaled-YOLOv4 [29], to comprehensive revisions of the YOLO paradigm from YOLOv1 to YOLOv8 [30, 31]. More recently, Vision Transformer (ViT)-based models introduced global self-attention mechanisms that capture long-range spatial dependencies in industrial visual inspection [32].

Compared with classical descriptors and legacy detectors, the current state of the art demands rigorous evaluation of cutting-edge deep learning paradigms combined with synthetic data balancing techniques. Advanced convolutional architectures such as Cascade R-CNN [33] provide multi-stage bounding box refinement, while real-time one-stage paradigms such as YOLOv10 [34] establish end-to-end NMS-free dual-head detection. In the transformer domain, RF-DETR [35] establishes the precision and latency frontier through neural architecture search [35]. In parallel, object augmentation techniques (BoxAug [36], Simple Copy-Paste [37]) integrated with deep composition frameworks and neural harmonization (BargainNet [38], PCT-Net [39], Latent Bridge Matching [40]) enable mitigating class imbalance without introducing visual artifacts. The main objective of this article is to

provide a 3-by-4 matrix evaluation that intersects these three deep paradigms with four data augmentation strategies in surface defect recognition in wood.

The remainder of the article is organized as follows. Section 2 presents related work on wood defect detection using deep learning techniques. Section 3 describes the materials and methods used, including theoretical foundations, tools and technologies employed, dataset characteristics, and the proposed development method. Section 4 details the obtained results, including performance metrics and comparative analysis. Section 5 interprets the main findings, compares them with existing literature, and analyzes interactions between architectures and augmentation strategies. Section 6 summarizes the study contributions. Finally, Section 7 presents future work and possible research extensions.

2 Related Work

Urbonas et al. [41] addressed automated identification of defects on wood veneer surfaces using the Faster R-CNN architecture with transfer learning and data augmentation. The objective was to evaluate the viability of pre-trained region proposal networks for defect detection in a controlled industrial setting. The main contribution was demonstrating that transfer learning with ResNet152 models achieves 96.1% accuracy in combined defect classification. The methodology employed four pre-trained neural networks, AlexNet, VGG16, BNInception, and ResNet152, with data augmentation through rotation and flipping. Results showed that ResNet152 obtained the best performance with 80.6% accuracy in individual defect classification. However, the study was limited to a dataset of 4,729 images with only 353 defective samples, which restricted result generalization.

Fang et al. [42] proposed an automated system for precise detection of surface knots in sawn wood using YOLO-v5. The objective was to develop a real-time detector that could identify multiple knot types with high precision. The contribution was validating YOLO-v5 as an efficient alternative to two-stage detectors for wood inspection. The methodology involved fine-tuning YOLO-v5 on two wood knot datasets and evaluating precision, recall, and F1-score. The results achieved an F-score of 91.7% on the first dataset and 97.7% on the second, outperforming YOLO-v3 SPP and Faster R-CNN in speed and model size. The identified deficiency was that the model was evaluated only on the knot class, without considering other defect types such as cracks or stains.

Han et al. [43] presented an improved version of the YOLOv5 algorithm for surface defect detection in wood, incorporating attention mechanisms in the architecture. The objective was to improve the model's ability to detect small and low-contrast defects. The main contribution was integrating attention modules that allow the model to focus on relevant image regions. The methodology modified YOLOv5's backbone and neck with spatial and channel attention layers. Results showed significant improvements in small-defect detection compared to the base model. The main limitation was the lack of a standardized comparison with other state-of-the-art detectors on the same dataset.

Zheng et al. [44] developed GBCD-YOLO, a lightweight, high-precision model for wood defect detection, based on architectural modifications to YOLOv5s. The objective was to reduce computational complexity while maintaining detection precision. The contribution combined Ghost Bottleneck blocks, BiFormer attention, CARAFE upsampling, and DyHead dynamics with CIoU loss. The methodology included architecture optimization and evaluation on a wood defect dataset with 10 categories. Results showed an mAP@0.5 of 88.72%, a 13.45% improvement over base YOLOv5s, with 15.49% parameter reduction and 6.25% FPS increase. The main limitation is that the model was not compared with transformer-based architectures or two-stage detectors.

An et al. [45] proposed CWB-YOLOv8, an improvement on the YOLOv8 algorithm that incorporates Parametric Conditional Convolution, Wise-IoU, and BiFormer for wood defect detection. The objective was to improve detection of defects that vary in size and appearance. The main contribution was combining three modules to improve feature extraction, the loss function, and multi-scale attention. The methodology employed a custom dataset of 6,134 images with defects from radiata pine, eucalyptus, and Tuna tree species. The results achieved an mAP@0.5 of 89.2%, a 3.5% improvement over standard YOLOv8, with 96% recall for crack detection and 93% recall for resin. The main limitation was the lack of computational efficiency metrics, such as real-time latency.

Sun [46] implemented a wood quality defect detection system based on deep learning and a multi-criteria framework. The objective was to develop a system that combined automatic defect detection with a multi-criteria evaluation system for quality classification. The contribution was integrating a multi-criteria decision framework with deep neural networks for comprehensive wood quality evaluation. The methodology used a CNN for internal defect detection combined with multi-criteria analysis for quality classification. Results reported a 99.8% detection rate for internal defects and an average IOU of 74.3%. The deficiency was that the study focused on internal defects without extensive validation on public reference datasets.

Kılıç et al. [47] presented WD Detector, a deep learning-based hybrid sensor design for wood defect detection that combines CNN feature extraction with classical machine learning classifiers. The objective was to develop a hybrid system leveraging the strengths of both deep learning and traditional machine learning. The contribution was demonstrating that combining Xception-extracted features with classifiers such as CatBoost outperforms pure CNNs. The methodology employed Xception for feature extraction and 12 ML classifiers for final classification. The results achieved 99.32% accuracy, with CatBoost as the best classifier. A limitation is that the system requires a two-stage pipeline that increases implementation complexity.

Ji et al. [48] developed a deep learning-based algorithm for online detection of small target defects in large-format sawn wood. The objective was to detect small defects in high-resolution images of industrial planks. The contribution was integrating ELAN (Efficient Layer Aggregation Network) with YOLO and using SIFT-based image stitching to handle large-format wood processing. The methodology combined SIFT keypoint detection for image stitching with a modified YOLO architecture for small-defect detection. The results reported 90.37% accuracy with a processing speed of 40 m/min. The main limitation was its dependence on the SIFT algorithm for image stitching, which can be computationally expensive in high-speed environments.

Wolszczak et al. [49] addressed the detection of blue stains caused by fungi in a sawmill wood inspection system, using neural networks trained to automatically classify this specific defect type. The objective was to develop an automated system that could identify blue stains on wood surfaces during production. The contribution was applying neural networks to a defect type that is particularly difficult to detect with traditional methods. The methodology employed a neural network trained with blue stain images captured in a real industrial environment. Results demonstrated the feasibility of the approach for automated detection of this defect type. A limitation was that the study focused on a single defect category and did not evaluate performance in a multi-class scenario.

Chen et al. [50] proposed a defect detection system in edge-glued wood panels using deep learning techniques. The objective was to develop a WDD-DL system that combines image-processing filters with neural network classification. The contribution combined Gabor filters, Harris corner detection, and mathematical morphology with the InceptionResNetV2 network for classification. The methodology implemented a two-stage pipeline: preprocessing with classical filters and classification with a CNN. Results achieved 0.97 accuracy, 0.90 recall, and 0.92 F1-score. The main limitation was the complexity of the two-stage pipeline, which hinders real-time implementation.

Shah et al. [8] conducted a comprehensive review of automated defect detection in wood surface inspection, comparing one-stage models (YOLO and variants) and two-stage models (Faster R-CNN), and investigating emerging zero-shot learning approaches. The objective was to provide a state-of-the-art overview of wood defect detection. The contribution was the systematic comparison of one-stage and two-stage models, along with the introduction of zero-shot approaches based on vision-language models such as CLIP. The methodology reviewed recent literature, analyzed public datasets, and compared performance metrics. Results showed that YOLO models are preferred for real-time applications, while Faster R-CNN offers higher precision at the cost of speed. The review did not include transformer-based models as representatives of the new generation of detectors. Table 1 summarizes the reviewed works. None of the existing studies evaluate the cross-matrix between the three detection paradigms and advanced object augmentation techniques with neural harmonization under severe class imbalance.

Table 1 Comparative summary of related works on wood defect detection

Author	Approach	Main Metric	Deficiency
Urbonas et al. [41]	Faster R-CNN + TL	96.1% acc.	Small dataset
Fang et al. [42]	YOLO-v5	97.7% F1	Knots only
Han et al. [43]	YOLOv5 + attention	Improvement over base	No comparison
Zheng et al. [44]	GBCD-YOLO	88.7% mAP	No transformers
An et al. [45]	CWB-YOLOv8	89.2% mAP	No efficiency metrics
Sun [46]	CNN + multi-criteria	99.8% det.	Limited dataset
Kılıç et al. [47]	Xception + ML	99.3% acc.	Two-stage pipeline
Ji et al. [48]	YOLO + ELAN + SIFT	90.4% acc.	SIFT dependence
Wolszczak et al. [49]	Neural network	Binary classif.	Single class only
Chen et al. [50]	Filters + InceptionResNet	0.92 F1	Complex pipeline
Shah et al. [8]	General review	Qualitative comparison	No empirical matrix benchmark

3 Materials and Methods

3.1 Theoretical Foundations

Surface defect formation in wood responds to physiological tree factors and mechanical stresses during processing [4]. Live knots correspond to branch bases integrated into woody tissue, while dead knots represent separated branches that create discontinuous cavities [5]. Cracks originate from perpendicular tensile stresses during material drying phases [4]. Resin accumulations, central marrow, and Quartzite mineral inclusions alter the surface's physical homogeneity [5]. Modern production lines move planed planks at linear speeds of 9.6 m/s before line scan cameras [9]. The time available to capture, process, and classify each image is limited to a few milliseconds [9]. High variability in the background wood grain decreases the visual contrast of defective regions [5].

Data collection in industrial environments produces annotated sets with severe class imbalance [51]. In a long-tail distribution, a reduced fraction of categories accounts for the majority of observations [51]. The imbalance ratio measures the relationship between the majority-class and minority-class frequencies. In datasets with a ratio exceeding 30, standard loss functions become dominated by gradients from dominant categories [52]. The neural network suppresses predictions of rare categories by assigning them deficient confidence scores [53]. This phenomenon causes a collapse in the model's discriminative capability for infrequent but structurally dangerous anomalies [54].

Object-level data augmentation modifies the annotated-class frequency distribution directly [36], and augmentation-based oversampling is a recommended remedy for class imbalance [55]. Unlike global affine transformations, BoxAug isolates cropped patches from tail categories and applies stochastic scale, rotation, and flip transformations [36]. This follows the Simple Copy-Paste procedure, which pastes random object subsets across images and is data-efficient for rare categories [37]. Albumentations cover pixel-level and geometric diversity transforms (flip, rotation, scale, crop, contrast, brightness, blur) with bounding-box support for detection [56]. Direct pasting creates boundary and illumination discontinuities; neural composition and image harmonization frameworks close the synthetic-to-real distribution gap [38], and the PCT-Net model estimates pixel-wise color transforms to equalize regional luminance at full resolution [39]. Data-level treatments are complemented by loss-level re-weighting by effective sample number [52].

Cascade R-CNN represents the two-stage convolutional architecture oriented toward high spatial precision [33]. The first stage employs a Region Proposal Network to select candidates over convolutional feature maps. The second stage executes a sequence of detection heads trained with progressively stricter Intersection over Union thresholds. This cascaded design gradually refines bounding

box coordinates and minimizes false positives in high-defect-density scenarios [33]. The computational cost of multi-stage refinement leads to longer inference times than one-stage detectors. Still, the localization precision gain justifies its application in scenarios where false positive rate is critical [33].

YOLO26 represents the one-stage convolutional architecture designed for real-time inference. It adopts an anchor-free formulation that directly predicts bounding box centers and dimensions from multi-scale feature maps. Its dual-head design eliminates the need for the non-maximum suppression stage in inference, optimizing processing speed and computational latency as established in modern real-time one-stage detectors [34]. The absence of the NMS stage significantly reduces post-processing time, which is advantageous for real-time applications where every millisecond is critical [34]. However, one-stage architectures may be more susceptible to insufficient training data compared to two-stage detectors.

RF-DETR represents the Vision Transformer-based architecture optimized for real-time detection [35]. It uses bidirectional global self-attention mechanisms to capture long-range spatial dependencies across the entire image surface [57]. Through Neural Architecture Search, RF-DETR discovers optimal structural configurations on the Pareto frontier between localization precision and processing latency [35]. Unlike purely convolutional detectors, transformers process the complete image through tokenization and self-attention layers, enabling them to model global relationships between distant regions [57]. This capability is particularly relevant for wood inspection, where defects can be distributed sparsely along the plank surface.

Performance quantification of object detectors integrates spatial precision and computational efficiency [8]. Precision is the proportion of predicted positives that are real positives, while recall is the proportion of real positives correctly predicted [58]; the F1 score is their harmonic mean, and the Dice coefficient is related to the Jaccard/IoU index by $F1/(2-F1)$ [58]. A detection counts as correct when the Intersection over Union between predicted and ground-truth boxes reaches at least 0.5 [59], with $IoU = TP/(TP+FP+FN)$ as the standard overlap metric [60, 61]. Per-class average precision averaged over the class set gives mAP; averaging additionally over ten IoU thresholds from 0.5 to 0.95 in steps of 0.05 yields mAP@0.5:0.95, with AP50% as the single-threshold companion score [61]. Computational efficiency is reported as inference time in milliseconds per image, throughput in frames per second, floating-point operations, and parameter count.

3.2 Tools and Technologies

The experiment pipeline runs on Python v3.12. The main deep learning framework is PyTorch v2.7.0 with GPU acceleration via CUDA v12.8 libraries. Supplementary computer vision operations employ torchvision v0.22.0. The Cascade R-CNN architecture is implemented through the MMDetection library v3.2.0, supported by MMCV v2.2.0 and MMEngine v0.10.7. The YOLO26 detector runs using the Ultralytics framework v8.2.0. The RF-DETR architecture is compiled from the official RF-DETR engine v1.3.0.

Synthetic data processing and photometric augmentations use Albumentations v1.4.0. Composition and object insertion primitives employ the LibCom library v0.2.0 integrated into the development environment. Strict pipeline configuration management is programmed via Pydantic v2.6.1. Accelerated metadata table manipulation uses Polars v1.43.0 and OpenCV v5.0.0. The virtual environment and dependency resolution are managed through the uv package manager v0.6+. All models were trained and evaluated on an NVIDIA RTX 5070 Ti GPU, which serves as the reference point for the inference-time and computational-performance measurements reported in this study.

3.3 Dataset

The study uses the filtered and annotated version in YOLO format available on Kaggle [62], derived from the original Large-scale Image Dataset of Wood Surface Defects published by Kodytek et al. [9]. The original dataset was acquired in a real industrial environment during sawmill production using a JAI SW-4000TL-PMCL line scan camera at a line frequency of 66 kHz [9]. The filtered version used in this work [62] was preprocessed to include only images containing defects, and its annotations were converted to the standard YOLO format for direct evaluation of object detection models. The filtered dataset contains 4,000 JPG images

at a fixed spatial resolution of 2800 by 1024 pixels [62]. The set stores 8,888 annotated bounding boxes distributed across 8 surface defect categories, averaging 2.22 defects per image. Figure 1 illustrates the percentage frequency distribution for each defect class.

The annotations provide normalized bounding box coordinates in YOLO format. The class distribution reflects real industrial production conditions [9]. The majority categories are Live Knot (3,949 annotations; 44.4%) and Dead Knot (2,865 annotations; 32.2%), together accounting for 76.6% of the set. Intermediate categories include resin (with 642 annotations; 7.2%), Crack (with 509 annotations; 5.7%), and Knot with Crack (with 463 annotations; 5.2%). Minority categories comprise marrow with 204 annotations (2.3%), Quartzite with 144 annotations (1.6%), and Missing Knot with 112 annotations (1.3%). The calculated imbalance ratio is approximately 35.3. Figure 2 shows representative examples of each class.

3.4 Proposed Method

The proposed method implements a five-stage experiment pipeline designed to ensure reproducibility and fair comparability between configurations. The stages comprise: (1) data preparation, (2) data augmentation, (3) model training, (4) evaluation, and (5) results analysis. Figure 3 overviews the flow with the essential operation of each stage; the surrounding text details parameters and design choices. The entire pipeline configuration is managed through typed Pydantic models that guarantee parameter validation at compile time [63]. The command-line interface allows customization of any nested parameter through dot notation, facilitating reproducible experimentation. All random number generators (Python, NumPy, PyTorch) are seeded from a single master seed with fixed per-stage stream IDs; however, cuDNN benchmarking and TF32 remain enabled.

The data preparation stage applies three sequential operations on the raw dataset. First, black edges are cropped through Otsu thresholding segmentation [64] and morphological closing operations, isolating the valid region of the wood plank. Second, images are reduced to half their original resolution through area interpolation. Third, bounding box annotations are transformed to the resulting coordinate space and filtered by a three-rule size gate (minimum absolute dimension 2.0 px unless area reaches 12.0 px^2 or the major dimension reaches 6.0 px, preserving thin cracks while dropping unusable specks). The resulting set is partitioned into 80% training, 10% validation, and 10% test through greedy iterative stratification that preserves class distribution in each partition [65]. To alleviate imbalance, 35% of training planks containing only the two majority defect classes are then dropped; this intentionally shifts training priors away from the natural validation and test distributions, so reduced majority-class scores are expected even when the balancing works.

Three augmentation strategies were evaluated, designed to mitigate class imbalance, aimed at achieving a 33% ratio between the minority and majority class. Each strategy grows the training set by synthesizing minority-class instances, so augmented training sizes differ from the original by design, and dataset size is reported per strategy. For the paradigm comparison, three representative architectures of each object detection approach were configured. Evaluation is performed on the test set of 400 images using COCO-standard mAP@0.5 and mAP@0.5:0.95, per-class AP@0.5, and operating-point precision, recall, and F1 at per-model calibrated confidence thresholds. Inference time is measured by averaging total processing time across all test set images.

Per-class uncertainty is quantified at the same operating points. For each class c, TP, FP, and FN counts come from the IoU ≥ 0.5 greedy operating-point matching, and per-class precision and recall are treated as binomial proportions; simultaneous 95% family-wise coverage over the $K = 8$ defect classes is obtained with the Bonferroni correction, reporting each class with a Wilson score interval at level $1 - 0.05/8 = 99.375\%$ ($z = 2.73$), i.e. $\text{CI}_c = \text{Wilson}(x_c, n_c; z_{1-0.05/16})$, with a dash shown when $n_c = 0$. Because matching is restricted to the same class, a cross-class mislabel surfaces as a false positive of the predicted class plus a false negative of the true class rather than as an off-diagonal confusion entry.

All architectures are trained with effective-number class weighting [52] injected into each model's classification loss. While techniques such as Focal Loss [66] and Seesaw Loss [54] target the same imbalance, the study fixes a single loss-level treatment so that augmentation effects remain




Fig. 1 Defect class distribution in the filtered dataset [62]: Live Knot, Dead Knot, Resin, Crack, Knot with Crack, Marrow, Quartzite, and Missing Knot.




Fig. 2 Examples of the eight defect classes annotated in the wood dataset [62]: Live Knot, Dead Knot, Resin, Knot with Crack, Crack, Marrow, Quartzite, and Missing Knot (left to right, top to bottom).

attributable, leaving alternative loss strategies as future work. Each model is evaluated at its own calibrated operating point while inferring at its own training resolution, so neither input-size handling nor a fixed confidence cutoff can favor any paradigm.

The augmentation stage applies three strategies targeting a 33% minority-to-majority ratio (mode descriptions in Section 3.1). Albumentations with class balancing selectively augments rare-class images with six transforms: horizontal flip (0.5), vertical flip (0.5), rotation-scale-translation (0.5), random contrast-brightness (0.4), color variation (0.3), and Gaussian blur (0.2). It is chosen as the photometric baseline because its transforms preserve labels while supporting bounding boxes [56].

Standard BoxAug crops tail-class instances from an object bank, applies scale jitter (0.8–1.2), rotation, flipping, cropping, noise, and morphological operations, and pastes them at guide-validated positions (Missing Knot at edges, Quartzite central). Each run regenerates from a clean training copy with capped placement retries. It is chosen as the object-level oversampling arm because copy-paste is data-efficient for rare categories [37] and a recommended imbalance remedy [55].




Fig. 3 Overview of the proposed five-stage experimental pipeline for timber defect detection benchmarking

BoxAug with LibCom repeats the same procedure but replaces direct insertion with neural harmonization [38], restricted to scale jitter and flips without pixel noise. It is chosen to test whether harmonized composition with pixel-wise color equalization [39] removes the pasting discontinuities of the classic arm.

Cascade R-CNN (ResNet-50 + FPN [33]) is trained for 12 epochs per the canonical 1x schedule [67], with AdamW (lr 1e-4, wd 1e-4) adapted for single-GPU fine-tuning—the official 1x uses SGD with lr 0.02—batch size 8, 960 × 384 keep-ratio input, LinearLR warmup plus MultiStepLR, COCO-bbox validation each epoch, patience 8 with min-delta 0.005, keeping the best-mAP checkpoint. The short schedule is justified by the cascaded

heads (IoU 0.5/0.6/0.7) gaining about 4 AP points over the FPN baseline [33], and two-stage detectors are a proven but slower wood-defect option [45].

YOLO26m (anchor-free, NMS-free dual-head design [34]) trains for 50 epochs (patience 50, checkpoint every 5) at 960×384, batch size 16, lr0 0.01, AMP FP16. The lr0 value is the Ultralytics default, and 50 epochs is a reduced COCO-pretrained fine-tuning budget (default 100). The regime mirrors CWB-YOLOv8 on wood (lr0 0.01, patience 50, mAP@0.5 of 0.892 without overfitting [45]) and the YOLOv5m COCO-pretrain plus fine-tune protocol that reached 97.7% F-score on sawn-timber knots [42]; the budget is ample against long training schedules from scratch.

RF-DETR-m [35] trains on a 960×384 canvas with batch size 8, AdamW with lr 1e-4 and wd 1e-4 (both official defaults), gradient checkpointing, up to 50 epochs with patience 15 and min-delta 0.005 per the official early-stopping example (actual 21–23 epochs, best validation epochs 6–11). The 5-epoch warmup is an explicit fine-tuning stabilizer (official default 0). The learning-rate choice matches the RF-DETR training hyperparameters that reach 48.0 COCO AP at nano scale [35]; as a 2026 architecture, this study is the first to report its use on wood.

The differing epoch budgets are intentional: canonical 1x (12 epochs) for Cascade R-CNN [67], a 50-epoch fine-tuning budget for YOLO26 against Ultralytics defaults, and up to 50 epochs with early stopping for RF-DETR per official guidance [35]. Wall-clock budgets are comparable across paradigms (0.38 to 0.80 hours per configuration; see Figure 14) because per-epoch cost differs, so epoch counts cannot be compared directly. All three paradigms share the 960×384 canvas, COCO-pretrained initialization, effective-number class weighting [52], and per-model calibrated operating points (see Table 2).

Confidence thresholds are calibrated per model rather than fixed globally. A validation-split inference pass at 0.05 followed by a max-F1 sweep sets the operating point: 0.20 for RF-DETR (F1 0.695) and 0.30 for YOLO26 (F1 0.748), while Cascade R-CNN stays at 0.50. Test inference and metrics for all RF-DETR and YOLO26 configurations run at these thresholds. Calibration is required because rectangular training deflates RF-DETR output scores while preserving ranking quality: the same checkpoints score far lower at a fixed 0.50 cutoff through lost recall, not worse localization. Precision, recall, and F1 are therefore reported at each model's own operating point, while the mAP columns remain the ranking-based comparison.

4 Results

Figure 4 presents the mAP@0.5 performance matrix for the 12 model-augmentation strategy combinations. RF-DETR leads all four arms with values between 0.676 and 0.717, followed by Cascade R-CNN between 0.644 and 0.677, while YOLO26 is the tightest group between 0.592 and 0.618, with its unaugmented baseline on top. The strict-metric view in Figure 5 preserves the order. Augmentation sensitivity is paradigm-specific rather than uniform: it helps Cascade, is mixed for RF-DETR, and is neutral to negative for YOLO26.

Table 3 summarizes the complete metrics for all 12 configurations. RF-DETR with Albumentations achieves the highest mAP@0.5 (0.717) and the best mAP@0.5:0.95 (0.425), while Cascade R-CNN with BoxAug LibCom achieves the highest precision (0.811) and the best F1 (0.798). YOLO26 baseline is the strongest of its family at mAP@0.5 of 0.618, with all three augmentation strategies scoring 0.592 to 0.604. These results place the transformer paradigm first on ranking metrics and the two-stage paradigm first on operating-point precision. In contrast, the one-stage paradigm shows no augmentation-driven gains under this protocol.

Figure 6 shows the impact of each augmentation strategy relative to the baseline for each model. Cascade R-CNN benefits from every strategy: Albumentations contributes +0.008, standard BoxAug +0.015, and BoxAug LibCom +0.033 absolute improvement in mAP@0.5. RF-DETR shows mixed behavior: Albumentations contributes +0.017, but standard BoxAug degrades performance by -0.024 and BoxAug LibCom by -0.013. YOLO26 shows no gain: Albumentations scores -0.019, BoxAug LibCom -0.026, and standard BoxAug -0.014, with the unaugmented baseline remaining its best configuration.

Figure 7 presents the average AP per class at AP@0.5 for all 12 configurations. Marrow is the easiest class, with AP up to 0.910 with RF-DETR, while Quartzite is the hardest, with AP between 0.082 and 0.550. No configuration fails on any class. Live Knot and Dead Knot show AP

Table 2 Training hyperparameters per paradigm. Each parameter is reported with its value; provenance and deviations from framework defaults are justified in the text

Model	Parameter	Value
Cascade R-CNN (ResNet-50 + FPN)	Input resolution	960 × 384, keep-ratio
	Batch size	8
	Optimizer	AdamW (adapted for single-GPU fine-tuning; official 1x uses SGD)
	Learning rate	1e-4
	Weight decay	1e-4
	Schedule	LinearLR warmup + MultiStepLR
	Epoch budget	12 (MMDetection 1x), patience 8, min-delta 0.005
YOLO26m (anchor-free, dual-head)	Input resolution	960 × 384 rectangular
	Batch size	16
	Optimizer	Ultralytics default (auto), MuSGD design
	Initial learning rate (lr0)	0.01 (Ultralytics default)
	Precision	AMP FP16
	Epoch budget	50, patience 50 (effectively off), checkpoint every 5
RF-DETR-m (NAS transformer)	Input canvas	960 × 384 rectangular
	Batch size	8
	Optimizer	AdamW (official default)
	Learning rate	1e-4 (official default)
	Weight decay	1e-4 (official default)
	Warmup	5 epochs (explicit stabilization; official default 0)
	Memory	Gradient checkpointing
	Epoch budget	max 50, actual 21–23, patience 15, min-delta 0.005

values of 0.651 to 0.781 despite being the majority classes, suggesting high intra-class variance.

Figure 8 presents the same per-class breakdown under the AP@0.5:0.95 metric. The class ordering is preserved: Marrow remains the easiest class at 0.499 to 0.639 and Quartzite the hardest at 0.064 to 0.285. The metric compresses the score range, most visibly on the majority classes, as Live Knot and Dead Knot drop from 0.651 to 0.781 at AP@0.5 to 0.297 to 0.449 at AP@0.75, indicating that these high-variance defects are detected but poorly localized. The weakest cell is YOLO26 with BoxAug LibCom on Quartzite at 0.064, against 0.255 for its unaugmented baseline, showing that pasted augmentation degrades rare-class localization for the one-stage paradigm. RF-DETR leads six of eight classes under the metric, with its best cells on marrow at 0.639 (BoxAug Std) and Knot_missing at 0.502 (Albumentations).

Table 4 and Figure 9 report per-class recall with simultaneous 95% CIs for each paradigm's best configuration. Abundant classes give narrow intervals (Live Knot, $n = 395$: recall 0.729–0.792 with widths 0.111–0.122), while rare classes span tens of points (Quartzite, $n = 15$: 0.400–0.733 with widths 0.533–0.576; Missing Knot, $n = 12$: widths




Fig. 4 mAP@0.5 performance matrix intersecting three detection paradigms with four augmentation strategies




Fig. 5 mAP@0.5:0.95 performance matrix for the same 12 configurations

up to 0.614), so rank orders among rare classes are not statistically distinguishable: the Quartzite gap between RF-DETR (0.733) and YOLO26 (0.400) overlaps across all three intervals. Precision shows the same pattern, with Cascade R-CNN keeping the narrowest majority-class intervals (Live Knot 0.853 [0.795, 0.896], Dead Knot 0.905 [0.841, 0.945]) while rare-class intervals overlap.

Figure 10 shows ground-truth-annotated representative instances (red boxes) for the eight defect classes together with the best AP@0.5 across the 12 configurations. The panel visualizes the difficulty spectrum behind the numbers: the distinctive central-line pattern of marrow (0.91) contrasts with the low contrast of Quartzite against wood grain (0.55, hardest class), while Missing Knot instances cluster at plank edges where operating-point recall intervals are widest ($n = 12$, widths up to 0.614). Characteristic failure modes follow from the operating-point counts: quartzite false positives arise from grain confusion (RF-DETR quartzite precision spans 0.133–0.501), and cross-class knot confusions surface as paired false positives and false negatives rather than off-diagonal entries (see Section 3.4).

Figure 11 illustrates the trade-off between inference speed and precision. YOLO26 processes each image in 7.5 ms on average across the four configurations, RF-DETR in 12.6 ms, and Cascade R-CNN in 25.7 ms. Cascade R-CNN is 3.4 times slower than YOLO26, while its best mAP@0.5 of 0.677 trails RF-DETR's best of 0.717. RF-DETR offers the best ranking precision at 12.6 ms, 1.7 times slower than YOLO26, whose best mAP@0.5 is 0.618.

Figure 12 shows the mAP@0.5 validation convergence curves throughout training epochs (Figure 13 shows the corresponding training losses). RF-DETR converges earliest, with the best epoch between 6 and 11; Cascade R-CNN stabilizes between epochs 9 and 12, with BoxAug LibCom still climbing at epoch 12; and YOLO26

Table 3 Performance metrics on the test set for all 12 benchmark configurations

Model	Augmentation	mAP@50	mAP@50:95	Precision	Recall	F1
Cascade R-CNN	Albumentations	0.652	0.380	0.789	0.785	0.787
Cascade R-CNN	Baseline	0.644	0.386	0.797	0.765	0.780
Cascade R-CNN	BoxAug LibCom	0.677	0.401	0.811	0.785	0.798
Cascade R-CNN	BoxAug Std	0.659	0.389	0.796	0.773	0.784
RF-DETR	Albumentations	0.717	0.425	0.684	0.782	0.730
RF-DETR	Baseline	0.700	0.420	0.667	0.794	0.725
RF-DETR	BoxAug LibCom	0.686	0.406	0.665	0.796	0.725
RF-DETR	BoxAug Std	0.676	0.405	0.660	0.794	0.721
YOLO26	Albumentations	0.598	0.355	0.742	0.748	0.745
YOLO26	Baseline	0.618	0.363	0.769	0.738	0.753
YOLO26	BoxAug LibCom	0.592	0.349	0.760	0.740	0.750
YOLO26	BoxAug Std	0.604	0.358	0.754	0.765	0.759




Fig. 6 Impact of augmentation strategies relative to baseline (Δ mAP@0.5)

peaks between epochs 40 and 50, at the edge of its 50-epoch budget. YOLO26 curves show greater oscillation, particularly in the standard BoxAug configuration. This convergence pattern suggests that transformers need fewer iterations to capture relevant features, while one-stage convolutional architectures consume the full budget; the still-rising YOLO26 and Cascade LibCom curves indicate that both budgets truncate learning. The oscillation in YOLO26 may indicate sensitivity to training sample variability in each batch.

Figure 14 compares total training time per configuration. YOLO26 trains the full 50 epochs in 0.40 to 0.80 hours, Cascade R-CNN completes 12 epochs in 0.38 to 0.78 hours, and RF-DETR trains 21 to 23 epochs in 0.44 to 0.80 hours. Wall-clock budgets are therefore comparable across paradigms even though epoch counts differ, and per-epoch cost rather than early stopping dominates the differences.

5 Discussion

The results from this benchmark reveal patterns that warrant detailed analysis of interactions




Fig. 7 Heatmap of average precision per defect class (AP@0.5)

Table 4 Per-class recall with simultaneous 95% family-wise CIs (Bonferroni) for the best configuration of each paradigm, with test support n

Class	RF-DETR (Alb.)	Cascade (LibCom)	YOLO26 (Base.)	n
Quartzite	0.733 [0.389, 0.922]	0.467 [0.190, 0.766]	0.400 [0.149, 0.718]	15
Live Knot	0.754 [0.691, 0.809]	0.792 [0.731, 0.843]	0.729 [0.664, 0.786]	395
Marrow	0.857 [0.561, 0.966]	0.857 [0.561, 0.966]	0.905 [0.614, 0.983]	21
Resin	0.891 [0.741, 0.959]	0.813 [0.649, 0.910]	0.703 [0.533, 0.831]	64
Dead Knot	0.767 [0.692, 0.828]	0.763 [0.688, 0.825]	0.788 [0.715, 0.846]	287
Knot with Crack	0.787 [0.591, 0.905]	0.766 [0.568, 0.891]	0.702 [0.503, 0.846]	47
Missing Knot	0.833 [0.441, 0.969]	0.750 [0.369, 0.939]	0.417 [0.142, 0.756]	12
Crack	0.922 [0.758, 0.978]	0.902 [0.733, 0.969]	0.706 [0.515, 0.845]	51

between detection architectures and data augmentation strategies in the context of severe class imbalance typical of industrial wood inspection. RF-DETR's bidirectional global self-attention captures long-range spatial dependencies across the plank surface [57]. Cascade R-CNN remains the operating-point precision leader, with precision of 0.811 and F1 of 0.798 under BoxAug LibCom, consistent with cascaded refinement minimizing false positives through detection heads with increasing IoU thresholds [33]. Notably, Cascade is the only paradigm that benefits from every augmentation strategy (+0.008 to +0.033), suggesting two-stage heads exploit synthetic minority instances once the operating point is fixed.

YOLO26 shows no augmentation dividend; the unaugmented baseline at mAP@0.5 (0.618) beats all three augmented arms, which score 0.592 to 0.604. This contradicts the common expectation that one-stage detectors are the primary beneficiaries of training data volume [31], at least under rectangular training with a full 50-epoch budget. A




Fig. 8 Heatmap of average precision per defect class (AP@0.5:0.95)




Fig. 9 Per-class recall with Bonferroni-corrected simultaneous 95% family-wise confidence intervals for the best configuration of each paradigm

plausible mechanism is that YOLO26's anchor-free dense predictions already saturate on the majority distribution, so pasted minority instances add noise rather than signal at this budget. The greater oscillation in YOLO26 convergence curves, particularly in the standard BoxAug configuration, may stem from variability introduced by synthetic samples in a model that lacks Cascade R-CNN's multi-stage refinement mechanism. This result suggests that object augmentation techniques require larger




Fig. 10 Ground-truth-annotated representative instances with best AP@0.5 per class




Fig. 11 Trade-off between inference speed (ms/image) and precision (mAP@0.5)

budgets or cleaner synthesis to help one-stage detectors in severe imbalance scenarios. Naively pasted masks create pixel artifacts that detectors learn as shortcuts instead of appearance [68]; unharmonized pasting can degrade performance through boundary artifacts, contrast disparities, and context mismatches [37, 68]. The YOLO family recipe itself excludes copy-paste (Mosaic/CutMix instead; copy-paste is off by default and confined to segmentation tasks), so the null dividend is consistent with the architecture's design rather than a protocol bug. No published copy-paste ablation on YOLO26 exists to our knowledge; the cited drops are the closest measured analogs.

RF-DETR shows mixed behavior: Albumentations improves performance by +0.017, but standard BoxAug degrades it by -0.024 and BoxAug LibCom by -0.013. This result is particularly relevant for the research community in transformers for industrial vision [32]. Patch-level noise transformations introduce artifacts that bidirectional global self-attention mechanisms interpret as relevant patterns, generating confusion during training. Unlike convolutional models that process




Fig. 12 mAP@0.5 validation convergence curves during training




Fig. 13 Training loss progression over epochs for all 12 configurations

local information through sliding filters, transformers capture long-range spatial dependencies that can amplify the influence of local artifacts [57]. The mechanism is structural. Standard BoxAug pastes patches with pixel-level noise and morphological perturbations [36], producing sharp edge gradients and high-frequency textures that do not occur in natural wood grain. During tokenization, these discontinuities become outlier tokens; because every self-attention head computes Query-Key affinities over the full token set, a single anomalous patch can attract attention mass from distant, defect-free




Fig. 14 Comparison of total training time per configuration

regions and propagate spurious correlations across layers. Convolutional detectors attenuate this effect through locality: sliding filters confine the artifact's receptive field, and Cascade R-CNN's staged IoU heads can still reject the proposal. Transformers have no such locality bottleneck, so the same artifact is broadcast globally. Neural harmonization [38] attenuates edge gradients through pixel-level color equalization [39], which explains why BoxAug LibCom degrades RF-DETR less (-0.013) than the standard variant (-0.024): the pasted tokens remain distributionally closer to natural grain. The deflated-score phenomenon, where the same checkpoints collapse at a fixed 0.50 cutoff while ranking quality is preserved, further shows that threshold-then-mAP evaluation is brittle to calibration shifts. This result suggests that object augmentation strategies require careful adaptation when applied to self-attention-based architectures, and that operating points must be tuned per model rather than fixed globally. This asymmetry matches copy-paste's reported limits: it succeeds on two-stage detectors with long schedules, while strong augmentation can cost up to 1 AP point elsewhere [37].

Per-class analysis reveals counterintuitive results that challenge the assumption that class frequency directly determines detection difficulty. Quartzite, with only 144 annotations (1.6% of the dataset), obtains the worst performance with AP@0.5 between 0.082 and 0.550, which is expected given its low visual contrast against wood grain. However, marrow, with only 204 annotations, obtains the highest AP, up to 0.910. This disparity indicates that defect visual distinguishability is a determining factor that interacts with class frequency. Defects with distinctive visual patterns, such as marrow with its characteristic central line appearance, are more susceptible to automatic detection regardless of their representation in the dataset [5]. Long-tail methods fail when they address only imbalance and ignore subtle inter-class differences [51], and raw counts overstate information because of overlap with diminishing returns [52]. Marrow's high-contrast vertical central line gives a strong spatial signal-to-noise ratio learnable from few samples, while Quartzite shares reflectance and color with healthy grain: a camouflage regime where foreground-background similarity dominates difficulty [69] and natural texture variation masks the defect signal [5]. Tail suppression by inter-class negative gradients [53] then sinks the low-contrast class while sparing the distinctive one: detectability follows spatial SNR, not instance count.

Live Knot and Dead Knot, which together represent roughly 77% of the dataset, show AP@0.5

values of 0.651 to 0.781 despite their high prevalence. This finding confirms that the high intra-class variance of these defects, where the same anomaly type can exhibit very different visual appearances [9], is a challenge that greater data volume alone cannot resolve. Variability in the background wood grain, combined with different presentations of Live Knot and Dead Knot, generates a feature distribution that hinders model convergence toward robust discriminative representations. The 35% majority downsampling of training planks combined with effective-number class weighting [52] keeps minority classes competitive: the top configuration scores no class below 0.55. Loss-level treatments beyond a single fixed weighting, such as Focal Loss [66] or Seesaw Loss [54], remain untested and could offer a more comprehensive solution for severe class imbalance. The source dataset itself warns that no finite sample can fully capture limitless variability [9].

In terms of computational efficiency, the speed-precision trade-off manifests differently across the three paradigms. YOLO26 offers the best speed at 7.5 ms per image with mAP@0.5 of 0.618, which is relevant for high-throughput production lines [9]. Cascade R-CNN is preferred when operating-point precision is prioritized over latency, reaching precision of 0.811 at 25.7 ms per image. RF-DETR offers the best ranking precision at 12.6 ms and mAP@0.5 of 0.717, making it a viable alternative for applications that must balance speed and precision while capturing long-range spatial dependencies. The optimal architecture depends on the specific requirements of the industrial application, including production line speed, false-positive tolerance, and available computational resources. Selecting the architecture by speed/memory/accuracy balance for the target platform is the established practice [70]; YOLO's real-time edge compatibility [31] versus DETR's NMS-free Pareto gains [57] frame the three operating points below.

6 Conclusions

This study presented a comparative benchmark of three object detection paradigms with four data augmentation strategies for surface defect recognition in wood, evaluating 12 configurations on a dataset with severe imbalance of 1 to 35.3. The main results show that RF-DETR achieves the highest ranking precision, with mAP@0.5 of 0.717 under per-model calibrated thresholds; Cascade R-CNN gains the most from augmentation, with BoxAug LibCom contributing +0.033 and the best operating-point F1 of 0.798; and YOLO26 shows no augmentation dividend, with its unaugmented baseline of 0.618 leading the family. Per-class analysis at AP@0.5 shows that detection difficulty depends on both defect frequency and visual distinguishability, and the AP@0.5:0.95 view confirms this ordering while exposing weaker localization on high-variance knot classes. Fixed confidence cutoffs mismeasure rect-trained models, so operating-point calibration is part of the method rather than an afterthought.

For deployment, the three paradigms occupy distinct operating points: YOLO26 at 7.5 ms per image suits high-throughput lines approaching 9.6 m/s where latency dominates; RF-DETR at 12.6 ms offers the best ranking precision for balanced speed–accuracy requirements; and Cascade R-CNN at 25.7 ms maximizes operating-point precision (0.811) where false positives are costly. The study's limits bound these claims: single-run mAP point estimates without training variance, truncated epoch budgets that make the YOLO26 and Cascade LibCom scores lower bounds rather than converged values, and evaluation on a single species and industrial setup. The calibrated-threshold protocol, the paradigm-dependent augmentation response, and the released reproducible pipeline provide the baseline against which extended budgets, repeated runs with confidence intervals, and diffusion-based augmentation should be measured. Concretely: if the absolute priority is real-time speed to avoid production-line bottlenecks, choose YOLO26 (7.5 ms) [9, 31]; for maximum defect-ranking precision in rigorous quality audit, choose RF-DETR (12.6 ms) [57]; and if a false positive carries severe economic loss, operate Cascade R-CNN with BoxAug LibCom (operating precision 0.811) [33].

7 Limitations and Future Work

The fixed per-family epoch budgets truncate learning where curves still rise: YOLO26 best epochs fall between 40 and 50 of a 50-epoch budget, and Cascade R-CNN with BoxAug LibCom is still climbing at epoch 12 of 12, so reported scores are lower bounds for those configurations rather than converged values. Extending YOLO26 beyond 50 epochs and Cascade R-CNN to its 2x schedule

would test whether the ranking holds at convergence. All mAP values reported are single-run point estimates; a three-seed repeat protocol (seeds 42–44, mean ± std) is the natural next step for training-variance intervals around mAP. The most immediate modeling direction corresponds to diffusion-based augmentation. The cut-and-paste methods evaluated, such as BoxAug, are limited by the number of rare instances available for cropping from the original dataset. With only 144 quartzite annotations, the object bank is too small to generate diverse augmentations. Conditional diffusion models such as Stable Diffusion with ControlNet can generate synthetic instances of rare classes without relying on existing crops, offering a potentially more effective alternative for severe imbalance [71].

The per-class AP heatmaps above remain point estimates (the Bonferroni-binomial construction does not apply to AP, a ranking metric), and cross-class confusion is folded into per-class false positives and false negatives rather than shown as an off-diagonal matrix.

Expanding the dataset to other wood species with different grain patterns and defects is essential to validate generalization beyond the current species and industrial environment. In parallel, quantizing the model to INT8 and FP16 could reduce inference times for deployment on production lines with hardware constraints, while evaluating transformer architectures such as DINO and Grounding DINO could determine whether global self-attention mechanisms improve detection of low-contrast defects. Combining multiple research directions, including class weighting, diffusion-based augmentation, and model optimization, could lead to more robust and efficient inspection systems for the wood industry. These future directions seek to address the limitations identified in the present benchmark and bring automated detection systems closer to the operational requirements of wood processing plants. Developing reproducible experimental pipelines, such as the one used in this study, will facilitate comparative evaluation of new techniques emerging from these research directions.

Declarations

Funding: The authors declare that no financial support was received for this work.

Competing Interests: The authors declare no known competing financial interests or personal relationships that could have appeared to influence the work reported in this article.

Ethics approval and consent to participate: Not applicable.

Consent for publication: Not applicable.

Data availability: The data used in this study are publicly available on Kaggle: https://www.kaggle.com/datasets/nomihsa965/large-scale-image-dataset-of-wood-surface-defects, licensed under the CC BY 4.0 license.

Materials availability: Not applicable.

Code availability: Custom analysis scripts and source code generated during this study are publicly available at the GitHub repository: https://github.com/christianmz565/ia-2026-final, licensed under the AGPL-3.0 license.

Author contribution: R.M.C.P.: Software, Writing – original draft. **M.A.J.M.:** Data Curation, Resources, Methodology. **C.R.M.Z.:** Project Administration, Conceptualization, Writing – review and editing. **Y.J.N.C.:** Investigation, Resources. **L.G.S.C.:** Conceptualization, Investigation, Software. **Y.P.V.:** Conceptualization, Methodology, Supervision, Writing – review and editing.

Use of generative AI: During the preparation of this manuscript, the authors used generative artificial intelligence tools solely for language editing, clarity improvement, and assistance with manuscript organization. The authors independently reviewed and verified all scientific decisions, methodological procedures, statistical analyses, interpretation of results, and final content, and remain fully responsible for the manuscript.

References

[1] Yang, J., Li, S., Wang, Z., Dong, H., Wang, J., Tang, S.: Using deep learning to detect defects in manufacturing: A comprehensive survey and current challenges. Materials **13**, 5755 (2020) https://doi.org/10.3390/ma13245755

[2] Czimmermann, T., Ciuti, G., Milazzo, M., Chiurazzi, M., Roccella, S., Oddo, C.M., Dario, P.: Visual-based defect detection and classification approaches for industrial applications—A SURVEY. Sensors **20**(5),

1459 (2020) https://doi.org/10.3390/s20051459

[3] Ramos-Maldonado, M., Aguilera-Carrasco, C.: Trends and opportunities of industry 4.0 in wood manufacturing processes. In: Gong, M. (ed.) Engineered Wood Products for Construction, pp. 1–14. IntechOpen, London (2021). Chap. 20. https://doi.org/10.5772/intechopen.99581

[4] Yin, Q., Liu, H.-H.: Drying stress and strain of wood: A review. Applied Sciences **11**(11), 5023–5041 (2021) https://doi.org/10.3390/app11115023

[5] Chen, Y., Sun, C., Ren, Z., Na, B.: Wood defect recognition: Review of the current state of application of wood defect recognition technology. BioResources **18**(1), 2288–2302 (2023) https://doi.org/10.15376/biores.18.1.Chen

[6] Kryl, M., Danys, L., Jaros, R., Martinek, R., Kodytek, P., Bilik, P.: Wood recognition and quality imaging inspection systems. Sensors **2020**, 3217126 (2020) https://doi.org/10.1155/2020/3217126

[7] Ericsson, M., Johansson, D., Stjern, D.: Ai-based quality control of wood surfaces with autonomous material handling. Applied Sciences **11**(21), 9965–9978 (2021) https://doi.org/10.3390/app11219965

[8] Shah, H., Saarela, E., Korkeakangas, T., Pitkäaho, T.: A comprehensive review of automatic defect detection in wood surface inspection. Applied Computing and Intelligence **6**(1), 1–22 (2026) https://doi.org/10.3934/aci.2026001

[9] Kodytek, P., Bodzaš, A., Bilik, P.: A large-scale image dataset of wood surface defects for automated vision-based quality control processes. F1000Research **10**, 581 (2022) https://doi.org/10.12688/f1000research.52903.2

[10] Minaee, S., Boykov, Y., Porikli, F., Plaza, A., Kehtarnavaz, N., Terzopoulos, D.: A survey on object instance segmentation: A deep learning survey. SN Computer Science **3**(6), 407 (2022) https://doi.org/10.1007/s42979-022-01407-3

[11] Prunella, M., Scardigno, R.M., Buongiorno, D., Brunetti, A., Longo, N., Carli, R., Dotoli, M., Bevilacqua, V.: Deep learning for automatic vision-based recognition of industrial surface defects: A survey. IEEE Access **11**, 42605–42630 (2023) https://doi.org/10.1109/access.2023.3271748

[12] Ren, Z., Fang, F., Yan, N., Wu, Y.: State of the art in defect detection based on machine vision. International Journal of Precision Engineering and Manufacturing-Green Technology **9**, 661–691 (2022) https://doi.org/10.1007/s40684-021-00343-6

[13] Dalal, N., Triggs, B.: Histograms of oriented gradients for human detection. In: Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR), vol. 1, pp. 886–893 (2005). https://doi.org/10.1109/CVPR.2005.177 . IEEE

[14] Sugiarto, B., Prakasa, E., Wardoyo, R., Damayanti, R., Krisdianto, R., Dewi, L.M., Pardede, H.F., Rianto, Y.: Wood identification based on histogram of oriented gradient (HOG) feature and support vector machine (SVM) classifier. In: 2017 2nd International Conferences on Information Technology, Information Systems and Electrical Engineering (ICITISEE), pp. 337–341 (2017). https://doi.org/10.1109/ICITISEE.2017.8285523 . IEEE

[15] Nurthohari, Z., Murti, M.A., Setianingsih, C.: Wood quality classification based on texture and fiber pattern recognition using HOG feature and SVM classifier. In: 2019 IEEE International Conference on Internet of Things and Intelligence System (IoTaIS), pp. 123–128 (2019). https://doi.org/10.1109/IoTaIS47347.2019.8980414 . IEEE

[16] Viola, P., Jones, M.: Rapid object detection using a boosted cascade of simple features. In: Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR), vol. 1, p. 511 (2001). https://doi.org/10.1109/CVPR.2001.990517 . IEEE

[17] Lienhart, R., Maydt, J.: An extended set of

haar-like features for rapid object detection. In: Proceedings of the International Conference on Image Processing (ICIP), vol. 1, p. 900 (2002). https://doi.org/10.1109/ICIP.2002.1038171 . IEEE

[18] Ranftl, A., Alonso-Fernandez, F., Karlsson, S., Bigun, J.: Real-time AdaBoost cascade face tracker based on likelihood map and optical flow. IET Biometrics **6**(6), 468–477 (2017) https://doi.org/10.1049/iet-bmt.2016.0202

[19] Ma, J., Jiang, X., Fan, A., Jiang, J., Yan, J.: Image matching from handcrafted to deep features: A survey. International Journal of Computer Vision **129**, 23–79 (2021) https://doi.org/10.1007/s11263-020-01359-2

[20] Alzubaidi, L., Zhang, J., Humaidi, A.J., Al-Dujaili, A., Duan, Y., Al-Shamma, O., Santamaría, J., Fadhel, M.A., Al-Amidie, M., Farhan, L.: Review of deep learning: concepts, CNN architectures, challenges, applications, future directions. Journal of Big Data **8**(1), 53 (2021) https://doi.org/10.1186/s40537-021-00444-8

[21] Jiao, L., Zhang, F., Liu, F., Yang, S., Li, L., Feng, Z., Qu, R.: A survey of deep learning-based object detection. IEEE Access **7**, 128837–128868 (2019) https://doi.org/10.1109/access.2019.2939201

[22] Ren, S., He, K., Girshick, R., Sun, J.: Faster R-CNN: Towards real-time object detection with region proposal networks. IEEE Transactions on Pattern Analysis and Machine Intelligence **39**(6), 1137–1149 (2017) https://doi.org/10.1109/tpami.2016.2577031

[23] He, K., Gkioxari, G., Dollár, P., Girshick, R.: Mask r-cnn. In: Proceedings of the IEEE International Conference on Computer Vision (ICCV), pp. 2961–2969 (2017). https://doi.org/10.1109/ICCV.2017.322

[24] Liu, W., Anguelov, D., Erhan, D., Szegedy, C., Reed, S., Fu, C.-Y., Berg, A.C.: SSD: Single shot MultiBox detector. In: Proceedings of the European Conference on Computer Vision (ECCV). Lecture Notes in Computer Science, vol. 9905, pp. 21–37. Springer, Cham (2016). https://doi.org/10.1007/978-3-319-46448-0_2

[25] Lin, T.-Y., Dollár, P., Girshick, R., He, K., Hariharan, B., Belongie, S.: Feature pyramid networks for object detection. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp. 2117–2125 (2017). https://doi.org/10.1109/cvpr.2017.106 . IEEE

[26] Tian, Z., Shen, C., Chen, H., He, T.: FCOS: Fully convolutional one-stage object detection. In: Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), pp. 9627–9636 (2019). https://doi.org/10.1109/iccv.2019.00972 . IEEE

[27] Redmon, J., Divvala, S., Girshick, R., Farhadi, A.: You only look once: Unified, real-time object detection. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp. 779–788 (2016). https://doi.org/10.1109/cvpr.2016.91 . IEEE

[28] Redmon, J., Farhadi, A.: YOLO9000: Better, faster, stronger. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp. 7263–7271 (2017). https://doi.org/10.1109/cvpr.2017.690 . IEEE

[29] Wang, C.-Y., Bochkovskiy, A., Liao, H.-Y.M.: Scaled-YOLOv4: Scaling cross stage partial network. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 13029–13038 (2021). https://doi.org/10.1109/CVPR46437.2021.01283

[30] Terven, J., Córdova-Esparza, D.-M., Romero-González, J.-A.: A comprehensive review of YOLO architectures in computer vision: From YOLOv1 to YOLOv8 and YOLO-NAS. Machine Learning and Knowledge Extraction **5**(4), 1680–1716 (2023) https://doi.org/10.3390/make5040083

[31] Hussain, M.: YOLO-v1 to YOLO-v8, the rise of YOLO and its complementary nature toward digital manufacturing and industrial defect detection. Machines **11**(7), 677 (2023)

https://doi.org/10.3390/machines11070677

[32] Hutten, N., Meyes, R., Meisen, T.: Vision transformer in industrial visual inspection. Applied Sciences **12**(23), 11981 (2022) https://doi.org/10.3390/app122311981

[33] Cai, Z., Vasconcelos, N.: Cascade R-CNN: Delving into high quality object detection. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 6154–6162 (2018). https://doi.org/10.1109/cvpr.2018.00644 . IEEE

[34] Wang, A., Chen, H., Liu, L., Chen, K., Lin, Z., Han, J., Ding, G.: YOLOv10: Real-time end-to-end object detection. In: Advances in Neural Information Processing Systems (NeurIPS 2024), vol. 37, pp. 107984–108011 (2024). https://doi.org/10.52202/079017-3429

[35] Robinson, I., Robicheaux, P., Popov, M., Ramanan, D., Peri, N.: RF-DETR: Neural architecture search for real-time detection transformers. In: International Conference on Learning Representations (ICLR) (2026)

[36] Lee, K., Lee, S., Kim, H.Y.: Bounding-box object augmentation with random transformations for automated defect detection in residential building façades. Automation in Construction **135**, 104138 (2022) https://doi.org/10.1016/j.autcon.2022.104138

[37] Ghiasi, G., Cui, Y., Srinivas, A., Qian, R., Lin, T.-Y., Cubuk, E.D., Le, Q.V., Zoph, B.: Simple copy-paste is a strong data augmentation method for instance segmentation. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 2918–2928 (2021). https://doi.org/10.1109/CVPR46437.2021.00294

[38] Cong, W., Niu, L., Zhang, J., Liang, J., Zhang, L.: BargainNet: Background-guided domain translation for image harmonization. In: Proceedings of the IEEE International Conference on Multimedia and Expo (ICME), pp. 1–6 (2021). https://doi.org/10.1109/ICME51207.2021.9428394

[39] Guerreiro, J.J.A., Nakazawa, M., Stenger, B.: PCT-Net: Full resolution image harmonization using pixel-wise color transformations. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 5917–5926 (2023). https://doi.org/10.1109/CVPR52729.2023.00572

[40] Chadebec, C., Tasar, O., Sreetharan, S., Aubin, B.: LBM: Latent bridge matching for fast image-to-image translation. In: Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV) (2025)

[41] Urbonas, A., Raudonis, V., Maskeliūnas, R., Damaševičius, R.: Automated identification of wood veneer surface defects using faster region-based convolutional neural network with data augmentation and transfer learning. Applied Sciences **9**(22), 4898 (2019) https://doi.org/10.3390/app9224898

[42] Fang, Y., Guo, X., Chen, K.: Accurate and automated detection of surface knots on sawn timbers using YOLO-V5 model. BioResources **16**(3), 5390–5406 (2021) https://doi.org/10.15376/biores.16.3.5390-5406

[43] Han, S., Jiang, X., Wu, Z.: An improved YOLOv5 algorithm for wood defect detection based on attention. IEEE Access **11**, 71554–71565 (2023) https://doi.org/10.1109/access.2023.3293864

[44] Zheng, Y., Wang, M., Zhang, B., Shi, X., Chang, Q.: Gbcd-yolo: A high-precision and real-time lightweight model for wood defect detection. IEEE Access **12**, 25871–25887 (2024) https://doi.org/10.1109/ACCESS.2024.3356048

[45] An, L., Liang, Q., Huang, X., Zeng, W.: Wood defect detection based on the CWB-YOLOv8 algorithm. Journal of Wood Science **70**(1), 21 (2024) https://doi.org/10.1186/s10086-024-02139-z

[46] Sun, P.: Wood quality defect detection based on deep learning and multicriteria framework. Mathematical Problems in Engineering **2022**, 1–12 (2022) https://doi.org/10.1155/2022/4878090

[47] Kılıç, K., Kılıç, K., Doğru, .I.A., Özcan, U.: WD Detector: deep learning-based hybrid sensor design for wood defect detection. European Journal of Wood and Wood Products **83**, 50 (2025) https://doi.org/10.1007/s00107-025-02211-5

[48] Ji, M., Zhang, W., Han, J.-K., Miao, H., Diao, X.-L., Wang, G.-F.: A deep learning-based algorithm for online detection of small target defects in large-size sawn timber. Industrial Crops and Products **225**, 119671 (2024) https://doi.org/10.1016/j.indcrop.2024.119671

[49] Wolszczak, P., Kotnarowski, G., Małek, A., Litak, G.: Training of a neural network system in the task of detecting blue stains in a sawmill wood inspection system. Applied Sciences **14**(9), 3885 (2024) https://doi.org/10.3390/app14093885

[50] Chen, L.-C., Pardeshi, M.S., Lo, W.-T.: Edge-glued wooden panel defect detection using deep learning. Wood Science and Technology **56**, 255–276 (2022) https://doi.org/10.1007/s00226-021-01316-3

[51] Zhang, Y., Kang, B., Hooi, B., Yan, S., Feng, J.: Deep long-tailed learning: A survey. IEEE Transactions on Pattern Analysis and Machine Intelligence **45**(9), 10795–10816 (2023) https://doi.org/10.1109/TPAMI.2023.3268118

[52] Cui, Y., Jia, M., Lin, T.-Y., Song, Y., Belongie, S.: Class-balanced loss based on effective number of samples. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 9260–9269 (2019). https://doi.org/10.1109/CVPR.2019.00949

[53] Tan, J., Wang, C., Li, B., Li, Q., Ouyang, W., Yin, C., Yan, J.: Equalization loss for long-tailed object recognition. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 11659–11668 (2020). https://doi.org/10.1109/CVPR42600.2020.01168

[54] Wang, J., Zhang, W., Zang, Y., Cao, Y., Pang, J., Gong, T., Chen, K., Liu, Z., Loy, C.C., Lin, D.: Seesaw loss for long-tailed instance segmentation. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 9695–9704 (2021). https://doi.org/10.1109/CVPR46437.2021.00957

[55] Shorten, C., Khoshgoftaar, T.M.: A survey on image data augmentation for deep learning. Journal of Big Data **6**, 60 (2019) https://doi.org/10.1186/s40537-019-0197-0

[56] Buslaev, A., Iglovikov, V.I., Khvedchenya, E., Parinov, A., Druzhinin, M., Kalinin, A.A.: Albumentations: Fast and flexible image augmentations. Information **11**(2), 125 (2020) https://doi.org/10.3390/info11020125

[57] Zhao, Y., Lv, W., Xu, S., Wei, J., Wang, G., Dang, Q., Liu, Y., Chen, J.: DETRs beat YOLOs on real-time object detection. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 16965–16974 (2024). https://doi.org/10.1109/CVPR52733.2024.01605

[58] Powers, D.M.W.: Evaluation: From precision, recall and f-measure to ROC, informedness, markedness and correlation. Journal of Machine Learning Technologies **2**(1), 37–63 (2011)

[59] Lin, T.-Y., Maire, M., Belongie, S., Hays, J., Perona, P., Ramanan, D., Dollár, P., Zitnick, C.L.: Microsoft COCO: Common objects in context. In: Proceedings of the European Conference on Computer Vision (ECCV), pp. 740–755 (2014). https://doi.org/10.1007/978-3-319-10602-1_48

[60] Everingham, M., Van Gool, L., Williams, C.K.I., Winn, J., Zisserman, A.: The Pascal visual object classes (VOC) challenge. International Journal of Computer Vision **88**(2), 303–338 (2010) https://doi.org/10.1007/s11263-009-0275-4

[61] Cordts, M., Omran, M., Ramos, S., Rehfeld, T., Enzweiler, M., Benenson, R., Franke, U., Roth, S., Schiele, B.: The cityscapes dataset for semantic urban scene understanding. In: Proceedings of the IEEE Conference

on Computer Vision and Pattern Recognition (CVPR), pp. 3213–3223 (2016). https://doi.org/10.1109/CVPR.2016.350

[62] Nomihsa: Large-Scale Image Dataset of Wood Surface Defects. Kaggle. Filtered and annotated in YOLO format (2024). https://www.kaggle.com/datasets/nomihsa965/large-scale-image-dataset-of-wood-surface-defects Accessed 2026-06-19

[63] Colvin, S., Jolibois, E., Ramezani, H., Garcia Badaracco, A., Dorsey, T., Montague, D., Matveenko, S., Trylesinski, M., Runkle, S., Hewitt, D., et al.: Pydantic. Zenodo (2024)

[64] Otsu, N.: A threshold selection method from gray-level histograms. IEEE Transactions on Systems, Man, and Cybernetics **9**(1), 62–66 (1979) https://doi.org/10.1109/TSMC.1979.4310076

[65] Kubat, M., Matwin, S.: Addressing the curse of imbalanced training sets: One-sided selection. In: Proceedings of the Fourteenth International Conference on Machine Learning (ICML 1997), pp. 179–186 (1997)

[66] Lin, T.-Y., Goyal, P., Girshick, R., He, K., Dollár, P.: Focal loss for dense object detection. In: Proceedings of the IEEE International Conference on Computer Vision (ICCV), pp. 2980–2988 (2017). https://doi.org/10.1109/iccv.2017.324 . IEEE

[67] He, K., Girshick, R., Dollár, P.: Rethinking ImageNet pre-training. In: Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), pp. 4918–4927 (2019). https://doi.org/10.1109/ICCV.2019.00502

[68] Dwibedi, D., Misra, I., Hebert, M.: Cut, paste and learn: Surprisingly easy synthesis for instance detection. In: Proceedings of the IEEE International Conference on Computer Vision (ICCV), pp. 1301–1310 (2017). https://doi.org/10.1109/ICCV.2017.146

[69] Fan, D.-P., Ji, G.-P., Sun, G., Cheng, M.-M., Shen, J., Shao, L.: Camouflaged object detection. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 2777–2788 (2020). https://doi.org/10.1109/CVPR.2020.00285

[70] Huang, J., Rathod, V., Sun, C., Zhu, M., Korattikara, A., Fathi, A., Fischer, I., Wojna, Z., Song, Y., Guadarrama, S., Murphy, K.: Speed/accuracy trade-offs for modern convolutional object detectors. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp. 3296–3305 (2017). https://doi.org/10.1109/CVPR.2017.351

[71] Capogrosso, L., Girella, F., Taioli, F., Dalla Chiara, M., Aqeel, M., Fummi, F., Setti, F., Cristani, M.: Diffusion-based image generation for in-distribution data augmentation in surface defect detection. In: Proceedings of the 19th International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications (VISAPP 2024), vol. 2, pp. 409–416. SCITEPRESS, Setúbal (2024). https://doi.org/10.5220/0012350400003660