

Locking

To specify the lock mode to be used, you can use the `@Lock` annotation on query methods, as shown in the following example:

Example 1. Defining lock metadata on query methods

```
interface UserRepository extends Repository<User, Long> {  
  
    // Plain query method  
    @Lock(LockModeType.READ)  
    List<User> findByLastname(String lastname);  
}
```

JAVA

This method declaration causes the query being triggered to be equipped with a `LockModeType` of `READ`. You can also define locking for CRUD methods by redeclaring them in your repository interface and adding the `@Lock` annotation, as shown in the following example:

Example 2. Defining lock metadata on CRUD methods

```
interface UserRepository extends Repository<User, Long> {  
  
    // Redclaration of a CRUD method  
    @Lock(LockModeType.READ)  
    List<User> findAll();  
}
```

JAVA

Apache®, Apache Tomcat®, Apache Kafka®, Apache Cassandra™, and Apache Geode™ are trademarks or registered trademarks of the Apache Software Foundation in the United States and/or other countries. Java™, Java™ SE, Java™ EE, and OpenJDK™ are trademarks of Oracle and/or its affiliates. Kubernetes® is a registered trademark of the Linux Foundation in the United States and other countries. Linux® is the registered trademark of Linus Torvalds in the United States and other countries. Windows® and Microsoft® Azure are registered trademarks of Microsoft Corporation. “AWS” and “Amazon Web Services” are trademarks or registered trademarks of Amazon.com Inc. or its affiliates. All other trademarks and copyrights are property of their respective owners and are only mentioned for informative purposes. Other names may be trademarks of their respective owners.