

Repository query keywords

Repository query keywords

Supported query method subject keywords

Reserved methods

Supported query method predicate keywords and modifiers

Supported query method subject keywords

The following table lists the subject keywords generally supported by the Spring Data repository query derivation mechanism to express the predicate. Consult the store-specific documentation for the exact list of supported keywords, because some keywords listed here might not be supported in a particular store.

Table 1. Query subject keywords

Keyword	Description
<code>find...By</code> , <code>read...By</code> , <code>get...By</code> , <code>query...By</code> , <code>search...By</code> , <code>stream...By</code>	General query method returning typically the repository type, a <code>Collection</code> or <code>Streamable</code> subtype or a result wrapper such as <code>Page</code> , <code>GeoResults</code> or any other store-specific result wrapper. Can be used as <code>findBy...</code> , <code>findMyDomainTypeBy...</code> or in combination with additional keywords.
<code>exists...By</code>	Exists projection, returning typically a <code>boolean</code> result.
<code>count...By</code>	Count projection returning a numeric result.
<code>delete...By</code> , <code>remove...By</code>	Delete query method returning either no result (<code>void</code>) or the delete count.
<code>...First<number>...</code> , <code>...Top<number>...</code>	Limit the query results to the first <code><number></code> of results. This keyword can occur in any place of the subject between <code>find</code> (and the other keywords) and <code>by</code> .
<code>...Distinct...</code>	Use a distinct query to return only unique results. Consult the store-specific documentation whether that feature is supported. This keyword can occur in any place of the subject between <code>find</code> (and the other keywords) and <code>by</code> .

Reserved methods

The following table lists reserved methods that use predefined functionality (as defined in `CrudRepository`). These methods are directly invoked on the backing (store-specific) implementation of the repository proxy. See also “[Defining Query Methods](#)”.

Table 2. Reserved methods

<code>deleteAllById(Iterable<ID> identifiers)</code>
<code>deleteById(ID identifier)</code>
<code>existsById(ID identifier)</code>
<code>findAllById(Iterable<ID> identifiers)</code>
<code>findById(ID identifier)</code>

Supported query method predicate keywords and modifiers

The following table lists the predicate keywords generally supported by the Spring Data repository query derivation mechanism. However, consult the store-specific documentation for the exact list of supported keywords, because some keywords listed here might not be supported in a particular store.

Table 3. Query predicate keywords

Logical keyword	Keyword expressions
AND	And
OR	Or
AFTER	After, IsAfter
BEFORE	Before, IsBefore
CONTAINING	Containing, IsContaining, Contains
BETWEEN	Between, IsBetween
ENDING_WITH	EndingWith, IsEndingWith, EndsWith
EXISTS	Exists
FALSE	False, IsFalse
GREATER_THAN	GreaterThan, IsGreaterThan
GREATER_THAN_EQUALS	GreaterThanOrEqualTo, IsGreaterThanOrEqualTo

Logical keyword	Keyword expressions
IN	In , IsIn
IS	Is , Equals , (or no keyword)
IS_EMPTY	IsEmpty , Empty
IS_NOT_EMPTY	IsNotEmpty , NotEmpty
IS_NOT_NULL	NotNull , IsNotNull
IS_NULL	Null , IsNull
LESS_THAN	LessThan , IsLessThan
LESS_THAN_EQUAL	LessThanEqual , IsLessThanEqual
LIKE	Like , IsLike
NEAR	Near , IsNear
NOT	Not , IsNot
NOT_IN	NotIn , IsNotIn
NOT_LIKE	NotLike , IsNotLike
REGEX	Regex , MatchesRegex , Matches
STARTING_WITH	StartingWith , IsStartingWith , StartsWith
TRUE	True , IsTrue
WITHIN	Within , IsWithin

In addition to filter predicates, the following list of modifiers is supported:

Table 4. Query predicate modifier keywords

Keyword	Description
IgnoreCase , IgnoringCase	Used with a predicate keyword for case-insensitive comparison.
AllIgnoreCase , AllIgnoringCase	Ignore case for all suitable properties. Used somewhere in the query method predicate.

Keyword	Description
OrderBy...	Specify a static sorting order followed by the property path and direction (e.g. OrderByFirstnameAscLastnameDesc).



Copyright © 2005 - 2026 Broadcom. All Rights Reserved. The term "Broadcom" refers to Broadcom Inc. and/or its subsidiaries.

[Terms of Use](#) • [Privacy](#) • [Trademark Guidelines](#) • [Thank you](#) • [Your California Privacy Rights](#) • [Cookies Settings](#)

Apache®, Apache Tomcat®, Apache Kafka®, Apache Cassandra™, and Apache Geode™ are trademarks or registered trademarks of the Apache Software Foundation in the United States and/or other countries. Java™, Java™ SE, Java™ EE, and OpenJDK™ are trademarks of Oracle and/or its affiliates. Kubernetes® is a registered trademark of the Linux Foundation in the United States and other countries. Linux® is the registered trademark of Linus Torvalds in the United States and other countries. Windows® and Microsoft® Azure are registered trademarks of Microsoft Corporation. "AWS" and "Amazon Web Services" are trademarks or registered trademarks of Amazon.com Inc. or its affiliates. All other trademarks and copyrights are property of their respective owners and are only mentioned for informative purposes. Other names may be trademarks of their respective owners.