

MP MetaAnalysis

Christina Bergmann

Contents

Preparation	2
Plotting defaults	2
Descriptive data	2
Type of data on which we calculated effect sizes	2
Type of comparison of the time-course data calculated	2
Type of distractor	3
Whether word was pronounced both correctly as well as mispronounced	3
Size of analysis time window	3
Duration of post naming window	4
Mispronunciation Sensitivity in the youngest ages	4
Meta-Analysis	5
Main Mispronunciation Sensitivity Effects	5
Main Mispronunciation Sensitivity Effects with Age Moderators	8
Correlation MP effect and Vocabulary	12
Number of features	15
Type of MP: Vowel, consonant, or tone	20
Distractor Familiarity (familiar, unfamiliar)	28
Position of Mispronunciation (onset, medial)	36
Distractor Overlap	41
Language effect	46
## Loading tidyverse: ggplot2	
## Loading tidyverse: tibble	
## Loading tidyverse: tidyr	
## Loading tidyverse: readr	
## Loading tidyverse: purrr	
## Loading tidyverse: dplyr	
## Conflicts with tidy packages -----	
## filter(): dplyr, stats	
## lag(): dplyr, stats	
## Loading required package: Matrix	
##	
## Attaching package: 'Matrix'	
## The following object is masked from 'package:tidyr':	
##	
## expand	
## Loading 'metafor' package (version 1.9-9). For an overview	
## and introduction to the package please type: help(metafor).	
## Loading 'meta' package (version 4.9-0).	
## Type 'help(meta)' for a brief overview.	

```
##
## Attaching package: 'meta'

## The following objects are masked from 'package:metafor':
##
##     baujat, forest, funnel, funnel.default, labbe, radial,
##     trimfill
```

Preparation

Read in data and tidy up dataset

Plotting defaults

```
# Themes and plot
apatheme = theme_bw() + theme(panel.grid.major = element_blank(), panel.grid.minor = element_blank(),
  panel.border = element_blank(), axis.line = element_line(), text = element_text(family = "Times",
    size = 25))
```

Descriptive data

The database contains data from 32 papers consisting of data from 2010 infants. In the tables below, we provide more descriptive information.

The next table shows what type of publications were included in our meta-analysis

publication_status	n_unique	count
dissertation	2	17
gray paper	2	14
paper	27	216
proceedings	1	4

Type of data on which we calculated effect sizes

The table below shows based on which data we calculated effect sizes.

es_method	n_unique	count
group_means_one	18	120
group_means_two	7	57
t_one	4	39
t_two	5	35

Type of comparison of the time-course data calculated

We also have different ways of comparison of the time-course data, as the next table shows.

within_measure_descriptive	n_unique	count
post-naming compared to pre-naming phase	10	29
post-naming phase compared with chance (=50%)	9	23
post-pre difference score compared with chance (=0)	13	52

Type of distractor

This is a summary of the type of distractor used in an experiment

object_pair	count
familiar_familiar	23
familiar_novel	10

Whether word was pronounced both correctly as well as mispronounced

This is a summary of whether an experiment had both correct and mispronounced versions of the word in the experiment

word_correct_and_MP	count
	2
no	10
yes	21

Size of analysis time window

Where possible, we noted the time window for analysis. First, let's look at the offset (in milliseconds) after the start of the word, i.e. the begin of a give analysis window for a naming effect

```
offset_info <- time_wind_dat %>% group_by(offset) %>% summarize(count = n())
```

```
kable(offset_info)
```

offset	count
0	3
200	1
231	1
267	1
300	1
360	5
365	1
367	14
400	1
500	1
1133	1
NA	4

Duration of post naming window

Next we look at duration (in seconds) of the post naming window, here,too, we see a lot of heterogeneity.

```
duration_info <- db_ET_correct %>% group_by(post_nam_dur) %>% summarize(count = n())
```

```
kable(duration_info)
```


post_nam_dur	count
1.510	2
2.000	45
2.500	18
2.600	4
2.750	4
2.767	1
2.805	4
3.000	13
3.500	6
4.000	6
6.000	1

In summary, we see little consistency in analysis methods of comparable studies looking at naming and mispronunciation effects.

Mispronunciation Sensitivity in the youngest ages

Even the youngest ages in the database (less than 1 year) show mispronunciation sensitivity

```
## [1] Zesiger et al. (2012)          Mani & Plunkett 2010
## [3] Bergelson & Swingley (2017)
## 34 Levels: Altvater-Mackensen (2010) ... Zesiger et al. (2012)
```



Meta-Analysis

Main Mispronunciation Sensitivity Effects

Correct object identification effect

```
rma_correct = rma.mv(g_calc, g_var_calc, data = db_ET_correct, random = ~collapse |
  short_cite)
```

```
summary(rma_correct)
```

```
##
## Multivariate Meta-Analysis Model (k = 104; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -111.8857   223.7713   229.7713   237.6755   230.0137
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##              estim      sqrt  fixed
## tau^2         0.4483   0.6696    no
```

```
## rho          0.8886          no
##
## Test for Heterogeneity:
## Q(df = 103) = 625.6267, p-val < .0001
##
## Model Results:
##
## estimate      se      zval      pval      ci.lb      ci.ub
## 0.9078    0.1198    7.5784    <.0001    0.6730    1.1426    ***
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

# kable(round(coef(summary(rma_correct)), 2))
```

Mispronunciation object identification effect

```
rma_MP = rma.mv(g_calc, g_var_calc, data = db_ET_MP, random = ~collapse | short_cite)

summary(rma_MP)

##
## Multivariate Meta-Analysis Model (k = 147; method: REML)
##
##   logLik Deviance      AIC      BIC      AICc
## -70.1217 140.2434 146.2434 155.1942 146.4124
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1192  0.3453     no
## rho        0.5924          no
##
## Test for Heterogeneity:
## Q(df = 146) = 462.5143, p-val < .0001
##
## Model Results:
##
## estimate      se      zval      pval      ci.lb      ci.ub
## 0.2498    0.0597    4.1835    <.0001    0.1328    0.3668    ***
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Mispronunciation Sensitivity effect

```
db_ET_correct$condition <- 1
db_ET_MP$condition <- 0
```

```

dat <- bind_rows(db_ET_correct, db_ET_MP)

rma_MPeffect <- rma.mv(g_calc, g_var_calc, mods = ~condition, data = dat, random = ~collapse |
  short_cite)

summary(rma_MPeffect)

```

```

##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -252.9095   505.8189   513.8189   527.8887   513.9829
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1371  0.3703     no
## rho        0.7381              no
##
## Test for Residual Heterogeneity:
## QE(df = 249) = 1088.1411, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 215.7609, p-val < .0001
##
## Model Results:
##
##           estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt      0.2792  0.0652   4.2827 <.0001  0.1514  0.4069 ***
## condition    0.4953  0.0337  14.6888 <.0001  0.4293  0.5614 ***
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

rma_MPeffect_1 <- rma.mv(g_calc, g_var_calc, mods = ~condition - 1, data = dat,
  random = ~collapse | short_cite)

summary(rma_MPeffect_1)

```

```

##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -261.1359   522.2718   528.2718   538.8362   528.3694
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed

```

```
## tau^2      0.2069  0.4549      no
## rho        0.8295              no
##
## Test for Residual Heterogeneity:
## QE(df = 250) = 1154.4618, p-val < .0001
##
## Model Results:
##
##           estimate      se      zval      pval      ci.lb      ci.ub
## condition      0.5139  0.0333  15.4186 <.0001  0.4486  0.5793 ***
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Main Mispronunciation Sensitivity Effects with Age Moderators

Correct object identification effect with age moderator

```
rma_correct_age = rma.mv(g_calc, g_var_calc, mods = ~age.C, data = db_ET_correct,
  random = ~collapse | short_cite)

summary(rma_correct_age)
```

```
##
## Multivariate Meta-Analysis Model (k = 104; method: REML)
##
##      logLik  Deviance      AIC      BIC      AICc
## -110.8134   221.6268   229.6268   240.1267   230.0392
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.4458  0.6677      no
## rho        0.8835              no
##
## Test for Residual Heterogeneity:
## QE(df = 102) = 619.1502, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.6778, p-val = 0.4103
##
## Model Results:
##
##           estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt      0.9202  0.1203  7.6515 <.0001  0.6845  1.1559 ***
## age.C        0.0145  0.0176  0.8233  0.4103 -0.0200  0.0490
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```



```
# kable(round(coef(summary(rma_correct_age)), 2))
```

Mispronunciation object identification effect with age moderator

```
rma_MP_age = rma.mv(g_calc, g_var_calc, mods = ~age.C, data = db_ET_MP, random = ~collapse | short_cite)
```

```
summary(rma_MP_age)
```

```
##
## Multivariate Meta-Analysis Model (k = 147; method: REML)
##
##   logLik  Deviance      AIC      BIC      AICc
## -68.8541  137.7083  145.7083  157.6152  145.9940
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1181  0.3437     no
## rho        0.5830              no
##
## Test for Residual Heterogeneity:
## QE(df = 145) = 449.1871, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 1.7151, p-val = 0.1903
##
## Model Results:
##
##           estimate      se    zval    pval    ci.lb    ci.ub
## intrcpt      0.2613  0.0599  4.3583 <.0001  0.1438  0.3788 ***
## age.C        0.0149  0.0114  1.3096  0.1903 -0.0074  0.0372
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Mispronunciation Sensitivity effect with age moderator

```
db_ET_correct$condition <- 1
db_ET_MP$condition <- 0

dat <- bind_rows(db_ET_correct, db_ET_MP)

rma_MPeffect_age <- rma.mv(g_calc, g_var_calc, mods = ~age.C * condition, data = dat,
  random = ~collapse | short_cite)

summary(rma_MPeffect_age)
```

```
##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -251.2299   502.4597   514.4597   535.5160   514.8097
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1331  0.3648     no
## rho        0.7254              no
##
## Test for Residual Heterogeneity:
## QE(df = 247) = 1068.3373, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4):
## QM(df = 3) = 218.6210, p-val < .0001
##
## Model Results:
##
##           estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt           0.2935  0.0648   4.5324 <.0001    0.1666    0.4204 ***
## age.C             0.0171  0.0113   1.5136  0.1301   -0.0051    0.0393
## condition         0.4984  0.0344  14.4930 <.0001    0.4310    0.5658 ***
## age.C:condition   0.0026  0.0076   0.3436  0.7312   -0.0123    0.0175
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```


Plot Mispronunciation Effect by Age (color)

```
dat$condition_label = ifelse(dat$condition == 1, "Correct", "Mispronunciation")

# Color Blind palette:
cbPalette <- c("#E69F00", "#56B4E9", "#009E73", "#F0E442", "#0072B2", "#D55E00",
               "#CC79A7")

p <- ggplot(dat, aes(mean_age_1/30.44, g_calc, color = condition_label)) + geom_point(aes(size = weight,
show.legend = FALSE) + geom_line(y = 0, linetype = "dotted") + geom_smooth(method = "lm",
formula = y ~ log(x), aes(weight = weights_g)) + scale_colour_manual(values = cbPalette) +
apatheme + theme(legend.title = element_blank(), legend.position = "bottom") +
xlab("Age in months") + ylab("Effect size Hedges' g")

p
```



```
min(dat$mean_age_1/30.44)
```

```
## [1] 6.826544
```

```
max(dat$mean_age_1/30.44)
```

```
## [1] 30.22996
```

```
# ggsave('figures/AgeEffect_log.jpg', p,height= 7,width= 6)
```

```
jpeg(filename = "figures/AgeEffect_log.jpg", width = 600, height = 400, units = "px")
```

```
p
```

```
dev.off()
```

```
## pdf
```

```
## 2
```

Plot Mispronunciation Effect by Age (bw)

```
p <- ggplot(dat, aes(mean_age_1/30.44, g_calc, color = condition_label)) + geom_point(aes(size = weights_g,
  shape = condition_label, color = condition_label), show.legend = FALSE) +
  geom_line(y = 0, linetype = "dotted") + geom_smooth(method = "lm", formula = y ~
  log(x), aes(weight = weights_g)) + scale_color_grey() + theme_bw() + theme(text = element_text(size = 12),
  legend.title = element_blank(), legend.position = "bottom") + xlab("Age in months") +
```



```
ggsave("figures/AgeEffect_log_BW.jpg", p, height = 3, width = 6)
```

Correlation MP effect and Vocabulary

First, let's take a look at which vocabulary data we have available.

```
vocab_info <- db_ET_correct %>% mutate(has_vocab = ifelse(!is.na(r_comprehension),
  "comprehension", ifelse(!is.na(r_production), "production", "none"))) %>%
  group_by(has_vocab) %>% summarize(count = n())

kable(vocab_info)
```

has_vocab	count
comprehension	12
none	87
production	5

We have 17 correlations, roughly evenly divided between comprehension and production data. There is reason to believe that production data are different from comprehension data (the former being easier to estimate for parents in the typical questionnaire-based assessment), so we should both analyze this data separately and see whether it makes sense in a joint analysis.

```
# we're relying on the library meta function metacor
compr <- subset(db_ET_correct, !is.na(db_ET_correct$r_comprehension) & r_comprehension >
-1)
```

```
metacor(cor = r_comprehension, n = n_1, studlab = short_cite, data = compr,
sm = "COR")
```

```
##                                COR                95%-CI %W(fixed)
## Zesiger et al. (2012)          0.0610 [-0.3553; 0.4773]      5.8
## Zesiger et al. (2012)         -0.1590 [-0.5663; 0.2483]      6.1
## Mani, Coleman, & Plunkett (2008) 0.0300 [-0.2271; 0.2871]     15.2
## Swingley & Aslin (2000)         0.1050 [-0.1564; 0.3664]     14.7
## Mani & Plunkett 2007             -0.1700 [-0.5234; 0.1834]      8.0
## Mani & Plunkett 2007             -0.1700 [-0.5175; 0.1775]      8.3
## Swingley & Aslin (2002)         0.1410 [-0.2432; 0.5252]      6.8
## Swingley & Aslin (2002)         0.1410 [-0.2596; 0.5416]      6.3
## Swingley 2003                  0.3400 [ 0.0470; 0.6330]     11.7
## Swingley 2003                  0.0600 [-0.3472; 0.4672]      6.1
## H\xbfjen et al.                0.2220 [-0.2591; 0.7031]      4.3
## H\xbfjen et al.                0.4820 [ 0.0935; 0.8705]      6.7
##                                %W(random)
## Zesiger et al. (2012)          6.2
## Zesiger et al. (2012)          6.5
## Mani, Coleman, & Plunkett (2008) 13.7
## Swingley & Aslin (2000)         13.4
## Mani & Plunkett 2007             8.3
## Mani & Plunkett 2007             8.5
## Swingley & Aslin (2002)         7.2
## Swingley & Aslin (2002)         6.7
## Swingley 2003                  11.2
## Swingley 2003                  6.5
## H\xbfjen et al.                4.8
## H\xbfjen et al.                7.0
##
## Number of studies combined: k = 12
##
##                                COR                95%-CI    z p-value
## Fixed effect model    0.0897 [-0.0105; 0.1900]  1.75  0.0795
## Random effects model  0.0893 [-0.0212; 0.1999]  1.58  0.1132
##
## Quantifying heterogeneity:
## tau^2 = 0.0060; H = 1.09 [1.00; 1.50]; I^2 = 15.7% [0.0%; 55.4%]
##
## Test of heterogeneity:
##      Q d.f. p-value
##  13.05  11  0.2899
##
## Details on meta-analytical method:
## - Inverse variance method
## - DerSimonian-Laird estimator for tau^2
## - Untransformed correlations
```

```
# we're relying on the library meta function metacor
prodr <- subset(db_ET_correct, !is.na(db_ET_correct$r_production) & r_production <
```

1)

```
metacor(cor = r_production, n = n_1, studlab = short_cite, data = prodr, sm = "COR")
```

```
##                                COR          95%-CI %W(fixed)
## Zesiger et al. (2012)          -0.0090 [-0.4268; 0.4088]    5.0
## Zesiger et al. (2012)          -0.1720 [-0.5775; 0.2335]    5.3
## Mani, Coleman, & Plunkett (2008) 0.0700 [-0.1861; 0.3261]   13.2
## Mani & Plunkett 2007            -0.1100 [-0.4696; 0.2496]    6.7
## Mani & Plunkett 2007            -0.1100 [-0.4635; 0.2435]    6.9
## Swingley & Aslin (2002)         0.1820 [-0.1970; 0.5610]    6.0
## Swingley & Aslin (2002)         0.1820 [-0.2131; 0.5771]    5.6
## Swingley 2003                  0.1800 [-0.1406; 0.5006]    8.4
## Swingley 2003                  0.0700 [-0.3367; 0.4767]    5.2
## Ramon-Casas et al. 2009         0.0980 [-0.3068; 0.5028]    5.3
## Ramon-Casas et al. 2009        -0.1470 [-0.5468; 0.2528]    5.4
## Ramon-Casas et al. 2009        -0.2300 [-0.6171; 0.1571]    5.8
## Ramon-Casas et al. 2009         0.2400 [-0.1451; 0.6251]    5.9
## Ramon-Casas et al. 2009         0.4350 [ 0.1037; 0.7663]    7.9
## H\xbfjen et al.                0.2220 [-0.2591; 0.7031]    3.7
## H\xbfjen et al.               -0.1480 [-0.6430; 0.3470]    3.5
##                                %W(random)
## Zesiger et al. (2012)           5.0
## Zesiger et al. (2012)           5.3
## Mani, Coleman, & Plunkett (2008) 13.2
## Mani & Plunkett 2007             6.7
## Mani & Plunkett 2007             6.9
## Swingley & Aslin (2002)         6.0
## Swingley & Aslin (2002)         5.6
## Swingley 2003                   8.4
## Swingley 2003                   5.2
## Ramon-Casas et al. 2009         5.3
## Ramon-Casas et al. 2009         5.4
## Ramon-Casas et al. 2009         5.8
## Ramon-Casas et al. 2009         5.9
## Ramon-Casas et al. 2009         7.9
## H\xbfjen et al.                 3.7
## H\xbfjen et al.                 3.5
##
## Number of studies combined: k = 16
##
##                                COR          95%-CI    z p-value
## Fixed effect model  0.0601 [-0.0331; 0.1533]  1.26  0.2061
## Random effects model 0.0601 [-0.0331; 0.1533]  1.26  0.2061
##
## Quantifying heterogeneity:
## tau^2 = 0; H = 1.00 [1.00; 1.42]; I^2 = 0.0% [0.0%; 50.7%]
##
## Test of heterogeneity:
##      Q d.f. p-value
## 14.51  15  0.4870
##
## Details on meta-analytical method:
## - Inverse variance method
```

```
## - DerSimonian-Laird estimator for tau^2
## - Untransformed correlations
```

Number of features

Size of mispronunciation, measured in features changed

```
db_ET_MPf = db_ET_MP %>% filter(n_feature != "1-3" & n_feature != "1-2" & n_feature !=
  "2-3")

# rma_NFeatures <- rma.mv(g_calc, g_var_calc, mods = ~as.ordered(n_feature),
# data = db_ET_MP, random = ~collapse | short_cite)
rma_NFeatures <- rma.mv(g_calc, g_var_calc, mods = ~as.factor(n_feature), data = db_ET_MPf,
  random = ~collapse | short_cite)

summary(rma_NFeatures)
```

```
##
## Multivariate Meta-Analysis Model (k = 132; method: REML)
##
##   logLik  Deviance      AIC      BIC      AICc
## -60.4794  120.9588  136.9588  159.6491  138.1896
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 27)
## inner factor: collapse   (nlvls = 46)
##
##           estim      sqrt  fixed
## tau^2      0.1229  0.3506     no
## rho         0.4838              no
##
## Test for Residual Heterogeneity:
## QE(df = 126) = 393.2688, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6):
## QM(df = 5) = 6.9417, p-val = 0.2250
##
## Model Results:
##
##              estimate      se      zval      pval      ci.lb
## intrcpt              0.2767  0.0659   4.1984 <.0001   0.1475
## as.factor(n_feature)2 -0.0889  0.0804  -1.1054  0.2690  -0.2465
## as.factor(n_feature)3 -0.2339  0.1056  -2.2159  0.0267  -0.4409
## as.factor(n_feature)41640 -0.2278  0.2436  -0.9349  0.3498  -0.7053
## as.factor(n_feature)41641 -0.2088  0.1355  -1.5408  0.1234  -0.4743
## as.factor(n_feature)41672 -0.2767  0.3527  -0.7846  0.4327  -0.9680
##              ci.ub
## intrcpt              0.4059 ***
## as.factor(n_feature)2  0.0687
## as.factor(n_feature)3 -0.0270 *
## as.factor(n_feature)41640  0.2497
## as.factor(n_feature)41641  0.0568
```

```
## as.factor(n_feature)41672    0.4146
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Number of features with condition moderator

```
dat_f <- subset(dat, n_feature == "0" | n_feature == "1" | n_feature == "2" |
  n_feature == "3")

# rma_NFeatures <- rma.mv(g_calc, g_var_calc, mods = ~as.ordered(n_feature),
# data = db_ET_MP, random = ~collapse | short_cite)
rma_NFeatures <- rma.mv(g_calc, g_var_calc, mods = ~as.factor(n_feature) * condition,
  data = dat_f, random = ~collapse | short_cite)

summary(rma_NFeatures)
```

```
##
## Multivariate Meta-Analysis Model (k = 211; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -234.6537   469.3074   483.3074   506.6025   483.8730
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 27)
## inner factor: collapse   (nlvls = 49)
##
##           estim      sqrt  fixed
## tau^2      0.1530  0.3911     no
## rho         0.6938              no
##
## Test for Residual Heterogeneity:
## QE(df = 206) = 980.4970, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5):
## QM(df = 4) = 184.5957, p-val < .0001
##
## Model Results:
##
##              estimate      se      zval      pval      ci.lb      ci.ub
## intrcpt              0.5966  0.1346   4.4341 <.0001    0.3329    0.8604
## as.factor(n_feature)1 -0.3195  0.1130  -2.8277  0.0047   -0.5409   -0.0980
## as.factor(n_feature)2 -0.2848  0.1290  -2.2078  0.0273   -0.5377   -0.0320
## as.factor(n_feature)3 -0.5037  0.1462  -3.4456  0.0006   -0.7902   -0.2172
## condition              0.1906  0.1062   1.7949  0.0727   -0.0175    0.3987
##
## intrcpt            ***
## as.factor(n_feature)1  **
## as.factor(n_feature)2   *
## as.factor(n_feature)3  ***
## condition            .
```



```
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Number of features with age moderator

```
db_ET_MPf = db_ET_MP %>% filter(n_feature != "1-3" & n_feature != "1-2" & n_feature !=
  "2-3")
```

```
rma_NFeaturesAge <- rma.mv(g_calc, g_var_calc, mods = ~as.factor(n_feature) *
  age.C, data = db_ET_MPf, random = ~collapse | short_cite)
```

```
summary(rma_NFeaturesAge)
```

```
##
## Multivariate Meta-Analysis Model (k = 132; method: REML)
##
##      logLik  Deviance      AIC      BIC      AICc
## -60.6887  121.3775  149.3775  188.4023  153.3775
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 27)
## inner factor: collapse   (nlvls = 46)
##
##              estim      sqrt  fixed
## tau^2         0.1305  0.3612    no
## rho           0.4368              no
##
## Test for Residual Heterogeneity:
## QE(df = 120) = 376.5908, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8,9,10,11,12):
## QM(df = 11) = 8.3544, p-val = 0.6812
##
## Model Results:
##
##              estimate      se      zval      pval
## intrcpt              0.2818  0.0668   4.2206 <.0001
## as.factor(n_feature)2 -0.0897  0.0813  -1.1032  0.2699
## as.factor(n_feature)3 -0.2222  0.1107  -2.0076  0.0447
## as.factor(n_feature)41640 -0.2750  0.2681  -1.0256  0.3051
## as.factor(n_feature)41641 -0.2265  0.1409  -1.6074  0.1080
## as.factor(n_feature)41672 -0.2818  0.8856  -0.3182  0.7503
## age.C                0.0135  0.0149   0.9111  0.3622
## as.factor(n_feature)2:age.C  0.0021  0.0181   0.1153  0.9082
## as.factor(n_feature)3:age.C -0.0067  0.0226  -0.2964  0.7669
## as.factor(n_feature)41640:age.C -0.0180  0.0531  -0.3381  0.7353
## as.factor(n_feature)41641:age.C -0.0311  0.0460  -0.6748  0.4998
## as.factor(n_feature)41672:age.C -0.0135  1.6520  -0.0082  0.9935
##              ci.lb      ci.ub
## intrcpt          0.1509   0.4127 ***
```

```
## as.factor(n_feature)2          -0.2491  0.0697
## as.factor(n_feature)3          -0.4392 -0.0053    *
## as.factor(n_feature)41640      -0.8005  0.2505
## as.factor(n_feature)41641      -0.5026  0.0497
## as.factor(n_feature)41672      -2.0176  1.4540
## age.C                          -0.0156  0.0427
## as.factor(n_feature)2:age.C     -0.0334  0.0376
## as.factor(n_feature)3:age.C     -0.0511  0.0377
## as.factor(n_feature)41640:age.C -0.1221  0.0862
## as.factor(n_feature)41641:age.C -0.1213  0.0592
## as.factor(n_feature)41672:age.C -3.2514  3.2243
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Number of features with condition and age moderators

```
dat_f <- subset(dat, n_feature == "0" | n_feature == "1" | n_feature == "2" |
  n_feature == "3")

rma_NFeaturesAge <- rma.mv(g_calc, g_var_calc, mods = ~as.factor(n_feature) *
  age.C * condition, data = dat_f, random = ~collapse | short_cite)
```

```
summary(rma_NFeaturesAge)
```

```
##
## Multivariate Meta-Analysis Model (k = 211; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -232.6365   465.2730   489.2730   528.9127   490.9326
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 27)
## inner factor: collapse   (nlvls = 49)
##
##           estim      sqrt  fixed
## tau^2      0.1581  0.3976    no
## rho         0.7224          no
##
## Test for Residual Heterogeneity:
## QE(df = 201) = 956.3669, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8,9,10):
## QM(df = 9) = 190.4816, p-val < .0001
##
## Model Results:
##
##              estimate      se      zval      pval      ci.lb
## intrcpt              0.6099  0.1361    4.4828 <.0001    0.3433
## as.factor(n_feature)1 -0.3219  0.1132   -2.8421  0.0045   -0.5438
```

```
## as.factor(n_feature)2      -0.2920  0.1293  -2.2593  0.0239  -0.5453
## as.factor(n_feature)3      -0.5182  0.1497  -3.4617  0.0005  -0.8116
## age.C                      0.0842  0.0506   1.6637  0.0962  -0.0150
## condition                  0.1919  0.1063   1.8056  0.0710  -0.0164
## as.factor(n_feature)1:age.C -0.0691  0.0488  -1.4153  0.1570  -0.1648
## as.factor(n_feature)2:age.C -0.0486  0.0510  -0.9533  0.3404  -0.1485
## as.factor(n_feature)3:age.C -0.0535  0.0526  -1.0173  0.3090  -0.1566
## age.C:condition            -0.0648  0.0481  -1.3465  0.1782  -0.1591
##                             ci.ub
## intrcpt                    0.8766 ***
## as.factor(n_feature)1      -0.0999 **
## as.factor(n_feature)2      -0.0387 *
## as.factor(n_feature)3      -0.2248 ***
## age.C                      0.1835 .
## condition                  0.4003 .
## as.factor(n_feature)1:age.C 0.0266
## as.factor(n_feature)2:age.C 0.0513
## as.factor(n_feature)3:age.C 0.0496
## age.C:condition            0.0295
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```


Plot number of Features

```
dat_f <- subset(dat, n_feature == "0" | n_feature == "1" | n_feature == "2" |
  n_feature == "3")

dat_f$feat_cat <- ifelse(dat_f$n_feature == 1, "one", ifelse(dat_f$n_feature ==
  2, "two", ifelse(dat_f$n_feature == 3, "three", ifelse(dat_f$n_feature ==
  0, "correct", "none"))))

dat_f <- subset(dat_f, feat_cat != "none")

p <- ggplot(dat_f, aes(mean_age_1/30.44, g_calc, color = feat_cat)) + geom_point(aes(size = weights_g,
  shape = feat_cat), show.legend = FALSE) + # facet_grid(.~type_feature)+
  geom_line(y = 0, linetype = "dotted") + geom_smooth(method = "lm", formula = y ~
  log(x), aes(weight = weights_g)) + theme(text = element_text(size = 16)) +
  xlab("Age in months") + ylab("Effect size Hedges' g")
p
```



```
ggsave("figures/AgeEffect_log_feat.jpg", p)
```

Type of MP: Vowel, consonant, or tone

```
db_MP_type <- subset(db_ET_MP, type_feature == "consonant" | type_feature ==
  "vowel")

rma_TypeFeaturesMP <- rma.mv(g_calc, g_var_calc, mods = ~type_feature, data = db_MP_type,
  random = ~collapse | short_cite)

summary(rma_TypeFeaturesMP)

##
## Multivariate Meta-Analysis Model (k = 133; method: REML)
##
##   logLik  Deviance      AIC      BIC     AICc
## -64.0402  128.0804  136.0804  147.5812  136.3979
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 26)
## inner factor: collapse   (nlvls = 46)
##
```

```
##           estim      sqrt  fixed
## tau^2      0.1263  0.3553     no
## rho        0.5620                no
##
## Test for Residual Heterogeneity:
## QE(df = 131) = 427.6655, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.1467, p-val = 0.7017
##
## Model Results:
##
##           estimate      se    zval    pval    ci.lb    ci.ub
## intrcpt           0.2262  0.0729  3.1022  0.0019   0.0833  0.3691  **
## type_featurevowel   0.0338  0.0881  0.3830  0.7017  -0.1390  0.2065
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Type of MP: Vowel, consonant, or tone with age moderator

```
db_MP_type <- subset(db_ET_MP, type_feature == "consonant" | type_feature ==
  "vowel")

rma_TypeFeaturesMPAge <- rma.mv(g_calc, g_var_calc, mods = ~type_feature * age.C,
  data = db_MP_type, random = ~collapse | short_cite)

summary(rma_TypeFeaturesMPAge)
```

```
##
## Multivariate Meta-Analysis Model (k = 133; method: REML)
##
##    logLik Deviance      AIC      BIC      AICc
## -62.8963 125.7927 137.7927 154.9515 138.4812
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 26)
## inner factor: collapse   (nlvls = 46)
##
##           estim      sqrt  fixed
## tau^2      0.1274  0.3570     no
## rho        0.5445                no
##
## Test for Residual Heterogeneity:
## QE(df = 129) = 415.3869, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4):
## QM(df = 3) = 1.5441, p-val = 0.6721
##
## Model Results:
```

```
##
##               estimate      se    zval    pval    ci.lb    ci.ub
## intrcpt          0.2283  0.0731  3.1237  0.0018   0.0851  0.3716
## type_featurevowel  0.0439  0.0889  0.4945  0.6210  -0.1302  0.2181
## age.C            0.0143  0.0147  0.9676  0.3332  -0.0146  0.0431
## type_featurevowel:age.C  0.0008  0.0171  0.0484  0.9614  -0.0327  0.0344
##
## intrcpt          **
## type_featurevowel
## age.C
## type_featurevowel:age.C
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Type of MP: Vowel, consonant, or tone with condition moderator

```
dat_type <- subset(dat, type_feature == "consonant" | type_feature == "vowel" |
  type_feature == "tone")
dat_type$type_feature <- as.factor(ifelse(dat_type$condition == 1, "none", dat_type$type_feature))

rma_TypeFeatures <- rma.mv(g_calc, g_var_calc, mods = ~relevel(type_feature,
  "none") * condition, data = dat_type, random = ~collapse | short_cite)

summary(rma_TypeFeatures)
```

```
##
## Multivariate Meta-Analysis Model (k = 228; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -236.8091   473.6183   485.6183   506.0882   486.0054
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 28)
## inner factor: collapse   (nlvls = 46)
##
##           estim    sqrt  fixed
## tau^2      0.1238  0.3519    no
## rho        0.6901          no
##
## Test for Residual Heterogeneity:
## QE(df = 224) = 981.7485, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4):
## QM(df = 3) = 154.6077, p-val < .0001
##
## Model Results:
##
##               estimate      se    zval    pval
## intrcpt          0.7114  0.0688  10.3387  <.0001
```

```
## relevel(type_feature, "none")1 -0.4417 0.0423 -10.4486 <.0001
## relevel(type_feature, "none")4 -0.6356 0.1549 -4.1033 <.0001
## relevel(type_feature, "none")5 -0.4680 0.0565 -8.2812 <.0001
##               ci.lb      ci.ub
## intrcpt                0.5765  0.8462 ***
## relevel(type_feature, "none")1 -0.5245 -0.3588 ***
## relevel(type_feature, "none")4 -0.9391 -0.3320 ***
## relevel(type_feature, "none")5 -0.5788 -0.3572 ***
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Type of MP: Vowel, consonant, or tone with age and condition moderator

```
dat_type <- subset(dat, type_feature == "consonant" | type_feature == "vowel" |
  type_feature == "tone")
dat_type$type_feature <- as.factor(ifelse(dat_type$condition == 1, "none", dat_type$type_feature))

rma_TypeFeaturesAge <- rma.mv(g_calc, g_var_calc, mods = ~relevel(type_feature,
  "none") * age.C * condition, data = dat_type, random = ~collapse | short_cite)

summary(rma_TypeFeaturesAge)
```

```
##
## Multivariate Meta-Analysis Model (k = 228; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -234.9545   469.9090   489.9090   523.8452   490.9616
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 28)
## inner factor: collapse   (nlvls = 46)
##
##              estim      sqrt  fixed
## tau^2         0.1260  0.3549     no
## rho           0.6767                no
##
## Test for Residual Heterogeneity:
## QE(df = 220) = 967.8211, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8):
## QM(df = 7) = 158.2894, p-val < .0001
##
## Model Results:
##
##              estimate      se      zval      pval
## intrcpt              0.7276  0.0702   10.3680 <.0001
## relevel(type_feature, "none")1 -0.4489  0.0427  -10.5083 <.0001
## relevel(type_feature, "none")4 -0.6202  0.1703   -3.6419 0.0003
## relevel(type_feature, "none")5 -0.4874  0.0630   -7.7322 <.0001
```

```
## age.C                                0.0161  0.0124   1.2981  0.1942
## relevel(type_feature, "none")1:age.C  0.0076  0.0104   0.7309  0.4648
## relevel(type_feature, "none")4:age.C  0.0055  0.0311   0.1770  0.8595
## relevel(type_feature, "none")5:age.C -0.0082  0.0114  -0.7146  0.4748
##                                     ci.lb   ci.ub
## intrcpt                             0.5901  0.8652 ***
## relevel(type_feature, "none")1      -0.5327 -0.3652 ***
## relevel(type_feature, "none")4      -0.9540 -0.2864 ***
## relevel(type_feature, "none")5      -0.6110 -0.3639 ***
## age.C                               -0.0082  0.0405
## relevel(type_feature, "none")1:age.C -0.0128  0.0279
## relevel(type_feature, "none")4:age.C -0.0555  0.0665
## relevel(type_feature, "none")5:age.C -0.0306  0.0142
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Type of MP with language family moderator

```
# dat_type <- subset(dat, type_feature == 'consonant' | type_feature ==
# 'vowel' | type_feature == 'tone')

dat_type <- subset(dat, type_feature == "consonant" | type_feature == "vowel")

dat_type$type_feature <- as.factor(ifelse(dat_type$condition == 1, "none", dat_type$type_feature))

dat_type$lang_family = ifelse(dat_type$native_lang == "American English" | dat_type$native_lang ==
  "British English" | dat_type$native_lang == "Dutch" | dat_type$native_lang ==
  "Danish" | dat_type$native_lang == "Swedish" | dat_type$native_lang == "English" |
  dat_type$native_lang == "German", "Germanic", ifelse(dat_type$native_lang ==
  "French" | dat_type$native_lang == "Catalan" | dat_type$native_lang == "Spanish" |
  dat_type$native_lang == "Catalan-Spanish" | dat_type$native_lang == "Swiss French",
  "Romanic", "Sino-Tibetan"))

dat_type_sub <- subset(dat_type, lang_family != "Sino-Tibetan")

rma_TypeFeatures_Lang <- rma.mv(g_calc, g_var_calc, mods = ~relevel(type_feature,
  "none") * lang_family, data = dat_type_sub, random = ~collapse | short_cite)

summary(rma_TypeFeatures_Lang)

##
## Multivariate Meta-Analysis Model (k = 212; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -226.0585   452.1170   468.1170   494.7400   468.8480
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 25)
## inner factor: collapse   (nlvls = 44)
##
```



```
##          estim      sqrt  fixed
## tau^2      0.1293  0.3596     no
## rho        0.5788              no
##
## Test for Residual Heterogeneity:
## QE(df = 206) = 893.9789, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6):
## QM(df = 5) = 158.2471, p-val < .0001
##
## Model Results:
##
##                                     estimate      se
## intrcpt                           0.6597  0.0777
## relevel(type_feature, "none")1     -0.4135  0.0441
## relevel(type_feature, "none")5     -0.4830  0.0640
## lang_familyRomanic                  0.4502  0.1801
## relevel(type_feature, "none")1:lang_familyRomanic -0.6549  0.2157
## relevel(type_feature, "none")5:lang_familyRomanic  0.0924  0.1490
##                                     zval      pval
## intrcpt                           8.4880 <.0001
## relevel(type_feature, "none")1     -9.3845 <.0001
## relevel(type_feature, "none")5     -7.5453 <.0001
## lang_familyRomanic                  2.4991  0.0124
## relevel(type_feature, "none")1:lang_familyRomanic -3.0359  0.0024
## relevel(type_feature, "none")5:lang_familyRomanic  0.6202  0.5351
##                                     ci.lb      ci.ub
## intrcpt                           0.5073  0.8120 ***
## relevel(type_feature, "none")1     -0.4998 -0.3271 ***
## relevel(type_feature, "none")5     -0.6084 -0.3575 ***
## lang_familyRomanic                  0.0971  0.8032  *
## relevel(type_feature, "none")1:lang_familyRomanic -1.0777 -0.2321 **
## relevel(type_feature, "none")5:lang_familyRomanic -0.1996  0.3843
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Type of MP with language family and condition moderators

```
dat_type <- subset(dat, type_feature == "consonant" | type_feature == "vowel") # /
# type_feature == 'tone')
dat_type$type_feature <- as.factor(ifelse(dat_type$condition == 1, "none", dat_type$type_feature))

dat_type$lang_family = ifelse(dat_type$native_lang == "American English" | dat_type$native_lang ==
  "British English" | dat_type$native_lang == "Dutch" | dat_type$native_lang ==
  "Danish" | dat_type$native_lang == "Swedish" | dat_type$native_lang == "English" |
  dat_type$native_lang == "German", "Germanic", ifelse(dat_type$native_lang ==
  "French" | dat_type$native_lang == "Catalan" | dat_type$native_lang == "Spanish" |
  dat_type$native_lang == "Catalan-Spanish" | dat_type$native_lang == "Swiss French",
  "Romanic", "Sino-Tibetian"))

dat_type_sub <- subset(dat_type, lang_family != "Sino-Tibetian")
dat_type_sub$lang_family <- as.factor(dat_type_sub$lang_family)
```

```
rma_TypeFeatures_Lang <- rma.mv(g_calc, g_var_calc, mods = ~relevel(type_feature,
  "none") * lang_family * condition, data = dat_type_sub, random = ~collapse |
  short_cite)
```

```
summary(rma_TypeFeatures_Lang)
```


```
##
## Multivariate Meta-Analysis Model (k = 212; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -226.0585   452.1170   468.1170   494.7400   468.8480
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 25)
## inner factor: collapse   (nlvls = 44)
##
##           estim      sqrt  fixed
## tau^2      0.1293  0.3596     no
## rho        0.5788                no
##
## Test for Residual Heterogeneity:
## QE(df = 206) = 893.9789, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6):
## QM(df = 5) = 158.2471, p-val < .0001
##
## Model Results:
##
##                                     estimate      se
## intrcpt                           0.6597  0.0777
## relevel(type_feature, "none")1     -0.4135  0.0441
## relevel(type_feature, "none")5     -0.4830  0.0640
## lang_familyRomanic                  0.4502  0.1801
## relevel(type_feature, "none")1:lang_familyRomanic -0.6549  0.2157
## relevel(type_feature, "none")5:lang_familyRomanic  0.0924  0.1490
##                                     zval      pval
## intrcpt                           8.4880 <.0001
## relevel(type_feature, "none")1     -9.3845 <.0001
## relevel(type_feature, "none")5     -7.5453 <.0001
## lang_familyRomanic                  2.4991  0.0124
## relevel(type_feature, "none")1:lang_familyRomanic -3.0359  0.0024
## relevel(type_feature, "none")5:lang_familyRomanic  0.6202  0.5351
##                                     ci.lb      ci.ub
## intrcpt                           0.5073  0.8120 ***
## relevel(type_feature, "none")1     -0.4998 -0.3271 ***
## relevel(type_feature, "none")5     -0.6084 -0.3575 ***
## lang_familyRomanic                  0.0971  0.8032  *
## relevel(type_feature, "none")1:lang_familyRomanic -1.0777 -0.2321 **
## relevel(type_feature, "none")5:lang_familyRomanic -0.1996  0.3843
```

```
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Plot MP type: Consonant, Vowel, or Tone?

```
p <- ggplot(dat, aes(mean_age_1/30.44, g_calc, color = condition_label)) + geom_point(aes(size = weight,
  shape = type_feature), show.legend = FALSE) + facet_grid(. ~ type_feature) +
  geom_line(y = 0, linetype = "dotted") + geom_smooth(method = "lm", formula = y ~
  log(x), aes(weight = weights_g)) + theme(text = element_text(size = 16)) +
  xlab("Age in months") + ylab("Effect size Hedges' g")
```

p




```
ggsave("figures/AgeEffect_log_CV.jpg", p)
```

Plot Language Family by MP type: Consonant, Vowel, or Tone?

```
p <- ggplot(dat_type_sub, aes(type_feature, g_calc, color = type_feature)) +
  geom_boxplot() + facet_grid(lang_family ~ condition_label) + # geom_line(y= 0, linetype='dotted') +
  # y ~ log(x), aes(weight=weights_g)) +
  theme(text = element_text(size = 16)) + xlab("Language Family") + ylab("Effect size Hedges' g")
```

p



```
ggsave("figures/LangFamily_CV.jpg", p)
```

Distractor Familiarity (familiar, unfamiliar)

```
rma_Distractor <- rma.mv(g_calc, g_var_calc, mods = ~as.factor(object_pair),
  data = dat, random = ~collapse | short_cite)
```

```
summary(rma_Distractor)
```

```
##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -358.9670   717.9341   725.9341   740.0039   726.0980
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1428  0.3778    no
## rho        0.7418                no
##
## Test for Residual Heterogeneity:
## QE(df = 249) = 1349.9968, p-val < .0001
```

```
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 1.1294, p-val = 0.2879
##
## Model Results:
##
##               estimate      se      zval      pval
## intrcpt          0.5036  0.0746   6.7468  <.0001
## as.factor(object_pair)familiar_novel -0.1357  0.1277  -1.0627  0.2879
##               ci.lb      ci.ub
## intrcpt          0.3573  0.6499   ***
## as.factor(object_pair)familiar_novel -0.3860  0.1146
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Distractor Familiarity with condition moderator

```
rma_Distractor <- rma.mv(g_calc, g_var_calc, mods = ~condition * as.factor(object_pair),
  data = dat, random = ~collapse | short_cite)
```

```
summary(rma_Distractor)
```

```
##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -250.6056   501.2111   513.2111   534.2675   513.5611
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1410  0.3754    no
## rho        0.7375          no
##
## Test for Residual Heterogeneity:
## QE(df = 247) = 1085.1211, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4):
## QM(df = 3) = 219.4592, p-val < .0001
##
## Model Results:
##
##               estimate      se      zval
## intrcpt          0.3230  0.0757   4.2641
## condition          0.4629  0.0384  12.0679
## as.factor(object_pair)familiar_novel -0.1523  0.1300  -1.1711
## condition:as.factor(object_pair)familiar_novel 0.1411  0.0806   1.7510
##               pval      ci.lb      ci.ub
## intrcpt          <.0001   0.1745  0.4714
```

```
## condition <.0001 0.3877 0.5381
## as.factor(object_pair)familiar_novel 0.2416 -0.4072 0.1026
## condition:as.factor(object_pair)familiar_novel 0.0799 -0.0168 0.2991
##
## intrcpt ***
## condition ***
## as.factor(object_pair)familiar_novel
## condition:as.factor(object_pair)familiar_novel .
##
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Distractor Familiarity with age moderator

```
rma_DistractorAge <- rma.mv(g_calc, g_var_calc, mods = ~age.C * as.factor(object_pair),
  data = dat, random = ~collapse | short_cite)
```

```
summary(rma_DistractorAge)
```

```
##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -355.6498   711.2996   723.2996   744.3559   723.6496
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##      estim      sqrt  fixed
## tau^2    0.1395  0.3735    no
## rho      0.7265          no
##
## Test for Residual Heterogeneity:
## QE(df = 247) = 1326.8487, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4):
## QM(df = 3) = 4.9682, p-val = 0.1741
##
## Model Results:
##
##      estimate      se      zval
## intrcpt      0.5503  0.0778   7.0694
## age.C        0.0236  0.0134   1.7615
## as.factor(object_pair)familiar_novel -0.2292  0.1459  -1.5711
## age.C:as.factor(object_pair)familiar_novel -0.0007  0.0285  -0.0230
##      pval      ci.lb      ci.ub
## intrcpt <.0001  0.3977  0.7029 ***
## age.C    0.0782 -0.0027  0.0499 .
## as.factor(object_pair)familiar_novel 0.1162 -0.5150  0.0567
## age.C:as.factor(object_pair)familiar_novel 0.9817 -0.0565  0.0551
##
```

```
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Distractor Familiarity with age and condition moderators

```
rma_DistractorAge <- rma.mv(g_calc, g_var_calc, mods = ~age.C * condition *
  as.factor(object_pair), data = dat, random = ~collapse | short_cite)

summary(rma_DistractorAge)
```

```
##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -247.3148   494.6296   514.6296   549.5602   515.5778
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1357  0.3684     no
## rho         0.7175           no
##
## Test for Residual Heterogeneity:
## QE(df = 243) = 1064.6022, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8):
## QM(df = 7) = 224.9573, p-val < .0001
##
## Model Results:
##
##                                     estimate      se
## intrcpt                           0.3698  0.0785
## age.C                             0.0242  0.0138
## condition                         0.4666  0.0415
## as.factor(object_pair)familiar_novel -0.2541  0.1471
## age.C:condition                    0.0020  0.0092
## age.C:as.factor(object_pair)familiar_novel 0.0038  0.0288
## condition:as.factor(object_pair)familiar_novel 0.1755  0.0894
## age.C:condition:as.factor(object_pair)familiar_novel -0.0203  0.0198
##                                     zval      pval
## intrcpt                           4.7107 <.0001
## age.C                             1.7481  0.0804
## condition                         11.2325 <.0001
## as.factor(object_pair)familiar_novel -1.7273  0.0841
## age.C:condition                    0.2153  0.8295
## age.C:as.factor(object_pair)familiar_novel 0.1312  0.8956
## condition:as.factor(object_pair)familiar_novel 1.9637  0.0496
## age.C:condition:as.factor(object_pair)familiar_novel -1.0267  0.3046
##                                     ci.lb    ci.ub
## intrcpt                           0.2160  0.5237 ***
```

```
## age.C -0.0029 0.0512 .
## condition 0.3852 0.5480 ***
## as.factor(object_pair)familiar_novel -0.5425 0.0342 .
## age.C:condition -0.0161 0.0201
## age.C:as.factor(object_pair)familiar_novel -0.0526 0.0602
## condition:as.factor(object_pair)familiar_novel 0.0003 0.3507 *
## age.C:condition:as.factor(object_pair)familiar_novel -0.0590 0.0184
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Distractor Familiarity with age moderator, subset to same age range

```
min_age <- min(dat[dat$object_pair == "familiar_novel", ]$mean_age_1)
max_age <- max(dat[dat$object_pair == "familiar_novel", ]$mean_age_1)

dat_age = dat %>% filter(mean_age_1 > min_age & mean_age_1 < max_age)

rma_DistractorAgeS <- rma.mv(g_calc, g_var_calc, mods = ~age.C * condition *
  as.factor(object_pair), data = dat_age, random = ~collapse | short_cite)

summary(rma_DistractorAgeS)
```

```
##
## Multivariate Meta-Analysis Model (k = 185; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -181.6354   363.2707   383.2707   415.0322   384.5960
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 24)
## inner factor: collapse   (nlvls = 38)
##
##           estim      sqrt  fixed
## tau^2      0.1852  0.4303     no
## rho        0.7698              no
##
## Test for Residual Heterogeneity:
## QE(df = 177) = 824.6499, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8):
## QM(df = 7) = 157.4337, p-val < .0001
##
## Model Results:
##
##                                     estimate      se
## intrcpt                          0.4127  0.1035
## age.C                           -0.0119  0.0261
## condition                        0.4086  0.0465
## as.factor(object_pair)familiar_novel -0.3230  0.2025
## age.C:condition                   0.0447  0.0188
## age.C:as.factor(object_pair)familiar_novel 0.0502  0.0538
```




```
## condition:as.factor(object_pair)familiar_novel      0.1987  0.1100
## age.C:condition:as.factor(object_pair)familiar_novel -0.0203  0.0342
##                                     zval      pval
## intrcpt                                     3.9865  <.0001
## age.C                                     -0.4578  0.6471
## condition                                    8.7811  <.0001
## as.factor(object_pair)familiar_novel          -1.5949  0.1107
## age.C:condition                             2.3724  0.0177
## age.C:as.factor(object_pair)familiar_novel      0.9326  0.3510
## condition:as.factor(object_pair)familiar_novel   1.8068  0.0708
## age.C:condition:as.factor(object_pair)familiar_novel -0.5931  0.5531
##                                     ci.lb      ci.ub
## intrcpt                                     0.2098  0.6156  ***
## age.C                                     -0.0631  0.0392
## condition                                    0.3174  0.4998  ***
## as.factor(object_pair)familiar_novel          -0.7198  0.0739
## age.C:condition                             0.0078  0.0816   *
## age.C:as.factor(object_pair)familiar_novel      -0.0553  0.1557
## condition:as.factor(object_pair)familiar_novel   -0.0168  0.4142   .
## age.C:condition:as.factor(object_pair)familiar_novel -0.0873  0.0468
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Plot Distractor Familiarity

```
dat$condition_label = ifelse(dat$condition == 1, "correct", "MP")
dat$dist_code <- ifelse(dat$object_pair == "familiar_familiar", "familiar",
  "unfamiliar")

p <- ggplot(dat, aes(mean_age_1/30.44, g_calc, color = condition_label)) + geom_point(aes(size = weight,
  shape = dist_code), show.legend = FALSE) + facet_grid(. ~ dist_code) + geom_line(y = 0,
  linetype = "dotted") + geom_smooth(method = "lm", formula = y ~ log(x),
  aes(weight = weights_g)) + scale_color_manual(values = wes_palette(name = "Darjeeling")) +
  theme_bw() + theme(text = element_text(size = 25), legend.title = element_blank(),
  legend.position = "bottom") + xlab("Age in months") + ylab("Effect size Hedges' g")
p
```




```
ggsave("figures/AgeEffect_log_distractor_fam.jpg", p)
```

Plot Distractor Familiarity (w/o age)

```
dat$condition_label = ifelse(dat$condition == 1, "correct", "MP")
dat$dist_code <- ifelse(dat$object_pair == "familiar_familiar", "familiar",
  "unfamiliar")

p <- ggplot(dat, aes(dist_code, g_calc, color = condition_label)) + geom_boxplot() +
  # geom_smooth(method = 'lm', formula = y ~ log(x), aes(weight=weights_g)) +
  scale_color_manual(values = wes_palette(name = "Darjeeling")) + theme_bw() +
  theme(text = element_text(size = 25), legend.title = element_blank(), legend.position = "bottom") +
  xlab("Distractor Familiarity") + geom_hline(yintercept = 0, linetype = "dotted") +
  ylab("Effect size Hedges' g")
p
```



correct MP

```
ggsave("figures/Distractor_fam_log.jpg", p)
```

Plot Distractor Familiarity (w/o age, subset to age range)


```
min_age <- min(dat[dat$object_pair == "familiar_novel", ]$mean_age_1)
max_age <- max(dat[dat$object_pair == "familiar_novel", ]$mean_age_1)

dat_age = dat %>% filter(mean_age_1 > min_age & mean_age_1 < max_age)

dat_age$condition_label = ifelse(dat_age$condition == 1, "correct", "MP")
dat_age$dist_code <- ifelse(dat_age$object_pair == "familiar_familiar", "familiar",
                             "unfamiliar")

p <- ggplot(dat_age, aes(dist_code, g_calc, color = condition_label)) + geom_boxplot() +
  # geom_line(y= 0, linetype='dotted') + geom_smooth(method = 'lm', formula =
  # y ~ log(x), aes(weight=weights_g)) +
  scale_color_manual(values = wes_palette(name = "Darjeeling")) + theme_bw() +
  theme(text = element_text(size = 25), legend.title = element_blank(), legend.position = "bottom") +
  xlab("Distractor Familiarity") + ylab("Effect size Hedges' g")

p
```



correct MP

```
ggsave("figures/AgeMatch_Distractor_fam_log.jpg", p)
```

Position of Mispronunciation (onset, medial)

```
# table(db_ET_MP$mispron_location)

db_ET_MP1 = db_ET_MP %>% filter(mispron_location == "onset" | mispron_location ==
  "medial")

# rma_NFeatures <- rma.mv(g_calc, g_var_calc, mods = ~as.ordered(n_feature),
# data = db_ET_MP, random = ~collapse | short_cite)
rma_Location <- rma.mv(g_calc, g_var_calc, mods = ~mispron_location, data = db_ET_MP1,
  random = ~collapse | short_cite)

summary(rma_Location)
```

```
##
## Multivariate Meta-Analysis Model (k = 114; method: REML)
##
##   logLik  Deviance      AIC      BIC     AICc
## -57.5043  115.0085  123.0085  133.8825  123.3823
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 24)
```

```
## inner factor: collapse (nlvls = 41)
##
##          estim      sqrt  fixed
## tau^2      0.1502  0.3876    no
## rho        0.5421          no
##
## Test for Residual Heterogeneity:
## QE(df = 112) = 392.6421, p-val < .0001
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.0419, p-val = 0.8378
##
## Model Results:
##
##              estimate      se    zval    pval    ci.lb    ci.ub
## intrcpt              0.2306  0.0852  2.7063  0.0068   0.0636  0.3977
## mispron_locationmedial  0.0307  0.1498  0.2048  0.8378  -0.2629  0.3243
##
## intrcpt              **
## mispron_locationmedial
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Position of Mispronunciation with age moderator

```
# table(db_ET_MP$mispron_location)

db_ET_MP1 = db_ET_MP %>% filter(mispron_location == "onset" | mispron_location ==
  "medial")

rma_LocationAge <- rma.mv(g_calc, g_var_calc, mods = ~mispron_location * age.C,
  data = db_ET_MP1, random = ~collapse | short_cite)

summary(rma_LocationAge)
```

```
##
## Multivariate Meta-Analysis Model (k = 114; method: REML)
##
##    logLik Deviance      AIC      BIC      AICc
## -56.0484 112.0967 124.0967 140.2996 124.9122
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 24)
## inner factor: collapse (nlvls = 41)
##
##          estim      sqrt  fixed
## tau^2      0.1563  0.3953    no
## rho        0.5238          no
##
```

```
## Test for Residual Heterogeneity:
## QE(df = 110) = 386.0990, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4):
## QM(df = 3) = 1.2243, p-val = 0.7472
##
## Model Results:
##
##               estimate      se    zval    pval    ci.lb
## intrcpt          0.2296  0.0872  2.6339  0.0084   0.0588
## mispron_locationmedial  0.0832  0.1684  0.4937  0.6215  -0.2470
## age.C            0.0117  0.0179  0.6531  0.5137  -0.0234
## mispron_locationmedial:age.C  0.0179  0.0337  0.5305  0.5958  -0.0482
##               ci.ub
## intrcpt          0.4005  **
## mispron_locationmedial  0.4133
## age.C            0.0469
## mispron_locationmedial:age.C  0.0840
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Position of Mispronunciation with condition moderator

```
# table(db_ET_MP$mispron_location)

db_ET_MP1 = db_ET_MP %>% filter(mispron_location == "onset" | mispron_location ==
  "medial")

rma_LocationCondition <- rma.mv(g_calc, g_var_calc, mods = ~mispron_location *
  condition, data = db_ET_MP1, random = ~collapse | short_cite)

summary(rma_LocationCondition)

##
## Multivariate Meta-Analysis Model (k = 114; method: REML)
##
##   logLik Deviance      AIC      BIC      AICc
## -57.5043  115.0085  123.0085  133.8825  123.3823
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 24)
## inner factor: collapse   (nlvls = 41)
##
##           estim    sqrt  fixed
## tau^2      0.1502  0.3876    no
## rho        0.5421          no
##
## Test for Residual Heterogeneity:
## QE(df = 112) = 392.6421, p-val < .0001
```

```
##
## Test of Moderators (coefficient(s) 2):
## QM(df = 1) = 0.0419, p-val = 0.8378
##
## Model Results:
##
##               estimate      se    zval    pval    ci.lb    ci.ub
## intrcpt           0.2306  0.0852  2.7063  0.0068   0.0636  0.3977
## mispron_locationmedial  0.0307  0.1498  0.2048  0.8378  -0.2629  0.3243
##
## intrcpt           **
## mispron_locationmedial
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Position of Mispronunciation with age and condition moderators

```
# table(db_ET_MP$mispron_location)

db_ET_MP1 = db_ET_MP %>% filter(mispron_location == "onset" | mispron_location ==
  "medial")

rma_LocationCondition <- rma.mv(g_calc, g_var_calc, mods = ~mispron_location *
  condition * age.C, data = db_ET_MP1, random = ~collapse | short_cite)

summary(rma_LocationCondition)

##
## Multivariate Meta-Analysis Model (k = 114; method: REML)
##
##    logLik Deviance      AIC      BIC      AICc
## -56.0484 112.0967 124.0967 140.2996 124.9122
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 24)
## inner factor: collapse   (nlvls = 41)
##
##           estim    sqrt  fixed
## tau^2      0.1563  0.3953    no
## rho         0.5238          no
##
## Test for Residual Heterogeneity:
## QE(df = 110) = 386.0990, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4):
## QM(df = 3) = 1.2243, p-val = 0.7472
##
## Model Results:
##
```


```
##               estimate      se    zval    pval    ci.lb
## intrcpt          0.2296  0.0872  2.6339  0.0084   0.0588
## mispron_locationmedial  0.0832  0.1684  0.4937  0.6215  -0.2470
## age.C            0.0117  0.0179  0.6531  0.5137  -0.0234
## mispron_locationmedial:age.C  0.0179  0.0337  0.5305  0.5958  -0.0482
##               ci.ub
## intrcpt          0.4005  **
## mispron_locationmedial  0.4133
## age.C            0.0469
## mispron_locationmedial:age.C  0.0840
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Plot Position of Mispronunciation

```
# dat.p <- subset(dat, mispron_location == 'onset' | mispron_location ==
# 'medial' | mispron_location == 'offset')

dat.p <- subset(dat, mispron_location == "onset" | mispron_location == "medial")

p <- ggplot(dat.p, aes(mean_age_1/30.44, g_calc, color = condition_label)) +
  geom_point(aes(size = weights_g, shape = mispron_location), show.legend = FALSE) +
  facet_grid(. ~ mispron_location) + geom_line(y = 0, linetype = "dotted") +
  geom_smooth(method = "lm", formula = y ~ log(x), aes(weight = weights_g)) +
  theme(text = element_text(size = 16)) + xlab("Age in months") + ylab("Effect size Hedges' g")
p
```

```
ggsave("figures/AgeEffect_log_position.jpg", p)
```

Distractor Overlap

```
rma_DistractorOverlap <- rma.mv(g_calc, g_var_calc, mods = ~distractor_overlap,
  data = db_ET_MP, random = ~collapse | short_cite)
```

```
summary(rma_DistractorOverlap)
```

```
##
## Multivariate Meta-Analysis Model (k = 147; method: REML)
##
##   logLik  Deviance      AIC      BIC     AICc
## -67.3747  134.7494  148.7494  169.4402  149.5852
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim  sqrt  fixed
## tau^2      0.1271 0.3565    no
## rho        0.6003          no
##
## Test for Residual Heterogeneity:
## QE(df = 142) = 459.3146, p-val < .0001
```

```
##
## Test of Moderators (coefficient(s) 2,3,4,5):
## QM(df = 4) = 1.9399, p-val = 0.7468
##
## Model Results:
##
##               estimate      se    zval    pval    ci.lb
## intrcpt           0.0868  0.3928  0.2209  0.8252 -0.6831
## distractor_overlapno 0.2610  0.4051  0.6444  0.5193 -0.5329
## distractor_overlapnovel 0.0609  0.4102  0.1485  0.8819 -0.7430
## distractor_overlapnonset 0.1245  0.3950  0.3151  0.7527 -0.6498
## distractor_overlapnonset/medial 0.2192  0.5461  0.4013  0.6882 -0.8513
##               ci.ub
## intrcpt           0.8566
## distractor_overlapno 1.0549
## distractor_overlapnovel 0.8648
## distractor_overlapnonset 0.8987
## distractor_overlapnonset/medial 1.2896
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Distractor Overlap with age moderator

```
rma_DistractorOverlap <- rma.mv(g_calc, g_var_calc, mods = ~age.C * distractor_overlap,
  data = db_ET_MP, random = ~collapse | short_cite)

summary(rma_DistractorOverlap)
```

```
##
## Multivariate Meta-Analysis Model (k = 147; method: REML)
##
##    logLik Deviance      AIC      BIC      AICc
## -63.8569 127.7138 147.7138 177.0586 149.4326
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse    (nlvls = 52)
##
##           estim    sqrt  fixed
## tau^2      0.1272  0.3567    no
## rho         0.5803          no
##
## Test for Residual Heterogeneity:
## QE(df = 139) = 426.8044, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8):
## QM(df = 7) = 6.1553, p-val = 0.5217
##
## Model Results:
##
##               estimate      se    zval    pval    ci.lb
```

```
## intrcpt                0.0983  0.3957  0.2483  0.8039 -0.6772
## age.C                  0.0174  0.0214  0.8130  0.4162 -0.0246
## distractor_overlapno   0.3432  0.4126  0.8319  0.4055 -0.4654
## distractor_overlapnovel -0.0319  0.4197 -0.0759  0.9395 -0.8544
## distractor_overlapset   0.1267  0.3979  0.3184  0.7502 -0.6532
## distractor_overlapset/medial 0.1484  0.5553  0.2672  0.7893 -0.9399
## age.C:distractor_overlapno 0.0132  0.0297  0.4431  0.6577 -0.0451
## age.C:distractor_overlapnovel 0.0142  0.0342  0.4142  0.6787 -0.0529
##                          ci.lb
## intrcpt                0.8737
## age.C                  0.0594
## distractor_overlapno   1.1518
## distractor_overlapnovel 0.7907
## distractor_overlapset   0.9066
## distractor_overlapset/medial 1.2367
## age.C:distractor_overlapno 0.0714
## age.C:distractor_overlapnovel 0.0812
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Distractor Overlap with condition moderator

```
rma_DistractorOverlap <- rma.mv(g_calc, g_var_calc, mods = ~condition * distractor_overlap,
  data = db_ET_MP, random = ~collapse | short_cite)
```

```
summary(rma_DistractorOverlap)
```

```
##
## Multivariate Meta-Analysis Model (k = 147; method: REML)
##
##      logLik  Deviance      AIC      BIC      AICc
## -67.3747  134.7494  148.7494  169.4402  149.5852
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1271  0.3565     no
## rho        0.6003                no
##
## Test for Residual Heterogeneity:
## QE(df = 142) = 459.3146, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5):
## QM(df = 4) = 1.9399, p-val = 0.7468
##
## Model Results:
##
##              estimate      se    zval    pval    ci.lb
## intrcpt          0.0868  0.3928  0.2209  0.8252 -0.6831
```

```
## distractor_overlapno      0.2610  0.4051  0.6444  0.5193 -0.5329
## distractor_overlapnovel   0.0609  0.4102  0.1485  0.8819 -0.7430
## distractor_overlapset     0.1245  0.3950  0.3151  0.7527 -0.6498
## distractor_overlapset/medial 0.2192  0.5461  0.4013  0.6882 -0.8513
##                               ci.ub
## intrcpt                   0.8566
## distractor_overlapno      1.0549
## distractor_overlapnovel   0.8648
## distractor_overlapset     0.8987
## distractor_overlapset/medial 1.2896
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Distractor Overlap with age and condition moderators

```
rma_DistractorOverlap <- rma.mv(g_calc, g_var_calc, mods = ~age.C * condition *
  distractor_overlap, data = db_ET_MP, random = ~collapse | short_cite)
```

```
summary(rma_DistractorOverlap)
```

```
##
## Multivariate Meta-Analysis Model (k = 147; method: REML)
##
##   logLik  Deviance      AIC      BIC      AICc
## -63.8569 127.7138 147.7138 177.0586 149.4326
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1272  0.3567    no
## rho        0.5803          no
##
## Test for Residual Heterogeneity:
## QE(df = 139) = 426.8044, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8):
## QM(df = 7) = 6.1553, p-val = 0.5217
##
## Model Results:
##
##              estimate      se      zval      pval      ci.lb
## intrcpt          0.0983  0.3957   0.2483  0.8039  -0.6772
## age.C            0.0174  0.0214   0.8130  0.4162  -0.0246
## distractor_overlapno 0.3432  0.4126   0.8319  0.4055  -0.4654
## distractor_overlapnovel -0.0319  0.4197  -0.0759  0.9395  -0.8544
## distractor_overlapset 0.1267  0.3979   0.3184  0.7502  -0.6532
## distractor_overlapset/medial 0.1484  0.5553   0.2672  0.7893  -0.9399
## age.C:distractor_overlapno 0.0132  0.0297   0.4431  0.6577  -0.0451
## age.C:distractor_overlapnovel 0.0142  0.0342   0.4142  0.6787  -0.0529
```

```
##                                     ci.ub
## intrcpt                           0.8737
## age.C                             0.0594
## distractor_overlapno              1.1518
## distractor_overlapnovel           0.7907
## distractor_overlap onset          0.9066
## distractor_overlap onset/medial  1.2367
## age.C:distractor_overlapno        0.0714
## age.C:distractor_overlapnovel     0.0812
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Plot Distractor Overlap

```
p <- ggplot(dat, aes(mean_age_1/30.44, g_calc, color = condition_label)) + geom_point(aes(size = weight,
  shape = distractor_overlap), show.legend = FALSE) + facet_grid(. ~ distractor_overlap) +
  geom_line(y = 0, linetype = "dotted") + geom_smooth(method = "lm", formula = y ~
  log(x), aes(weight = weights_g)) + theme(text = element_text(size = 16)) +
  xlab("Age in months") + ylab("Effect size Hedges' g")
p
```



```
ggsave("figures/AgeEffect_log_distractor_overlap.jpg", p)
```

Language effect

```
dat$condition_label = ifelse(dat$condition == 1, "Correct", "Misp")

dat$lang_family = ifelse(dat$native_lang == "American English" | dat$native_lang ==
  "British English" | dat$native_lang == "Dutch" | dat$native_lang == "English" |
  dat$native_lang == "Danish" | dat$native_lang == "Swedish" | dat$native_lang ==
  "German", "Germanic", ifelse(dat$native_lang == "French" | dat$native_lang ==
  "Catalan" | dat$native_lang == "Spanish" | dat$native_lang == "Catalan-Spanish" |
  dat$native_lang == "Swiss French", "Romanic", "Sino-Tibetan"))

rma_lang_interaction <- rma.mv(g_calc, g_var_calc, mods = ~lang_family, data = dat,
  random = ~collapse | short_cite)
summary(rma_lang_interaction)
```

```
##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -356.7240   713.4480   723.4480   741.0151   723.6959
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1291  0.3593     no
## rho        0.6903                no
##
## Test for Residual Heterogeneity:
## QE(df = 248) = 1273.5943, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3):
## QM(df = 2) = 4.6882, p-val = 0.0959
##
## Model Results:
##
##              estimate      se      zval      pval      ci.lb
## intrcpt              0.4313  0.0680   6.3464 <.0001    0.2981
## lang_familyRomanic     0.3308  0.1670   1.9805  0.0476    0.0034
## lang_familySino-Tibetan -0.1382  0.2034  -0.6793  0.4970   -0.5369
##              ci.ub
## intrcpt              0.5645 ***
## lang_familyRomanic     0.6582  *
## lang_familySino-Tibetan 0.2605
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Language effect with age moderator

```
dat$condition_label = ifelse(dat$condition == 1, "Correct", "Misp")

dat$lang_family = ifelse(dat$native_lang == "American English" | dat$native_lang ==
  "British English" | dat$native_lang == "Dutch" | dat$native_lang == "English" |
  dat$native_lang == "Danish" | dat$native_lang == "Swedish" | dat$native_lang ==
  "German", "Germanic", ifelse(dat$native_lang == "French" | dat$native_lang ==
  "Catalan" | dat$native_lang == "Spanish" | dat$native_lang == "Catalan-Spanish" |
  dat$native_lang == "Swiss French", "Romanic", "Sino-Tibetian"))

rma_lang_interaction <- rma.mv(g_calc, g_var_calc, mods = ~age.C * lang_family,
  data = dat, random = ~collapse | short_cite)
summary(rma_lang_interaction)
```

```
##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -352.2890    704.5780    720.5780    748.5880    721.1881
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1382  0.3717    no
## rho         0.7726              no
##
## Test for Residual Heterogeneity:
## QE(df = 245) = 1249.7278, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6):
## QM(df = 5) = 9.3777, p-val = 0.0949
##
## Model Results:
##
##              estimate      se      zval      pval      ci.lb
## intrcpt          0.4475  0.0717   6.2378 <.0001    0.3069
## age.C             0.0105  0.0119   0.8803  0.3787  -0.0129
## lang_familyRomanic 0.3390  0.1725   1.9652  0.0494   0.0009
## lang_familySino-Tibetian -0.1789  0.2463  -0.7264  0.4676  -0.6615
## age.C:lang_familyRomanic 0.0562  0.0328   1.7147  0.0864  -0.0080
## age.C:lang_familySino-Tibetian -0.0153  0.0444  -0.3453  0.7299  -0.1024
##              ci.ub
## intrcpt          0.5882 ***
## age.C             0.0338
## lang_familyRomanic 0.6770  *
## lang_familySino-Tibetian 0.3038
## age.C:lang_familyRomanic 0.1205  .
## age.C:lang_familySino-Tibetian 0.0717
##
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Language effect with condition moderator

```
dat$condition_label = ifelse(dat$condition == 1, "Correct", "Misp")

dat$lang_family = ifelse(dat$native_lang == "American English" | dat$native_lang ==
  "British English" | dat$native_lang == "Dutch" | dat$native_lang == "English" |
  dat$native_lang == "Danish" | dat$native_lang == "Swedish" | dat$native_lang ==
  "German", "Germanic", ifelse(dat$native_lang == "French" | dat$native_lang ==
  "Catalan" | dat$native_lang == "Spanish" | dat$native_lang == "Catalan-Spanish" |
  dat$native_lang == "Swiss French", "Romanic", "Sino-Tibetian"))

rma_lang_interaction <- rma.mv(g_calc, g_var_calc, mods = ~condition * lang_family,
  data = dat, random = ~collapse | short_cite)
summary(rma_lang_interaction)
```

```
##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -249.3297   498.6593   514.6593   542.6694   515.2695
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1287  0.3588     no
## rho         0.6904              no
##
## Test for Residual Heterogeneity:
## QE(df = 245) = 1027.2297, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6):
## QM(df = 5) = 221.2361, p-val < .0001
##
## Model Results:
##
##              estimate      se      zval      pval
## intrcpt          0.2675  0.0691   3.8723  0.0001
## condition          0.4775  0.0360  13.2740 <.0001
## lang_familyRomanic  0.2014  0.1782   1.1303  0.2584
## lang_familySino-Tibetian -0.2804  0.2176  -1.2883  0.1976
## condition:lang_familyRomanic  0.0919  0.1238   0.7423  0.4579
## condition:lang_familySino-Tibetian  0.2343  0.1757   1.3338  0.1823
##              ci.lb      ci.ub
## intrcpt          0.1321  0.4029 ***
## condition          0.4070  0.5480 ***
## lang_familyRomanic -0.1479  0.5507
## lang_familySino-Tibetian -0.7069  0.1462
## condition:lang_familyRomanic -0.1508  0.3346
```



```
## condition:lang_familySino-Tibetan -0.1100 0.5787
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Language effect with age and condition moderators

```
dat$condition_label = ifelse(dat$condition == 1, "Correct", "Misp")

dat$lang_family = ifelse(dat$native_lang == "American English" | dat$native_lang ==
  "British English" | dat$native_lang == "Dutch" | dat$native_lang == "English" |
  dat$native_lang == "Danish" | dat$native_lang == "Swedish" | dat$native_lang ==
  "German", "Germanic", ifelse(dat$native_lang == "French" | dat$native_lang ==
  "Catalan" | dat$native_lang == "Spanish" | dat$native_lang == "Catalan-Spanish" |
  dat$native_lang == "Swiss French", "Romanic", "Sino-Tibetan"))

rma_lang_interaction <- rma.mv(g_calc, g_var_calc, mods = ~age.C * condition *
  lang_family, data = dat, random = ~collapse | short_cite)
summary(rma_lang_interaction)
```

```
##
## Multivariate Meta-Analysis Model (k = 251; method: REML)
##
##      logLik   Deviance      AIC      BIC      AICc
## -245.9822   491.9645   519.9645   568.6350   521.8395
##
## Variance Components:
##
## outer factor: short_cite (nlvls = 32)
## inner factor: collapse   (nlvls = 52)
##
##           estim      sqrt  fixed
## tau^2      0.1334  0.3653     no
## rho        0.7359              no
##
## Test for Residual Heterogeneity:
## QE(df = 239) = 998.1810, p-val < .0001
##
## Test of Moderators (coefficient(s) 2,3,4,5,6,7,8,9,10,11,12):
## QM(df = 11) = 225.6133, p-val < .0001
##
## Model Results:
##
##              estimate      se      zval
## intrcpt          0.2813  0.0713   3.9440
## age.C            0.0124  0.0124   1.0028
## condition        0.4795  0.0365  13.1408
## lang_familyRomanic 0.2318  0.1881   1.2323
## lang_familySino-Tibetan -0.2461 0.2491 -0.9879
## age.C:condition    0.0024  0.0082   0.2884
## age.C:lang_familyRomanic 0.0419 0.0352   1.1900
## age.C:lang_familySino-Tibetan -0.0012 0.0461 -0.0264
## condition:lang_familyRomanic 0.0558 0.1366   0.4083
```

```
## condition:lang_familySino-Tibetan      0.2910  0.1877  1.5506
## age.C:condition:lang_familyRomanic      -0.0116  0.0295 -0.3940
## age.C:condition:lang_familySino-Tibetan  0.0215  0.0336  0.6405
##                                     pval    ci.lb    ci.ub
## intrcpt                               <.0001    0.1415  0.4210 ***
## age.C                                0.3159 -0.0118  0.0367
## condition                             <.0001    0.4080  0.5510 ***
## lang_familyRomanic                    0.2178 -0.1369  0.6004
## lang_familySino-Tibetan                0.3232 -0.7343  0.2421
## age.C:condition                       0.7730 -0.0137  0.0184
## age.C:lang_familyRomanic               0.2341 -0.0271  0.1108
## age.C:lang_familySino-Tibetan          0.9790 -0.0915  0.0891
## condition:lang_familyRomanic           0.6831 -0.2120  0.3236
## condition:lang_familySino-Tibetan      0.1210 -0.0768  0.6588
## age.C:condition:lang_familyRomanic      0.6935 -0.0694  0.0462
## age.C:condition:lang_familySino-Tibetan 0.5219 -0.0443  0.0874
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Plot Language Effect

```
dat$lang_family = ifelse(dat$native_lang == "American English" | dat$native_lang ==
  "British English" | dat$native_lang == "Dutch" | dat$native_lang == "English" |
  dat$native_lang == "German", "Germanic", ifelse(dat$native_lang == "French" |
  dat$native_lang == "Catalan" | dat$native_lang == "Spanish" | dat$native_lang ==
  "Catalan-Spanish" | dat$native_lang == "Swiss French", "Romanic", "Sino-Tibetan"))

p <- ggplot(dat, aes(mean_age_1/30.44, g_calc, color = condition_label)) + geom_point(aes(size = weight,
  shape = lang_family), show.legend = FALSE) + facet_grid(. ~ lang_family) +
  geom_line(y = 0, linetype = "dotted") + geom_smooth(method = "lm", formula = y ~
  log(x), aes(weight = weights_g)) + theme(text = element_text(size = 16)) +
  xlab("Age in months") + ylab("Effect size Hedges' g")

p
```



```
ggsave("figures/AgeEffect_log_language.jpg", p)
```