

The background of the slide is a faded, blue-toned architectural drawing or blueprint. It features a complex network of lines, rectangles, and circles, resembling a technical drawing of a building or a circuit board. The lines are thin and light blue, creating a subtle pattern across the entire slide.

# Refactoring & Anti-Patterns

---

CSC207 Software Design

# Refactoring

Changing the code **without** changing its functionality.

Refactor to fix problems with the design.

Programmers often refactor their code to make it easier to then implement a new feature.

# A few refactoring techniques

- Extract Method
- Change Method Declaration
- Encapsulate Fields
- Split Loop
- Slide Statements
- Replace Constructor with Builder
- Replace Constructor with Factory Method

# A few refactoring techniques

- Extract Method
- Change Method Declaration
- Encapsulate Fields
- Split Loop
- Slide Statements
- Replace Constructor with Builder
- Replace Constructor with Factory Method

Performing a sequence of refactoring steps can lead to better code — while each step makes just a small change so that it is easy to avoid introducing bugs.

Advice: test after each change to the code!

# Extract Method

## Steps:

- Create a helper method containing the code for one step of a longer method.
- Update the original method to call the helper.

## Benefits:

- Improves readability

# Change Method Declaration

## Steps:

- Modify the parameter list to a method.
- Update the method body as needed.
- Update any calls to the method.

## Benefits:

- Adds flexibility (by adding parameters) or hide details (by removing parameters)

# Encapsulate Fields

## Steps:

- Change instance variable visibility to private.
- Add getters or setters as appropriate.
- Update client code to use setters and getters.

## Benefits:

- Controls access to instance variables.

# Split Loop

## Steps:

- Move independent operations from one loop into separate loops.

## Benefits:

- Improves readability and can make other refactoring techniques, like extract method, easier to perform.



# Slide Statements

## Steps:

- Reorder independent operations.

## Benefits:

- Improves readability and can make other refactoring techniques, like extract method, easier to perform.
- Group together related operations.

# Replace Constructor with Builder

## Steps:

- Create a Builder class with setters to customize the object being built and a method to build the object.
- Update constructor calls in the client code to use the Builder instead.

## Benefits:

- Improves readability of code.
- Can replace the need for many overloaded constructors for customizable classes.

# Replace Constructor with Factory Method

## Steps:

- Define a new method that returns an instance of the class.
- Hide the constructor from the client and have them use the factory method instead.

## Benefits:

- Hides explicit calls to the constructor

# Anti-Patterns

- Anti-patterns refer to code that would benefit from having a design pattern applied to it.
- Through a sequence of refactoring steps, we can transform code that follows an anti-pattern into code that follows an appropriate design pattern.
- The course notes contains examples of some anti-patterns for the design patterns covered in this course.

# Example

```
public class Student {  
    public int studentNumber;  
}
```

```
public class Student {  
    private int studentNumber;  
  
    public Student(int number) {  
        this.studentNumber = number;  
    }  
  
    public int getStudentNumber() {  
        return studentNumber;  
    }  
}
```

# Example

```
public class Pizza {  
    private final String size;  
    private final boolean cheese;  
    private final boolean pepperoni;  
    public Pizza(String size) { this(size, false); }  
    public Pizza(String size, boolean cheese) { this(size, cheese, false); }  
    public Pizza(String size, boolean cheese, boolean pepperoni) {  
        this.size = size;  
        this.cheese = cheese;  
        this.pepperoni = pepperoni;  
    }  
  
    public static void main(String[] args) {  
        Pizza pizza = new Pizza("Large", true, true);  
    }  
}
```

```
public class PizzaBuilder {
    private String size;
    private boolean cheese = false;
    private boolean pepperoni = false;

    public PizzaBuilder setSize(String size) {
        this.size = size;
        return this;
    }
    public PizzaBuilder addCheese() {
        this.cheese = true;
        return this;
    }
    public PizzaBuilder addPepperoni() {
        this.pepperoni = true;
        return this;
    }
    public Pizza build() {
        return new Pizza(size, cheese,
                           pepperoni);
    }
}
```

```
public class Pizza {
    private final String size;
    private final boolean cheese;
    private final boolean pepperoni;

    public Pizza(String size,
                  boolean cheese, boolean pepperoni) {
        this.size = size;
        this.cheese = cheese;
        this.pepperoni = pepperoni;
    }

    public static void main(String[] args) {
        Pizza pizza = new PizzaBuilder()
                        .setSize("Large")
                        .addCheese()
                        .addPepperoni()
                        .build();
    }
}
```



# Example

```
public class RefactoringExample {  
    public static void main(String[] args) {  
        List<String> names = Arrays.asList("Alice", "Bob", "Charlie", "David");  
        List<String> upperNames = new ArrayList<>();  
        int totalLength = 0;  
  
        for (String name : names) {  
            upperNames.add(name.toUpperCase());  
            totalLength += name.length();  
        }  
  
        System.out.println("Uppercase Names: " + upperNames);  
        System.out.println("Total Length: " + totalLength);  
    }  
}
```

```
public class RefactoringExample {  
    public static void main(String[] args) {  
        List<String> names = Arrays.asList("Alice", "Bob", "Charlie", "David");  
        List<String> upperNames = new ArrayList<>();  
        int totalLength = 0;  
  
        for (String name : names) {  
            upperNames.add(name.toUpperCase());  
        }  
        for (String name : names) {  
            totalLength += name.length();  
        }  
  
        System.out.println("Uppercase Names: " + upperNames);  
        System.out.println("Total Length: " + totalLength);  
    }  
}
```

```
public class RefactoringExample {  
    public static void main(String[] args) {  
        List<String> names = Arrays.asList("Alice", "Bob", "Charlie", "David");
```

```
        List<String> upperNames = new ArrayList<>();  
        for (String name : names) {  
            upperNames.add(name.toUpperCase());  
        }  
        System.out.println("Uppercase Names: " + upperNames);
```

```
        int totalLength = 0;  
        for (String name : names) {  
            totalLength += name.length();  
        }  
        System.out.println("Total Length: " + totalLength);
```

```
    }
```

```
}
```

```
public class RefactoringExample {  
    public static void main(String[] args) {  
        List<String> names = Arrays.asList("Alice", "Bob", "Charlie", "David");  
  
        printUppercaseNames(names);  
        printTotalLength(names);  
    }  
  
    private static void printUppercaseNames(List<String> names) {  
        ...  
        System.out.println("Uppercase Names: " + upperNames);  
    }  
  
    private static void printTotalLength(List<String> names) {  
        ...  
        System.out.println("Total Length: " + totalLength);  
    }  
}
```