

Explanation of code

Function read_fasta:

With the following function I insert the sequences in a list.

```
def read_fasta(filename):  
  
    with open(filename) as file:  
        lines = file.readlines()  
        seq = [line.replace("\n", "") for line in lines]  
  
    return seq
```

Function find_kmers(seq,k):

With the following function I cut every sequence in kmers.

```
def find_kmers(seq,k):  
  
    # There is a case where the sequence is not a multiple of k.  
    # For example seq = ACACT and k = 2 -> kmers = AC, AC, T so I have to consider the last item.  
    # So I make dummy = AC, AC, T and then I make the list of kmers = AC, AC  
  
    dummy = list(set([seq[i:i+k] for i in range(0, len(seq), k)]))  
    kmers = [i for i in dummy if len(i)==k]  
  
    return kmers
```

Function pwm_kmers(sequences,k):

With the following function I calculate the PWM from a set of aligned sequences of the same length. I copied from your example.

```
def pwm_kmers(sequences,k):  
  
    nuc = ['A', 'C', 'G', 'T']  
    profile=[[0 for i in range(len(sequences[0]))] for j in range(len(nuc))]  
  
    for instance in sequences:  
        for j in range(len(instance)):  
            residue=instance[j]  
            profile[nuc.index(residue)][j] += 1  
            profile[nuc.index(residue)][j]=float(profile[nuc.index(residue)][j])  
  
    pwm = np.array(profile)  
    pwm = pwm/len(sequences)  
  
    return pwm
```

Function select_rand_kmers(sequences,k):

The following function select randomly one kmer from every sequence.

```
def select_rand_kmers(sequences,k):  
  
    rand_kmers = []  
  
    for seq in sequences:  
        kmers = find_kmers(seq,k)  
        rand_kmers.append(random.choice(kmers))  
  
    return rand_kmers
```

Function scores_pwm(kmers,pwm):

The following function calculate the score for every kmer based on the values of PWM.

```
def scores_pwm(kmers,pwm):  
  
    nuc = ['A', 'C', 'G', 'T']  
    scores = [0 for i in kmers]  
  
    for i, kmer in enumerate(kmers):  
        for j, nucleotide in enumerate(kmer):  
            scores[i] += pwm[nuc.index(nucleotide)][j]  
  
    return scores
```

Function random_better_scores(scores_1,kmers_1,sequences,pwm,k):

The following function take the kmers (kmers_1) and scores (scores_1) that I had. It selects with the same way new random kmers (kmers_2) and calculates the new scores (scores_2). If the function finds a higher scored kmer from the selected sequence, it replace the old kmer with the new one.

```
def random_better_scores(scores_1,kmers_1,sequences,pwm,k):  
  
    kmers_2 = select_rand_kmers(sequences,k)  
    scores_2 = scores_pwm(kmers_2,pwm)  
  
    for i in range(len(scores_1)):  
        if scores_1[i]<scores_2[i]:  
            kmers_1[i] = kmers_2[i]  
            scores_1[i]=scores_2[i]  
  
    return kmers_1,scores_1
```

Function pwm_Entropy_Information(pwm):

This function calculates the mean information based on the entropy's formula using as data the PWM.

```
def pwm_Entropy_Information(pwm):  
  
    k = pwm.shape[1]  
  
    information = np.zeros([1,k]) #computing the information of each position  
  
    for i in range(k):  
        information[0,i] = 2-abs(sum([elem*np.log2(elem) for elem in pwm[:,i] if elem > 0]))  
  
    sum_information = np.sum(information)  
    mean_information = sum_information/k  
  
    return mean_information
```

Function Gibbs(filename,I,k):

This function is the implementation of Gibb's Algorithm for k with values from 3 to 8. It takes the threshold (I) and I want to returns the PWM for every single one k, that has greater score (mean_information) than the threshold (I).

```
def Gibbs(filename,I,k):  
  
    sequences = read_fasta(filename)  
  
    kmers = select_rand_kmers(sequences,k)  
    pwm = pwm_kmers(kmers,k)  
    scores = scores_pwm(kmers,pwm)  
    max_score = pwm_Entropy_Information(pwm)  
  
    while max_score < I:  
  
        kmers,scores = random_better_scores(scores,kmers,sequences,pwm,k)  
        pwm = pwm_kmers(kmers,k)  
        max_score = pwm_Entropy_Information(pwm)  
  
    return pwm,max_score
```