# https://github.com/christopherchristensen 12. April 2019

# Inhaltsverzeichnis

ecurity Requirements			
Security	 	 	
Safety	 	 	
Important Notes about Security	 	 	
Security vs. Safety			
Perimeter Security			
Why is Perimeter Security not sufficient anymore?	 	 	
Why Perimeter Security often focused on before Insecurities in Software?	 	 	
How to Intrusion happens	 	 	
Malware	 	 	
Infection	 	 	
Exploit	 	 	
Vulnerabilities	 	 	
Example of an Indirect Error	 	 	
Can Vulnerabilities and Exploits be prevented?	 	 	
Ways to improve Security	 	 	
Security Cost Considerations	 	 	
Attributes of Software Security	 	 	
What does Software Engineering deal with?	 	 	
Scales of Software Project	 	 	
Attributes of Software Quality	 	 	
Software Quality	 	 	
Development- vs. Maintenance-Costs	 	 	
Where do bugs come from?	 	 	
How much do Bugs cost in Relation to their Source?	 	 	
Process Models	 	 	
Different Process Models	 	 	
Waterfall	 	 	
Prototyping	 	 	
Unified Process	 	 	
Agile Development			
SCRUM	 	 	
DevOps			
DREAD			

DREAD: Damage (Potential)	8
DREAD: Reproducibility	9
DREAD: Exploitability	9
	9
DREAD: Discoverability	0
Why don't all organizations include Discoverability in DREAD?	0
DREAD Rating Calculation	0
Possible Exam Question to DREAD	0
OWASP Risk Rating	0
Attack Tree	1
Attack Tree - Node Values	1
Attack Tree - Node Value Calculation	1
Attack Tree - Countermeasures	1
UML	1
9 UML Diagrams	2
Use Case Diagram	2
4 Elements of UCD	2
Use Case	2
Actor	2
User Cases vs. User-Stories	2
Analysis with Use Cases	3
Context Model	3
Analysis with Use Cases including Security	3
Minuse Cores	ก

# **Security Requirements**

# **Security**

- Defense of computers against
  - instrusion
  - unauthorized use of resources
  - humans with malicious or criminal intent

# Safety

- Avoiding hazardous situations
- Alerting the correct systems if situation becomes unsafe
- Defending humans / environment against malfunctioning systems

# Important Notes about Security

- Security
  - is not a programming problem only
  - must be considered from the beginning on
  - is relevant in all phases of software development
  - can't be fixed by using special methods / tools
  - can't be seen isolated from deployment / operations

# Security vs. Safety

- No strict borderline between both concepts
- Security breaches may have serious safety consequences

# **Perimeter Security**

- Measures to protect external perimeter of a system
  - Access Control
  - Firewalls
  - Anti Virus Software
- Not sufficient by today's standards (medieval concept of yesterday)

# Why is Perimeter Security not sufficient anymore?

- More applications offer direct access to external users
- Modern applications often considered to be doors into OS ( $\sim$  wall)

## Why Perimeter Security often focused on before Insecurities in Software?

## **Bad Practice**

- Secure coding often not considered to be important in the past
- Often, security professionals ≠ software developers (full insight into software vulnerabilities missing)
- Functionality often focus of software developers

- Vendors want quick time to market, often no time for proper security architecture, design and testing
- Customers used to flaws and regular security updates (patches)
- Customers can't control software flaws, therefore depend upon perimeter protection

# How to Intrusion happens

- 1. Infection
- 2. Exploit
- 3. Payload

## Malware

#### Malicious Software

- Software doing something the user / owner of the computer doesn't like
- Special forms of malware
  - Virus
  - Worm
  - Trojan

#### Infection

- How malware gets into system
- When user trusts a piece of software (with malware)

# **Exploit**

"to use something to one's own advantage"

- Taking advantage of weak points in systems / applications
- Piece of software, chunk of data, or a sequence of commands
  - that takes advantage of a bug / vulnerability
  - to cause unintended / unanticipated behavior on computer software, hardware, or something electronic

## **Vulnerabilities**

- Programming errors (direct or indirect)
- Vulnerabilities lead to exploits
- Attacker must have applicable tool / technique that can connect to a system weakness (attack surface)

# **Example of an Indirect Error**

- Flawed handling of memory management
  - may render a system vulnerable to denial-of-service attacks
  - doesn't effect system's functionality therefore may remain undetected during testing

# Can Vulnerabilities and Exploits be prevented?

- Every system of minimum complexity contains errors
- No way of completely preventing it
- Relative security can be reached by
  - clean and intelligent software development
  - including security considerations in all phases of a system

# Ways to improve Security

- Security and functionality need to be designed and integrated into the individual phases of a development life cycle
- Security considerations need to be interlaced into product core
- Understand security needs, implement the right controls and test thoroughly

# **Security Cost Considerations**

- The higher the security efforts, the lower the costs for security breaches
- The higher the security efforts, the higher the costs for security measures
- With the right amount of security efforts the total costs can be kept at a minimum

# **Attributes of Software Security**

- Quality
- Correctness
- Availability
- Robustness
- Verifiability
- Reliability
- Safety

## What does Software Engineering deal with?

- Cost-effective development of high-quality software
- ... of software systems
  - Construction...
  - Control...
  - Rollout...
  - Operation and maintenance...

# **Scales of Software Project**

- Trivial
  - Staff: 1, 4-6 Weeks, Lines of code < 500
  - e.g. Simple administrative programs
- Small
  - Staff: 1, 1-6 Months, Lines of code: 1'000-2'000
  - e.g. Small commercial applications
- Medium
  - Staff: 2-5, 1-2 Years, Lines of code: 10'000-50'000

- e.g. Warehouse management
- Big
  - Staff: 5-20, 2-3 Years, Lines of code: 50'000-100'000
  - e.g. Small operating system
- Very Big
  - Staff: 100-1'000, 4-5 Years, Lines of code: ca. 1'000'000
  - e.g. Database system
- Extremely Big
  - Staff: 2'000-5'000, 5-10 years, Lines of code > 10'000'000
  - e.g. Air traffic control

# **Attributes of Software Quality**

- Correctness / Verifiability
- Reliability
- Robustness
- User-Friendliness
- Maintainability
- High Performant
- Portability / Compatability
- Reusability

# **Software Quality**

- Features of software necessary for meeting requirements
- Features of security and safety (partly competing)
- Importance of features dependant on project

# **Development- vs. Maintenance-Costs**

• Cost-effective = ca. 20% Dev / 80% Maintenance

# Where do bugs come from?

- $\bullet$  56% Analysis and Specification
- 27% Design
- 7% Coding
- 10% Other

# How much do Bugs cost in Relation to their Source?

- 82% Analysis and Specification
- 13% Design
- 1% Coding
- 4% Other

## **Process Models**

# Description of a process

- Activities must be
  - defined exactly
  - arranged along a time scale
- Process model is the starting point for
  - project planning
  - project management
- Process model must be adapted to
  - the project
  - the development environment (personnel / tools)

## **Different Process Models**

- Waterfall
- Prototyping
- Unified Process
- Agile Development
- SCRUM
- $\bullet \to \text{Devops}$

## Waterfall

- Strict linear sequence of activities
- Simple definition of milestones
- Relatively easy project management
- Little freedom for developers
- Problems
  - Not flexible

# **Prototyping**

- Iterative
- Flexible reactions to user requests possible
- More freedom for developers
- Problems
  - Hard to manage (hard to define milestones)
  - "quick-and-dirty" solutions stay in product forever

# **Unified Process**

- Compromise between Waterfall and Prototyping
- Iterative
- Flexible reaction to user requests possible
- Little freedom for developers
- Function-Oriented
- Problems
  - Often too slow, complicated, inefficient (cumbersome)

# **Agile Development**

- Agile Values
  - Individuals / Interactions > Processes / Tools
  - Working Programs > Elaborate Documentation
  - Constant Cooperations with Customer > Contracts
  - Courage / Openness for Change > Obeying fixed plans
- Agile Principles
  - Reuse existing ressources
  - KISS
  - Functional / Customer-Oriented
  - Collective Code Ownership
- Agile Methods
  - Pair Programming
  - Testdriven Programming
  - Refactoring
  - **–** ...

## **SCRUM**

- Process Model for Agile Methods
- Time-Oriented

# **DevOps**

- Build
- Deploy
- Test
- Release
- Build

[Content missing here]...

#### **DREAD**

## Methodology for risk rating

- Damage
- Reproducibility
- Exploitability
- Affected Users
- Discoverability

# **DREAD:** Damage (Potential)

- How bad would an attack be?
- Rating High (3):
  - Attacker can undermine security system

- Get full trust authorization
- Run as admin
- Upload content
- Rating Medium (2):
  - Lead sensitive information
- Rating Low (1):
  - Lead trivial information

# **DREAD:** Reproducibility

- How easy to reproduce attack?
- Rating High (3):
  - Attack reproducable every time
  - Attack doesn't require timing window
- Rating Medium (2):
  - Attack reproducable
  - Only within a timing window and partical race situation
- Rating Low (1):
  - Attack difficult to reproduce
  - Even with knowledge of security hole

# **DREAD: Exploitability**

- How much work to launch attack?
- Rating High (3):
  - Novice programmer could make attack in short time
- Rating Medium (2):
  - Skilled programmer could make attack, then repeat steps
- Rating Low (1):
  - Attack requires extremely skilled person
  - Requires in-depth knowledge every time

## **DREAD: Affected Users**

- How many people will be impacted?
- Rating High (3):
  - All users
  - Default configuration
  - Key customers
- Rating Medium (2):
  - Some users
  - Non-default configuration
- Rating Low (1):

- Very small percentage of users
- Obscure feature
- Affects anonymous users

# **DREAD:** Discoverability

- How easy is it to discover threat?
- Rating High (3):
  - Published info explains attack
  - Vulnerability found in most commonly used feature
  - Very noticeable
- Rating Medium (2):
  - Vulnerability in seldom-used part of product
  - Only some user should come across it
  - Requires some thinking to see malicious use
- Rating Low (1):
  - Bug is obscure
  - Unlikely that users will find damage potential

# Why don't all organizations include Discoverability in DREAD?

# DREAD-D, "DREAD minus D"

- They feel Discoverability rewards "Security through Obscurity"
- They then ignore it or always assume Discoverability at maximum rating (3)

# **DREAD Rating Calculation**

- After rating each Bug or Threat
- Put all into rows of table and sum up DREAD ratings

## Possible Exam Question to DREAD

- Threat given
- Attacker Profile given (Skill, Motivation, ...)
- Rate the Threat

# **OWASP Risk Rating**

## Part of Threat Modelling

- Threat Agent
- Vulnerability
- Technical Impact
- Business Impact

## Attack Tree

# Part of Threat Modelling

- Conceptual diagrams showing how an asset, or target, might be attacked
- Nodes combined by AND / OR
  - OR: Represents different ways to achieve same goal
  - AND: Represents different steps in achieving goal
- Costs assigned to activities

#### Attack Tree - Node Values

- Values can be assigned to leaf nodes
  - Boolean
  - Cost to attack
  - Cost to defend
  - Time to achieve
  - Time to repulse
  - Probability of success of attack
  - Likelihood that attacker will try attack

## Attack Tree - Node Value Calculation

- AND-Nodes: Values of subnodes must be added
- OR-Nodes: Take one (the minimum) value of subnodes

#### Attack Tree - Countermeasures

• Add further nodes with countermeasures

# **UML**

# Unified Modeling Language

- Modeling requirements during system analysis
- Standard language for...
  - specifying,
  - visualising,
  - constructing,
  - documenting
- ... software systems

# 9 UML Diagrams

- (Use case diagram)
- Class diagram
- Object diagram
- State diagram
- Activity diagram
- Sequence diagram
- Collaboration diagram
- Component diagram
- Deployment diagram
- Timing diagram

# **Use Case Diagram**

#### UCD

- To identify primary elements (actors) and processes (use cases) of system
- Shows which actors interact with each use case
- Actions described from actor's view

## 4 Elements of UCD

- Actors (elements that interact with system)
- System
- Use Cases (services that system performs)
- Lines (relationships)

## **Use Case**

- Distinct business functionality or behaviour of system
- Sequence of related activities done by actor together with system
- Represents some action the user might perform to complete a task

#### **Actor**

- External interface of system
- Any entity that performs certain roles in system
- Activates flow of actions in system and influences them

# User Cases vs. User-Stories

- User-Stories
  - common in Agile Dev. / Scrum
  - used for planning Use Cases
  - cut into pieces until they are implemented in one iteration
- Use Cases
  - bigger, more context information
  - define and document functionality

# **Analysis with Use Cases**

- Draw a context model
- Write a glossary
- Detail the context model
- Define scenarios with sequence diagrams
- Use activity diagrams to generalize

# **Context Model**

- Draw one Use Case for whole system
- Includes all actors that interact with system
- For each actor all functions shown

# Analysis with Use Cases including Security

- (Steps above)
- Add Misuse Cases

# Misuse Cases

- Based on Use-Case terminology
- Defined and completed by Mitigation Cases
- Process
  - Insert Misuse Cases
  - Describe Misuse Cases
  - Find Mitigation Use Case