



Usage Guideline

CBPRPlus-pacs.009.001.08_ADV_Financial-InstitutionCreditTransfer

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX pacs.009.001.08**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality	3
1 Restriction summary	5
2 Structure	7
3 ISO 20022 Rules	10
4 Message Building Blocks	12
5 Message Components	23
6 Message Datatypes	243
Legal Notices	290

Message Functionality

This Usage Guideline is based on the pacs.009.001.08 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the pacs.009.001.08 only.

Overview

Principles:

1. AGENTS IDENTIFICATION - Textual Rules

-> If BICFI is present, then (Name & Postal Address) is NOT allowed (ClearingSystemMemberIdentification and LEI may complement) - However, in case of conflicting information, the BICFI will always take precedence.

-> If BICFI is absent, (Name & Postal Address) OR [(Name & Postal Address) and ClearingSystemMemberIdentification] must be present.

Exception: If BICFI is absent, whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

Note: "Instructing/ Instructed Agents" must be identified with a BICFI - Clearing System Members Identification and LEI are optional.

2. This usage guideline covers the scenario "Advise for transfer of funds" and the pacs.009ADV is sent to pre-advise the receipt of the cover via a pacs.009 CORE.

IMPORTANT NOTE: in such scenario, the pacs.009 ADV message is sent by a debtor financial institution to a creditor financial institution, directly or through other agents. It is NEVER sent via a payment clearing and settlement system, the settlement will happen with the pacs.009 CORE.

-> More information on this scenario can be found in the UHB.

3. Character Set:

All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

```
!#$%&*='^_-'{|}~";<>@[\\]
```

< is replaced with <

> is replaced with >

4. CBPR_Agent_PointToPointOnSWIFT:

If the transaction is exchanged on the SWIFT network (ie if the instructing agent/ sender and instructed agent/receiver of the message are on SWIFT), then BICFI is mandatory and other elements are optional, eg LEI

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-pacs.009.001.08_ADV_FinancialInstitutionCreditTransfer message is composed of 3 building blocks

a. GroupHeader

Set of characteristics shared by all individual transactions included in the message.

b. CreditTransferTransactionInformation

Set of elements providing information specific to the individual credit transfer(s).

c. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the pacs.009.001.08 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	11, 16, 17, 22, 35, 35, 35, 35, 35, 35, 35, 35, 35, 35, 35, 36, 37, 37, 37, 37, 37, 37, 43, 44, 53, 53, 53, 53, 53, 54, 54, 54, 54, 54, 54, 54, 54, 54, 54, 54, 54, 54, 54, 54, 55, 79, 85, 88, 89, 122, 122, 122, 122, 122, 122, 122, 122, 122, 122, 122, 123, 124, 124, 125, 125, 125, 125, 126, 126, 126, 126, 126, 126, 126, 126, 126, 126, 127, 127, 141, 141, 141, 142, 143, 143, 144, 147, 150, 150, 150, 150, 151, 151, 151, 151, 153, 153, 153, 153, 154, 154, 154, 154, 155, 155, 155, 156, 156, 156, 157, 157, 157, 157, 157, 157, 157, 157, 158, 158, 158, 158, 158, 158, 169, 169, 169, 169, 169, 169, 169, 169, 169, 169, 169, 169, 169, 169, 170, 170, 170, 170, 170, 170, 170, 170, 170, 170, 170, 170, 173, 173, 173, 173, 173, 173, 173, 173, 173, 173, 174, 174, 174, 175, 175, 175, 175, 175, 175, 175, 175, 175, 213, 213, 214, 214, 215, 216, 219, 220, 285, 285, 286
Make mandatory	15, 56, 56, 56, 57, 57, 57, 57, 57, 58, 58, 58, 58, 58, 58, 58, 58, 58, 58, 58, 58, 59, 69, 74, 75, 123, 123, 123, 123, 124, 124, 138, 139, 159, 161, 172, 186, 186, 186, 186, 186, 186, 186, 186, 186, 186, 186, 186, 191, 191, 191, 191, 191, 192, 192, 192, 192, 192, 192, 192, 196, 196, 196, 196, 196, 196, 196, 196, 196, 196, 196, 196
Reduce Multiplicity	18, 21, 86, 86, 165, 192, 192, 192, 193, 193, 193, 193, 193, 193, 193, 193, 193, 209
Ignore	n.a.
Text rules	18, 41, 42, 42, 70, 70, 70, 70, 71, 72, 72, 72, 73, 73, 73, 73, 75, 75, 75, 75, 77, 77, 77, 77, 78, 78, 78, 78, 80, 80, 80, 80, 81, 81, 81, 81, 82, 82, 83, 83, 84, 84, 84, 84, 120, 120, 120, 120, 121, 121, 121, 121, 121, 121, 121, 121, 216, 216, 217, 217, 218, 218, 218, 218
Conditional rules	n.a.
Formal rules	12, 12, 12, 13, 13, 19, 21, 30, 30, 31, 31, 31, 32, 32, 33, 33, 33, 34, 34, 68, 160, 160

Restriction Type	See page
Fixed values	15, 15, 141
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	14, 16, 17, 26, 26, 26, 26, 26, 26, 26, 26, 26, 26, 26, 27, 41, 41, 42, 42, 43, 48, 48, 48, 48, 48, 48, 48, 48, 48, 48, 48, 48, 50, 50, 50, 50, 50, 50, 51, 51, 51, 51, 51, 51, 52, 59, 59, 59, 59, 59, 59, 59, 59, 59, 60, 60, 60, 60, 60, 60, 60, 60, 60, 68, 69, 118, 118, 118, 118, 118, 119, 119, 119, 119, 119, 119, 119, 132, 132, 132, 133, 133, 133, 133, 133, 133, 133, 133, 133, 134, 134, 134, 134, 134, 134, 134, 134, 134, 135, 135, 135, 140, 140, 146, 148, 149, 160, 160, 161, 162, 175, 175, 175, 175, 176, 176, 176, 176, 176, 176, 176, 176, 176, 176, 177, 177, 177, 177, 177, 177, 177, 177, 177, 177, 178, 178, 178, 178, 178, 178, 178, 178, 178, 178, 178, 178, 179, 179, 179, 179, 179, 179, 179, 179, 179, 179, 179, 180, 180, 180, 180, 180, 180, 180, 180, 180, 180, 181, 181, 181, 181, 181, 181, 181, 181, 181, 181, 182, 182, 182, 182, 182, 182, 182, 182, 182, 182, 183, 183, 183, 183, 183, 183, 183, 183, 183, 183, 184, 184, 184, 184, 184, 184, 184, 184, 184, 184, 185, 185, 185, 185, 185, 185, 185, 185, 185, 185, 185, 187, 187, 187, 187, 187, 187, 187, 187, 187, 187, 187, 187, 188, 188, 188, 188, 188, 188, 188, 188, 188, 188, 188, 189, 189, 189, 189, 189, 189, 189, 189, 189, 189, 190, 190, 190, 190, 190, 190, 190, 190, 190, 190, 191, 191, 191, 191, 191, 193, 193, 193, 193, 194, 194, 194, 194, 194, 194, 194, 194, 197, 197, 197, 197, 197, 197, 197, 197, 197, 197, 198, 198, 199, 199, 199, 199, 199, 199, 200, 200, 200, 200, 200, 200, 201, 209, 211, 211, 212, 220, 221, 221, 221
Extensions	n.a.
Synonyms	160, 215

2 Structure

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		13
	From	<Fr>		[1..1]		13
	OrganisationIdentification	<OrgId>	{Or	[1..1]		154
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		154
	To	<To>		[1..1]		14
	OrganisationIdentification	<OrgId>	{Or	[1..1]		154
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		154
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		14
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		15
	BusinessService	<BizSvc>		[0..1]	 	15
	MarketPractice	<MktPrctc>		[0..1]		15
	Registry	<Regy>		[1..1]		144
	Identification	<Id>		[1..1]		144
	CreationDate	<CreDt>		[1..1]		16
	BusinessProcessingDate	<BizPrcgDt>		[0..1]		16
	CopyDuplicate	<CpyDplct>		[0..1]		16
	PossibleDuplicate	<PssblDplct>		[0..1]		17
	Priority	<Prty>		[0..1]		17
	Signature	<Sgntr>		[0..1]		17
	Related	<Rltd>		[0..*]	 R[0..1]	17
	CharacterSet	<CharSet>		[0..1]		40
	From	<Fr>		[1..1]		40
	To	<To>		[1..1]		40
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		41
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		41
	BusinessService	<BizSvc>		[0..1]		42
	CreationDate	<CreDt>		[1..1]		42

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		42
	PossibleDuplicate	<PssblDplct>		[0..1]		43
	Priority	<Prty>		[0..1]		43
	Signature	<Sgntr>		[0..1]		43
	<i>FinancialInstitutionCreditTransferV08</i>	<FICdtTrf>		[1..1]		19
	GroupHeader	<GrpHdr>		[1..1]		19
	MessageIdentification	<MsgId>		[1..1]		140
	CreationDateTime	<CreDtTm>		[1..1]		140
	BatchBooking	<BtchBookg>		[0..1]		140
	NumberOfTransactions	<NbOfTxs>		[1..1]		141
	ControlSum	<CtrlSum>		[0..1]		141
	TotalInterbankSettlementAmount	<TtlIntrBkSttlmAmt>		[0..1]		141
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		141
	SettlementInformation	<SttlmInf>		[1..1]		142
	PaymentTypeInformation	<PmtTpInf>		[0..1]		142
	InstructingAgent	<InstgAgt>		[0..1]		143
	InstructedAgent	<InstdAgt>		[0..1]		143
	CreditTransferTransactionInformation	<CdtTrfTxInf>		[1..*]	 R[1..1]	19
	PaymentIdentification	<PmtId>		[1..1]		67
	PaymentTypeInformation	<PmtTpInf>		[0..1]		68
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[1..1]		68
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]	 	68
	SettlementPriority	<SttlmPrty>		[0..1]		69
	SettlementTimeIndication	<SttlmTmIndctn>		[0..1]		69
	SettlementTimeRequest	<SttlmTmReq>		[0..1]		69
	PreviousInstructingAgent1	<PrvsInstgAgt1>		[0..1]		70
	PreviousInstructingAgent1Account	<PrvsInstgAgt1Acct>		[0..1]		71
	PreviousInstructingAgent2	<PrvsInstgAgt2>		[0..1]		71
	PreviousInstructingAgent2Account	<PrvsInstgAgt2Acct>		[0..1]		72
	PreviousInstructingAgent3	<PrvsInstgAgt3>		[0..1]		72
	PreviousInstructingAgent3Account	<PrvsInstgAgt3Acct>		[0..1]		73

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructingAgent	<InstgAgt>		[0..1]		74
	InstructedAgent	<InstdAgt>		[0..1]		74
	IntermediaryAgent1	<IntrmyAgt1>		[0..1]		75
	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		76
	IntermediaryAgent2	<IntrmyAgt2>		[0..1]		76
	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		77
	IntermediaryAgent3	<IntrmyAgt3>		[0..1]		77
	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		78
	UltimateDebtor	<UltmtDbtr>		[0..1]		79
	Debtor	<Dbtr>		[1..1]		79
	DebtorAccount	<DbtrAcct>		[0..1]		80
	DebtorAgent	<DbtrAgt>		[0..1]		81
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		82
	CreditorAgent	<CdtrAgt>		[0..1]		82
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		83
	Creditor	<Cdtr>		[1..1]		83
	CreditorAccount	<CdtrAcct>		[0..1]		84
	UltimateCreditor	<UltmtCdtr>		[0..1]		85
	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]	R[0..2]	85
	InstructionForNextAgent	<InstrForNxtAgt>		[0..*]	R[0..6]	86
	Purpose	<Purp>		[0..1]		86
	RemittanceInformation	<RmtInf>		[0..1]		87
	UnderlyingCustomerCreditTransfer	<UndrlygCstmrCdtTrf>		[0..1]		87
	SupplementaryData	<SplmtryData>		[0..*]		88
	SupplementaryData	<SplmtryData>		[0..*]		21
	PlaceAndName	<PlcAndNm>		[0..1]		226
	Envelope	<Envlp>		[1..1]		226

3 ISO 20022 Rules

R1 **RelatedPresentWhenCopyDupl** ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

R4 **InstructedAgentRule** ✓

If GroupHeader/InstructedAgent is present, then CreditTransferTransactionInformation/InstructedAgent is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00008
- *Error Text:* Invalid message content for instructed agent.

R5 **InstructingAgentRule** ✓

If GroupHeader/InstructingAgent is present, then CreditTransferTransactionInformation/InstructingAgent is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00007
- *Error Text:* Invalid message content for instructing agent.

R6 **TotalInterbankSettlementAmountRule** ✓

If GroupHeader/TotalInterbankSettlementAmount is present, then all occurrences of CreditTransferTransactionInformation/InterbankSettlementAmount must have the same currency as the currency of GroupHeader/TotalInterbankSettlementAmount.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00042
- *Error Text:* Invalid message content for the total interbank settlement amount and individual interbank settlement amount currencies.

R7 **TotalInterbankSettlementAmountAndSumRule**

If GroupHeader/TotalInterbankSettlementAmount is present, then it must equal the sum of all occurrences of CreditTransferTransactionInformation/InterbankSettlementAmount.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00043
- *Error Text:* Invalid message content for the total interbank settlement amount and sum of individual interbank settlement amounts.

R8 GroupHeaderInterbankSettlementDateRule ✓

If GroupHeader/InterbankSettlementDate is present, then CreditTransferTransactionInformation/InterbankSettlementDate is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00045
- *Error Text:* Invalid message content for interbank settlement date.

R9 TransactionInterbankSettlementDateRule ✓

If GroupHeader/InterbankSettlementDate is not present, then CreditTransferTransactionInformation/InterbankSettlementDate must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00290
- *Error Text:* Invalid message content for interbank settlement date.

R10 PaymentTypeInformationRule ✓

If GroupHeader/PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00009
- *Error Text:* Invalid message content for payment type information.

R11 SupplementaryDataRule

The SupplementaryData building block at message level must not be used to provide additional information about a transaction. The SupplementaryData element at transaction level should be used for that purpose.

Error handling: Undefined

Usage Guideline restrictions for this element

- **This rule(pacs.009.001.08/SupplementaryDataRule) is removed.**

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-pacs.009.001.08_ADV_FinancialInstitutionCreditTransfer message definition.

Usage Guideline on Root Node

- on pacs.009.001.08/fullmessage

- CBPR_BusinessMessageIdentifier_FormalRule:

The Business Message Identifier must match the Message Identification in the Group Header.

For each [Full Message], every occurrence of [Full Message/BusinessApplicationHeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/FinancialInstitutionCreditTransferV08/GroupHeader/MessageIdentification] value

- on pacs.009.001.08/fullmessage

- CBPR_Priority_Instruction_Priority_FormalRule:

If "Priority" is used in the BAH for pacs messages, the value should be identical to the one in the "Payment Type Information/InstructionPriority" if present.

For each [Full Message], if
 at least one occurrence of the following element(s) [Full Message/BusinessApplicationHeaderV02/Priority] and [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/PaymentTypeInformation/InstructionPriority] is (are) present
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/Priority]
 must have the same value than every occurrence of [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/PaymentTypeInformation/InstructionPriority]

- on pacs.009.001.08/fullmessage

- CBPR_To_Instructed_Agent_BIC_2_FormalRule:

BAH "To" BIC must match "Instructed Agent" BIC if CopyDuplicate is absent.

For each [Full Message], if
 the following element(s) [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] is (are) absent
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must
 have the same value than every occurrence of [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/InstructedAgent/FinancialInstitutionIdentification/BICFI]

- on pacs.009.001.08/fullmessage

– **CBPR_To_Instructed_Agent_BIC_1_FormalRule:**

BAH "To" BIC must match "Instructed Agent" BIC, except where BAH CopyDuplicate = COPY or = CODU

For each [Full Message], if
 every occurrence of [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] has value not included in the following list 'COPY' or 'CODU'
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must have the same value than every occurrence of [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/InstructedAgent/FinancialInstitutionIdentification/BICFI]

• **on pacs.009.001.08/fullmessage**

– **CBPR_From_Instructing_Agent_BIC_FormalRule:**

BAH "From" BIC must match "Instructing Agent" BIC

For each [Full Message], every occurrence of [Full Message/BusinessApplicationHeaderV02/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] value must be equal to every occurrence of [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/InstructingAgent/FinancialInstitutionIdentification/BICFI] value

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 289

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 153 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	154
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		154

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 153 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	154
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		154

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 253

Usage Guideline details

- on **pacs.009.001.08/.header/BusinessMessageIdentifier**
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 253

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefldr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "Max35Text" on page 280

Usage Guideline details

- on pacs.009.001.08/header/MessageDefinitionIdentifier

Single value: pacs.009.001.08

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 280

Usage Guideline details

- on pacs.009.001.08/header/BusinessService

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/header/BusinessService

Single value: swift.cbprplus.adv.04

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "[ImplementationSpecification1](#)" on page 144 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		144
	Identification	<Id>		[1..1]		144

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: "[CBPR_DateTime](#)" on page 250

Usage Guideline details

- on **pacs.009.001.08/.header/CreationDate**
Type changed to: [CBPR_DateTime](#) on page 250

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: "[ISODatetime](#)" on page 275

Usage Guideline details

- This element(**pacs.009.001.08/.header/BusinessProcessingDate**) is removed.

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: "[CopyDuplicate1Code](#)" on page 256

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: "YesNoIndicator" on page 289

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: "Priority2Code" on page 284

Usage Guideline details

- on pacs.009.001.08/.header/Priority
Type changed to: Priority2Code on page 284

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element(pacs.009.001.08/.header/Signature) is removed.

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype "BusinessApplicationHeader5__1" on page 39 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		40
	From	<Fr>		[1..1]		40
	To	<To>		[1..1]		40
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		41
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		41
	BusinessService	<BizSvc>		[0..1]		42
	CreationDate	<CreDt>		[1..1]		42
	CopyDuplicate	<CpyDplct>		[0..1]		42
	PossibleDuplicate	<PssblDplct>		[0..1]		43
	Priority	<Prty>		[0..1]		43
	Signature	<Sgntr>		[0..1]		43

Usage Guideline details

- on **pacs.009.001.08/header/Related**

This element has change repeatability, the maximum occurrence has been changed to : 1

- on **pacs.009.001.08/header/Related**

- **CBPR_Related_Business_Application_Header_TextualRule:**

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-pacs.009.001.08_ADV_FinancialInstitutionCreditTransfer payload definition.

Usage Guideline on Root Node

- on pacs.009.001.08/

- **CBPR_GPI_ServiceLevel_Code_FormalRule:**

The GPI ServiceLevel Code in pacs.009 ADV must be 'G004'.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08], if at least one occurrence of the following element(s) [FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/PaymentTypeInformation/ServiceLevel] is (are) present, then the value of every occurrence of [FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/PaymentTypeInformation/ServiceLevel/Code] must not comply with the following XML pattern : '(G001|G002|G003|G005|G006|G007|G009)'

4.2.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Set of characteristics shared by all individual transactions included in the message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader93__1" on page 139 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		140
	CreationDateTime	<CreDtTm>		[1..1]		140
	BatchBooking	<BtchBookg>		[0..1]		140
	NumberOfTransactions	<NbOfTx>		[1..1]		141
	ControlSum	<CtrlSum>		[0..1]		141
	TotalInterbankSettlementAmount	<TtlIntrBkSttlmAmt>		[0..1]		141
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		141
	SettlementInformation	<SttlmInf>		[1..1]		142
	PaymentTypeInformation	<PmtTplnf>		[0..1]		142
	InstructingAgent	<InstgAg>		[0..1]		143
	InstructedAgent	<InstdAg>		[0..1]		143

4.2.2 CreditTransferTransactionInformation

XML Tag: CdtTrfTxInf

Presence: [1..*]

Definition: Set of elements providing information specific to the individual credit transfer(s).

The **CdtTrfTxInf** block contains the following elements (see datatype "CreditTransferTransaction36__1" on page 63 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PaymentIdentification	<PmtId>		[1..1]		67
	PaymentTypeInformation	<PmtTplnf>		[0..1]		68
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[1..1]		68
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]	 	68
	SettlementPriority	<SttlmPrty>		[0..1]		69
	SettlementTimeIndication	<SttlmTmIndctn>		[0..1]		69
	SettlementTimeRequest	<SttlmTmReq>		[0..1]		69
	PreviousInstructingAgent1	<PrvsInstgAgt1>		[0..1]		70
	PreviousInstructingAgent1Ac-count	<PrvsInstgAgt1Acct>		[0..1]		71
	PreviousInstructingAgent2	<PrvsInstgAgt2>		[0..1]		71
	PreviousInstructingAgent2Ac-count	<PrvsInstgAgt2Acct>		[0..1]		72
	PreviousInstructingAgent3	<PrvsInstgAgt3>		[0..1]		72
	PreviousInstructingAgent3Ac-count	<PrvsInstgAgt3Acct>		[0..1]		73
	InstructingAgent	<InstgAgt>		[0..1]		74
	InstructedAgent	<InstdAgt>		[0..1]		74
	IntermediaryAgent1	<IntrmyAgt1>		[0..1]		75
	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		76
	IntermediaryAgent2	<IntrmyAgt2>		[0..1]		76
	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		77
	IntermediaryAgent3	<IntrmyAgt3>		[0..1]		77
	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		78
	UltimateDebtor	<UltmtDbtr>		[0..1]		79
	Debtor	<Dbtr>		[1..1]		79
	DebtorAccount	<DbtrAcct>		[0..1]		80

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebtorAgent	<DbtrAgt>		[0..1]		81
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		82
	CreditorAgent	<CdtrAgt>		[0..1]		82
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		83
	Creditor	<Cdtr>		[1..1]		83
	CreditorAccount	<CdtrAcct>		[0..1]		84
	UltimateCreditor	<UltmtCdtr>		[0..1]		85
	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]	R[0..2]	85
	InstructionForNextAgent	<InstrForNxtAgt>		[0..*]	R[0..6]	86
	Purpose	<Purp>		[0..1]		86
	RemittanceInformation	<RmtInf>		[0..1]		87
	UnderlyingCustomerCreditTransfer	<UndrlygCstmrCdtTrf>		[0..1]		87
	SupplementaryData	<SplmtryData>		[0..*]		88

Usage Guideline details

- **on pacs.009.001.08/CreditTransferTransactionInformation**

This element has change repeatability, the maximum occurrence has been changed to : 1

- **on pacs.009.001.08/CreditTransferTransactionInformation**

- **CBPR_Instruction_For_Creditor_Presence_Code_FormalRule:**

Each code can only be used once for element Instruction For Creditor Agent.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/Credit-TransferTransactionInformation], if

at least one occurrence of the following element(s) [CreditTransferTransactionInformation/InstructionForCreditorAgent/Code] is (are) present
, then

every occurrence of [CreditTransferTransactionInformation/Instruction-ForCreditorAgent/Code] must have the same value than between '1' and '1' occurrences of [CreditTransferTransactionInformation/InstructionForCreditorAgent/Code]

4.2.3 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on [page 225](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		226
	Envelope	<Envlp>		[1..1]		226

Usage Guideline details

- This element(pacs.009.001.08/SupplementaryData) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		23
	Other	<Othr>	Or}	[1..1]		23

Used in element(s)

"Identification" on page 44

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 274

5.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1](#)" on page 131 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		131
	SchemeName	<SchmeNm>		[0..1]		131
	Issuer	<Issr>		[0..1]		132

5.2 AccountIdentification4Choice__1

Definition: Specifies the unique identification of an account as assigned by the account servicer.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		24
	Other	<Othr>	Or}	[1..1]		24

Used in element(s)

"Identification" on page 46

5.2.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 274

5.2.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1__1](#)" on page 132 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	132
	SchemeName	<SchmeNm>		[0..1]		133
	Issuer	<Issr>		[0..1]	⚠	134

5.3 AccountSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		25

Used in element(s)

["SchemeName" on page 131](#)

5.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalAccountIdentification1Code" on page 262](#)

5.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 280](#)

5.4 AccountSchemeName1Choice__1

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		26

Used in element(s)

["SchemeName" on page 133](#)

5.4.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalAccountIdentification1Code" on page 262](#)

5.4.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 253

Usage Guideline details

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2Account/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1Account/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3Account/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgentAccount/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2Account/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1Account/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3Account/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAccount/Identification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other/SchemeName/Proprietary

Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/DebtorAccount/Identification/Other/SchemeName/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

5.5 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		27
	Proprietary	<Prtry>	Or}	[1..1]		27

Used in element(s)

["AddressType" on page 168](#), ["AddressType" on page 174](#)

5.5.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: ["AddressType2Code" on page 245](#)

5.5.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype ["GenericIdentification30" on page 136](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		136
	Issuer	<Issr>		[1..1]		136
	SchemeName	<SchmeNm>		[0..1]		136

5.6 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

Used in element(s)

"CreditorAgent" on page 100, "DebtorAgent" on page 94, "InstructedAgent" on page 143, "InstructingAgent" on page 143, "IntermediaryAgent1" on page 97, "IntermediaryAgent2" on page 98, "IntermediaryAgent3" on page 99, "PreviousInstructingAgent1" on page 95, "PreviousInstructingAgent2" on page 95, "PreviousInstructingAgent3" on page 96, "ThirdReimbursementAgent" on page 219, "UltimateCreditor" on page 85, "UltimateDebtor" on page 79

5.6.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18" on page 114 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		115
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		115
	LEI	<LEI>		[0..1]		115
	Name	<Nm>		[0..1]		116
	PostalAddress	<PstlAdr>		[0..1]		116
	Other	<Othr>		[0..1]		116

5.6.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 37 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		38
	LEI	<LEI>		[0..1]		38
	Name	<Nm>		[0..1]		38
	PostalAddress	<PstlAdr>		[0..1]		38

5.7 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	34

Used in element(s)

"Creditor" on page 83, "CreditorAgent" on page 82, "Debtor" on page 79, "DebtorAgent" on page 81, "InstructedReimbursementAgent" on page 217, "InstructingReimbursementAgent" on page 216, "IntermediaryAgent1" on page 75, "IntermediaryAgent2" on page 76, "IntermediaryAgent3" on page 77, "PreviousInstructingAgent1" on page 70, "PreviousInstructingAgent2" on page 71, "PreviousInstructingAgent3" on page 72

5.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18__1](#)" on page 117 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		117
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		117
	LEI	<LEI>		[0..1]		118
	Name	<Nm>		[0..1]		118
	PostalAddress	<PstlAdr>		[0..1]		119
	Other	<Othr>		[0..1]		122

Usage Guideline details

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if

at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification],

if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification],

for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

```

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/Credit-
TransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentifica-
tion],
  if
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] must be present
      and if
        at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] must be present

```

- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

```

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/Credit-
TransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentifi-
cation],
  if
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] must be present
      and if
        at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] must be present

```

- **on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

```

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/Credit-
TransferTransactionInformation/Debtor/FinancialInstitutionIdentification],
  if
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] must be present
      and if
        at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] must be present

```


- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/Credit-TransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification],
 if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/Credit-TransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification],
 if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/Credit-TransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification],
 if

```

        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
        then
            at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
            and if
                at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
                then
                    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

```

- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification**

– **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

```

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification],
    if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
        then
            at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
            and if
                at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
                then
                    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

```

- **on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification**

– **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

```

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification],
    if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
        then
            at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
            and if
                at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
                then
                    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

```

5.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 37 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		38
	LEI	<LEI>		[0..1]		38
	Name	<Nm>		[0..1]		38
	PostalAddress	<PstlAdr>		[0..1]		38

Usage Guideline details

- This element(pacs.009.001.08/CreditTransferTransactionInformation/Debtor/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/BranchIdentification) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Creditor/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/BranchIdentification) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/BranchIdentification) is removed.

- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/BranchIdentification) is removed.

5.8 BranchAndFinancialInstitutionIdentification6__2

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		36
	BranchIdentification	<BrnchId>		[0..1]	🚫	36

Used in element(s)

"FinancialInstitutionIdentification" on page 154, "InstructedAgent" on page 74, "InstructingAgent" on page 74

5.8.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18__2" on page 123 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	123
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		124
	LEI	<LEI>		[0..1]		124
	Name	<Nm>		[0..1]	🚫	124
	PostalAddress	<PstlAdr>		[0..1]	🚫	125
	Other	<Othr>		[0..1]	🚫	126

5.8.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 37 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		38
	LEI	<LEI>		[0..1]		38
	Name	<Nm>		[0..1]		38
	PostalAddress	<PstlAdr>		[0..1]		38

Usage Guideline details

- This element(pacs.009.001.08/.header/Related/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(pacs.009.001.08/.header/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(pacs.009.001.08/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(pacs.009.001.08/.header/From/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructedAgent/BranchIdentification) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructingAgent/BranchIdentification) is removed.

5.9 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		38
	LEI	<LEI>		[0..1]		38
	Name	<Nm>		[0..1]		38

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostalAddress	<PstlAdr>		[0..1]		38

Used in element(s)

"BranchIdentification" on page 28, "BranchIdentification" on page 34, "BranchIdentification" on page 36

5.9.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "Max35Text" on page 280

5.9.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: "LEIIdentifier" on page 277

5.9.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 278

5.9.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 167 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		168
	Department	<Dept>		[0..1]		169
	SubDepartment	<SubDept>		[0..1]		170

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	StreetName	<StrtNm>		[0..1]		170
	BuildingNumber	<BldgNb>		[0..1]		171
	BuildingName	<BldgNm>		[0..1]		171
	Floor	<Flr>		[0..1]		171
	PostBox	<PstBx>		[0..1]		171
	Room	<Room>		[0..1]		171
	PostCode	<PstCd>		[0..1]		171
	TownName	<TwnNm>		[0..1]		172
	TownLocationName	<TwnLctnNm>		[0..1]		172
	DistrictName	<DstrctNm>		[0..1]		172
	CountrySubDivision	<CtrySubDvsn>		[0..1]		172
	Country	<Ctry>		[0..1]		172
	AddressLine	<AdrLine>		[0..7]		172

5.10 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		40
	From	<Fr>		[1..1]		40
	To	<To>		[1..1]		40
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		41
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		41
	BusinessService	<BizSvc>		[0..1]		42
	CreationDate	<CreDt>		[1..1]		42
	CopyDuplicate	<CpyDplct>		[0..1]		42
	PossibleDuplicate	<PssblDplct>		[0..1]		43
	Priority	<Prty>		[0..1]		43
	Signature	<Sgntr>		[0..1]		43

Used in element(s)

"Related" on page 17

5.10.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 289

5.10.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice__1" on page 153 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		154
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		154

5.10.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "Party44Choice__1" on page 153 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		154
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		154

5.10.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 253

Usage Guideline details

- on pacs.009.001.08/.header/Related/BusinessMessageIdentifier

Type changed to: CBPR_RestrictedFINXMax35Text on page 253

- on pacs.009.001.08/.header/Related/BusinessMessageIdentifier

– **CBPR_Business_Message_Identifier_TextualRule:**

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

5.10.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 253

Usage Guideline details

- on pacs.009.001.08/.header/Related/MessageDefinitionIdentifier

Type changed to: CBPR_RestrictedFINXMax35Text on page 253

- on pacs.009.001.08/.header/Related/MessageDefinitionIdentifier

– CBPR_Message_Definition_Identifier_TextualRule:

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.10.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 253](#)

Usage Guideline details

- **on pacs.009.001.08/.header/Related/BusinessService**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- **on pacs.009.001.08/.header/Related/BusinessService**
 - **CBPR_Related_BAH_Business_Service_TextualRule:**
If related BAH is present, it should transport the element Business Service.

5.10.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 250](#)

Usage Guideline details

- **on pacs.009.001.08/.header/Related/CreationDate**
Type changed to: [CBPR_DateTime on page 250](#)

5.10.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 256](#)

5.10.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 289](#)

Usage Guideline details

- This element([pacs.009.001.08/.header/Related/PossibleDuplicate](#)) is removed.

5.10.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 284](#)

Usage Guideline details

- on [pacs.009.001.08/.header/Related/Priority](#)
Type changed to: [Priority2Code on page 284](#)

5.10.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element(pacs.009.001.08/.header/Related/Signature) is removed.

5.11 CashAccount38

Definition: Provides the details to identify an account.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

Used in element(s)

"CreditorAccount" on page 101, "CreditorAgentAccount" on page 100, "DebtorAccount" on page 93, "DebtorAgentAccount" on page 94, "IntermediaryAgent1Account" on page 97, "IntermediaryAgent2Account" on page 98, "IntermediaryAgent3Account" on page 99, "PreviousInstructingAgent1Account" on page 95, "PreviousInstructingAgent2Account" on page 96, "PreviousInstructingAgent3Account" on page 97, "SettlementAccount" on page 215, "ThirdReimbursementAgentAccount" on page 219

5.11.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "AccountIdentification4Choice" on page 23 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		23
	Other	<Othr>	Or}	[1..1]		23

5.11.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice](#)" on page 49 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		49
	Proprietary	<Prtry>	Or}	[1..1]		49

5.11.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on page 245

5.11.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "[Max70Text](#)" on page 280

5.11.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "[ProxyAccountIdentification1](#)" on page 194 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		195
	Identification	<Id>		[1..1]		195

5.12 CashAccount38__1

Definition: Provides the details to identify an account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

Used in element(s)

["CreditorAccount"](#) on page 84, ["CreditorAgentAccount"](#) on page 83, ["DebtorAccount"](#) on page 80, ["DebtorAgentAccount"](#) on page 82, ["InstructedReimbursementAgentAccount"](#) on page 218, ["InstructingReimbursementAgentAccount"](#) on page 217, ["IntermediaryAgent1Account"](#) on page 76, ["IntermediaryAgent2Account"](#) on page 77, ["IntermediaryAgent3Account"](#) on page 78, ["PreviousInstructingAgent1Account"](#) on page 71, ["PreviousInstructingAgent2Account"](#) on page 72, ["PreviousInstructingAgent3Account"](#) on page 73

5.12.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice__1](#)" on page 24 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		24
	Other	<Othr>	Or}	[1..1]		24

5.12.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice__1](#)" on page 49 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		50
	Proprietary	<Prtry>	Or}	[1..1]		50

5.12.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on page 245

5.12.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "[CBPR_RestrictedFINXMax70Text](#)" on page 254

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgentAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1Account/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3Account/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgentAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2Account/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2Account/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgentAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3Account/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1Account/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgentAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 254](#)

5.12.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "[ProxyAccountIdentification1__1](#)" on [page 195](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		195
	Identification	<Id>		[1..1]		197

5.13 CashAccountType2Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		49
	Proprietary	<Prtry>	Or}	[1..1]		49

Used in element(s)

["Type" on page 45](#)

5.13.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: "[ExternalCashAccountType1Code](#)" on [page 262](#)

5.13.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: "[Max35Text](#)" on [page 280](#)

5.14 CashAccountType2Choice__1

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		50
	Proprietary	<Prtry>	Or}	[1..1]		50

Used in element(s)

["Type" on page 47](#)

5.14.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: ["ExternalCashAccountType1Code" on page 262](#)

5.14.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 253](#)

Usage Guideline details

- on **pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgentAccount/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on **pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgentAccount/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on **pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2Account/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on **pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3Account/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on **pacs.009.001.08/CreditTransferTransactionInformation/CreditorAccount/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on **pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3Account/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2Account/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgentAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1Account/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1Account/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgentAccount/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

5.15 CategoryPurpose1Choice

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		51
	Proprietary	<Prtry>	Or}	[1..1]		52

Used in element(s)

["CategoryPurpose" on page 163](#)

5.15.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: ["ExternalCategoryPurpose1Code" on page 264](#)

5.15.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: "Max35Text" on page 280

5.16 CategoryPurpose1Choice__1

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		52
	Proprietary	<Prtry>	Or}	[1..1]	⚠️	52

Used in element(s)

"CategoryPurpose" on page 165

5.16.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: "ExternalCategoryPurpose1Code" on page 264

5.16.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 253

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PaymentTypeInformation/Category-Purpose/Proprietary
 Type changed to: CBPR_RestrictedFINXMax35Text on page 253

5.17 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		53
	Proprietary	<Prtry>	Or}	[1..1]		53

Used in element(s)

"ClearingSystemIdentification" on page 56, "ClearingSystemIdentification" on page 57

5.17.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: "ExternalClearingSystemIdentification1Code" on page 265

5.17.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: "Max35Text" on page 280

Usage Guideline details

- This element(pacs.009.001.08/GroupHeader/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.

- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/ThirdReimbursementAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.

- This element([pacs.009.001.08/GroupHeader/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.

5.18 ClearingSystemIdentification3Choice

Definition: Specifies the clearing system identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		55
	Proprietary	<Prtry>	Or}	[1..1]		55

Used in element(s)

["ClearingSystem" on page 215](#)

5.18.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list.

Datatype: ["ExternalCashClearingSystem1Code" on page 263](#)

5.18.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Clearing system identification in a proprietary form.

Datatype: ["Max35Text" on page 280](#)

5.19 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		56
	MemberIdentification	<Mmbld>		[1..1]		56

Used in element(s)

"ClearingSystemMemberIdentification" on page 115

5.19.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 53 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		53
	Proprietary	<Prtry>	Or}	[1..1]		53

Usage Guideline details

- on pacs.009.001.08/GroupHeader/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.009.001.08/CreditTransferTransactionInformation/UnderlyingCustomerCreditTransfer/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.009.001.08/GroupHeader/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.19.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "Max35Text" on page 280

5.20 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		57
	MemberIdentification	<MmbId>		[1..1]		59

Used in element(s)

"ClearingSystemMemberIdentification" on page 117, "ClearingSystemMemberIdentification" on page 124

5.20.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "[ClearingSystemIdentification2Choice](#)" on page 53 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		53
	Proprietary	<Prtry>	Or}	[1..1]		53

Usage Guideline details

- on pacs.009.001.08/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.009.001.08/CreditTransferTransactionInformation/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

5.20.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "CBPR_RestrictedFINXMax28Text" on page 252

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 252](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 252](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 252](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 252](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 252](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 252](#)
- on pacs.009.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 252](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 252](#)
- on pacs.009.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 252](#)

- on pacs.009.001.08/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 252
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 252
- on pacs.009.001.08/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 252
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 252

5.21 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		61
	Name	<Nm>		[0..1]		61
	PhoneNumber	<PhneNb>		[0..1]		61
	MobileNumber	<MobNb>		[0..1]		61

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FaxNumber	<FaxNb>		[0..1]		62
	EmailAddress	<EmailAdr>		[0..1]		62
	EmailPurpose	<EmailPurp>		[0..1]		62
	JobTitle	<JobTitt>		[0..1]		62
	Responsibility	<Rspnsblty>		[0..1]		62
	Department	<Dept>		[0..1]		62
	Other	<Othr>		[0..*]		62
	PreferredMethod	<PrefrdMtd>		[0..1]		63

Used in element(s)

"ContactDetails" on page 158

5.21.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 281

5.21.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 278

5.21.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 282

5.21.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 282

5.21.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 282

5.21.6 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max2048Text" on page 279

5.21.7 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: "Max35Text" on page 280

5.21.8 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: "Max35Text" on page 280

5.21.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: "Max35Text" on page 280

5.21.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 280

5.21.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 152 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		152
	Identification	<Id>		[0..1]		152

5.21.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod1Code" on page 283

5.22 CreditTransferTransaction36__1

Definition: Provide further details specific to the individual transaction(s) included in the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PaymentIdentification	<PmtId>		[1..1]		67
	PaymentTypeInformation	<PmtTpInf>		[0..1]		68
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[1..1]		68
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]	 	68
	SettlementPriority	<SttlmPrty>		[0..1]		69
	SettlementTimeIndication	<SttlmTmIndctn>		[0..1]		69
	SettlementTimeRequest	<SttlmTmReq>		[0..1]		69
	PreviousInstructingAgent1	<PrvsInstgAgt1>		[0..1]		70
	PreviousInstructingAgent1Ac-count	<PrvsInstgAgt1Acct>		[0..1]		71
	PreviousInstructingAgent2	<PrvsInstgAgt2>		[0..1]		71
	PreviousInstructingAgent2Ac-count	<PrvsInstgAgt2Acct>		[0..1]		72
	PreviousInstructingAgent3	<PrvsInstgAgt3>		[0..1]		72

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PreviousInstructingAgent3Account	<PrvsInstgAgt3Acct>		[0..1]		73
	InstructingAgent	<InstgAgt>		[0..1]	M	74
	InstructedAgent	<InstdAgt>		[0..1]	M	74
	IntermediaryAgent1	<IntrmyAgt1>		[0..1]	⚠	75
	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		76
	IntermediaryAgent2	<IntrmyAgt2>		[0..1]	⚠	76
	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		77
	IntermediaryAgent3	<IntrmyAgt3>		[0..1]	⚠	77
	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		78
	UltimateDebtor	<UltmtDbtr>		[0..1]	⊘	79
	Debtor	<Dbtr>		[1..1]	⚠	79
	DebtorAccount	<DbtrAcct>		[0..1]		80
	DebtorAgent	<DbtrAgt>		[0..1]	⚠	81
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		82
	CreditorAgent	<CdtrAgt>		[0..1]	⚠	82
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		83
	Creditor	<Cdtr>		[1..1]	⚠	83
	CreditorAccount	<CdtrAcct>		[0..1]		84
	UltimateCreditor	<UltmtCdtr>		[0..1]	⊘	85
	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]	R[0..2]	85
	InstructionForNextAgent	<InstrForNxtAgt>		[0..*]	R[0..6]	86
	Purpose	<Purp>		[0..1]		86
	RemittanceInformation	<RmtInf>		[0..1]		87
	UnderlyingCustomerCreditTransfer	<UndrlygCstmrCdtTrf>		[0..1]	⊘	87
	SupplementaryData	<SplmtryData>		[0..*]	⊘	88

Rules

R40 IntermediaryAgent2Rule ✓

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

– *Error severity:* Fatal

- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

R41 IntermediaryAgent3Rule ✓

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

R42 IntermediaryAgent1Rule ✓

If IntermediaryAgent1 is present, then CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00060
- *Error Text:* Invalid message content for intermediary agent 1.

R43 IntermediaryAgent1AccountRule ✓

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

R44 IntermediaryAgent2AccountRule ✓

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

R45 IntermediaryAgent3AccountRule ✓

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

R46 DebtorAgentAccountRule ✓

If DebtorAgentAccount is present, then DebtorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00059
- *Error Text:* Invalid message content for debtor agent account.

R47 CreditorAgentAccountRule ✓

If CreditorAgentAccount is present, then CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00058
- *Error Text:* Invalid message content for creditor agent account.

R48 PreviousInstructingAgent1AccountRule ✓

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00411
- *Error Text:* Invalid message content for previous instructing agent account.

R49 PreviousInstructingAgent2AccountRule ✓

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00412
- *Error Text:* Invalid message content for previous instructing agent account.

R50 PreviousInstructingAgent3AccountRule ✓

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00413
- *Error Text:* Invalid message content for previous instructing agent account.

R51 PreviousInstructionAgent2Rule ✓

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00415
- *Error Text:* Invalid message content for intermediary agent 1.

R52 PreviousInstructionAgent3Rule ✓

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00416
- *Error Text:* Invalid message content for intermediary agent 1.

Guidelines**1. UltimateDebtorGuideline**

UltimateDebtor may only be present if different from Debtor.

2. UltimateCreditorGuideline

UltimateCreditor may only be present if different from Creditor.

3. PreviousInstructingAgent1Guideline

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

Used in element(s)

"CreditTransferTransactionInformation" on page 19

5.22.1 PaymentIdentification

XML Tag: PmtId

Presence: [1..1]

Definition: Set of elements used to reference a payment instruction.

The **PmtId** block contains the following elements (see datatype "PaymentIdentification7_1" on page 159 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionIdentification	<InstrId>		[0..1]	M ⚠	159
	EndToEndIdentification	<EndToEndId>		[1..1]	⚠	160
	TransactionIdentification	<TxId>		[0..1]	⚠	161
	UETR	<UETR>		[0..1]	M	161
	ClearingSystemReference	<ClrSysRef>		[0..1]	⚠	161

5.22.2 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "PaymentTypeInformation28__1" on page 164 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		164
	ClearingChannel	<ClrChan>		[0..1]		164
	ServiceLevel	<SvcLvl>		[0..*]	R[0..3]	164
	LocalInstrument	<LclInstrm>		[0..1]		165
	CategoryPurpose	<CtgyPurp>		[0..1]		165

5.22.3 InterbankSettlementAmount

XML Tag: IntrBkSttlmAmt

Presence: [1..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: "CBPR_Amount" on page 248

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/InterbankSettlementAmount
Type changed to: CBPR_Amount on page 249

- on pacs.009.001.08/CreditTransferTransactionInformation/InterbankSettlementAmount
– **CBPR_Interbank_Settlement_Currency_FormalRule:**

The codes XAU, XAG, XPD and XPT are not allowed, as these are codes are only used for commodities.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/Credit-TransferTransactionInformation/InterbankSettlementAmount], every occurrence of [InterbankSettlementAmount/Currency] must have value not included in the following list 'XAU' or 'XAG' or 'XPD' or 'XPT'

5.22.4 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: ["CBPR_Date" on page 249](#)

Usage Guideline details

- on **pacs.009.001.08/CreditTransferTransactionInformation/InterbankSettlementDate**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pacs.009.001.08/CreditTransferTransactionInformation/InterbankSettlementDate**
Type changed to: [CBPR_Date on page 249](#)

5.22.5 SettlementPriority

XML Tag: SttlmPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction.

Datatype: ["Priority3Code" on page 284](#)

5.22.6 SettlementTimeIndication

XML Tag: SttlmTmIndctn

Presence: [0..1]

Definition: Provides information on the occurred settlement time(s) of the payment transaction.

The **SttlmTmIndctn** block contains the following elements (see datatype ["SettlementDateTimeIndication1__1" on page 211](#) for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebitDateTime	<DbtDtTm>		[0..1]		211
	CreditDateTime	<CdtDtTm>		[0..1]		212

5.22.7 SettlementTimeRequest

XML Tag: SttlmTmReq

Presence: [0..1]

Definition: Provides information on the requested settlement time(s) of the payment instruction.

The **SttlmTmReq** block contains the following elements (see datatype ["SettlementTimeRequest2__1" on page 220](#) for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CLSTime	<CLSTm>		[0..1]	⚠	220
	TillTime	<TillTm>		[0..1]	⚠	221
	FromTime	<FrTm>		[0..1]	⚠	221
	RejectTime	<RjctTm>		[0..1]	⚠	221

5.22.8 PreviousInstructingAgent1

XML Tag: PrvsInstgAgt1

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

The **PrvsInstgAgt1** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6_1](#)" on page 29 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.22.9 PreviousInstructingAgent1Account

XML Tag: PrvsInstgAgt1Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

The **PrvsInstgAgt1Acct** block contains the following elements (see datatype "[CashAccount38__1](#)" on [page 46](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

5.22.10 PreviousInstructingAgent2

XML Tag: PrvsInstgAgt2

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

The **PrvsInstgAgt2** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on [page 29](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2
 - CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2
 - CBPR_Agent_Option_1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2
 - CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2
 - CBPR_Agent_Option_2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.22.11 PreviousInstructingAgent2Account

XML Tag: PrvsInstgAgt2Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

The **PrvsInstgAgt2Acct** block contains the following elements (see datatype "CashAccount38__1" on page 46 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

5.22.12 PreviousInstructingAgent3

XML Tag: PrvsInstgAgt3

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

The **PrvsInstgAgt3** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__1" on page 29 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3**
 - CBPR_Agent_Option_1_TextualRule:**
 BICFI, complemented optionally with a LEI (preferred option)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3**
 - CBPR_Agent_National_only_TextualRule:**
 Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3**
 - CBPR_Agent_Option_3_TextualRule:**
 Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3**
 - CBPR_Agent_Option_2_TextualRule:**
 (Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.22.13 PreviousInstructingAgent3Account

XML Tag: PrvsInstgAgt3Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

The **PrvsInstgAgt3Acct** block contains the following elements (see datatype "[CashAccount38__1](#)" on page 46 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

5.22.14 InstructingAgent

XML Tag: InstgAgt

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

The **InstgAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6_2](#)" on page 36 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		36
	BranchIdentification	<BrnchId>		[0..1]		36

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/InstructingAgent
This element is now mandatory, the minimum occurrence has been changed to : 1

5.22.15 InstructedAgent

XML Tag: InstdAgt

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

The **InstdAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6_2](#)" on page 36 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		36
	BranchIdentification	<BrnchId>		[0..1]		36

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/InstructedAgent

This element is now mandatory, the minimum occurrence has been changed to : 1

5.22.16 IntermediaryAgent1

XML Tag: IntrmyAgt1

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

The **IntrmyAgt1** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__1" on page 29 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1

- CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1

- CBPR_Agent_Option_1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1

- CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1

- CBPR_Agent_Option_2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.22.17 IntermediaryAgent1Account

XML Tag: IntrmyAgt1Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.

The **IntrmyAgt1Acct** block contains the following elements (see datatype "[CashAccount38__1](#)" on page 46 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

5.22.18 IntermediaryAgent2

XML Tag: IntrmyAgt2

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

The **IntrmyAgt2** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 29 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2

– **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

• **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2**

– **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

• **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2**

– **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

• **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2**

– **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.22.19 IntermediaryAgent2Account

XML Tag: IntrmyAgt2Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.

The **IntrmyAgt2Acct** block contains the following elements (see datatype "[CashAccount38__1](#)" on [page 46](#) for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

5.22.20 IntermediaryAgent3

XML Tag: IntrmyAgt3

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

The **IntrmyAgt3** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__1" on page 29 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.22.21 IntermediaryAgent3Account

XML Tag: IntrmyAgt3Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain.

The **IntrmyAgt3Acct** block contains the following elements (see datatype "CashAccount38__1" on page 46 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

5.22.22 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate financial institution that owes an amount of money to the (ultimate) institutional creditor.

The **UltmtDbtr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

Usage Guideline details

- This element(pacs.009.001.08/CreditTransferTransactionInformation/UltimateDebtor) is removed.

5.22.23 Debtor

XML Tag: Dbtr

Presence: [1..1]

Definition: Financial institution that owes an amount of money to the (ultimate) financial institutional creditor.

The **Dbtr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__1" on page 29 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor

- CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor

- CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor

- CBPR_Agent_Option_2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor

- CBPR_Agent_Option_1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)

5.22.24 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "CashAccount38__1" on page 46 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

5.22.25 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6_1](#)" on page 29 for details)

🚫 Removed - 🚫 Partial Removed - 🔹 Ignored - 🔹 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.22.26 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount38__1" on page 46 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

5.22.27 CreditorAgent

XML Tag: CdtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__1" on page 29 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent
 - CBPR_Agent_Option_1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent
 - CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent

- CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent

- CBPR_Agent_Option_2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

5.22.28 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "CashAccount38__1" on page 46 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

5.22.29 Creditor

XML Tag: Cdtr

Presence: [1..1]

Definition: Financial institution that receives an amount of money from the financial institutional debtor.

The **Cdtr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__1" on page 29 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		34

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor
 - CBPR_Agent_National_only_TextualRule:
Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor
 - CBPR_Agent_Option_1_TextualRule:
BICFI, complemented optionally with a LEI (preferred option)
- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor
 - CBPR_Agent_Option_2_TextualRule:
(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor
 - CBPR_Agent_Option_3_TextualRule:
Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.22.30 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount38__1" on page 46 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

5.22.31 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate financial institution to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 28 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

Usage Guideline details

- This element([pacs.009.001.08/CreditTransferTransactionInformation/UltimateCreditor](#)) is removed.

5.22.32 InstructionForCreditorAgent

XML Tag: InstrForCdtrAgt

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

The **InstrForCdtrAgt** block contains the following elements (see datatype "[InstructionForCreditorAgent2_1](#)" on page 145 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		146
	InstructionInformation	<InstrInf>		[0..1]		146

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/InstructionForCreditorAgent
This element has change repeatability, the maximum occurrence has been changed to : 2

5.22.33 InstructionForNextAgent

XML Tag: InstrForNxtAgt

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the next agent.

Usage: The next agent may not be the creditor agent.

The instruction can relate to a level of service, can be an instruction that has to be executed by the agent, or can be information required by the next agent.

The **InstrForNxtAgt** block contains the following elements (see datatype "InstructionForNextAgent1__1" on page 147 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]	🚫	147
	InstructionInformation	<InstrInf>		[0..1]	⚠	147

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/InstructionForNextAgent
This element has change repeatability, the maximum occurrence has been changed to : 6

5.22.34 Purpose

XML Tag: Purp

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype "Purpose2Choice__1" on page 200 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		200
	Proprietary	<Prtry>	Or}	[1..1]	⚠	201

5.22.35 RemittanceInformation

XML Tag: RmtInf

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

The **RmtInf** block contains the following elements (see datatype "RemittanceInformation2__1" on page 209 for details)

⓪ Removed - ⓧ Partial Removed - ⬠ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]	⚠ R[0..1]	209

5.22.36 UnderlyingCustomerCreditTransfer

XML Tag: UndrlygCstmrCdtTrf

Presence: [0..1]

Definition: Provides information on the underlying customer credit transfer for which cover is provided.

The **UndrlygCstmrCdtTrf** block contains the following elements (see datatype "CreditTransferTransaction37" on page 89 for details)

⓪ Removed - ⓧ Partial Removed - ⬠ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	UltimateDebtor	<UltmtDbtr>		[0..1]		92
	InitiatingParty	<InitgPty>		[0..1]		93
	Debtor	<Dbtr>		[1..1]		93
	DebtorAccount	<DbtrAcct>		[0..1]		93
	DebtorAgent	<DbtrAgt>		[1..1]		94
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		94
	PreviousInstructingAgent1	<PrvsInstgAgt1>		[0..1]		95
	PreviousInstructingAgent1Account	<PrvsInstgAgt1Acct>		[0..1]		95
	PreviousInstructingAgent2	<PrvsInstgAgt2>		[0..1]		95

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PreviousInstructingAgent2Account	<PrvsInstgAgt2Acct>		[0..1]		96
	PreviousInstructingAgent3	<PrvsInstgAgt3>		[0..1]		96
	PreviousInstructingAgent3Account	<PrvsInstgAgt3Acct>		[0..1]		97
	IntermediaryAgent1	<IntrmyAgt1>		[0..1]		97
	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		97
	IntermediaryAgent2	<IntrmyAgt2>		[0..1]		98
	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		98
	IntermediaryAgent3	<IntrmyAgt3>		[0..1]		99
	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		99
	CreditorAgent	<CdtrAgt>		[1..1]		100
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		100
	Creditor	<Cdtr>		[1..1]		100
	CreditorAccount	<CdtrAcct>		[0..1]		101
	UltimateCreditor	<UltmtCdtr>		[0..1]		101
	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]		102
	InstructionForNextAgent	<InstrForNxtAgt>		[0..*]		102
	Tax	<Tax>		[0..1]		102
	RemittanceInformation	<RmtInf>		[0..1]		103
	InstructedAmount	<InstdAmt>		[0..1]		103

Usage Guideline details

- This element(pacs.009.001.08/CreditTransferTransactionInformation/UnderlyingCustomer-CreditTransfer) is removed.

5.22.37 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 225 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		226
	Envelope	<Envlp>		[1..1]		226

Usage Guideline details

- This element(pacs.009.001.08/CreditTransferTransactionInformation/SupplementaryData) is removed.

5.23 CreditTransferTransaction37

Definition: Provides further details specific to the individual transaction(s) included in the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	UltimateDebtor	<UltmtDbtr>		[0..1]		92
	InitiatingParty	<InitgPty>		[0..1]		93
	Debtor	<Dbtr>		[1..1]		93
	DebtorAccount	<DbtrAcct>		[0..1]		93
	DebtorAgent	<DbtrAgt>		[1..1]		94
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		94
	PreviousInstructingAgent1	<PrvsInstgAgt1>		[0..1]		95
	PreviousInstructingAgent1Account	<PrvsInstgAgt1Acct>		[0..1]		95
	PreviousInstructingAgent2	<PrvsInstgAgt2>		[0..1]		95
	PreviousInstructingAgent2Account	<PrvsInstgAgt2Acct>		[0..1]		96
	PreviousInstructingAgent3	<PrvsInstgAgt3>		[0..1]		96
	PreviousInstructingAgent3Account	<PrvsInstgAgt3Acct>		[0..1]		97
	IntermediaryAgent1	<IntrmyAgt1>		[0..1]		97
	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		97
	IntermediaryAgent2	<IntrmyAgt2>		[0..1]		98
	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		98
	IntermediaryAgent3	<IntrmyAgt3>		[0..1]		99
	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		99

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CreditorAgent	<CdtrAgt>		[1..1]		100
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		100
	Creditor	<Cdtr>		[1..1]		100
	CreditorAccount	<CdtrAcct>		[0..1]		101
	UltimateCreditor	<UltmtCdtr>		[0..1]		101
	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]		102
	InstructionForNextAgent	<InstrForNxtAgt>		[0..*]		102
	Tax	<Tax>		[0..1]		102
	RemittanceInformation	<RmtInf>		[0..1]		103
	InstructedAmount	<InstdAmt>		[0..1]		103

Rules

R14 IntermediaryAgent2Rule ✓

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

R15 IntermediaryAgent3Rule ✓

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

R16 IntermediaryAgent1AccountRule ✓

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

R17 IntermediaryAgent2AccountRule ✓

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

R18 IntermediaryAgent3AccountRule ✓

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

R19 PreviousInstructingAgent1AccountRule ✓

If PreviousInstructingAgent1Account is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00411
- *Error Text:* Invalid message content for previous instructing agent account.

R20 PreviousInstructingAgent2AccountRule ✓

If PreviousInstructingAgent2Account is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00412
- *Error Text:* Invalid message content for previous instructing agent account.

R21 PreviousInstructingAgent3AccountRule ✓

If PreviousInstructingAgent3Account is present, then PreviousInstructingAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00413
- *Error Text:* Invalid message content for previous instructing agent account.

R22 PreviousInstructionAgent2Rule ✓

If PreviousInstructingAgent2 is present, then PreviousInstructingAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00415
- *Error Text:* Invalid message content for intermediary agent 1.

R23 PreviousInstructingAgent3Rule ✓

If PreviousInstructingAgent3 is present, then PreviousInstructingAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00416
- *Error Text:* Invalid message content for intermediary agent 1.

Guidelines**1. UltimateDebtorGuideline**

UltimateDebtor may only be present if different from Debtor.

2. UltimateCreditorGuideline

UltimateCreditor may only be present if different from Creditor.

3. PreviousInstructingAgent1Guideline

It is recommended that, when present, PreviousInstructingAgent1 is the closest to the DebtorAgent in the payment chain.

Used in element(s)

"UnderlyingCustomerCreditTransfer" on page 87

5.23.1 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 155 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157
	ContactDetails	<CtctDtls>		[0..1]		158

5.23.2 InitiatingParty

XML Tag: InitgPty

Presence: [0..1]

Definition: Party that initiates the payment.

Usage: This can be either the debtor or a party that initiates the credit transfer on behalf of the debtor.

The **InitgPty** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 155 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157
	ContactDetails	<CtctDtls>		[0..1]		158

5.23.3 Debtor

XML Tag: Dbtr

Presence: [1..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

The **Dbtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 155 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157
	ContactDetails	<CtctDtls>		[0..1]		158

5.23.4 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "CashAccount38" on page 44 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.5 DebtorAgent

XML Tag: DbtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

5.23.6 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount38" on page 44 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.7 PreviousInstructingAgent1

XML Tag: PrvsInstgAgt1

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

The **PrvsInstgAgt1** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on [page 28](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

5.23.8 PreviousInstructingAgent1Account

XML Tag: PrvsInstgAgt1Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

The **PrvsInstgAgt1Acct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 44](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.9 PreviousInstructingAgent2

XML Tag: PrvsInstgAgt2

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

The **PrvsInstgAgt2** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

5.23.10 PreviousInstructingAgent2Account

XML Tag: PrvsInstgAgt2Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

The **PrvsInstgAgt2Acct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.11 PreviousInstructingAgent3

XML Tag: PrvsInstgAgt3

Presence: [0..1]

Definition: Agent immediately prior to the instructing agent.

The **PrvsInstgAgt3** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

5.23.12 PreviousInstructingAgent3Account

XML Tag: PrvsInstgAgt3Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.

The **PrvsInstgAgt3Acct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.13 IntermediaryAgent1

XML Tag: IntrmyAgt1

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

The **IntrmyAgt1** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 28 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

5.23.14 IntermediaryAgent1Account

XML Tag: IntrmyAgt1Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.

The **IntrmyAgt1Acct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 44](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.15 IntermediaryAgent2

XML Tag: IntrmyAgt2

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

The **IntrmyAgt2** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on [page 28](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

5.23.16 IntermediaryAgent2Account

XML Tag: IntrmyAgt2Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.

The **IntrmyAgt2Acct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 44](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.17 IntermediaryAgent3

XML Tag: IntrmyAgt3

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

The **IntrmyAgt3** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 28 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

5.23.18 IntermediaryAgent3Account

XML Tag: IntrmyAgt3Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain.

The **IntrmyAgt3Acct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.19 CreditorAgent

XML Tag: CdtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 28 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

5.23.20 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.21 Creditor

XML Tag: Cdtr

Presence: [1..1]

Definition: Party to which an amount of money is due.

The **Cdtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 155 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157
	ContactDetails	<CtctDtls>		[0..1]		158

5.23.22 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

5.23.23 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 155 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157
	ContactDetails	<CtctDtls>		[0..1]		158

5.23.24 InstructionForCreditorAgent

XML Tag: InstrForCdtrAgt

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

The **InstrForCdtrAgt** block contains the following elements (see datatype "InstructionForCreditorAgent1" on page 145 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		145
	InstructionInformation	<InstrInf>		[0..1]		145

5.23.25 InstructionForNextAgent

XML Tag: InstrForNxtAgt

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the next agent.

The **InstrForNxtAgt** block contains the following elements (see datatype "InstructionForNextAgent1" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		146
	InstructionInformation	<InstrInf>		[0..1]		147

5.23.26 Tax

XML Tag: Tax

Presence: [0..1]

Definition: Provides details on the tax.

The **Tax** block contains the following elements (see datatype "[TaxInformation8](#)" on page 233 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		233
	Debtor	<Dbtr>		[0..1]		234
	AdministrationZone	<AdmstnZone>		[0..1]		234
	ReferenceNumber	<RefNb>		[0..1]		234
	Method	<Mtd>		[0..1]		234
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		235
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		235
	Date	<Dt>		[0..1]		235
	SequenceNumber	<SeqNb>		[0..1]		235
	Record	<Rcrd>		[0..*]		235

5.23.27 RemittanceInformation

XML Tag: RmtInf

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

The **RmtInf** block contains the following elements (see datatype "[RemittanceInformation16](#)" on page 208 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]		208
	Structured	<Strd>		[0..*]		208

5.23.28 InstructedAmount

XML Tag: InstdAmt

Presence: [0..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Usage: This amount has to be transported unchanged through the transaction chain.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 244

5.24 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		104
	Reference	<Ref>		[0..1]		104

Used in element(s)

"CreditorReferenceInformation" on page 223

5.24.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of creditor reference.

The **Tp** block contains the following elements (see datatype "CreditorReferenceType2" on page 105 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		105
	Issuer	<Issr>		[0..1]		106

5.24.2 Reference

XML Tag: Ref

Presence: [0..1]

Definition: Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: "Max35Text" on page 280

5.25 CreditorReferenceType1Choice

Definition: Specifies the type of document referred by the creditor.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		105
	Proprietary	<Prtry>	Or}	[1..1]		105

Used in element(s)

"CodeOrProprietary" on page 105

5.25.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: "DocumentType3Code" on page 258

5.25.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Creditor reference type, in a proprietary form.

Datatype: "Max35Text" on page 280

5.26 CreditorReferenceType2

Definition: Specifies the type of creditor reference.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		105
	Issuer	<Issr>		[0..1]		106

Used in element(s)

"Type" on page 104

5.26.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

The **CdOrPrtry** block contains the following elements (see datatype "[CreditorReferenceType1Choice](#)" on page 105 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		105
	Proprietary	<Prtry>	Or}	[1..1]		105

5.26.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the credit reference type.

Datatype: "[Max35Text](#)" on page 280

5.27 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		106
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		107
	CityOfBirth	<CityOfBirth>		[1..1]		107
	CountryOfBirth	<CtryOfBirth>		[1..1]		107

Used in element(s)

"[DateAndPlaceOfBirth](#)" on page 166

5.27.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "[ISODate](#)" on page 275

5.27.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["Max35Text" on page 280](#)

5.27.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["Max35Text" on page 280](#)

5.27.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 257](#)

5.28 DatePeriod2

Definition: Range of time defined by a start date and an end date.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FromDate	<FrDt>		[1..1]		107
	ToDate	<ToDt>		[1..1]		107

Used in element(s)

["FromToDate" on page 238](#)

5.28.1 FromDate

XML Tag: FrDt

Presence: [1..1]

Definition: Start date of the range.

Datatype: ["ISODate" on page 275](#)

5.28.2 ToDate

XML Tag: ToDt

Presence: [1..1]

Definition: End date of the range.

Datatype: ["ISODate" on page 275](#)

5.29 DiscountAmountAndType1

Definition: Specifies the amount with a specific type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		108
	Amount	<Amt>		[1..1]		108

Used in element(s)

["DiscountAppliedAmount" on page 204](#), ["DiscountAppliedAmount" on page 206](#)

5.29.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype ["DiscountAmountType1Choice" on page 108](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		109
	Proprietary	<Prtry>	Or}	[1..1]		109

5.29.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 244](#)

5.30 DiscountAmountType1Choice

Definition: Specifies the amount type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		109
	Proprietary	<Prtry>	Or}	[1..1]		109

Used in element(s)

"Type" on page 108

5.30.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: "ExternalDiscountAmountType1Code" on page 265

5.30.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: "Max35Text" on page 280

5.31 DocumentAdjustment1

Definition: Set of elements used to provide information on the amount and reason of the document adjustment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		109
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		110
	Reason	<Rsn>		[0..1]		110
	AdditionalInformation	<AddtlInf>		[0..1]		110

Used in element(s)

"AdjustmentAmountAndReason" on page 205, "AdjustmentAmountAndReason" on page 207

5.31.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 244](#)

5.31.2 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: ["CreditDebitCode" on page 258](#)

5.31.3 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: ["Max4Text" on page 280](#)

5.31.4 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: ["Max140Text" on page 278](#)

5.32 DocumentLineIdentification1

Definition: Identifies the documents referred to in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		110
	Number	<Nb>		[0..1]		111
	RelatedDate	<RltdDt>		[0..1]		111

Used in element(s)

["Identification" on page 111](#)

5.32.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document line identification.

The **Tp** block contains the following elements (see datatype "[DocumentLineType1](#)" on page 112 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		113
	Issuer	<Issr>		[0..1]		113

5.32.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Identification of the type specified for the referred document line.

Datatype: "[Max35Text](#)" on page 280

5.32.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document line.

Datatype: "[ISODate](#)" on page 275

5.33 DocumentLineInformation1

Definition: Provides document line information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..*]		111
	Description	<Desc>		[0..1]		112
	Amount	<Amt>		[0..1]		112

Used in element(s)

"[LineDetails](#)" on page 202

5.33.1 Identification

XML Tag: Id

Presence: [1..*]

Definition: Provides identification of the document line.

The **Id** block contains the following elements (see datatype "[DocumentLineIdentification1](#)" on page 110 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		110
	Number	<Nb>		[0..1]		111
	RelatedDate	<RltdDt>		[0..1]		111

5.33.2 Description

XML Tag: Desc

Presence: [0..1]

Definition: Description associated with the document line.

Datatype: "[Max2048Text](#)" on page 279

5.33.3 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Provides details on the amounts of the document line.

The **Amt** block contains the following elements (see datatype "[RemittanceAmount3](#)" on page 206 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		206
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		206
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		207
	TaxAmount	<TaxAmt>		[0..*]		207
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		207
	RemittedAmount	<RmtdAmt>		[0..1]		208

5.34 DocumentLineType1

Definition: Specifies the type of the document line identification.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		113
	Issuer	<Issr>		[0..1]		113

Used in element(s)

"Type" on page 110

5.34.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document line identification.

The **CdOrPrtry** block contains the following elements (see datatype "[DocumentLineType1Choice](#)" on page 113 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		114
	Proprietary	<Prtry>	Or}	[1..1]		114

5.34.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document line identificationtype.

Datatype: "[Max35Text](#)" on page 280

5.35 DocumentLineType1Choice

Definition: Specifies the type of the document line identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		114
	Proprietary	<Prtry>	Or}	[1..1]		114

Used in element(s)

"CodeOrProprietary" on page 113

5.35.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Line identification type in a coded form.

Datatype: ["ExternalDocumentLineType1Code" on page 266](#)

5.35.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: ["Max35Text" on page 280](#)

5.36 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		114
	Proprietary	<Prtry>	Or}	[1..1]		114

Used in element(s)

["SchemeName" on page 135](#)

5.36.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalFinancialInstitutionIdentification1Code" on page 267](#)

5.36.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 280](#)

5.37 FinancialInstitutionIdentification18

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		115
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		115
	LEI	<LEI>		[0..1]		115
	Name	<Nm>		[0..1]		116
	PostalAddress	<PstlAdr>		[0..1]		116
	Other	<Othr>		[0..1]		116

Used in element(s)

"FinancialInstitutionIdentification" on page 28

5.37.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 247

5.37.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2](#)" on page 55 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		56
	MemberIdentification	<Mmbld>		[1..1]		56

5.37.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 277

5.37.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 278

5.37.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 167 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		168
	Department	<Dept>		[0..1]		169
	SubDepartment	<SubDept>		[0..1]		170
	StreetName	<StrtNm>		[0..1]		170
	BuildingNumber	<BldgNb>		[0..1]		171
	BuildingName	<BldgNm>		[0..1]		171
	Floor	<Flr>		[0..1]		171
	PostBox	<PstBx>		[0..1]		171
	Room	<Room>		[0..1]		171
	PostCode	<PstCd>		[0..1]		171
	TownName	<TwnNm>		[0..1]		172
	TownLocationName	<TwnLctnNm>		[0..1]		172
	DistrictName	<DstrctNm>		[0..1]		172
	CountrySubDivision	<CtrySubDvsn>		[0..1]		172
	Country	<Ctry>		[0..1]		172
	AddressLine	<AdrLine>		[0..7]		172

5.37.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on [page 135](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		135
	SchemeName	<SchmeNm>		[0..1]		135
	Issuer	<Issr>		[0..1]		136

5.38 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		117
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		117
	LEI	<LEI>		[0..1]		118
	Name	<Nm>		[0..1]		118
	PostalAddress	<PstlAdr>		[0..1]		119
	Other	<Othr>		[0..1]		122

Used in element(s)

"[FinancialInstitutionIdentification](#)" on [page 29](#)

5.38.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "[BICFIDec2014Identifier](#)" on [page 247](#)

5.38.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 56 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	57
	MemberIdentification	<Mmbld>		[1..1]	⚠	59

5.38.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 277

5.38.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 251

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/Name
 Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251
- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/Name
 Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/Name
 Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/Name
 Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251

5.38.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__1" on page 173 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		174
	Department	<Dept>		[0..1]		175
	SubDepartment	<SubDept>		[0..1]		176
	StreetName	<StrtNm>		[0..1]		177
	BuildingNumber	<BldgNb>		[0..1]		179

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BuildingName	<BldgNm>		[0..1]		180
	Floor	<Flr>		[0..1]		181
	PostBox	<PstBx>		[0..1]		182
	Room	<Room>		[0..1]		183
	PostCode	<PstCd>		[0..1]		184
	TownName	<TwnNm>		[0..1]	 	185
	TownLocationName	<TwnLctnNm>		[0..1]		188
	DistrictName	<DstrctNm>		[0..1]		189
	CountrySubDivision	<CtrySubDvsn>		[0..1]		190
	Country	<Ctry>		[0..1]		191
	AddressLine	<AdrLine>		[0..7]	 R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2]	192

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- **on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.38.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 135 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		135
	SchemeName	<SchmeNm>		[0..1]		135
	Issuer	<Issr>		[0..1]		136

Usage Guideline details

- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/Other) is removed.

- This element([pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/Other](#)) is removed.

5.39 FinancialInstitutionIdentification18__2

Definition: Specifies the details to identify a financial institution.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		123
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		124
	LEI	<LEI>		[0..1]		124
	Name	<Nm>		[0..1]		124
	PostalAddress	<PstlAdr>		[0..1]		125
	Other	<Othr>		[0..1]		126

Used in element(s)

"[FinancialInstitutionIdentification](#)" on page 36

5.39.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "[BICFIDec2014Identifier](#)" on page 247

Usage Guideline details

- on [pacs.009.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [pacs.009.001.08/CreditTransferTransactionInformation/InstructingAgent/FinancialInstitutionIdentification/BICFI](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [pacs.009.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [pacs.009.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/InstructedAgent/FinancialInstitutionIdentification/BICFI

This element is now mandatory, the minimum occurrence has been changed to : 1

5.39.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2_1" on page 56 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		57
	MemberIdentification	<Mmbld>		[1..1]		59

5.39.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 277

5.39.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 278

Usage Guideline details

- This element(pacs.009.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructedAgent/FinancialInstitutionIdentification/Name) is removed.

- This element(pacs.009.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.009.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.009.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructingAgent/FinancialInstitutionIdentification/Name) is removed.

5.39.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 167 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		168
	Department	<Dept>		[0..1]		169
	SubDepartment	<SubDept>		[0..1]		170
	StreetName	<StrtNm>		[0..1]		170
	BuildingNumber	<BldgNb>		[0..1]		171
	BuildingName	<BldgNm>		[0..1]		171
	Floor	<Flr>		[0..1]		171
	PostBox	<PstBx>		[0..1]		171
	Room	<Room>		[0..1]		171
	PostCode	<PstCd>		[0..1]		171
	TownName	<TwnNm>		[0..1]		172
	TownLocationName	<TwnLctnNm>		[0..1]		172
	DistrictName	<DstrctNm>		[0..1]		172
	CountrySubDivision	<CtrySubDvsn>		[0..1]		172
	Country	<Ctry>		[0..1]		172
	AddressLine	<AdrLine>		[0..7]		172

Usage Guideline details

- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructedAgent/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.009.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.009.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.009.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.009.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructingAgent/FinancialInstitutionIdentification/PostalAddress) is removed.

5.39.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 135 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		135
	SchemeName	<SchmeNm>		[0..1]		135
	Issuer	<Issr>		[0..1]		136

Usage Guideline details

- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructedAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/InstructingAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.009.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.

- This element([pacs.009.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other](#)) is removed.
- This element([pacs.009.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other](#)) is removed.

5.40 Garnishment3

Definition: Provides remittance information about a payment for garnishment-related purposes.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		127
	Garnishee	<Grnshee>		[0..1]		127
	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]		128
	ReferenceNumber	<RefNb>		[0..1]		128
	Date	<Dt>		[0..1]		129
	RemittedAmount	<RmtdAmt>		[0..1]		129
	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrncInd>		[0..1]		129
	EmployeeTerminationIndicator	<MplyeeTermntnInd>		[0..1]		129

Used in element(s)

["GarnishmentRemittance" on page 225](#)

5.40.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies the type of garnishment.

The **Tp** block contains the following elements (see datatype ["GarnishmentType1" on page 129](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		129
	Issuer	<Issr>		[0..1]		130

5.40.2 Garnishee

XML Tag: Grnshee

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the garnisher.

The **Grnshee** block contains the following elements (see datatype "[PartyIdentification135](#)" on [page 155](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157
	ContactDetails	<CtctDtls>		[0..1]		158

5.40.3 GarnishmentAdministrator

XML Tag: GrnshmtAdmstr

Presence: [0..1]

Definition: Party on the credit side of the transaction who administers the garnishment on behalf of the ultimate beneficiary.

The **GrnshmtAdmstr** block contains the following elements (see datatype "[PartyIdentification135](#)" on [page 155](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157
	ContactDetails	<CtctDtls>		[0..1]		158

5.40.4 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Reference information that is specific to the agency receiving the garnishment.

Datatype: "[Max140Text](#)" on [page 278](#)

5.40.5 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date of payment which garnishment was taken from.

Datatype: ["ISODate" on page 275](#)

5.40.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 244](#)

5.40.7 FamilyMedicalInsuranceIndicator

XML Tag: FmlyMdclInsrncInd

Presence: [0..1]

Definition: Indicates if the person to whom the garnishment applies (that is, the ultimate debtor) has family medical insurance coverage available.

Datatype: ["TrueFalseIndicator" on page 288](#)

5.40.8 EmployeeTerminationIndicator

XML Tag: MplyeeTermntnInd

Presence: [0..1]

Definition: Indicates if the employment of the person to whom the garnishment applies (that is, the ultimate debtor) has been terminated.

Datatype: ["TrueFalseIndicator" on page 288](#)

5.41 GarnishmentType1

Definition: Specifies the type of garnishment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		129
	Issuer	<Issr>		[0..1]		130

Used in element(s)

["Type" on page 127](#)

5.41.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the garnishment.

The **CdOrPrtry** block contains the following elements (see datatype "[GarnishmentType1Choice](#)" on [page 130](#) for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		130
	Proprietary	<Prtry>	Or}	[1..1]		131

5.41.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the garnishment type.

Datatype: "[Max35Text](#)" on [page 280](#)

5.42 GarnishmentType1Choice

Definition: Specifies the type of garnishment.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		130
	Proprietary	<Prtry>	Or}	[1..1]		131

Used in element(s)

"[CodeOrProprietary](#)" on [page 129](#)

5.42.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Garnishment type in a coded form.

Would suggest this to be an External Code List to contain:

GNCS Garnishment from a third party payer for Child Support

GNDP Garnishment from a Direct Payer for Child Support

GTPP Garnishment from a third party payer to taxing agency.

Datatype: ["ExternalGarnishmentType1Code" on page 268](#)

5.42.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of garnishment.

Datatype: ["Max35Text" on page 280](#)

5.43 GenericAccountIdentification1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		131
	SchemeName	<SchmeNm>		[0..1]		131
	Issuer	<Issr>		[0..1]		132

Used in element(s)

["Other" on page 23](#)

5.43.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: ["Max34Text" on page 279](#)

5.43.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["AccountSchemeName1Choice" on page 24](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		25

5.43.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 280

5.44 GenericAccountIdentification1__1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		132
	SchemeName	<SchmeNm>		[0..1]		133
	Issuer	<Issr>		[0..1]		134

Used in element(s)

"Other" on page 24

5.44.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR_RestrictedFINXMax34Text" on page 253

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAccount/Identification/Other/Identification
 Type changed to: CBPR_RestrictedFINXMax34Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other/Identification
 Type changed to: CBPR_RestrictedFINXMax34Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1Account/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3Account/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2Account/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1Account/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3Account/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgentAccount/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2Account/Identification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax34Text on page 253](#)

5.44.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountScheme-Name1Choice__1" on page 25 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		26

5.44.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 253

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2Account/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1Account/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1Account/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2Account/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3Account/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3Account/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

5.45 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		135
	SchemeName	<SchmeNm>		[0..1]		135
	Issuer	<Issr>		[0..1]		136

Used in element(s)

"Other" on page 116, "Other" on page 122, "Other" on page 126

5.45.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: ["Max35Text" on page 280](#)

5.45.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["FinancialIdentificationScheme-Name1Choice" on page 114](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		114
	Proprietary	<Prtry>	Or}	[1..1]		114

5.45.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 280

5.46 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		136
	Issuer	<Issr>		[1..1]		136
	SchemeName	<SchmeNm>		[0..1]		136

Used in element(s)

"Proprietary" on page 27

5.46.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 261

5.46.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 280

5.46.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max35Text" on page 280

5.47 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		137
	SchemeName	<SchmeNm>		[0..1]		137
	Issuer	<Issr>		[0..1]		138

Used in element(s)

"Other" on page 150

5.47.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 280

5.47.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "OrganisationIdentificationSchemeName1Choice" on page 151 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		151
	Proprietary	<Prtry>	Or}	[1..1]		151

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/UnderlyingCustomerCreditTransfer/Debtor/Identification/OrganisationIdentification/Other/SchemeName

This element is now mandatory, the minimum occurrence has been changed to : 1

5.47.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 280

5.48 GenericPersonIdentification1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		138
	SchemeName	<SchmeNm>		[0..1]		138
	Issuer	<Issr>		[0..1]		139

Used in element(s)

"Other" on page 166

5.48.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 280

5.48.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationSchemeName1Choice](#)" on page 167 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		167
	Proprietary	<Prtry>	Or}	[1..1]		167

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/UnderlyingCustomerCreditTransfer/Debtor/Identification/PrivateIdentification/Other/SchemeName

This element is now mandatory, the minimum occurrence has been changed to : 1

5.48.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 280

5.49 GroupHeader93__1

Definition: Set of characteristics shared by all individual transactions included in the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		140
	CreationDateTime	<CreDtTm>		[1..1]		140
	BatchBooking	<BtchBookg>		[0..1]		140
	NumberOfTransactions	<NbOfTxs>		[1..1]		141
	ControlSum	<CtrlSum>		[0..1]		141
	TotalInterbankSettlementAmount	<TtlIntrBkSttlmAmt>		[0..1]		141
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		141
	SettlementInformation	<SttlmInf>		[1..1]		142
	PaymentTypeInformation	<PmtTpInf>		[0..1]		142
	InstructingAgent	<InstgAgt>		[0..1]		143
	InstructedAgent	<InstdAgt>		[0..1]		143

Rules

R29 TotalInterbankSettlementAmountAndDateRule ✓

If TotalInterbankSettlementAmount is present, then InterbankSettlementDate must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00044
- *Error Text:* Invalid message content for group header interbank settlement date.

Used in element(s)

"GroupHeader" on page 19

5.49.1 **MessageIdentification**

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 253

Usage Guideline details

- **on pacs.009.001.08/GroupHeader/MessageIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 253

5.49.2 **CreationDateTime**

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: "CBPR_DateTime" on page 250

Usage Guideline details

- **on pacs.009.001.08/GroupHeader/CreationDateTime**
Type changed to: CBPR_DateTime on page 250

5.49.3 **BatchBooking**

XML Tag: BtchBookg

Presence: [0..1]

Definition: Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.

Usage: Batch booking is used to request and not order a possible batch booking.

Datatype: ["BatchBookingIndicator" on page 248](#)

Usage Guideline details

- This element([pacs.009.001.08/GroupHeader/BatchBooking](#)) is removed.

5.49.4 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [1..1]

Definition: Number of individual transactions contained in the message.

Datatype: ["Max15NumericText" on page 278](#)

Usage Guideline details

- on [pacs.009.001.08/GroupHeader/NumberOfTransactions](#)
Single value: 1

5.49.5 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: ["DecimalNumber" on page 258](#)

Usage Guideline details

- This element([pacs.009.001.08/GroupHeader/ControlSum](#)) is removed.

5.49.6 TotalInterbankSettlementAmount

XML Tag: TtlIntrBkSttlmAmt

Presence: [0..1]

Definition: Total amount of money moved between the instructing agent and the instructed agent.

Datatype: ["ActiveCurrencyAndAmount" on page 243](#)

Usage Guideline details

- This element([pacs.009.001.08/GroupHeader/TotalInterbankSettlementAmount](#)) is removed.

5.49.7 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "ISODate" on page 275

Usage Guideline details

- This element(pacs.009.001.08/GroupHeader/InterbankSettlementDate) is removed.

5.49.8 SettlementInformation

XML Tag: SttlmInf

Presence: [1..1]

Definition: Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed.

The **SttlmInf** block contains the following elements (see datatype "SettlementInstruction7__1" on page 212 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementMethod	<SttlmMtd>		[1..1]		215
	SettlementAccount	<SttlmAcct>		[0..1]	🚫 ⚠	215
	ClearingSystem	<ClrSys>		[0..1]	🚫	215
	InstructingReimbursementAgent	<InstgRmbrsmntAgt>		[0..1]	⚠	216
	InstructingReimbursementAgentAccount	<InstgRmbrsmntAgtAcct>		[0..1]		217
	InstructedReimbursementAgent	<InstdRmbrsmntAgt>		[0..1]	⚠	217
	InstructedReimbursementAgentAccount	<InstdRmbrsmntAgtAcct>		[0..1]		218
	ThirdReimbursementAgent	<ThrdRmbrsmntAgt>		[0..1]	🚫	219
	ThirdReimbursementAgentAccount	<ThrdRmbrsmntAgtAcct>		[0..1]	🚫	219

5.49.9 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "PaymentTypeInformation28" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		162
	ClearingChannel	<ClrChan>		[0..1]		162
	ServiceLevel	<SvcLv>		[0..*]		163
	LocalInstrument	<LclInstrm>		[0..1]		163
	CategoryPurpose	<CtgyPurp>		[0..1]		163

Usage Guideline details

- This element(pacs.009.001.08/GroupHeader/PaymentTypeInfoInformation) is removed.

5.49.10 InstructingAgent

XML Tag: InstgAgt

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

The **InstgAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 28 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

Usage Guideline details

- This element(pacs.009.001.08/GroupHeader/InstructingAgent) is removed.

5.49.11 InstructedAgent

XML Tag: InstdAgt

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

The **InstdAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 28 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

Usage Guideline details

- This element(pacs.009.001.08/GroupHeader/InstructedAgent) is removed.

5.50 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		144
	Identification	<Id>		[1..1]		144

Used in element(s)

"MarketPractice" on page 15

5.50.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "Max350Text" on page 279

5.50.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: "Max2048Text" on page 279

5.51 InstructionForCreditorAgent1

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		145
	InstructionInformation	<InstrInf>		[0..1]		145

Used in element(s)

"InstructionForCreditorAgent" on page 102

5.51.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

Datatype: "Instruction3Code" on page 275

5.51.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

Datatype: "Max140Text" on page 278

5.52 InstructionForCreditorAgent2__1

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		146
	InstructionInformation	<InstrInf>		[0..1]	⚠	146

Used in element(s)

["InstructionForCreditorAgent" on page 85](#)

5.52.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

Datatype: ["Instruction5Code" on page 276](#)

5.52.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

Datatype: ["CBPR_RestrictedFINXMax140Text" on page 250](#)

Usage Guideline details

- **on pacs.009.001.08/CreditTransferTransactionInformation/InstructionForCreditorAgent/InstructionInformation**

Type changed to: [CBPR_RestrictedFINXMax140Text on page 250](#)

5.53 InstructionForNextAgent1

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by an other agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the other agent.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		146
	InstructionInformation	<InstrInf>		[0..1]		147

Used in element(s)

["InstructionForNextAgent" on page 102](#)

5.53.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the next agent in the payment chain.

Datatype: ["Instruction4Code" on page 276](#)

5.53.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the next agent that is bilaterally agreed or specific to a user community.

Datatype: ["Max140Text" on page 278](#)

5.54 InstructionForNextAgent1__1

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by an other agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the other agent.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		147
	InstructionInformation	<InstrInf>		[0..1]		147

Used in element(s)

["InstructionForNextAgent" on page 86](#)

5.54.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the next agent in the payment chain.

Datatype: ["Instruction4Code" on page 276](#)

Usage Guideline details

- This element([pacs.009.001.08/CreditTransferTransactionInformation/InstructionForNextAgent/Code](#)) is removed.

5.54.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the next agent that is bilaterally agreed or specific to a user community.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 253](#)

Usage Guideline details

- on [pacs.009.001.08/CreditTransferTransactionInformation/InstructionForNextAgent/InstructionInformation](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

5.55 LocalInstrument2Choice

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		148
	Proprietary	<Prtry>	Or}	[1..1]		148

Used in element(s)

["LocalInstrument" on page 163](#)

5.55.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: ["ExternalLocalInstrument1Code" on page 268](#)

5.55.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: ["Max35Text" on page 280](#)

5.56 LocalInstrument2Choice__1

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		149
	Proprietary	<Prtry>	Or}	[1..1]		149

Used in element(s)

["LocalInstrument" on page 165](#)

5.56.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: ["ExternalLocalInstrument1Code" on page 268](#)

5.56.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 253](#)

Usage Guideline details

- on [pacs.009.001.08/CreditTransferTransactionInformation/PaymentTypeInformation/LocalInstrument/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

5.57 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		150
	LEI	<LEI>		[0..1]		150
	Other	<Othr>		[0..*]		150

Used in element(s)

["OrganisationIdentification" on page 152](#)

5.57.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: ["AnyBICDec2014Identifier" on page 247](#)

Usage Guideline details

- This element([pacs.009.001.08/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC](#)) is removed.
- This element([pacs.009.001.08/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC](#)) is removed.

5.57.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: ["LEIIdentifier" on page 277](#)

Usage Guideline details

- This element([pacs.009.001.08/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/LEI](#)) is removed.
- This element([pacs.009.001.08/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/LEI](#)) is removed.

5.57.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype ["GenericOrganisationIdentification1" on page 137](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		137
	SchemeName	<SchmeNm>		[0..1]		137

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Issuer	</Issr>		[0..1]		138

Usage Guideline details

- This element(pacs.009.001.08/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(pacs.009.001.08/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(pacs.009.001.08/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(pacs.009.001.08/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.

5.58 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		151
	Proprietary	<Prtry>	Or}	[1..1]		151

Used in element(s)

["SchemeName" on page 137](#)

5.58.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalOrganisationIdentification1Code" on page 269](#)

5.58.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 280](#)

5.59 OtherContact1

Definition: Communication device number or electronic address used for communication.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		152
	Identification	<Id>		[0..1]		152

Used in element(s)

"Other" on page 62

5.59.1 ChannelType

XML Tag: ChanlTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 280

5.59.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 278

5.60 Party38Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		152
	PrivateIdentification	<PrvtId>	Or}	[1..1]		153

Used in element(s)

"Identification" on page 157

5.60.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification29](#)" on page 149 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		150
	LEI	<LEI>		[0..1]		150
	Other	<Othr>		[0..*]		150

5.60.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification13](#)" on page 166 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		166
	Other	<Othr>		[0..*]		166

Usage Guideline details

- This element(pacs.009.001.08/.header/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(pacs.009.001.08/.header/Related/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(pacs.009.001.08/.header/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(pacs.009.001.08/.header/Related/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.

5.61 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		154
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		154

Used in element(s)

"From" on page 13, "From" on page 40, "To" on page 14, "To" on page 40

5.61.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 155 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157
	ContactDetails	<CtctDtls>		[0..1]		158

Usage Guideline details

- This element(pacs.009.001.08/.header/Related/From/OrganisationIdentification) is removed.
- This element(pacs.009.001.08/.header/To/OrganisationIdentification) is removed.
- This element(pacs.009.001.08/.header/Related/To/OrganisationIdentification) is removed.
- This element(pacs.009.001.08/.header/From/OrganisationIdentification) is removed.

5.61.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__2](#)" on page 36 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		36
	BranchIdentification	<BrnchId>		[0..1]	🚫	36

5.62 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]	🚫	155
	PostalAddress	<PstlAdr>		[0..1]	🚫	156
	Identification	<Id>		[0..1]	🚫	157
	CountryOfResidence	<CtryOfRes>		[0..1]	🚫	157
	ContactDetails	<CtctDtls>		[0..1]	🚫	158

Used in element(s)

"Creditor" on page 100, "Debtor" on page 93, "Garnishee" on page 127, "GarnishmentAdministrator" on page 128, "InitiatingParty" on page 93, "Invoicee" on page 224, "Invoicer" on page 223, "OrganisationIdentification" on page 154, "UltimateCreditor" on page 101, "UltimateDebtor" on page 92

5.62.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "[Max140Text](#)" on page 278

Usage Guideline details

- This element(pacs.009.001.08/.header/Related/To/OrganisationIdentification/Name) is removed.
- This element(pacs.009.001.08/.header/From/OrganisationIdentification/Name) is removed.
- This element(pacs.009.001.08/.header/To/OrganisationIdentification/Name) is removed.

- This element(pacs.009.001.08/.header/Related/From/OrganisationIdentification/Name) is removed.

5.62.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 167 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		168
	Department	<Dept>		[0..1]		169
	SubDepartment	<SubDept>		[0..1]		170
	StreetName	<StrtNm>		[0..1]		170
	BuildingNumber	<BldgNb>		[0..1]		171
	BuildingName	<BldgNm>		[0..1]		171
	Floor	<Flr>		[0..1]		171
	PostBox	<PstBx>		[0..1]		171
	Room	<Room>		[0..1]		171
	PostCode	<PstCd>		[0..1]		171
	TownName	<TwnNm>		[0..1]		172
	TownLocationName	<TwnLctnNm>		[0..1]		172
	DistrictName	<DstrctNm>		[0..1]		172
	CountrySubDivision	<CtrySubDvsn>		[0..1]		172
	Country	<Ctry>		[0..1]		172
	AddressLine	<AdrLine>		[0..7]		172

Usage Guideline details

- This element(pacs.009.001.08/.header/Related/To/OrganisationIdentification/PostalAddress) is removed.
- This element(pacs.009.001.08/.header/To/OrganisationIdentification/PostalAddress) is removed.

- This element(pacs.009.001.08/.header/From/OrganisationIdentification/PostalAddress) is removed.
- This element(pacs.009.001.08/.header/Related/From/OrganisationIdentification/PostalAddress) is removed.

5.62.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice" on page 152 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		152
	PrivateIdentification	<PrvtId>	Or}	[1..1]	🚫	153

Usage Guideline details

- This element(pacs.009.001.08/.header/To/OrganisationIdentification/Identification) is removed.
- This element(pacs.009.001.08/.header/From/OrganisationIdentification/Identification) is removed.
- This element(pacs.009.001.08/.header/Related/To/OrganisationIdentification/Identification) is removed.
- This element(pacs.009.001.08/.header/Related/From/OrganisationIdentification/Identification) is removed.

5.62.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 257

Usage Guideline details

- This element(pacs.009.001.08/.header/Related/To/OrganisationIdentification/CountryOfResidence) is removed.
- This element(pacs.009.001.08/.header/To/OrganisationIdentification/CountryOfResidence) is removed.

- This element(pacs.009.001.08/.header/From/OrganisationIdentification/CountryOfResidence) is removed.
- This element(pacs.009.001.08/.header/Related/From/OrganisationIdentification/CountryOfResidence) is removed.

5.62.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 60 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		61
	Name	<Nm>		[0..1]		61
	PhoneNumber	<PhneNb>		[0..1]		61
	MobileNumber	<MobNb>		[0..1]		61
	FaxNumber	<FaxNb>		[0..1]		62
	EmailAddress	<EmailAdr>		[0..1]		62
	EmailPurpose	<EmailPurp>		[0..1]		62
	JobTitle	<JobTitl>		[0..1]		62
	Responsibility	<Rspnsblty>		[0..1]		62
	Department	<Dept>		[0..1]		62
	Other	<Othr>		[0..*]		62
	PreferredMethod	<PrefrdMtd>		[0..1]		63

Usage Guideline details

- This element(pacs.009.001.08/.header/Related/From/OrganisationIdentification/ContactDetails) is removed.
- This element(pacs.009.001.08/.header/Related/To/OrganisationIdentification/ContactDetails) is removed.
- This element(pacs.009.001.08/.header/To/OrganisationIdentification/ContactDetails) is removed.
- This element(pacs.009.001.08/.header/From/OrganisationIdentification/ContactDetails) is removed.

5.63 PaymentIdentification7__1

Definition: Provides further means of referencing a payment transaction.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionIdentification	<InstrId>		[0..1]	M ⚠	159
	EndToEndIdentification	<EndToEndId>		[1..1]	⚠	160
	TransactionIdentification	<TxId>		[0..1]	⚠	161
	UETR	<UETR>		[0..1]	M	161
	ClearingSystemReference	<ClrSysRef>		[0..1]	⚠	161

Rules

R54 TransactionIdentificationPresenceRule

TransactionIdentification or UETR must be present. Both may be present

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00420
- *Error Text:* No transaction identification is present

Used in element(s)

"PaymentIdentification" on page 67

5.63.1 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 251

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PaymentIdentification/InstructionIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/PaymentIdentification/InstructionIdentification
Type changed to: CBPR_RestrictedFINXMax16Text on page 251
- on pacs.009.001.08/CreditTransferTransactionInformation/PaymentIdentification/InstructionIdentification
Synonym (Transaction Reference Number): 20
- on pacs.009.001.08/CreditTransferTransactionInformation/PaymentIdentification/InstructionIdentification
 - **CBPR_Instruction_Identification_FormalRule:**

This element must not start or end with a slash '/' and must not contain two consecutive slashes '//'.

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/CreditTransferTransactionInformation/PaymentIdentification/InstructionIdentification],
the value of every occurrence of [InstructionIdentification] must not comply with the following XML pattern : '(/.*)|(.*//)|(.*//.*)'

5.63.2 EndToEndIdentification

XML Tag: EndToEndId

Presence: [1..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 253

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PaymentIdentification/EndToEndIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 253
- on pacs.009.001.08/CreditTransferTransactionInformation/PaymentIdentification/EndToEndIdentification
 - **CBPR_End_To_End_Identification_FormalRule:**

In the E2E identification, the below restrictions apply to the first 16 characters:

- The first one and the 16th one cannot be "/" and
- The string of 16 characters cannot contain "/"

For each [Full Message/Document/FinancialInstitutionCreditTransferV08/Credit-TransferTransactionInformation/PaymentIdentification/EndToEndIdentification], the value of every occurrence of [EndToEndIdentification] must not comply with the following XML pattern : '/.*' and the value of every occurrence of [EndToEndIdentification] must not comply with the following XML pattern : '.{15}/.*' and the value of every occurrence of [EndToEndIdentification] must not comply with the following XML pattern : '.{0,14}/.*'

5.63.3 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: CBPR_RestrictedFINXMax35Text on page 253

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PaymentIdentification/TransactionIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 253

5.63.4 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: UUIDv4Identifier on page 289

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PaymentIdentification/UETR

This element is now mandatory, the minimum occurrence has been changed to : 1

5.63.5 ClearingSystemReference

XML Tag: ClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 253](#)

Usage Guideline details

- on [pacs.009.001.08/CreditTransferTransactionInformation/PaymentIdentification/ClearingSystemReference](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

5.64 PaymentTypeInformation28

Definition: Provides further details of the type of payment.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		162
	ClearingChannel	<ClrChanl>		[0..1]		162
	ServiceLevel	<SvcLvl>		[0..*]		163
	LocalInstrument	<LclInstrm>		[0..1]		163
	CategoryPurpose	<CtgyPurp>		[0..1]		163

Used in element(s)

["PaymentTypeInformation" on page 142](#)

5.64.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: ["Priority2Code" on page 284](#)

5.64.2 ClearingChannel

XML Tag: ClrChanl

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: ["ClearingChannel2Code" on page 256](#)

5.64.3 ServiceLevel

XML Tag: SvcLvl

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype "[ServiceLevel8Choice](#)" on page 210 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		210
	Proprietary	<Prtry>	Or}	[1..1]		210

5.64.4 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype "[LocalInstrument2Choice](#)" on page 148 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		148
	Proprietary	<Prtry>	Or}	[1..1]		148

5.64.5 CategoryPurpose

XML Tag: Ctgypurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **Ctgypurp** block contains the following elements (see datatype "[CategoryPurpose1Choice](#)" on page 51 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		51
	Proprietary	<Prtry>	Or}	[1..1]		52

5.65 PaymentTypeInformation28__1

Definition: Provides further details of the type of payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		164
	ClearingChannel	<ClrChanl>		[0..1]		164
	ServiceLevel	<SvcLvl>		[0..*]	R[0..3]	164
	LocalInstrument	<LclInstrm>		[0..1]		165
	CategoryPurpose	<CtgyPurp>		[0..1]		165

Used in element(s)

"PaymentTypeInformation" on page 68

5.65.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: "Priority2Code" on page 284

5.65.2 ClearingChannel

XML Tag: ClrChanl

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: "ClearingChannel2Code" on page 256

5.65.3 ServiceLevel

XML Tag: SvcLvl

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype "[ServiceLevel8Choice__1](#)" on [page 210](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		210
	Proprietary	<Prtry>	Or}	[1..1]	⚠	211

Usage Guideline details

- on [pacs.009.001.08/CreditTransferTransactionInformation/PaymentTypeInformation/ServiceLevel](#)

This element has change repeatability, the maximum occurrence has been changed to : 3

5.65.4 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype "[LocalInstrument2Choice__1](#)" on [page 148](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		149
	Proprietary	<Prtry>	Or}	[1..1]	⚠	149

5.65.5 CategoryPurpose

XML Tag: Ctgypurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **Ctgypurp** block contains the following elements (see datatype "[CategoryPurpose1Choice__1](#)" on [page 52](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		52
	Proprietary	<Prtry>	Or}	[1..1]		52

5.66 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		166
	Other	<Othr>		[0..*]		166

Used in element(s)

"PrivateIdentification" on page 153

5.66.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1" on page 106 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		106
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		107
	CityOfBirth	<CityOfBirth>		[1..1]		107
	CountryOfBirth	<CtryOfBirth>		[1..1]		107

5.66.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on [page 138](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		138
	SchemeName	<SchmeNm>		[0..1]		138
	Issuer	<Issr>		[0..1]		139

5.67 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		167
	Proprietary	<Prtry>	Or}	[1..1]		167

Used in element(s)

"[SchemeName](#)" on [page 138](#)

5.67.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "[ExternalPersonIdentification1Code](#)" on [page 270](#)

5.67.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "[Max35Text](#)" on [page 280](#)

5.68 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		168
	Department	<Dept>		[0..1]		169
	SubDepartment	<SubDept>		[0..1]		170
	StreetName	<StrtNm>		[0..1]		170
	BuildingNumber	<BldgNb>		[0..1]		171
	BuildingName	<BldgNm>		[0..1]		171
	Floor	<Flr>		[0..1]		171
	PostBox	<PstBx>		[0..1]		171
	Room	<Room>		[0..1]		171
	PostCode	<PstCd>		[0..1]		171
	TownName	<TwnNm>		[0..1]		172
	TownLocationName	<TwnLctnNm>		[0..1]		172
	DistrictName	<DstrctNm>		[0..1]		172
	CountrySubDivision	<CtrySubDvsn>		[0..1]		172
	Country	<Ctry>		[0..1]		172
	AddressLine	<AdrLine>		[0..7]		172

Used in element(s)

"PostalAddress" on page 38, "PostalAddress" on page 116, "PostalAddress" on page 156,
 "PostalAddress" on page 125

5.68.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 27 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		27
	Proprietary	<Prtry>	Or}	[1..1]		27

Usage Guideline details

- This element(pacs.009.001.08/CreditTransferTransactionInformation/Debtor/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/UnderlyingCustomer-CreditTransfer/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/UnderlyingCustomer-CreditTransfer/InitiatingParty/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/ThirdReimbursementAgent/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Creditor/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/BranchIdentification/PostalAddress/AddressType) is removed.

5.68.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 280

Usage Guideline details

- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/BranchIdentification/PostalAddress/Department) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/BranchIdentification/PostalAddress/Department) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/BranchIdentification/PostalAddress/Department) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/BranchIdentification/PostalAddress/Department) is removed.

- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/BranchIdentification/PostalAddress/Department) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/ThirdReimbursementAgent/BranchIdentification/PostalAddress/Department) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Creditor/BranchIdentification/PostalAddress/Department) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Debtor/BranchIdentification/PostalAddress/Department) is removed.

5.68.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 280

Usage Guideline details

- This element(pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/ThirdReimbursementAgent/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Creditor/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Debtor/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/BranchIdentification/PostalAddress/SubDepartment) is removed.

5.68.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max70Text" on page 280

5.68.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 278

5.68.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max35Text" on page 280

5.68.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 280

5.68.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 278

5.68.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 280

5.68.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 278

5.68.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 280

5.68.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 280

5.68.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 280

5.68.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 280

5.68.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 257

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/UnderlyingCustomerCreditTransfer/InitiatingParty/PostalAddress/Country

This element is now mandatory, the minimum occurrence has been changed to : 1

5.68.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 280

Usage Guideline details

- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/ThirdReimbursementAgent/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/UnderlyingCustomer-CreditTransfer/DebtorAgent/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Debtor/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Creditor/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/UnderlyingCustomer-CreditTransfer/InitiatingParty/PostalAddress/AddressLine) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/BranchIdentification/PostalAddress/AddressLine) is removed.

5.69 PostalAddress24__1

Definition: Information that locates and identifies a specific address, as defined by postal services.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	🚫	174
	Department	<Dept>		[0..1]	⚠	175
	SubDepartment	<SubDept>		[0..1]	⚠	176
	StreetName	<StrtNm>		[0..1]	⚠	177
	BuildingNumber	<BldgNb>		[0..1]	⚠	179

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BuildingName	<BldgNm>		[0..1]		180
	Floor	<Flr>		[0..1]		181
	PostBox	<PstBx>		[0..1]		182
	Room	<Room>		[0..1]		183
	PostCode	<PstCd>		[0..1]		184
	TownName	<TwnNm>		[0..1]	 	185
	TownLocationName	<TwnLctnNm>		[0..1]		188
	DistrictName	<DstrctNm>		[0..1]		189
	CountrySubDivision	<CtrySubDvsn>		[0..1]		190
	Country	<Ctry>		[0..1]		191
	AddressLine	<AdrLine>		[0..7]	 R[0..2] R[0..2] R[0..2] R	192

Used in element(s)

"PostalAddress" on page 119

5.69.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "[AddressType3Choice](#)" on page 27 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		27
	Proprietary	<Prtry>	Or}	[1..1]		27

Usage Guideline details

- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

5.69.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 254

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

5.69.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 254](#)

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254

5.69.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 254

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254

5.69.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 252

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 252
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/BuildingNumber](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

5.69.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 254](#)

Usage Guideline details

- on [pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on [pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on [pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on [pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on [pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on [pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on [pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on [pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on [pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/BuildingName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/BuildingName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/BuildingName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

5.69.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 254](#)

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

5.69.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 252](#)

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

5.69.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 254](#)

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/Room

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

5.69.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 252](#)

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 252](#)

5.69.11 TownName

XML Tag: TwNnm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 254

Usage Guideline details

- **on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/TownName**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254
- **on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 254

5.69.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 254

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/TownLocationName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

5.69.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 254](#)

Usage Guideline details

- on [pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on [pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on [pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/DistrictName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/DistrictName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

5.69.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 254](#)

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 254](#)

5.69.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 257](#)

Usage Guideline details

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/Country

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/Country

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/Country

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/Country

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/Country

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.69.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 254

Usage Guideline details

- **on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- **on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.009.001.08/CreditTransferTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254

- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 254

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/Creditor/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 254](#)

5.70 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

❌ Removed -
 ❌ Partial Removed -
 ◆ Ignored -
 ◆ Partial Ignored -
 ⚠️ Details below -
 M Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		195
	Identification	<Id>		[1..1]		195

Used in element(s)

["Proxy" on page 45](#)

5.70.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "[ProxyAccountType1Choice](#)" on page 198 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		198
	Proprietary	<Prtry>	Or}	[1..1]		198

5.70.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "[Max2048Text](#)" on page 279

5.71 ProxyAccountIdentification1__1

Definition: Information related to a proxy identification of the account.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		195
	Identification	<Id>		[1..1]		197

Used in element(s)

"[Proxy](#)" on page 48

5.71.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "[ProxyAccountType1Choice__1](#)" on page 198 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		199
	Proprietary	<Prtry>	Or}	[1..1]		199

Usage Guideline details

- **on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1Account/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2Account/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3Account/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1Account/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2Account/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3Account/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAccount/Proxy/Type**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.71.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "CBPR_RestrictedFINXMax320Text_Extended" on page 252

Usage Guideline details

- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1Account/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252
- **on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2Account/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1Account/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3Account/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252
- **on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252
- **on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgentAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252
- **on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3Account/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252
- **on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgentAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252
- **on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2Account/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 252

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended](#) on page 252
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgentAccount/Proxy/Identification
Type changed to: [CBPR_RestrictedFINXMax320Text_Extended](#) on page 252

5.72 ProxyAccountType1Choice

Definition: Specifies the scheme used for the identification of an account alias.

⊖ Removed - ⊖ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		198
	Proprietary	<Prtry>	Or}	[1..1]		198

Used in element(s)

"Type" on page 195

5.72.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalProxyAccountType1Code"](#) on page 271

5.72.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text"](#) on page 280

5.73 ProxyAccountType1Choice__1

Definition: Specifies the scheme used for the identification of an account alias.

⊖ Removed - ⊖ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		199

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		199

Used in element(s)

["Type" on page 195](#)

5.73.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalProxyAccountType1Code" on page 271](#)

5.73.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 253](#)

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent3Account/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgentAccount/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent2Account/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAgentAccount/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgentAccount/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent1Account/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent1Account/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/PreviousInstructingAgent2Account/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/DebtorAccount/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAccount/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/IntermediaryAgent3Account/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)
- on pacs.009.001.08/CreditTransferTransactionInformation/CreditorAgentAccount/Proxy/Type/Proprietary
Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

5.74 Purpose2Choice__1

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		200
	Proprietary	<Prtry>	Or}	[1..1]		201

Used in element(s)

["Purpose" on page 86](#)

5.74.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: ["ExternalPurpose1Code" on page 271](#)

5.74.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 253

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/Purpose/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 253

5.75 ReferredDocumentInformation7

Definition: Set of elements used to identify the documents referred to in the remittance information.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		201
	Number	<Nb>		[0..1]		202
	RelatedDate	<RltdDt>		[0..1]		202
	LineDetails	<LineDtls>		[0..*]		202

Used in element(s)

"ReferredDocumentInformation" on page 222

5.75.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document.

The **Tp** block contains the following elements (see datatype "ReferredDocumentType4" on page 203 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		203
	Issuer	<Issr>		[0..1]		203

5.75.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: "Max35Text" on page 280

5.75.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: "ISODate" on page 275

5.75.4 LineDetails

XML Tag: LineDtls

Presence: [0..*]

Definition: Set of elements used to provide the content of the referred document line.

The **LineDtls** block contains the following elements (see datatype "[DocumentLineInformation1](#)" on page 111 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..*]		111
	Description	<Desc>		[0..1]		112
	Amount	<Amt>		[0..1]		112

5.76 ReferredDocumentType3Choice

Definition: Specifies the type of the document referred in the remittance information.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		203
	Proprietary	<Prtry>	Or}	[1..1]		203

Used in element(s)

"[CodeOrProprietary](#)" on page 203

5.76.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: ["DocumentType6Code" on page 259](#)

5.76.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: ["Max35Text" on page 280](#)

5.77 ReferredDocumentType4

Definition: Specifies the type of the document referred in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		203
	Issuer	<Issr>		[0..1]		203

Used in element(s)

["Type" on page 201](#)

5.77.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document.

The **CdOrPrtry** block contains the following elements (see datatype ["ReferredDocumentType3Choice" on page 202](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		203
	Proprietary	<Prtry>	Or}	[1..1]		203

5.77.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "Max35Text" on page 280

5.78 RemittanceAmount2

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		204
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		204
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		205
	TaxAmount	<TaxAmt>		[0..*]		205
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		205
	RemittedAmount	<RmtdAmt>		[0..1]		206

Used in element(s)

"ReferredDocumentAmount" on page 222

5.78.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 244

5.78.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApldAmt** block contains the following elements (see datatype "DiscountAmountAndType1" on page 108 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		108
	Amount	<Amt>		[1..1]		108

5.78.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 244

5.78.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Quantity of cash resulting from the calculation of the tax.

The **TaxAmt** block contains the following elements (see datatype "TaxAmountAndType1" on page 227 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		228
	Amount	<Amt>		[1..1]		228

5.78.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the document adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "DocumentAdjustment1" on page 109 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		109
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		110
	Reason	<Rsn>		[0..1]		110
	AdditionalInformation	<AddtlInf>		[0..1]		110

5.78.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 244

5.79 RemittanceAmount3

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		206
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		206
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		207
	TaxAmount	<TaxAmt>		[0..*]		207
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		207
	RemittedAmount	<RmtdAmt>		[0..1]		208

Used in element(s)

"Amount" on page 112

5.79.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 244

5.79.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApldAmt** block contains the following elements (see datatype "DiscountAmountAndType1" on page 108 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		108
	Amount	<Amt>		[1..1]		108

5.79.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount of a credit note.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 244

5.79.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Amount of the tax.

The **TaxAmt** block contains the following elements (see datatype "TaxAmountAndType1" on page 227 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		228
	Amount	<Amt>		[1..1]		228

5.79.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "DocumentAdjustment1" on page 109 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		109
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		110
	Reason	<Rsn>		[0..1]		110
	AdditionalInformation	<AddtlInf>		[0..1]		110

5.79.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 244

5.80 RemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]		208
	Structured	<Strd>		[0..*]		208

Used in element(s)

"RemittanceInformation" on page 103

5.80.1 Unstructured

XML Tag: Ustrd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 278

5.80.2 Structured

XML Tag: Strd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

The **Strd** block contains the following elements (see datatype "StructuredRemittanceInformation16" on page 221 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		222

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		222
	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		223
	Invoicer	<Invcr>		[0..1]		223
	Invoicee	<Invcee>		[0..1]		224
	TaxRemittance	<TaxRmt>		[0..1]		224
	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		225
	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		225

5.81 RemittanceInformation2__1

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]	 R[0..1]	209

Used in element(s)

"RemittanceInformation" on page 87

5.81.1 Unstructured

XML Tag: Ustrd

Presence: [0..*]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, for example, commercial invoices in an accounts' receivable system in an unstructured form.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 251

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/RemittanceInformation/Unstructured**
This element has change repeatability, the maximum occurrence has been changed to : 1
- on pacs.009.001.08/CreditTransferTransactionInformation/RemittanceInformation/Unstructured**
Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 251

5.82 ServiceLevel8Choice

Definition: Specifies the service level of the transaction.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		210
	Proprietary	<Prtry>	Or}	[1..1]		210

Used in element(s)

"ServiceLevel" on page 163

5.82.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: "ExternalServiceLevel1Code" on page 272

5.82.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: "Max35Text" on page 280

5.83 ServiceLevel8Choice__1

Definition: Specifies the service level of the transaction.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		210
	Proprietary	<Prtry>	Or}	[1..1]	⚠	211

Used in element(s)

"ServiceLevel" on page 164

5.83.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: ["ExternalServiceLevel1Code" on page 272](#)

5.83.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 253](#)

Usage Guideline details

- on [pacs.009.001.08/CreditTransferTransactionInformation/PaymentTypeInformation/ServiceLevel/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 253](#)

5.84 SettlementDateTimelIndication1__1

Definition: Information on the occurred settlement time(s) of the payment transaction.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebitDateTime	<DbtDtTm>		[0..1]	⚠	211
	CreditDateTime	<CdtDtTm>		[0..1]	⚠	212

Used in element(s)

["SettlementTimeIndication" on page 69](#)

5.84.1 DebitDateTime

XML Tag: DbtDtTm

Presence: [0..1]

Definition: Date and time at which a payment has been debited at the transaction administrator. In the case of TARGET, the date and time at which the payment has been debited at the central bank, expressed in Central European Time (CET).

Datatype: ["CBPR_DateTime" on page 250](#)

Usage Guideline details

- on [pacs.009.001.08/CreditTransferTransactionInformation/SettlementTimeIndication/DebitDateTime](#)

Type changed to: [CBPR_DateTime on page 250](#)

5.84.2 CreditDateTime

XML Tag: CdtDtTm

Presence: [0..1]

Definition: Date and time at which a payment has been credited at the transaction administrator. In the case of TARGET, the date and time at which the payment has been credited at the receiving central bank, expressed in Central European Time (CET).

Datatype: ["CBPR_DateTime" on page 250](#)

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/SettlementTimeIndication/Credit-DateTime

Type changed to: [CBPR_DateTime on page 250](#)

5.85 SettlementInstruction7__1

Definition: Provides further details on the settlement of the instruction.

⊘ Removed - ⊘ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementMethod	<SttlmMtd>		[1..1]		215
	SettlementAccount	<SttlmAcct>		[0..1]	⊘ ⚠	215
	ClearingSystem	<ClrSys>		[0..1]	⊘	215
	InstructingReimbursementAgent	<InstgRmbrsmntAgt>		[0..1]	⚠	216
	InstructingReimbursementAgentAccount	<InstgRmbrsmntAgtAcct>		[0..1]		217
	InstructedReimbursementAgent	<InstdRmbrsmntAgt>		[0..1]	⚠	217
	InstructedReimbursementAgentAccount	<InstdRmbrsmntAgtAcct>		[0..1]		218
	ThirdReimbursementAgent	<ThrdRmbrsmntAgt>		[0..1]	⊘	219
	ThirdReimbursementAgentAccount	<ThrdRmbrsmntAgtAcct>		[0..1]	⊘	219

Rules

R32 ThirdReimbursementAgentRule ✓

If ThirdReimbursementAgent is present, then InstructingReimbursementAgent and InstructedReimbursementAgent must both be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00040
- *Error Text:* Invalid message content for third reimbursement agent.

Usage Guideline restrictions for this element

- **This rule(pacs.009.001.08/GroupHeader/SettlementInformation/ThirdReimbursementAgentRule) is removed.**

R33 SettlementMethodAgentRule ✓

If SettlementMethod is equal to INDA or INGA, then ReimbursementAgent(s) and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00018
- *Error Text:* Invalid message content for settlement method INGA or INDA.

Usage Guideline restrictions for this element

- **This rule(pacs.009.001.08/GroupHeader/SettlementInformation/SettlementMethodAgentRule) is removed.**

R34 SettlementMethodCoverRule ✓

If SettlementMethod is equal to COVE, then SettlementAccount and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00075
- *Error Text:* Invalid message content for cover settlement method with settlement account and clearing system.

R35 SettlementMethodCoverAgentRule ✓

If SettlementMethod is equal to COVE, then InstructedReimbursementAgent or InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00076
- *Error Text:* Invalid message content for cover settlement method and reimbursement agents.

R36 SettlementMethodClearingRule ✓

If SettlementMethod is equal to CLRG, then SettlementAccount and ReimbursementAgent(s) are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00019
- *Error Text:* Invalid message content for settlement method CLRG.

Usage Guideline restrictions for this element

- **This rule(pacs.009.001.08/GroupHeader/SettlementInformation/Settlement-MethodClearingRule) is removed.**
-

R37 InstructingReimbursementAgentAccountRule ✓

If InstructingReimbursementAgentAccount is present, then InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00038
- *Error Text:* Invalid message content for instructing reimbursement agent account.

R38 InstructedReimbursementAgentAccountRule ✓

If InstructedReimbursementAgentAccount is present, then InstructedReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00037
- *Error Text:* Invalid message content for instructed reimbursement agent account.

R39 ThirdReimbursementAgentAccountRule ✓

If ThirdReimbursementAgentAccount is present, then ThirdReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00039
- *Error Text:* Invalid message content for third reimbursement agent account.

Usage Guideline restrictions for this element

- **This rule(pacs.009.001.08/GroupHeader/SettlementInformation/ThirdReimbursementAgentAccountRule) is removed.**
-

Used in element(s)

["SettlementInformation" on page 142](#)

5.85.1 SettlementMethod

XML Tag: SttlmMtd

Presence: [1..1]

Definition: Method used to settle the (batch of) payment instructions.

Datatype: ["SettlementMethod1Code" on page 285](#)

5.85.2 SettlementAccount

XML Tag: SttlmAcct

Presence: [0..1]

Definition: A specific purpose account used to post debit and credit entries as a result of the transaction.

The **SttlmAcct** block contains the following elements (see datatype ["CashAccount38" on page 44](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

Usage Guideline details

- This element([pacs.009.001.08/GroupHeader/SettlementInformation/SettlementAccount](#)) is removed.
- on [pacs.009.001.08/GroupHeader/SettlementInformation/SettlementAccount](#)
Synonym (Sender's Correspondent (option 53B - account to be debited)): 53B

5.85.3 ClearingSystem

XML Tag: ClrSys

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSys** block contains the following elements (see datatype ["ClearingSystemIdentification3Choice" on page 55](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		55
	Proprietary	<Prtry>	Or}	[1..1]		55

Usage Guideline details

- This element(**pacs.009.001.08/GroupHeader/SettlementInformation/ClearingSystem**) is removed.

5.85.4 InstructingReimbursementAgent

XML Tag: InstgRmbrsmntAgt

Presence: [0..1]

Definition: Agent through which the instructing agent will reimburse the instructed agent.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

The **InstgRmbrsmntAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__1" on page 29 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		34

Usage Guideline details

- on **pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent**
 - **CBPR_Agent_Option_3_TextualRule:**
Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on **pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent**
 - **CBPR_Agent_Option_2_TextualRule:**
(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on **pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent**

– **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

• **on pacs.009.001.08/GroupHeader/SettlementInformation/InstructingReimbursementAgent**

– **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.85.5 InstructingReimbursementAgentAccount

XML Tag: InstgRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain.

The **InstgRmbrsmntAgtAcct** block contains the following elements (see datatype "CashAccount38__1" on page 46 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

5.85.6 InstructedReimbursementAgent

XML Tag: InstdRmbrsmntAgt

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

The **InstdRmbrsmntAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__1" on page 29 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		34

Usage Guideline details

- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent
 - CBPR_Agent_National_only_TextualRule:
Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent
 - CBPR_Agent_Option_1_TextualRule:
BICFI, complemented optionally with a LEI (preferred option)
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent
 - CBPR_Agent_Option_3_TextualRule:
Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on pacs.009.001.08/GroupHeader/SettlementInformation/InstructedReimbursementAgent
 - CBPR_Agent_Option_2_TextualRule:
(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.85.7 InstructedReimbursementAgentAccount

XML Tag: InstdRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain.

The **InstdRmbrsmntAgtAcct** block contains the following elements (see datatype "CashAccount38__1" on page 46 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	Type	<Tp>		[0..1]		47

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

5.85.8 ThirdReimbursementAgent

XML Tag: ThrdRmbrsmntAgt

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

The **ThrdRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 28 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		28

Usage Guideline details

- This element([pacs.009.001.08/GroupHeader/SettlementInformation/ThirdReimbursementAgent](#)) is removed.

5.85.9 ThirdReimbursementAgentAccount

XML Tag: ThrdRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain.

The **ThrdRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		45

Usage Guideline details

- This element(pacs.009.001.08/GroupHeader/SettlementInformation/ThirdReimbursementAgentAccount) is removed.

5.86 SettlementTimeRequest2__1

Definition: Provides information on the requested settlement time(s) of the payment instruction.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CLSTime	<CLSTm>		[0..1]		220
	TillTime	<TillTm>		[0..1]		221
	FromTime	<FrTm>		[0..1]		221
	RejectTime	<RjctTm>		[0..1]		221

Used in element(s)

"SettlementTimeRequest" on page 69

5.86.1 CLSTime

XML Tag: CLSTm

Presence: [0..1]

Definition: Time by which the amount of money must be credited, with confirmation, to the CLS Bank's account at the central bank.

Usage: Time must be expressed in Central European Time (CET).

Datatype: "CBPR_Time" on page 255

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/SettlementTimeRequest/CLSTime
Type changed to: CBPR_Time on page 255

5.86.2 TillTime

XML Tag: TillTm

Presence: [0..1]

Definition: Time until when the payment may be settled.

Datatype: "CBPR_Time" on page 255

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/SettlementTimeRequest/TillTime
Type changed to: CBPR_Time on page 255

5.86.3 FromTime

XML Tag: FrTm

Presence: [0..1]

Definition: Time as from when the payment may be settled.

Datatype: "CBPR_Time" on page 255

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/SettlementTimeRequest/FromTime
Type changed to: CBPR_Time on page 255

5.86.4 RejectTime

XML Tag: RjctTm

Presence: [0..1]

Definition: Time by when the payment must be settled to avoid rejection.

Datatype: "CBPR_Time" on page 255

Usage Guideline details

- on pacs.009.001.08/CreditTransferTransactionInformation/SettlementTimeRequest/RejectTime
Type changed to: CBPR_Time on page 255

5.87 StructuredRemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		222
	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		222
	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		223
	Invoice	<Invcr>		[0..1]		223
	Invoicee	<Invcee>		[0..1]		224
	TaxRemittance	<TaxRmt>		[0..1]		224
	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		225
	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		225

Used in element(s)

"Structured" on page 208

5.87.1 ReferredDocumentInformation

XML Tag: RfrdDocInf

Presence: [0..*]

Definition: Provides the identification and the content of the referred document.

The **RfrdDocInf** block contains the following elements (see datatype "[ReferredDocumentInformation7](#)" on page 201 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		201
	Number	<Nb>		[0..1]		202
	RelatedDate	<RltdDt>		[0..1]		202
	LineDetails	<LineDtls>		[0..*]		202

5.87.2 ReferredDocumentAmount

XML Tag: RfrdDocAmt

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

The **RfrdDocAmt** block contains the following elements (see datatype "[RemittanceAmount2](#)" on page 204 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		204
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		204
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		205
	TaxAmount	<TaxAmt>		[0..*]		205
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		205
	RemittedAmount	<RmtdAmt>		[0..1]		206

5.87.3 CreditorReferenceInformation

XML Tag: CdtrRefInf

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

The **CdtrRefInf** block contains the following elements (see datatype "[CreditorReferenceInformation2](#)" on page 104 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		104
	Reference	<Ref>		[0..1]		104

5.87.4 Invoicer

XML Tag: Invcr

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

The **Invcr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 155 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ContactDetails	<CtctDtls>		[0..1]		158

5.87.5 Invoicee

XML Tag: Invcee

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

The **Invcee** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 155 for details)

⊗ Removed - ⊗ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		156
	Identification	<Id>		[0..1]		157
	CountryOfResidence	<CtryOfRes>		[0..1]		157
	ContactDetails	<CtctDtls>		[0..1]		158

5.87.6 TaxRemittance

XML Tag: TaxRmt

Presence: [0..1]

Definition: Provides remittance information about a payment made for tax-related purposes.

The **TaxRmt** block contains the following elements (see datatype "[TaxInformation7](#)" on page 229 for details)

⊗ Removed - ⊗ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		230
	Debtor	<Dbtr>		[0..1]		230
	UltimateDebtor	<UltmtDbtr>		[0..1]		231
	AdministrationZone	<AdmstnZone>		[0..1]		231
	ReferenceNumber	<RefNb>		[0..1]		231
	Method	<Mtd>		[0..1]		232
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		232

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		232
	Date	<Dt>		[0..1]		232
	SequenceNumber	<SeqNb>		[0..1]		232
	Record	<Rcrd>		[0..*]		232

5.87.7 GarnishmentRemittance

XML Tag: GrnshmtRmt

Presence: [0..1]

Definition: Provides remittance information about a payment for garnishment-related purposes.

The **GrnshmtRmt** block contains the following elements (see datatype "[Garnishment3](#)" on page 127 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		127
	Garnishee	<Grnshee>		[0..1]		127
	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]		128
	ReferenceNumber	<RefNb>		[0..1]		128
	Date	<Dt>		[0..1]		129
	RemittedAmount	<RmtdAmt>		[0..1]		129
	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrncInd>		[0..1]		129
	EmployeeTerminationIndicator	<MplyeeTermntnInd>		[0..1]		129

5.87.8 AdditionalRemittanceInformation

XML Tag: AddtlRmtInf

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "[Max140Text](#)" on page 278

5.88 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		226
	Envelope	<Envlp>		[1..1]		226

Rules**R28 SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 21, "SupplementaryData" on page 88

5.88.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 279

5.88.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

5.89 TaxAmount2

Definition: Set of elements used to provide information on the tax amount(s) of tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Rate	<Rate>		[0..1]		227
	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		227
	TotalAmount	<TtlAmt>		[0..1]		227
	Details	<Dtls>		[0..*]		227

Used in element(s)

["TaxAmount" on page 241](#)

5.89.1 Rate

XML Tag: Rate

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: ["PercentageRate" on page 282](#)

5.89.2 TaxableBaseAmount

XML Tag: TaxblBaseAmt

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 244](#)

5.89.3 TotalAmount

XML Tag: TtlAmt

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 244](#)

5.89.4 Details

XML Tag: Dtls

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

The **Dtls** block contains the following elements (see datatype ["TaxRecordDetails2" on page 241](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Period	<Prd>		[0..1]		242
	Amount	<Amt>		[1..1]		242

5.90 TaxAmountAndType1

Definition: Specifies the amount with a specific type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		228
	Amount	<Amt>		[1..1]		228

Used in element(s)

["TaxAmount" on page 205](#), ["TaxAmount" on page 207](#)

5.90.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype ["TaxAmountType1Choice" on page 228](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		229
	Proprietary	<Prtry>	Or}	[1..1]		229

5.90.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 244](#)

5.91 TaxAmountType1Choice

Definition: Specifies the amount type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		229
	Proprietary	<Prtry>	Or}	[1..1]		229

Used in element(s)

["Type" on page 228](#)

5.91.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: ["ExternalTaxAmountType1Code" on page 273](#)

5.91.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: ["Max35Text" on page 280](#)

5.92 TaxAuthorisation1

Definition: Details of the authorised tax paying party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Title	<Titl>		[0..1]		229
	Name	<Nm>		[0..1]		229

Used in element(s)

["Authorisation" on page 237](#)

5.92.1 Title

XML Tag: Titl

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: ["Max35Text" on page 280](#)

5.92.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: ["Max140Text" on page 278](#)

5.93 TaxInformation7

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		230
	Debtor	<Dbtr>		[0..1]		230
	UltimateDebtor	<UltmtDbtr>		[0..1]		231
	AdministrationZone	<AdmstnZone>		[0..1]		231
	ReferenceNumber	<RefNb>		[0..1]		231
	Method	<Mtd>		[0..1]		232
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		232
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		232
	Date	<Dt>		[0..1]		232
	SequenceNumber	<SeqNb>		[0..1]		232
	Record	<Rcrd>		[0..*]		232

Used in element(s)

"TaxRemittance" on page 224

5.93.1 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

The **Cdtr** block contains the following elements (see datatype "TaxParty1" on page 236 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		236
	RegistrationIdentification	<RegnId>		[0..1]		236
	TaxType	<TaxTp>		[0..1]		236

5.93.2 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Identifies the party on the debit side of the transaction to which the tax applies.

The **Dbtr** block contains the following elements (see datatype "TaxParty2" on page 237 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		237
	RegistrationIdentification	<RegnId>		[0..1]		237
	TaxType	<TaxTp>		[0..1]		237
	Authorisation	<Authstn>		[0..1]		237

5.93.3 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the taxing authority.

The **UltmtDbtr** block contains the following elements (see datatype "TaxParty2" on page 237 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		237
	RegistrationIdentification	<RegnId>		[0..1]		237
	TaxType	<TaxTp>		[0..1]		237
	Authorisation	<Authstn>		[0..1]		237

5.93.4 AdministrationZone

XML Tag: AdmstnZone

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "Max35Text" on page 280

5.93.5 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "Max140Text" on page 278

5.93.6 Method

XML Tag: Mtd

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: "Max35Text" on page 280

5.93.7 TotalTaxableBaseAmount

XML Tag: TtlTaxblBaseAmt

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 244

5.93.8 TotalTaxAmount

XML Tag: TtlTaxAmt

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 244

5.93.9 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: "ISODate" on page 275

5.93.10 SequenceNumber

XML Tag: SeqNb

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: "Number" on page 282

5.93.11 Record

XML Tag: Rcrd

Presence: [0..*]

Definition: Record of tax details.

The **Rcrd** block contains the following elements (see datatype "TaxRecord2" on page 239 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		239
	Category	<Ctgy>		[0..1]		240
	CategoryDetails	<CtgyDtls>		[0..1]		240
	DebtorStatus	<DbtrSts>		[0..1]		240
	CertificateIdentification	<CertId>		[0..1]		240
	FormsCode	<FrmsCd>		[0..1]		240
	Period	<Prd>		[0..1]		240
	TaxAmount	<TaxAmt>		[0..1]		241
	AdditionalInformation	<AddtlInf>		[0..1]		241

5.94 TaxInformation8

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		233
	Debtor	<Dbtr>		[0..1]		234
	AdministrationZone	<AdmstnZone>		[0..1]		234
	ReferenceNumber	<RefNb>		[0..1]		234
	Method	<Mtd>		[0..1]		234
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		235
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		235
	Date	<Dt>		[0..1]		235
	SequenceNumber	<SeqNb>		[0..1]		235
	Record	<Rcrd>		[0..*]		235

Used in element(s)

"Tax" on page 102

5.94.1 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

The **Cdtr** block contains the following elements (see datatype "[TaxParty1](#)" on page 236 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		236
	RegistrationIdentification	<RegnId>		[0..1]		236
	TaxType	<TaxTp>		[0..1]		236

5.94.2 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Party on the debit side of the transaction to which the tax applies.

The **Dbtr** block contains the following elements (see datatype "[TaxParty2](#)" on page 237 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		237
	RegistrationIdentification	<RegnId>		[0..1]		237
	TaxType	<TaxTp>		[0..1]		237
	Authorisation	<Authstn>		[0..1]		237

5.94.3 AdministrationZone

XML Tag: AdmstnZone

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "[Max35Text](#)" on page 280

5.94.4 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "[Max140Text](#)" on page 278

5.94.5 Method

XML Tag: Mtd

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: ["Max35Text" on page 280](#)

5.94.6 TotalTaxableBaseAmount

XML Tag: TtlTaxblBaseAmt

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 244](#)

5.94.7 TotalTaxAmount

XML Tag: TtlTaxAmt

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 244](#)

5.94.8 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ["ISODate" on page 275](#)

5.94.9 SequenceNumber

XML Tag: SeqNb

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: ["Number" on page 282](#)

5.94.10 Record

XML Tag: Rcrd

Presence: [0..*]

Definition: Record of tax details.

The **Rcrd** block contains the following elements (see datatype ["TaxRecord2" on page 239](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		239

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Category	<Ctgy>		[0..1]		240
	CategoryDetails	<CtgyDtls>		[0..1]		240
	DebtorStatus	<DbtrSts>		[0..1]		240
	CertificateIdentification	<CertId>		[0..1]		240
	FormsCode	<FrmsCd>		[0..1]		240
	Period	<Prd>		[0..1]		240
	TaxAmount	<TaxAmt>		[0..1]		241
	AdditionalInformation	<AddtlInf>		[0..1]		241

5.95 TaxParty1

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		236
	RegistrationIdentification	<RegnId>		[0..1]		236
	TaxType	<TaxTp>		[0..1]		236

Used in element(s)

"Creditor" on page 230, "Creditor" on page 233

5.95.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 280

5.95.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 280

5.95.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: ["Max35Text" on page 280](#)

5.96 TaxParty2

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		237
	RegistrationIdentification	<RegnId>		[0..1]		237
	TaxType	<TaxTp>		[0..1]		237
	Authorisation	<Authstn>		[0..1]		237

Used in element(s)

["Debtor" on page 230](#), ["Debtor" on page 234](#), ["UltimateDebtor" on page 231](#)

5.96.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: ["Max35Text" on page 280](#)

5.96.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: ["Max35Text" on page 280](#)

5.96.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: ["Max35Text" on page 280](#)

5.96.4 Authorisation

XML Tag: Authstn

Presence: [0..1]

Definition: Details of the authorised tax paying party.

The **Authstn** block contains the following elements (see datatype "[TaxAuthorisation1](#)" on page 229 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Title	<Titl>		[0..1]		229
	Name	<Nm>		[0..1]		229

5.97 TaxPeriod2

Definition: Period of time details related to the tax payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		238
	Type	<Tp>		[0..1]		238
	FromToDate	<FrToDt>		[0..1]		238

Used in element(s)

["Period" on page 240](#), ["Period" on page 242](#)

5.97.1 Year

XML Tag: Yr

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: ["ISODate" on page 275](#)

5.97.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: ["TaxRecordPeriod1Code" on page 286](#)

5.97.3 FromToDate

XML Tag: FrToDt

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

The **FrToDt** block contains the following elements (see datatype "[DatePeriod2](#)" on page 107 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FromDate	<FrDt>		[1..1]		107
	ToDate	<ToDt>		[1..1]		107

5.98 TaxRecord2

Definition: Set of elements used to define the tax record.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		239
	Category	<Ctgy>		[0..1]		240
	CategoryDetails	<CtgyDtls>		[0..1]		240
	DebtorStatus	<DbtrSts>		[0..1]		240
	CertificateIdentification	<CertId>		[0..1]		240
	FormsCode	<FrmsCd>		[0..1]		240
	Period	<Prd>		[0..1]		240
	TaxAmount	<TaxAmt>		[0..1]		241
	AdditionalInformation	<AddtlInf>		[0..1]		241

Used in element(s)

"Record" on page 232, "Record" on page 235

5.98.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "[Max35Text](#)" on page 280

5.98.2 Category

XML Tag: CtgY

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: "Max35Text" on page 280

5.98.3 CategoryDetails

XML Tag: CtgYDtlS

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: "Max35Text" on page 280

5.98.4 DebtorStatus

XML Tag: DbtrSts

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: "Max35Text" on page 280

5.98.5 CertificateIdentification

XML Tag: CertId

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: "Max35Text" on page 280

5.98.6 FormsCode

XML Tag: FrmsCd

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: "Max35Text" on page 280

5.98.7 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod2" on page 238 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		238
	Type	<Tp>		[0..1]		238
	FromToDate	<FrToDt>		[0..1]		238

5.98.8 TaxAmount

XML Tag: TaxAmt

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

The **TaxAmt** block contains the following elements (see datatype "[TaxAmount2](#)" on page 226 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Rate	<Rate>		[0..1]		227
	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		227
	TotalAmount	<TtlAmt>		[0..1]		227
	Details	<Dtls>		[0..*]		227

5.98.9 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "[Max140Text](#)" on page 278

5.99 TaxRecordDetails2

Definition: Provides information on the individual tax amount(s) per period of the tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Period	<Prd>		[0..1]		242
	Amount	<Amt>		[1..1]		242

Used in element(s)

"Details" on page 227

5.99.1 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "[TaxPeriod2](#)" on page 238 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		238
	Type	<Tp>		[0..1]		238
	FromToDate	<FrToDt>		[0..1]		238

5.99.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 244

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 ActiveCurrencyAndAmount

Definition: A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 243

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules

R30 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

"TotalInterbankSettlementAmount" on page 141

6.2 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Rules**R31 ActiveCurrency ✓**

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Used in attribute(s)

"ActiveCurrencyAndAmount" on page 243, "CBPR_Amount" on page 248, "CBPR_Amount" on page 249

Restricts

"ParentCurrencyCode" on page 282

6.3 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveOrHistoricCurrencyCode" on page 245

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules**R24 CurrencyAmount ✓**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

["Amount" on page 108](#), ["Amount" on page 109](#), ["Amount" on page 228](#), ["Amount" on page 242](#), ["CreditNoteAmount" on page 205](#), ["CreditNoteAmount" on page 207](#), ["DuePayableAmount" on page 204](#), ["DuePayableAmount" on page 206](#), ["InstructedAmount" on page 103](#), ["RemittedAmount" on page 129](#), ["RemittedAmount" on page 206](#), ["RemittedAmount" on page 208](#), ["TaxableBaseAmount" on page 227](#), ["TotalAmount" on page 227](#), ["TotalTaxAmount" on page 232](#), ["TotalTaxAmount" on page 235](#), ["TotalTaxableBaseAmount" on page 232](#), ["TotalTaxableBaseAmount" on page 235](#)

6.4 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Rules**R13 ActiveOrHistoricCurrency ✓**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Used in element(s)

["Currency" on page 45](#), ["Currency" on page 47](#)

Used in attribute(s)

["ActiveOrHistoricCurrencyAndAmount" on page 244](#)

Restricts

["ParentCurrencyCode" on page 282](#)

6.5 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.

Code	Name	Definition
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["Code" on page 27](#)

Restricts

["AddressTypeCode" on page 246](#)

6.6 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 245](#)

6.7 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.

Code	Name	Definition
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.

Is restricted by

"CreditDebitCode" on page 258

6.8 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R27 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

"AnyBIC" on page 150

6.9 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R26 BICFI ✓

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

["BICFI" on page 115](#), ["BICFI" on page 117](#), ["BICFI" on page 123](#)

6.10 BatchBookingIndicator

Definition: Identifies whether the sending party requests a single debit or credit entry per individual transaction or a batch entry for the sum of the amounts of all transactions.

Type: Indicator

Meaning When True: Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.

Meaning When False: Identifies that a single entry for each of the transactions in the batch or message is requested.

Used in element(s)

["BatchBooking" on page 140](#)

6.11 CBPR_Amount

Definition:

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 243

Format

fractionDigits	5
minInclusive	0
totalDigits	14

Rules

R53 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits

Used in element(s)

"InterbankSettlementAmount" on page 68

6.12 CBPR_Amount

Definition:

This datatype has been created by the Publisher of this Usage Guideline.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 243

Format

fractionDigits	5
minInclusive	0
totalDigits	14

Rules

R55 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits

6.13 CBPR_Date

Definition: This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Date

Format

pattern [0-9]{4}-[0-9]{2}-[0-9]{2}

Used in element(s)

"InterbankSettlementDate" on page 68

6.14 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern .*(\+|-)(([0-9]))(1[0-4])):[0-5][0-9]

Used in element(s)

"CreationDate" on page 42, "CreationDateTime" on page 140, "CreditDateTime" on page 212, "DebitDateTime" on page 211

6.15 CBPR_RestrictedFINXMax140Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+]+

Used in element(s)

"InstructionInformation" on page 146

6.16 CBPR_RestrictedFINXMax140Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+ !#\$%&!*^_`{ }~";<>@[\\]]+

Used in element(s)

"Name" on page 118, "Unstructured" on page 209

6.17 CBPR_RestrictedFINXMax16Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+]+

Used in element(s)

["InstructionIdentification" on page 159](#)

6.18 CBPR_RestrictedFINXMax16Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+ !#\$%&!*='^_`{ }\}~";<>@[\\\\]]+

Used in element(s)

["BuildingNumber" on page 179](#), ["PostBox" on page 182](#), ["PostCode" on page 184](#)

6.19 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+]+

Used in element(s)

["MemberIdentification" on page 59](#)

6.20 CBPR_RestrictedFINXMax320Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 320 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	320
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*=-^_`{\ }~";<>@\[\]\+]

Used in element(s)

"Identification" on page 197

6.21 CBPR_RestrictedFINXMax34Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 34 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . and disable the use of slash "/" at the beginning and end of line and double slash "/" within the line.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	34
minLength	1
pattern	(([0-9a-zA-Z/\-!\?:\(\)\.,'+]([0-9a-zA-Z/\-!\?:\(\)\.,'+])*([0-9a-zA-Z/\-!\?:\(\)\.,'+])?)*

Used in element(s)

"Identification" on page 132

6.22 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+]+

Used in element(s)

["BusinessMessageIdentifier" on page 41](#), ["BusinessService" on page 42](#), ["ClearingSystemReference" on page 161](#), ["EndToEndIdentification" on page 160](#), ["InstructionInformation" on page 147](#), ["Issuer" on page 134](#), ["MessageDefinitionIdentifier" on page 41](#), ["MessageIdentification" on page 140](#), ["Proprietary" on page 26](#), ["Proprietary" on page 50](#), ["Proprietary" on page 199](#), ["Proprietary" on page 211](#), ["Proprietary" on page 149](#), ["Proprietary" on page 52](#), ["Proprietary" on page 201](#), ["TransactionIdentification" on page 161](#)

6.23 CBPR_RestrictedFINXMax35Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+ !#\$%&!*='^_`{ }\~";<>@[\\]]+

Used in element(s)

["BuildingName" on page 180](#), ["CountrySubDivision" on page 190](#), ["DistrictName" on page 189](#), ["Town-LocationName" on page 188](#), ["TownName" on page 185](#)

6.24 CBPR_RestrictedFINXMax70Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+]+

Used in element(s)

["Name" on page 47](#)

6.25 CBPR_RestrictedFINXMax70Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*='^_`{ }\}~";<>@[\]]+

Used in element(s)

"AddressLine" on page 192, "Department" on page 175, "Floor" on page 181, "Room" on page 183, "StreetName" on page 177, "SubDepartment" on page 176

6.26 CBPR_Time

Definition: A particular point in the progression of time defined by a mandatory time component, expressed in local time with UTC offset format (hh:mm:ss.sss+/-hh:mm).

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: Time

Format

pattern	.*(\+ -)((0[0-9]) (1[0-4])):[0-5][0-9]
---------	--

Used in element(s)

"CLSTime" on page 220, "FromTime" on page 221, "RejectTime" on page 221, "TillTime" on page 221

6.27 ClearingChannel2Code

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Used in element(s)

"ClearingChannel" on page 162, "ClearingChannel" on page 164

Restricts

"ClearingChannelCode" on page 256

6.28 ClearingChannelCode

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Is restricted by

"ClearingChannel2Code" on page 256

6.29 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for

Code	Name	Definition
		information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

"CopyDuplicate" on page 42

Restricts

"CopyDuplicateCode" on page 257

6.30 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

"CopyDuplicate1Code" on page 256

6.31 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules**R25 Country ✓**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

"Country" on page 172, "Country" on page 191, "CountryOfBirth" on page 107, "CountryOfResidence" on page 157

6.32 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

Used in element(s)

"CreditDebitIndicator" on page 110

Restricts

"AmountDirectionCode" on page 246

6.33 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

fractionDigits	17
totalDigits	18

Used in element(s)

"ControlSum" on page 141

6.34 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
DISP	DispatchAdvice	Document is a dispatch advice.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Used in element(s)

"Code" on page 105

Restricts

"DocumentTypeCode" on page 260

6.35 DocumentType6Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.

Code	Name	Definition
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Used in element(s)

"Code" on page 203

Restricts

"DocumentTypeCode" on page 260

6.36 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CRCP	CustomerReceipt	When the Sale System requires the POI system to print the Customer receipt.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.

Code	Name	Definition
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
HRCP	CashierReceipt	When the Sale system print the Cashier copy of the Payment receipt.
JNRL	Journal	When the POI or the Sale System wants to store a message on the journal printer or electronic journal of the Sale Terminal (it is sometimes a Sale Logging/Journal Printer).
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
SRCP	SaleReceipt	When the Sale System requires the POI system to print the Sale receipt.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Is restricted by

"DocumentType3Code" on page 258, "DocumentType6Code" on page 259

6.37 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

Used in element(s)

["Identification" on page 136](#)

6.38 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 25](#), ["Code" on page 25](#)

Restricts

["ExternalAccountIdentificationCode" on page 262](#)

6.39 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalAccountIdentification1Code" on page 262](#)

6.40 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 49](#), ["Code" on page 50](#)

Restricts

["ExternalCashAccountTypeCode" on page 263](#)

6.41 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalCashAccountType1Code" on page 262](#)

6.42 ExternalCashClearingSystem1Code

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	3
minLength	1

Used in element(s)

"Code" on page 55

Restricts

"ExternalCashClearingSystemCode" on page 264

6.43 ExternalCashClearingSystemCode

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCashClearingSystem1Code" on page 263

6.44 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 51, "Code" on page 52

Restricts

"ExternalCategoryPurposeCode" on page 264

6.45 ExternalCategoryPurposeCode

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCategoryPurpose1Code" on page 264

6.46 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

"Code" on page 53

Restricts

"ExternalClearingSystemIdentificationCode" on page 265

6.47 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

"ExternalClearingSystemIdentification1Code" on page 265

6.48 ExternalDiscountAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 109](#)

Restricts

["ExternalDiscountAmountTypeCode" on page 266](#)

6.49 ExternalDiscountAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalDiscountAmountType1Code" on page 265](#)

6.50 ExternalDocumentLineType1Code

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 114](#)

Restricts

"ExternalDocumentLineTypeCode" on page 267

6.51 ExternalDocumentLineTypeCode

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalDocumentLineType1Code" on page 266

6.52 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 114

Restricts

"ExternalFinancialInstitutionIdentificationCode" on page 267

6.53 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 267

6.54 ExternalGarnishmentType1Code

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 130

Restricts

"ExternalGarnishmentTypeCode" on page 268

6.55 ExternalGarnishmentTypeCode

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalGarnishmentType1Code" on page 268

6.56 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Used in element(s)

["Code" on page 148](#), ["Code" on page 149](#)

Restricts

["ExternalLocalInstrumentCode" on page 269](#)

6.57 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Is restricted by

["ExternalLocalInstrument1Code" on page 268](#)

6.58 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 151](#)

Restricts

"ExternalOrganisationIdentificationCode" on page 270

6.59 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalOrganisationIdentification1Code" on page 269

6.60 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 167

Restricts

"ExternalPersonIdentificationCode" on page 270

6.61 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPersonIdentification1Code" on page 270

6.62 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 198, "Code" on page 199

Restricts

"ExternalProxyAccountTypeCode" on page 271

6.63 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalProxyAccountType1Code" on page 271

6.64 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 200

Restricts

"ExternalPurposeCode" on page 272

6.65 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPurpose1Code" on page 271

6.66 ExternalServiceLevel1Code

Definition: Specifies the external service level code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 210, "Code" on page 210

Restricts

"ExternalServiceLevelCode" on page 273

6.67 ExternalServiceLevelCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalServiceLevel1Code" on page 272

6.68 ExternalTaxAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 229

Restricts

["ExternalTaxAmountTypeCode" on page 274](#)

6.69 ExternalTaxAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalTaxAmountType1Code" on page 273](#)

6.70 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Format

pattern	[A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}
---------	---------------------------------------

Rules**R12 IBAN ✓**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

["IBAN" on page 23](#), ["IBAN" on page 24](#)

6.71 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

"BirthDate" on page 106, "Date" on page 129, "Date" on page 232, "Date" on page 235, "FromDate" on page 107, "InterbankSettlementDate" on page 141, "RelatedDate" on page 111, "RelatedDate" on page 202, "ToDate" on page 107, "Year" on page 238

6.72 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

6.73 Instruction3Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

Code	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.

Code	Name	Definition
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

Used in element(s)

"Code" on page 145

Restricts

"InstructionCode" on page 277

6.74 Instruction4Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

Code	Name	Definition
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.

Used in element(s)

"Code" on page 146, "Code" on page 147

Restricts

"InstructionCode" on page 277

6.75 Instruction5Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

Code	Name	Definition
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

Used in element(s)

"Code" on page 146

Restricts

["InstructionCode" on page 277](#)

6.76 InstructionCode

Definition: Specifies further instructions concerning the processing of a payment instruction.

Type: CodeSet

Code	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PBEN	PayTheBeneficiary	(Ultimate) creditor to be paid only after verification of identity.
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.
TFRO	TimeFrom	Payment instruction will be valid and eligible for execution from the date and time stipulated.
TTIL	TimeTill	Payment instruction is valid and eligible for execution until the date and time stipulated. Otherwise, the payment instruction will be rejected.

Is restricted by

["Instruction3Code" on page 275](#), ["Instruction4Code" on page 276](#), ["Instruction5Code" on page 276](#)

6.77 LEIIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{18,18}[0-9]{2,2}

Used in element(s)

["LEI" on page 38](#), ["LEI" on page 115](#), ["LEI" on page 150](#), ["LEI" on page 118](#), ["LEI" on page 124](#)

6.78 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength	128
minLength	1

Used in element(s)

["Identification" on page 152](#)

6.79 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

["AdditionalInformation" on page 110](#), ["AdditionalInformation" on page 241](#), ["AdditionalRemittanceInformation" on page 225](#), ["InstructionInformation" on page 145](#), ["InstructionInformation" on page 147](#), ["Name" on page 38](#), ["Name" on page 61](#), ["Name" on page 116](#), ["Name" on page 155](#), ["Name" on page 229](#), ["Name" on page 124](#), ["ReferenceNumber" on page 128](#), ["ReferenceNumber" on page 231](#), ["ReferenceNumber" on page 234](#), ["Unstructured" on page 208](#)

6.80 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

["NumberOfTransactions" on page 141](#)

6.81 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

"BuildingNumber" on page 171, "PostBox" on page 171, "PostCode" on page 171

6.82 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

"Description" on page 112, "EmailAddress" on page 62, "Identification" on page 144, "Identification" on page 195

6.83 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

maxLength	34
minLength	1

Used in element(s)

"Identification" on page 131

6.84 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

["PlaceAndName" on page 226](#), ["Registry" on page 144](#)

6.85 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

["AdministrationZone" on page 231](#), ["AdministrationZone" on page 234](#), ["BuildingName" on page 171](#), ["Category" on page 240](#), ["CategoryDetails" on page 240](#), ["CertificateIdentification" on page 240](#), ["City-OfBirth" on page 107](#), ["CountrySubDivision" on page 172](#), ["DebtorStatus" on page 240](#), ["DistrictName" on page 172](#), ["EmailPurpose" on page 62](#), ["FormsCode" on page 240](#), ["Identification" on page 38](#), ["Identification" on page 135](#), ["Identification" on page 137](#), ["Identification" on page 138](#), ["Issuer" on page 106](#), ["Issuer" on page 113](#), ["Issuer" on page 130](#), ["Issuer" on page 132](#), ["Issuer" on page 136](#), ["Issuer" on page 136](#), ["Issuer" on page 138](#), ["Issuer" on page 139](#), ["Issuer" on page 203](#), ["JobTitle" on page 62](#), ["MemberIdentification" on page 56](#), ["Method" on page 232](#), ["Method" on page 234](#), ["Number" on page 111](#), ["Number" on page 202](#), ["Proprietary" on page 25](#), ["Proprietary" on page 49](#), ["Proprietary" on page 52](#), ["Proprietary" on page 53](#), ["Proprietary" on page 55](#), ["Proprietary" on page 105](#), ["Proprietary" on page 109](#), ["Proprietary" on page 114](#), ["Proprietary" on page 114](#), ["Proprietary" on page 131](#), ["Proprietary" on page 148](#), ["Proprietary" on page 151](#), ["Proprietary" on page 167](#), ["Proprietary" on page 198](#), ["Proprietary" on page 203](#), ["Proprietary" on page 210](#), ["Proprietary" on page 229](#), ["ProvinceOfBirth" on page 107](#), ["Reference" on page 104](#), ["RegistrationIdentification" on page 236](#), ["RegistrationIdentification" on page 237](#), ["Responsibility" on page 62](#), ["SchemeName" on page 136](#), ["TaxIdentification" on page 236](#), ["TaxIdentification" on page 237](#), ["TaxType" on page 236](#), ["TaxType" on page 237](#), ["Title" on page 229](#), ["TownLocationName" on page 172](#), ["TownName" on page 172](#), ["Type" on page 239](#)

6.86 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

["ChannelType" on page 152](#), ["Reason" on page 110](#)

6.87 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

["AddressLine" on page 172](#), ["Department" on page 62](#), ["Department" on page 169](#), ["Floor" on page 171](#), ["Name" on page 45](#), ["Room" on page 171](#), ["StreetName" on page 170](#), ["SubDepartment" on page 170](#)

6.88 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

["NamePrefix" on page 61](#)

Restricts

["NamePrefixCode" on page 281](#)

6.89 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

["NamePrefix2Code" on page 281](#)

6.90 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

fractionDigits	0
totalDigits	18

Used in element(s)

"SequenceNumber" on page 232, "SequenceNumber" on page 235

6.91 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Is restricted by

"ActiveCurrencyCode" on page 243, "ActiveOrHistoricCurrencyCode" on page 245

6.92 PercentageRate

Definition: Rate expressed as a percentage, that is, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

fractionDigits	10
totalDigits	11

Used in element(s)

"Rate" on page 227

6.93 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+" and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+\-]{1,30}

Used in element(s)

["FaxNumber" on page 62](#), ["MobileNumber" on page 61](#), ["PhoneNumber" on page 61](#)

6.94 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 63](#)

Restricts

["PreferredContactMethodCode" on page 283](#)

6.95 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.

Code	Name	Definition
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

"PreferredContactMethod1Code" on page 283

6.96 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

"InstructionPriority" on page 162, "InstructionPriority" on page 164, "Priority" on page 43

Restricts

"PriorityCode" on page 284

6.97 Priority3Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Used in element(s)

"SettlementPriority" on page 69

Restricts

"PriorityCode" on page 284

6.98 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

"Priority2Code" on page 284, "Priority3Code" on page 284

6.99 SettlementMethod1Code

Definition: Specifies the method used to settle the credit transfer instruction.

Type: CodeSet

Code	Name	Definition
CLRG	ClearingSystem	Settlement is done through a payment clearing system. Usage Guideline restrictions for this code • This code(pacs.009.001.08/Group-Header/SettlementInformation/SettlementMethod/ClearingSystem) is removed.
COVE	CoverMethod	Settlement is done through a cover payment.
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction. Usage Guideline restrictions for this code • This code(pacs.009.001.08/Group-Header/SettlementInformation/SettlementMethod/InstructedAgent) is removed.

Code	Name	Definition
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain. Usage Guideline restrictions for this code • This code(pacs.009.001.08/Group-Header/SettlementInformation/SettlementMethod/InstructingAgent) is removed.

Used in element(s)

"SettlementMethod" on page 215

Restricts

"SettlementMethodCode" on page 286

6.100 SettlementMethodCode

Definition: Specifies the method used to settle the payment instruction.

Type: CodeSet

Code	Name	Definition
CLRG	ClearingSystem	Settlement is done through a payment clearing system.
COVE	CoverMethod	Settlement is done through a cover payment.
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.

Is restricted by

"SettlementMethod1Code" on page 285

6.101 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.

Code	Name	Definition
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Used in element(s)

"Type" on page 238

Restricts

"TaxRecordPeriodCode" on page 287

6.102 TaxRecordPeriodCode

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Is restricted by

"TaxRecordPeriod1Code" on page 286

6.103 TrueFalseIndicator

Definition: A flag indicating a True or False value.

Type: Indicator

Meaning When True: True

Meaning When False: False

Used in element(s)

"EmployeeTerminationIndicator" on page 129, "FamilyMedicalInsuranceIndicator" on page 129

6.104 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

Used in element(s)

"UETR" on page 161

6.105 UnicodeChartsCode

Definition: codelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R2 ValidationByTable

Error handling: Undefined

Used in element(s)

"CharacterSet" on page 40

6.106 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

"PossibleDuplicate" on page 43

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.