



Usage Guideline

CBPRPlus-pacs.010.001.03_Interbank Direct Debit

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX pacs.010.001.03**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality 3

1 Restriction summary 5

2 Structure 7

3 ISO 20022 Rules 10

4 Message Building Blocks 11

5 Message Components 20

6 Message Datatypes 149

Legal Notices 181

Message Functionality

This Usage Guideline is based on the pacs.010.001.03 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the pacs.010.001.03 only.

Overview

This usage guideline can also support a scenario where the CCP has debit authority of the member's account (Debtor) and sends a pacs.010 to the Debtor Agent that is different than the Creditor Agent. A pacs.009 is sent to the Creditor Agent, through one or more agents.

Principles:

1. AGENTS IDENTIFICATION - Textual Rules

-> If BICFI is present, then (Name & Postal Address) is NOT allowed (ClearingSystemMemberIdentification and LEI may complement) - However, in case of conflicting information, the BICFI will always take precedence.

-> If BICFI is absent, (Name & Postal Address) OR [(Name & Postal Address) and ClearingSystemMemberIdentification] must be present.

Exception: If BICFI is absent, whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

Note: "Instructing/ Instructed Agents" must be identified with a BICFI - Clearing System Members Identification and LEI are optional.

2. Character Set:

All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

```
!#$%&*='^_ '{|}~";<>@[\\
```

< is replaced with <

> is replaced with >

3. CBPR_Agent_PointToPointOnSWIFT:

If the transaction is exchanged on the SWIFT network (ie if the instructing agent/ sender and instructed agent/receiver of the message are on SWIFT), then BICFI is mandatory and other elements are optional, eg LEI

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-pacs.010.001.03_Interbank Direct Debit message is composed of 3 building blocks

a. GroupHeader

Common characteristics for all individual transactions included in the message.

b. CreditInstruction

Characteristics that apply to the credit side of the payment transaction(s) included in the message.

c. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the pacs.010.001.03 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	10, 15, 16, 19, 24, 24, 25, 25, 26, 26, 28, 28, 28, 31, 31, 31, 31, 37, 38, 43, 43, 43, 43, 43, 43, 44, 44, 44, 44, 44, 53, 53, 53, 54, 55, 55, 56, 64, 64, 66, 69, 70, 70, 76, 76, 77, 77, 78, 78, 80, 80, 80, 80, 81, 81, 81, 81, 81, 81, 81, 81, 85, 85, 85, 88, 88, 88, 88, 96, 96, 97, 100, 100, 101, 101, 101, 101, 101, 101, 104, 104, 104, 104, 105, 105, 106, 106, 107, 107, 107, 107, 108, 108, 108, 108, 109, 109, 109, 109, 109, 109, 109, 110, 110, 110, 110, 113, 114, 114, 116, 120, 120, 120, 120, 120, 120, 120, 120, 121, 121, 121, 121, 123, 123, 123, 123, 124, 125, 125, 130, 130, 130, 130
Make mandatory	14, 45, 45, 45, 46, 46, 46, 46, 46, 46, 46, 46, 56, 57, 69, 75, 76, 79, 79, 79, 79, 111, 112, 126, 126, 126, 127, 128, 128, 135, 135, 135, 135, 137, 137, 137, 137, 139, 139, 139, 139, 139, 139, 140, 143
Reduce Multiplicity	17, 19, 65, 116, 128, 128, 128, 138, 138, 138, 138, 143
Ignore	n.a.
Text rules	17, 35, 36, 36, 57, 57, 57, 57, 59, 59, 59, 59, 60, 60, 60, 60, 61, 61, 61, 62, 63, 63, 63, 63, 71, 71, 71, 71, 72, 72, 72, 73, 84, 84, 84, 87, 87, 88, 88
Conditional rules	n.a.
Formal rules	11, 11, 11, 12, 27, 27, 27, 29, 30, 30, 30
Fixed values	13, 14, 96
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	13, 15, 16, 21, 21, 21, 21, 21, 22, 22, 35, 36, 36, 37, 38, 40, 40, 40, 40, 40, 40, 40, 41, 41, 41, 41, 41, 41, 41, 42, 42, 47, 47, 47, 47, 47, 47, 47, 47, 54, 69, 73, 83, 83, 83, 86, 86, 86, 86, 89, 89, 89, 89, 89,

Restriction Type	See page
	89, 89, 90, 90, 90, 90, 90, 90, 90, 95, 95, 100, 111, 112, 112, 127, 127, 127, 128, 128, 128, 130, 130, 130, 130, 131, 131, 131, 131, 131, 131, 131, 131, 132, 132, 132, 132, 132, 132, 132, 132, 133, 133, 133, 133, 133, 133, 133, 133, 134, 134, 134, 134, 134, 134, 134, 135, 135, 135, 135, 135, 136, 136, 136, 136, 136, 136, 136, 136, 137, 137, 137, 137, 138, 138, 138, 138, 140, 140, 140, 140, 140, 140, 140, 141, 141, 141, 141, 141, 141, 141, 142, 143, 144, 146, 146, 146, 147
Extensions	n.a.
Synonyms	n.a.

2 Structure

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		12
	From	<Fr>		[1..1]		12
	OrganisationIdentification	<OrgId>	{Or	[1..1]		106
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		106
	To	<To>		[1..1]		12
	OrganisationIdentification	<OrgId>	{Or	[1..1]		106
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		106
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		13
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		13
	BusinessService	<BizSvc>		[0..1]	 	14
	MarketPractice	<MktPrctc>		[0..1]		14
	Registry	<Regy>		[1..1]		97
	Identification	<Id>		[1..1]		97
	CreationDate	<CreDt>		[1..1]		14
	BusinessProcessingDate	<BizPrcgDt>		[0..1]		15
	CopyDuplicate	<CpyDplct>		[0..1]		15
	PossibleDuplicate	<PssblDplct>		[0..1]		15
	Priority	<Prty>		[0..1]		16
	Signature	<Sgntr>		[0..1]		16
	Related	<Rltd>		[0..*]	 R[0..1]	16
	CharacterSet	<CharSet>		[0..1]		34
	From	<Fr>		[1..1]		34
	To	<To>		[1..1]		34
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		35
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		35
	BusinessService	<BizSvc>		[0..1]		36
	CreationDate	<CreDt>		[1..1]		36

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		37
	PossibleDuplicate	<PssblDplct>		[0..1]		37
	Priority	<Prty>		[0..1]		37
	Signature	<Sgntr>		[0..1]		38
	<i>FinancialInstitutionDirectDebitV03</i>	<FIDrctDbt>		[1..1]		
	GroupHeader	<GrpHdr>		[1..1]		17
	MessageIdentification	<MsgId>		[1..1]		95
	CreationDateTime	<CreDtTm>		[1..1]		95
	NumberOfTransactions	<NbOfTx>		[1..1]		96
	ControlSum	<CtrlSum>		[0..1]		96
	InstructingAgent	<InstgAgt>		[0..1]		96
	InstructedAgent	<InstdAgt>		[0..1]		96
	CreditInstruction	<CdtInstr>		[1..*]	R[1..1]	18
	CreditIdentification	<CdtId>		[1..1]		54
	BatchBooking	<BtchBookg>		[0..1]		54
	PaymentTypeInformation	<PmtTpInf>		[0..1]		54
	TotalInterbankSettlementAmount	<TtlIntrBkSttlmAmt>		[0..1]		55
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		55
	SettlementTimeIndication	<SttlmTmIndctn>		[0..1]		55
	InstructingAgent	<InstgAgt>		[0..1]		56
	InstructedAgent	<InstdAgt>		[0..1]		56
	IntermediaryAgent1	<IntrmyAgt1>		[0..1]		57
	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		58
	IntermediaryAgent2	<IntrmyAgt2>		[0..1]		58
	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		59
	IntermediaryAgent3	<IntrmyAgt3>		[0..1]		59
	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		60
	CreditorAgent	<CdtrAgt>		[0..1]		61
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		62
	Creditor	<Cdtr>		[1..1]		62
	CreditorAccount	<CdtrAcct>		[0..1]		63

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	UltimateCreditor	<UltmtCdtr>		[0..1]	⊘	63
	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]	⊘	64
	DirectDebitTransactionInformation	<DrctDbtTxInf>		[1..*]	R[1..1]	64
	SupplementaryData	<SplmtryData>		[0..*]	⊘	65
	SupplementaryData	<SplmtryData>		[0..*]	⊘	19
	PlaceAndName	<PlcAndNm>		[0..1]		147
	Envelope	<Envlp>		[1..1]		147

3 ISO 20022 Rules

R1 **RelatedPresentWhenCopyDupl** ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

R4 **SupplementaryDataRule**

The SupplementaryData building block at message level must not be used to provide additional information about a transaction. The SupplementaryData element at transaction level should be used for that purpose.

Error handling: Undefined

Usage Guideline restrictions for this element

- **This rule(pacs.010.001.03/SupplementaryDataRule) is removed.**
-

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-pacs.010.001.03_Interbank Direct Debit message definition.

Usage Guideline on Root Node

- on pacs.010.001.03/fullmessage

- CBPR_To_Instructed_Agent_BIC_2_FormalRule:

BAH "To" BIC must match "Instructed Agent" BIC if CopyDuplicate is absent.

For each [Full Message], if
 the following element(s) [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] is (are) absent
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must
 have the same value than every occurrence of [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditInstruction/InstructedAgent/FinancialInstitutionIdentification/BICFI]

- on pacs.010.001.03/fullmessage

- CBPR_To_Instructed_Agent_BIC_1_FormalRule:

BAH "To" BIC must match "Instructed Agent" BIC, except where BAH CopyDuplicate = COPY or = CODU

For each [Full Message], if
 every occurrence of [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] has value not included in the following list 'COPY' or 'CODU'
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must
 have the same value than every occurrence of [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditInstruction/InstructedAgent/FinancialInstitutionIdentification/BICFI]

- on pacs.010.001.03/fullmessage

- CBPR_BusinessMessageIdentifier_FormalRule:

The Business Message Identifier must match the Message Identification in the Group Header.

For each [Full Message], every occurrence of [Full Message/BusinessApplicationHeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/FinancialInstitutionDirectDebitV03/GroupHeader/MessageIdentification] value

- on pacs.010.001.03/fullmessage

– **CBPR_From_Instructing_Agent_BIC_FormalRule:**

BAH "From" BIC must match "Instructing Agent" BIC

For each [Full Message], every occurrence of [Full Message/BusinessApplication-HeaderV02/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] value must be equal to every occurrence of [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditInstruction/InstructingAgent/FinancialInstitutionIdentification/BICFI] value

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 180

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice__1" on page 105 for details)

🚫 Removed - 🚫 Partial Removed - 💠 Ignored - 💠 Partial Ignored - ⚠️ Details below -
 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	106
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		106

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 105 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	106
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		106

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 157

Usage Guideline details

- on [pacs.010.001.03/header/BusinessMessageIdentifier](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 157

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "[Max35Text](#)" on page 175

Usage Guideline details

- on [pacs.010.001.03/header/MessageDefinitionIdentifier](#)

Single value: pacs.010.001.03

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 175

Usage Guideline details

- **on pacs.010.001.03/header/BusinessService**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.010.001.03/header/BusinessService**
Single value: swift.cbprplus.04

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "[ImplementationSpecification1](#)" on page 97 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		97
	Identification	<Id>		[1..1]		97

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: ["CBPR_DateTime" on page 153](#)

Usage Guideline details

- **on pacs.010.001.03/.header/CreationDate**
Type changed to: [CBPR_DateTime on page 153](#)

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: ["ISODatetime" on page 171](#)

Usage Guideline details

- **This element(pacs.010.001.03/.header/BusinessProcessingDate) is removed.**

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 160](#)

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 180](#)

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 178](#)

Usage Guideline details

- on [pacs.010.001.03/.header/Priority](#)
Type changed to: [Priority2Code on page 178](#)

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element([pacs.010.001.03/.header/Signature](#)) is removed.

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype ["BusinessApplicationHeader5__1" on page 33](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		34

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	From	<Fr>		[1..1]		34
	To	<To>		[1..1]		34
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]	⚠	35
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]	⚠	35
	BusinessService	<BizSvc>		[0..1]	⚠	36
	CreationDate	<CreDt>		[1..1]	⚠	36
	CopyDuplicate	<CpyDplct>		[0..1]		37
	PossibleDuplicate	<PssblDplct>		[0..1]	🚫	37
	Priority	<Prty>		[0..1]	⚠	37
	Signature	<Sgntr>		[0..1]	🚫	38

Usage Guideline details

- on pacs.010.001.03/.header/Related

This element has change repeatability, the maximum occurrence has been changed to : 1

- on pacs.010.001.03/.header/Related

- CBPR_Related_Business_Application_Header_TextualRule:

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-pacs.010.001.03_Interbank Direct Debit payload definition.

4.2.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Common characteristics for all individual transactions included in the message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader92__1" on page 94 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]	⚠	95
	CreationDateTime	<CreDtTm>		[1..1]	⚠	95
	NumberOfTransactions	<NbOfTx>		[1..1]	⚠	96
	ControlSum	<CtrlSum>		[0..1]	🚫	96
	InstructingAgent	<InstgAgt>		[0..1]	🚫	96
	InstructedAgent	<InstdAgt>		[0..1]	🚫	96

4.2.2 CreditInstruction

XML Tag: CdtInstr

Presence: [1..*]

Definition: Characteristics that apply to the credit side of the payment transaction(s) included in the message.

The **CdtInstr** block contains the following elements (see datatype "[CreditTransferTransaction38__1](#)" on page 50 for details)

🚫 Removed - 🚫 Partial Removed - ⚠ Ignored - ⚠ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CreditIdentification	<CdtId>		[1..1]	⚠	54
	BatchBooking	<BtchBookg>		[0..1]	🚫	54
	PaymentTypeInformation	<PmtTpInf>		[0..1]		54
	TotalInterbankSettlementAmount	<TtlIntrBkSttlmAmt>		[0..1]	🚫	55
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]	🚫	55
	SettlementTimeIndication	<SttlmTmIndctn>		[0..1]	🚫	55
	InstructingAgent	<InstgAgt>		[0..1]	M	56
	InstructedAgent	<InstdAgt>		[0..1]	M	56
	IntermediaryAgent1	<IntrmyAgt1>		[0..1]	⚠	57
	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		58
	IntermediaryAgent2	<IntrmyAgt2>		[0..1]	⚠	58
	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		59
	IntermediaryAgent3	<IntrmyAgt3>		[0..1]	⚠	59
	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		60
	CreditorAgent	<CdtrAgt>		[0..1]	⚠	61
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		62

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[1..1]		62
	CreditorAccount	<CdtrAcct>		[0..1]		63
	UltimateCreditor	<UltmtCdtr>		[0..1]		63
	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]		64
	DirectDebitTransactionInformation	<DrctDbtTxInf>		[1..*]	R[1..1]	64
	SupplementaryData	<SplmtryData>		[0..*]		65

Usage Guideline details

- on pacs.010.001.03/CreditInstruction

This element has change repeatability, the maximum occurrence has been changed to : 1

4.2.3 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "SupplementaryData1" on page 147 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		147
	Envelope	<Envlp>		[1..1]		147

Usage Guideline details

- This element(pacs.010.001.03/SupplementaryData) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification4Choice__1

Definition: Specifies the unique identification of an account as assigned by the account servicer.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		20
	Other	<Othr>	Or}	[1..1]		20

Used in element(s)

"Identification" on page 38

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 171

5.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1__1](#)" on page 89 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		89
	SchemeName	<SchmeNm>		[0..1]		90
	Issuer	<Issr>		[0..1]		90

5.2 AccountSchemeName1Choice__1

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		21
	Proprietary	<Prtry>	Or}	[1..1]		21

Used in element(s)

"SchemeName" on page 90

5.2.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 162

5.2.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAccount/Identification/Other/SchemeName/Proprietary
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgentAccount/Identification/Other/SchemeName/Proprietary
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on pacs.010.001.03/CreditInstruction/CreditorAgentAccount/Identification/Other/SchemeName/Proprietary
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on pacs.010.001.03/CreditInstruction/CreditorAccount/Identification/Other/SchemeName/Proprietary
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2Account/Identification/Other/SchemeName/Proprietary

Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)

- on [pacs.010.001.03/CreditInstruction/IntermediaryAgent3Account/Identification/Other/SchemeName/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)

- on [pacs.010.001.03/CreditInstruction/IntermediaryAgent1Account/Identification/Other/SchemeName/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)

5.3 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		22
	Proprietary	<Prtry>	Or}	[1..1]		22

Used in element(s)

["AddressType" on page 120](#), ["AddressType" on page 124](#), ["AddressType" on page 129](#)

5.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: ["AddressType2Code" on page 151](#)

5.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype ["GenericIdentification30" on page 92](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		92
	Issuer	<Issr>		[1..1]		92

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SchemeName	<SchmeNm>		[0..1]		92

5.4 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		23
	BranchIdentification	<BrnchId>		[0..1]		23

Used in element(s)

["FinancialInstitutionIdentification" on page 105](#),
 ["InstructedAgent" on page 96](#),
 ["InstructingAgent" on page 96](#),
 ["UltimateCreditor" on page 63](#),
 ["UltimateDebtor" on page 70](#)

5.4.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype ["FinancialInstitutionIdentification18" on page 75](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		75
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		76
	LEI	<LEI>		[0..1]		76
	Name	<Nm>		[0..1]		76
	PostalAddress	<PstlAdr>		[0..1]		76
	Other	<Othr>		[0..1]		77

5.4.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 32 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		32
	LEI	<LEI>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PostalAddress	<PstlAdr>		[0..1]		32

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(pacs.010.001.03/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification) is removed.

5.5 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		24
	BranchIdentification	<BrnchId>		[0..1]	🚫	25

Used in element(s)

"FinancialInstitutionIdentification" on page 106, "InstructedAgent" on page 56, "InstructingAgent" on page 56

5.5.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18__1" on page 78 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	78
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		79
	LEI	<LEI>		[0..1]		79
	Name	<Nm>		[0..1]	🚫	79
	PostalAddress	<PstlAdr>		[0..1]	🚫	80
	Other	<Othr>		[0..1]	🚫	81

5.5.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData3" on page 32 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		32
	LEI	<LEI>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PostalAddress	<PstlAdr>		[0..1]		32

Usage Guideline details

- This element(pacs.010.001.03/.header/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(pacs.010.001.03/CreditInstruction/InstructingAgent/BranchIdentification) is removed.

- This element([pacs.010.001.03/.header/From/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([pacs.010.001.03/CreditInstruction/InstructedAgent/BranchIdentification](#)) is removed.

5.6 BranchAndFinancialInstitutionIdentification6__2

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		26
	BranchIdentification	<BrnchId>		[0..1]		28

Used in element(s)

["IntermediaryAgent1" on page 57](#),
 ["IntermediaryAgent2" on page 58](#),
 ["IntermediaryAgent3" on page 59](#)

5.6.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18__2](#)" on page 81 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		82
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		82
	LEI	<LEI>		[0..1]		82
	Name	<Nm>		[0..1]		83
	PostalAddress	<PstlAdr>		[0..1]		83
	Other	<Othr>		[0..1]		84

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

```
For each [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditIn-
struction/IntermediaryAgent1/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] is (are) present
  then
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] must be present
    and for each [FinancialInstitutionIdentification], if
      at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] must be present
```

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

```
For each [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditIn-
struction/IntermediaryAgent2/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] is (are) present
  then
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] must be present
    and for each [FinancialInstitutionIdentification], if
      at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] must be present
```

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

```
For each [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditIn-
struction/IntermediaryAgent3/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] is (are) present
  then
```

at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

5.6.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 32 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		32
	LEI	<LEI>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PostalAddress	<PstlAdr>		[0..1]		32

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent1/BranchIdentification) is removed.
- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent2/BranchIdentification) is removed.
- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent3/BranchIdentification) is removed.

5.7 BranchAndFinancialInstitutionIdentification6__3

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		31

Used in element(s)

"Creditor" on page 62, "CreditorAgent" on page 61, "Debtor" on page 71, "DebtorAgent" on page 72

5.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18_3" on page 85 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		85
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		86
	LEI	<LEI>		[0..1]		86
	Name	<Nm>		[0..1]		86
	PostalAddress	<PstlAdr>		[0..1]		87
	Other	<Othr>		[0..1]		88

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification

- CBPR_Agent_Name_Postal_Address_FormalRule:

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditInstruction/Creditor/FinancialInstitutionIdentification],
for each [FinancialInstitutionIdentification], if
at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
then
at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
and for each [FinancialInstitutionIdentification], if

at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

For each [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

```

For each [Full Message/Document/FinancialInstitutionDirectDebitV03/CreditIn-
struction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionI-
dentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] must be present
      and for each [FinancialInstitutionIdentification], if
        at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitu-
tionIdentification/Name] must be present

```

5.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 32 for details)

 Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		32
	LEI	<LEI>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PostalAddress	<PstlAdr>		[0..1]		32

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/CreditorAgent/BranchIdentification) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/BranchIdentification) is removed.
- This element(pacs.010.001.03/CreditInstruction/Creditor/BranchIdentification) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/BranchIdentification) is removed.

5.8 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		32
	LEI	<LEI>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PostalAddress	<PstlAdr>		[0..1]		32

Used in element(s)

["BranchIdentification" on page 23](#),
 ["BranchIdentification" on page 25](#),
 ["BranchIdentification" on page 28](#),
 ["BranchIdentification" on page 31](#)

5.8.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: ["Max35Text" on page 175](#)

5.8.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: ["LEIIdentifier" on page 173](#)

5.8.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: ["Max140Text" on page 173](#)

5.8.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 119 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		120
	Department	<Dept>		[0..1]		120
	SubDepartment	<SubDept>		[0..1]		121
	StreetName	<StrtNm>		[0..1]		121
	BuildingNumber	<BldgNb>		[0..1]		121
	BuildingName	<BldgNm>		[0..1]		121
	Floor	<Flr>		[0..1]		121
	PostBox	<PstBx>		[0..1]		122
	Room	<Room>		[0..1]		122
	PostCode	<PstCd>		[0..1]		122
	TownName	<TwnNm>		[0..1]		122
	TownLocationName	<TwnLctnNm>		[0..1]		122
	DistrictName	<DstrctNm>		[0..1]		122
	CountrySubDivision	<CtrySubDvsn>		[0..1]		123
	Country	<Ctry>		[0..1]		123
	AddressLine	<AdrLine>		[0..7]		123

5.9 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		34
	From	<Fr>		[1..1]		34
	To	<To>		[1..1]		34
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		35
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		35

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BusinessService	<BizSvc>		[0..1]		36
	CreationDate	<CreDt>		[1..1]		36
	CopyDuplicate	<CpyDplct>		[0..1]		37
	PossibleDuplicate	<PssblDplct>		[0..1]		37
	Priority	<Prty>		[0..1]		37
	Signature	<Sgntr>		[0..1]		38

Used in element(s)

"Related" on page 16

5.9.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 180

5.9.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice" on page 104 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		104
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		105

5.9.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "Party44Choice" on page 104 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	104
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		105

5.9.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- on pacs.010.001.03/.header/Related/BusinessMessageIdentifier

Type changed to: CBPR_RestrictedFINXMax35Text on page 157

- on pacs.010.001.03/.header/Related/BusinessMessageIdentifier

– CBPR_Business_Message_Identifier_TextualRule:

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

5.9.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 157](#)

Usage Guideline details

- on **pacs.010.001.03/header/Related/MessageDefinitionIdentifier**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)

- on **pacs.010.001.03/header/Related/MessageDefinitionIdentifier**

- **CBPR_Message_Definition_Identifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.9.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 157](#)

Usage Guideline details

- on **pacs.010.001.03/header/Related/BusinessService**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)

- on **pacs.010.001.03/header/Related/BusinessService**

- **CBPR_Related_BAH_Business_Service_TextualRule:**

If related BAH is present, it should transport the element Business Service.

5.9.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 153](#)

Usage Guideline details

- on `pacs.010.001.03/.header/Related/CreationDate`

Type changed to: [CBPR_DateTime on page 153](#)

5.9.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 160](#)

5.9.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 180](#)

Usage Guideline details

- This element(`pacs.010.001.03/.header/Related/PossibleDuplicate`) is removed.

5.9.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 178](#)

Usage Guideline details

- on pacs.010.001.03/.header/Related/Priority
Type changed to: [Priority2Code](#) on page 178

5.9.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/Signature) is removed.

5.10 CashAccount38__1

Definition: Provides the details to identify an account.

❌ Removed - ❌ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		38
	Type	<Tp>		[0..1]		39
	Currency	<Ccy>		[0..1]		39
	Name	<Nm>		[0..1]	⚠️	39
	Proxy	<Prxy>		[0..1]		40

Used in element(s)

["CreditorAccount"](#) on page 63, ["CreditorAgentAccount"](#) on page 62, ["DebtorAccount"](#) on page 71, ["DebtorAgentAccount"](#) on page 73, ["IntermediaryAgent1Account"](#) on page 58, ["IntermediaryAgent2Account"](#) on page 59, ["IntermediaryAgent3Account"](#) on page 60

5.10.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype ["AccountIdentification4Choice__1"](#) on page 20 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		20
	Other	<Othr>	Or}	[1..1]		20

5.10.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice__1](#)" on page 40 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		41
	Proprietary	<Prtry>	Or}	[1..1]		41

5.10.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on page 150

5.10.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "CBPR_RestrictedFINXMax70Text" on page 158

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/CreditorAgentAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 158](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgentAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 158](#)
- on pacs.010.001.03/CreditInstruction/CreditorAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 158](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAccount/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 158](#)
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1Account/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 158](#)
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2Account/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 158](#)
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3Account/Name
Type changed to: [CBPR_RestrictedFINXMax70Text on page 158](#)

5.10.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "[ProxyAccountIdentification1__1](#)" on page 138 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		139
	Identification	<Id>		[1..1]		140

5.11 CashAccountType2Choice__1

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		41
	Proprietary	<Prtry>	Or}	[1..1]		41

Used in element(s)

["Type" on page 39](#)

5.11.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: ["ExternalCashAccountType1Code" on page 163](#)

5.11.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 157](#)

Usage Guideline details

- on **pacs.010.001.03/CreditInstruction/CreditorAccount/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgentAccount/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAccount/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/CreditorAgentAccount/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/IntermediaryAgent1Account/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/IntermediaryAgent2Account/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/IntermediaryAgent3Account/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)

5.12 CategoryPurpose1Choice__1

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		42
	Proprietary	<Prtry>	Or}	[1..1]	⚠️	42

Used in element(s)

"CategoryPurpose" on page 114, "CategoryPurpose" on page 117

5.12.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: "ExternalCategoryPurpose1Code" on page 164

5.12.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/PaymentTypeInformation/CategoryPurpose/Proprietary
 Type changed to: CBPR_RestrictedFINXMax35Text on page 157
- on pacs.010.001.03/CreditInstruction/PaymentTypeInformation/CategoryPurpose/Proprietary
 Type changed to: CBPR_RestrictedFINXMax35Text on page 157

5.13 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		43
	Proprietary	<Prtry>	Or}	[1..1]		43

Used in element(s)

["ClearingSystemIdentification" on page 44](#), ["ClearingSystemIdentification" on page 45](#)

5.13.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code" on page 164](#)

5.13.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text" on page 175](#)

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.010.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.010.001.03/CreditInstruction/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.

- This element(pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.010.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.

5.14 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	44
	MemberIdentification	<MmbId>		[1..1]		45

Used in element(s)

"ClearingSystemMemberIdentification" on page 76, "ClearingSystemMemberIdentification" on page 82

5.14.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 42 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		43
	Proprietary	<Prtry>	Or}	[1..1]		43

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1

5.14.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "Max35Text" on page 175

5.15 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		45
	MemberIdentification	<Mmbld>		[1..1]		46

Used in element(s)

"ClearingSystemMemberIdentification" on page 79, "ClearingSystemMemberIdentification" on page 86

5.15.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 42 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		43
	Proprietary	<Prtry>	Or}	[1..1]		43

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.15.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "CBPR_RestrictedFINXMax28Text" on page 155

Usage Guideline details

- on pacs.010.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 155](#)
- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 155](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 155](#)
- on pacs.010.001.03/CreditInstruction/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 155](#)
- on pacs.010.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 155](#)
- on pacs.010.001.03/CreditInstruction/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 155](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 155](#)
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 155](#)

5.16 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		48

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		48
	PhoneNumber	<PhneNb>		[0..1]		48
	MobileNumber	<MobNb>		[0..1]		48
	FaxNumber	<FaxNb>		[0..1]		49
	EmailAddress	<EmailAdr>		[0..1]		49
	EmailPurpose	<EmailPurp>		[0..1]		49
	JobTitle	<JobTitt>		[0..1]		49
	Responsibility	<Rspnsblty>		[0..1]		49
	Department	<Dept>		[0..1]		49
	Other	<Othr>		[0..*]		50
	PreferredMethod	<PrefrdMtd>		[0..1]		50

Used in element(s)

"ContactDetails" on page 109

5.16.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 176

5.16.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 173

5.16.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 177

5.16.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 177](#)

5.16.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 177](#)

5.16.6 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: ["Max2048Text" on page 174](#)

5.16.7 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: ["Max35Text" on page 175](#)

5.16.8 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: ["Max35Text" on page 175](#)

5.16.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: ["Max35Text" on page 175](#)

5.16.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 176

5.16.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 102 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		102
	Identification	<Id>		[0..1]		103

5.16.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod1Code" on page 177

5.17 CreditTransferTransaction38__1

Definition: Provides further details specific to the individual transaction(s) included in the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CreditIdentification	<CdtId>		[1..1]		54
	BatchBooking	<BtchBookg>		[0..1]		54
	PaymentTypeInformation	<PmtTplnf>		[0..1]		54
	TotalInterbankSettlementAmount	<TtlIntrBkSttlmAmt>		[0..1]		55
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		55
	SettlementTimeIndication	<SttlmTmIndctn>		[0..1]		55
	InstructingAgent	<InstgAgt>		[0..1]		56
	InstructedAgent	<InstdAgt>		[0..1]		56
	IntermediaryAgent1	<IntrmyAgt1>		[0..1]		57

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		58
	IntermediaryAgent2	<IntrmyAgt2>		[0..1]		58
	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		59
	IntermediaryAgent3	<IntrmyAgt3>		[0..1]		59
	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		60
	CreditorAgent	<CdtrAgt>		[0..1]		61
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		62
	Creditor	<Cdtr>		[1..1]		62
	CreditorAccount	<CdtrAcct>		[0..1]		63
	UltimateCreditor	<UltmtCdtr>		[0..1]		63
	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]		64
	DirectDebitTransactionInformation	<DrctDbtTxInf>		[1..*]	R[1..1]	64
	SupplementaryData	<SplmtryData>		[0..*]		65

Rules

R9 IntermediaryAgent2Rule ✓

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

R10 IntermediaryAgent3Rule ✓

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

R11 IntermediaryAgent1Rule ✓

If IntermediaryAgent1 is present, then CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00060

- *Error Text:* Invalid message content for intermediary agent 1.

R12 IntermediaryAgent1AccountRule ✓

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

R13 IntermediaryAgent2AccountRule ✓

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

R14 IntermediaryAgent3AccountRule ✓

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

R15 CreditorAgentAccountRule ✓

If CreditorAgentAccount is present, then CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00058
- *Error Text:* Invalid message content for creditor agent account.

R16 TotalInterbankSettlementAmountRule ✓

If CreditInformation/TotalInterbankSettlementAmount is present, then all occurrences of Direct-DebitTransactionInformation/InterbankSettlementAmount must have the same currency as the currency of CreditInformation/TotalInterbankSettlementAmount.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00042
- *Error Text:* Invalid message content for the total interbank settlement amount and individual interbank settlement amount currencies.

Usage Guideline restrictions for this element

- This rule(pacs.010.001.03/CreditInstruction/TotalInterbankSettlementAmountRule) is removed.

R17 TotalInterbankSettlementAmountAndSumRule

If TotalInterbankSettlementAmount is present, then it must equal the sum of all occurrences of DirectDebitTransactionInformation/InterbankSettlementAmount.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00043
- *Error Text:* Invalid message content for the total interbank settlement amount and sum of individual interbank settlement amounts.

Usage Guideline restrictions for this element

- This rule(pacs.010.001.03/CreditInstruction/TotalInterbankSettlementAmountAndSumRule) is removed.

R18 InterbankSettlementDateRule ✓

If InterbankSettlementDate is present, then DirectDebitTransactionInformation/InterbankSettlementDate is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00045
- *Error Text:* Invalid message content for interbank settlement date.

Usage Guideline restrictions for this element

- This rule(pacs.010.001.03/CreditInstruction/InterbankSettlementDateRule) is removed.

R19 PaymentTypeInfoRule ✓

If PaymentTypeInfo is present, then DirectDebitTransactionInformation/PaymentTypeInfo is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00009
- *Error Text:* Invalid message content for payment type information.

Guidelines

1. UltimateCreditorGuideline

UltimateCreditor may only be present if different from Creditor.

Used in element(s)

"CreditInstruction" on page 18

5.17.1 CreditIdentification

XML Tag: CdtId

Presence: [1..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the credit instruction within the message.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 154

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/CreditIdentification
Type changed to: CBPR_RestrictedFINXMax16Text on page 154

5.17.2 BatchBooking

XML Tag: BtchBookg

Presence: [0..1]

Definition: Identifies whether a single entry per individual direct debit transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.

Usage: Batch booking is used to request and not order a possible batch booking.

Datatype: "BatchBookingIndicator" on page 153

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/BatchBooking) is removed.

5.17.3 PaymentTypeInfo

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Further specifies the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "PaymentTypeInfoInformation28_1" on page 113 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		113

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingChannel	<ClrChanl>		[0..1]		113
	ServiceLevel	<SvcLv>		[0..*]		114
	LocalInstrument	<LclInstrm>		[0..1]		114
	CategoryPurpose	<CtgyPurp>		[0..1]		114

5.17.4 TotalInterbankSettlementAmount

XML Tag: TtlIntrBkSttlmAmt

Presence: [0..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: "ActiveCurrencyAndAmount" on page 149

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/TotalInterbankSettlementAmount) is removed.

5.17.5 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "ISODate" on page 171

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/InterbankSettlementDate) is removed.

5.17.6 SettlementTimeIndication

XML Tag: SttlmTmIndctn

Presence: [0..1]

Definition: Provides information on the occurred settlement time(s) of the payment transaction.

The **SttlmTmIndctn** block contains the following elements (see datatype "SettlementDateTimelndication1" on page 144 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebitDateTime	<DbtDtTm>		[0..1]		145

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CreditDateTime	<CdtDtTm>		[0..1]		145

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/SettlementTimeIndication) is removed.

5.17.7 InstructingAgent

XML Tag: InstgAgt

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

The **InstgAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6_1" on page 24 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		24
	BranchIdentification	<BrnchId>		[0..1]		25

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/InstructingAgent

This element is now mandatory, the minimum occurrence has been changed to : 1

5.17.8 InstructedAgent

XML Tag: InstdAgt

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

The **InstdAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6_1" on page 24 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		24
	BranchIdentification	<BrnchId>		[0..1]		25

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/InstructedAgent

This element is now mandatory, the minimum occurrence has been changed to : 1

5.17.9 IntermediaryAgent1

XML Tag: IntrmyAgt1

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

The **IntrmyAgt1** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__2" on page 26 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		26
	BranchIdentification	<BrnchId>		[0..1]		28

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1

- CBPR_Agent_Option_1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1

- CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1

- CBPR_Agent_Option_2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1

- CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.17.10 IntermediaryAgent1Account

XML Tag: IntrmyAgt1Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.

The **IntrmyAgt1Acct** block contains the following elements (see datatype "[CashAccount38__1](#)" on [page 38](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		38
	Type	<Tp>		[0..1]		39
	Currency	<Ccy>		[0..1]		39
	Name	<Nm>		[0..1]		39
	Proxy	<Prxy>		[0..1]		40

5.17.11 IntermediaryAgent2

XML Tag: IntrmyAgt2

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

The **IntrmyAgt2** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__2](#)" on [page 26](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		26
	BranchIdentification	<BrnchId>		[0..1]		28

Usage Guideline details

- on [pacs.010.001.03/CreditInstruction/IntermediaryAgent2](#)

– **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

• **on pacs.010.001.03/CreditInstruction/IntermediaryAgent2**

– **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

• **on pacs.010.001.03/CreditInstruction/IntermediaryAgent2**

– **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

• **on pacs.010.001.03/CreditInstruction/IntermediaryAgent2**

– **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.17.12 IntermediaryAgent2Account

XML Tag: IntrmyAgt2Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.

The **IntrmyAgt2Acct** block contains the following elements (see datatype "[CashAccount38__1](#)" on [page 38](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		38
	Type	<Tp>		[0..1]		39
	Currency	<Ccy>		[0..1]		39
	Name	<Nm>		[0..1]	⚠	39
	Proxy	<Prxy>		[0..1]		40

5.17.13 IntermediaryAgent3

XML Tag: IntrmyAgt3

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

The **IntrmyAgt3** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__2" on page 26 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	26
	BranchIdentification	<BrnchId>		[0..1]	🚫	28

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.17.14 IntermediaryAgent3Account

XML Tag: IntrmyAgt3Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain.

The **IntrmyAgt3Acct** block contains the following elements (see datatype "[CashAccount38__1](#)" on [page 38](#) for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		38
	Type	<Tp>		[0..1]		39
	Currency	<Ccy>		[0..1]		39
	Name	<Nm>		[0..1]		39
	Proxy	<Prxy>		[0..1]		40

5.17.15 CreditorAgent

XML Tag: CdtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__3](#)" on [page 28](#) for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		31

Usage Guideline details

- on [pacs.010.001.03/CreditInstruction/CreditorAgent](#)
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on [pacs.010.001.03/CreditInstruction/CreditorAgent](#)
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on [pacs.010.001.03/CreditInstruction/CreditorAgent](#)
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on pacs.010.001.03/CreditInstruction/CreditorAgent

- CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.17.16 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "CashAccount38__1" on page 38 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		38
	Type	<Tp>		[0..1]		39
	Currency	<Ccy>		[0..1]		39
	Name	<Nm>		[0..1]		39
	Proxy	<Prxy>		[0..1]		40

5.17.17 Creditor

XML Tag: Cdtr

Presence: [1..1]

Definition: Financial institution that receives an amount of money from the financial institutional debtor.

The **Cdtr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__3" on page 28 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		29
	BranchIdentification	<BrnchId>		[0..1]		31

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/Creditor
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on pacs.010.001.03/CreditInstruction/Creditor
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on pacs.010.001.03/CreditInstruction/Creditor
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on pacs.010.001.03/CreditInstruction/Creditor
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.17.18 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount38__1" on page 38 for details)

⊘ Removed - ⊘ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ▲ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		38
	Type	<Tp>		[0..1]		39
	Currency	<Ccy>		[0..1]		39
	Name	<Nm>		[0..1]	▲	39
	Proxy	<Prxy>		[0..1]		40

5.17.19 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate financial institution to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 23 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		23
	BranchIdentification	<BrnchId>		[0..1]		23

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/UltimateCreditor) is removed.

5.17.20 InstructionForCreditorAgent

XML Tag: InstrForCdtrAgt

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

The **InstrForCdtrAgt** block contains the following elements (see datatype "[InstructionForCreditorAgent2](#)" on page 98 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		98
	InstructionInformation	<InstrInf>		[0..1]		98

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/InstructionForCreditorAgent) is removed.

5.17.21 DirectDebitTransactionInformation

XML Tag: DrctDbtTxInf

Presence: [1..*]

Definition: Provides information on the individual debit transaction(s) included in the message.

The **DrctDbtTxInf** block contains the following elements (see datatype "[DirectDebitTransactionInformation25__1](#)" on page 67 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PaymentIdentification	<PmtId>		[1..1]		68
	PaymentTypeInformation	<PmtTpInf>		[0..1]		68
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[1..1]		68
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]	 	69
	SettlementPriority	<SttlmPrty>		[0..1]		69
	SettlementTimeIndication	<SttlmTmIndctn>		[0..1]		69
	SettlementTimeRequest	<SttlmTmReq>		[0..1]		70
	UltimateDebtor	<UltmtDbtr>		[0..1]		70
	Debtor	<Dbtr>		[1..1]		71
	DebtorAccount	<DbtrAcct>		[0..1]		71
	DebtorAgent	<DbtrAgt>		[0..1]		72
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		73
	InstructionForDebtorAgent	<InstrForDbtrAgt>		[0..1]		73
	Purpose	<Purp>		[0..1]		73
	RemittanceInformation	<RmtInf>		[0..1]		74

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation

This element has change repeatability, the maximum occurrence has been changed to : 1

5.17.22 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "SupplementaryData1" on page 147 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		147

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Envelope	<Envlp>		[1..1]		147

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/SupplementaryData) is removed.

5.18 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		66
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		66
	CityOfBirth	<CityOfBirth>		[1..1]		66
	CountryOfBirth	<CtryOfBirth>		[1..1]		67

Used in element(s)

"DateAndPlaceOfBirth" on page 117

5.18.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 171

5.18.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "Max35Text" on page 175

5.18.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: "Max35Text" on page 175

5.18.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 161

5.19 DirectDebitTransactionInformation25__1

Definition: Provides further details specific to the individual direct debit transaction(s) included in the message.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PaymentIdentification	<PmtId>		[1..1]		68
	PaymentTypeInformation	<PmtTpInf>		[0..1]		68
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[1..1]		68
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]	M ⚠	69
	SettlementPriority	<SttlmPrty>		[0..1]	🚫	69
	SettlementTimeIndication	<SttlmTmIndctn>		[0..1]	🚫	69
	SettlementTimeRequest	<SttlmTmReq>		[0..1]		70
	UltimateDebtor	<UltmtDbtr>		[0..1]	🚫	70
	Debtor	<Dbtr>		[1..1]	⚠	71
	DebtorAccount	<DbtrAcct>		[0..1]		71
	DebtorAgent	<DbtrAgt>		[0..1]	⚠	72
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		73
	InstructionForDebtorAgent	<InstrForDbtrAgt>		[0..1]	⚠	73
	Purpose	<Purp>		[0..1]		73
	RemittanceInformation	<RmtInf>		[0..1]		74

Guidelines

1. UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

Used in element(s)

"DirectDebitTransactionInformation" on page 64

5.19.1 PaymentIdentification

XML Tag: PmtId

Presence: [1..1]

Definition: References used for a payment instruction.

The **PmtId** block contains the following elements (see datatype "[PaymentIdentification7__1](#)" on page 110 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionIdentification	<InstrId>		[0..1]	 	111
	EndToEndIdentification	<EndToEndId>		[1..1]		111
	TransactionIdentification	<TxId>		[0..1]		112
	UETR	<UETR>		[0..1]		112
	ClearingSystemReference	<ClrSysRef>		[0..1]		112

5.19.2 PaymentTypeInfo

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Specifies the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "[PaymentTypeInfoInformation28__2](#)" on page 115 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		115
	ClearingChannel	<ClrChanl>		[0..1]		115
	ServiceLevel	<SvcLvl>		[0..*]	R[0..3]	116
	LocalInstrument	<LclInstrm>		[0..1]		116
	CategoryPurpose	<CtgyPurp>		[0..1]		117

5.19.3 InterbankSettlementAmount

XML Tag: IntrBkSttlmAmt

Presence: [1..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: "[ActiveCurrencyAndAmount](#)" on page 149

5.19.4 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "CBPR_Date" on page 153

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/InterbankSettlementDate

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/InterbankSettlementDate

Type changed to: CBPR_Date on page 153

5.19.5 SettlementPriority

XML Tag: SttlmPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction.

Datatype: "Priority3Code" on page 179

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/SettlementPriority) is removed.

5.19.6 SettlementTimeIndication

XML Tag: SttlmTmIndctn

Presence: [0..1]

Definition: Provides information on the occurred settlement time(s) of the payment transaction.

The **SttlmTmIndctn** block contains the following elements (see datatype "SettlementDateTimelIndication1" on page 144 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebitDateTime	<DbtDtTm>		[0..1]		145
	CreditDateTime	<CdtDtTm>		[0..1]		145

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/SettlementTimeIndication) is removed.

5.19.7 SettlementTimeRequest

XML Tag: SttlmTmReq

Presence: [0..1]

Definition: Provides information on the requested settlement time(s) of the payment instruction.

The **SttlmTmReq** block contains the following elements (see datatype "SettlementTimeRequest2__1" on page 145 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CLSTime	<CLSTm>		[0..1]	⚠	146
	TillTime	<TillTm>		[0..1]	⚠	146
	FromTime	<FrTm>		[0..1]	⚠	146
	RejectTime	<RjctTm>		[0..1]	⚠	146

5.19.8 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate financial institution that owes an amount of money to the (ultimate) institutional creditor.

The **UltmtDbtr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 23 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		23
	BranchIdentification	<BrnchId>		[0..1]		23

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/UltimateDebtor) is removed.

5.19.9 Debtor

XML Tag: Dbtr

Presence: [1..1]

Definition: Financial institution that owes an amount of money to the (ultimate) financial institutional creditor.

The **Dbtr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__3" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	31

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.19.10 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "CashAccount38__1" on page 38 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		38
	Type	<Tp>		[0..1]		39
	Currency	<Ccy>		[0..1]		39
	Name	<Nm>		[0..1]	⚠	39
	Proxy	<Prxy>		[0..1]		40

5.19.11 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__3" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	29
	BranchIdentification	<BrnchId>		[0..1]	🚫	31

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent
 - **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent

- CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

5.19.12 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount38__1" on page 38 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		38
	Type	<Tp>		[0..1]		39
	Currency	<Ccy>		[0..1]		39
	Name	<Nm>		[0..1]		39
	Proxy	<Prxy>		[0..1]		40

5.19.13 InstructionForDebtorAgent

XML Tag: InstrForDbtrAgt

Presence: [0..1]

Definition: Further information related to the processing of the payment instruction, that may need to be acted upon by the debtor agent, depending on agreement between debtor and the debtor agent.

Datatype: "CBPR_RestrictedFINXMax210Text" on page 155

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Instruction-ForDebtorAgent

Type changed to: CBPR_RestrictedFINXMax210Text on page 155

5.19.14 Purpose

XML Tag: Purp

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype "[Purpose2Choice__1](#)" on page 141 for details)

⊘ Removed - !⊘ Partial Removed - ◇ Ignored - !◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		142
	Proprietary	<Prtry>	Or}	[1..1]	⚠	142

5.19.15 RemittanceInformation

XML Tag: RmtInf

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

The **RmtInf** block contains the following elements (see datatype "[RemittanceInformation2__1](#)" on page 142 for details)

⊘ Removed - !⊘ Partial Removed - ◇ Ignored - !◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]	M ⚠ R[1..1]	143

5.20 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

⊘ Removed - !⊘ Partial Removed - ◇ Ignored - !◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		74
	Proprietary	<Prtry>	Or}	[1..1]		75

Used in element(s)

"[SchemeName](#)" on page 91

5.20.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalFinancialInstitutionIdentification1Code" on page 165](#)

5.20.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 175](#)

5.21 FinancialInstitutionIdentification18

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		75
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		76
	LEI	<LEI>		[0..1]		76
	Name	<Nm>		[0..1]		76
	PostalAddress	<PstlAdr>		[0..1]		76
	Other	<Othr>		[0..1]		77

Used in element(s)

["FinancialInstitutionIdentification" on page 23](#)

5.21.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: ["BICFIDec2014Identifier" on page 152](#)

Usage Guideline details

- on pacs.010.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.010.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI

This element is now mandatory, the minimum occurrence has been changed to : 1

5.21.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		44
	MemberIdentification	<Mmbld>		[1..1]		45

5.21.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "[LEIIdentifier](#)" on page 173

5.21.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[Max140Text](#)" on page 173

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.010.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.

5.21.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		120
	Department	<Dept>		[0..1]		120
	SubDepartment	<SubDept>		[0..1]		121
	StreetName	<StrtNm>		[0..1]		121
	BuildingNumber	<BldgNb>		[0..1]		121
	BuildingName	<BldgNm>		[0..1]		121
	Floor	<Flr>		[0..1]		121
	PostBox	<PstBx>		[0..1]		122
	Room	<Room>		[0..1]		122
	PostCode	<PstCd>		[0..1]		122
	TownName	<TwnNm>		[0..1]		122
	TownLocationName	<TwnLctnNm>		[0..1]		122
	DistrictName	<DstrctNm>		[0..1]		122
	CountrySubDivision	<CtrySubDvsn>		[0..1]		123
	Country	<Ctry>		[0..1]		123
	AddressLine	<AdrLine>		[0..7]		123

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.010.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.

5.21.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 91 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]		91
	Issuer	<Issr>		[0..1]		91

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.010.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.

5.22 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		78
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		79
	LEI	<LEI>		[0..1]		79
	Name	<Nm>		[0..1]		79
	PostalAddress	<PstlAdr>		[0..1]		80
	Other	<Othr>		[0..1]		81

Used in element(s)

"FinancialInstitutionIdentification" on page 24

5.22.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 152

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/InstructingAgent/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/InstructedAgent/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1

5.22.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		45
	MemberIdentification	<Mmbld>		[1..1]		46

5.22.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 173

5.22.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 173

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/InstructedAgent/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.010.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.010.001.03/CreditInstruction/InstructingAgent/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.010.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.

5.22.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		120
	Department	<Dept>		[0..1]		120
	SubDepartment	<SubDept>		[0..1]		121
	StreetName	<StrtNm>		[0..1]		121
	BuildingNumber	<BldgNb>		[0..1]		121
	BuildingName	<BldgNm>		[0..1]		121
	Floor	<Flr>		[0..1]		121
	PostBox	<PstBx>		[0..1]		122
	Room	<Room>		[0..1]		122
	PostCode	<PstCd>		[0..1]		122
	TownName	<TwnNm>		[0..1]		122
	TownLocationName	<TwnLctnNm>		[0..1]		122
	DistrictName	<DstrctNm>		[0..1]		122
	CountrySubDivision	<CtrySubDvsn>		[0..1]		123
	Country	<Ctry>		[0..1]		123
	AddressLine	<AdrLine>		[0..7]		123

Usage Guideline details

- This element(pacs.010.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.010.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.010.001.03/CreditInstruction/InstructingAgent/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.010.001.03/CreditInstruction/InstructedAgent/FinancialInstitutionIdentification/PostalAddress) is removed.

5.22.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 91 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]		91
	Issuer	<Issr>		[0..1]		91

Usage Guideline details

- This element(pacs.010.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.010.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.010.001.03/CreditInstruction/InstructedAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.010.001.03/CreditInstruction/InstructingAgent/FinancialInstitutionIdentification/Other) is removed.

5.23 FinancialInstitutionIdentification18__2

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		82
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		82
	LEI	<LEI>		[0..1]		82
	Name	<Nm>		[0..1]		83
	PostalAddress	<PstlAdr>		[0..1]		83
	Other	<Othr>		[0..1]		84

Used in element(s)

"FinancialInstitutionIdentification" on page 26

5.23.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 152

5.23.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		44
	MemberIdentification	<Mmbld>		[1..1]		45

5.23.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 173

5.23.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 154

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 154](#)
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 154](#)
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 154](#)

5.23.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__1" on page 123 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		124
	Department	<Dept>		[0..1]		125
	SubDepartment	<SubDept>		[0..1]		125
	StreetName	<StrtNm>		[0..1]		125
	BuildingNumber	<BldgNb>		[0..1]		125
	BuildingName	<BldgNm>		[0..1]		125
	Floor	<Flr>		[0..1]		125
	PostBox	<PstBx>		[0..1]		126

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Room	<Room>		[0..1]		126
	PostCode	<PstCd>		[0..1]		126
	TownName	<TwnNm>		[0..1]	M ⚠	126
	TownLocationName	<TwnLctnNm>		[0..1]		127
	DistrictName	<DstrctNm>		[0..1]		127
	CountrySubDivision	<CtrySubDvsn>		[0..1]		127
	Country	<Ctry>		[0..1]	M	127
	AddressLine	<AdrLine>		[0..7]	⚠ R[0..2] R[0..2] R[0..2]	127

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.23.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 91 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]		91
	Issuer	<Issr>		[0..1]		91

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/Other) is removed.

5.24 FinancialInstitutionIdentification18__3

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		85
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		86
	LEI	<LEI>		[0..1]		86
	Name	<Nm>		[0..1]		86
	PostalAddress	<PstlAdr>		[0..1]		87
	Other	<Othr>		[0..1]		88

Used in element(s)

"FinancialInstitutionIdentification" on page 29

5.24.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 152

5.24.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		45
	MemberIdentification	<Mmbld>		[1..1]		46

5.24.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 173

5.24.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 154

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/Name**
 Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 154
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/Name**
 Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 154
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/Name**
 Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 154
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/Name**
 Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 154

5.24.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__2" on page 128 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		129
	Department	<Dept>		[0..1]		130
	SubDepartment	<SubDept>		[0..1]		130
	StreetName	<StrtNm>		[0..1]		131
	BuildingNumber	<BldgNb>		[0..1]		131
	BuildingName	<BldgNm>		[0..1]		132
	Floor	<Flr>		[0..1]		132
	PostBox	<PstBx>		[0..1]		133
	Room	<Room>		[0..1]		134
	PostCode	<PstCd>		[0..1]		134
	TownName	<TwnNm>		[0..1]	 	135
	TownLocationName	<TwnLctnNm>		[0..1]		135
	DistrictName	<DstrctNm>		[0..1]		136
	CountrySubDivision	<CtrySubDvsn>		[0..1]		137
	Country	<Ctry>		[0..1]		137
	AddressLine	<AdrLine>		[0..7]	 R[0..2] R[0..2] R[0..2] R[0..2]	138

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/Postal-Address
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress

- CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress

- CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.24.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 91 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]		91
	Issuer	<Issr>		[0..1]		91

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/Othr) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/Other) is removed.

5.25 GenericAccountIdentification1__1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		89
	SchemeName	<SchmeNm>		[0..1]		90
	Issuer	<Issr>		[0..1]		90

Used in element(s)

"Other" on page 20

5.25.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: ["CBPR_RestrictedFINXMax34Text" on page 156](#)

Usage Guideline details

- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAccount/Identification/Other/Identification](#)
 Type changed to: [CBPR_RestrictedFINXMax34Text on page 156](#)
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgentAccount/Identification/Other/Identification](#)
 Type changed to: [CBPR_RestrictedFINXMax34Text on page 156](#)
- on [pacs.010.001.03/CreditInstruction/CreditorAccount/Identification/Other/Identification](#)
 Type changed to: [CBPR_RestrictedFINXMax34Text on page 156](#)
- on [pacs.010.001.03/CreditInstruction/CreditorAgentAccount/Identification/Other/Identification](#)
 Type changed to: [CBPR_RestrictedFINXMax34Text on page 156](#)
- on [pacs.010.001.03/CreditInstruction/IntermediaryAgent1Account/Identification/Other/Identification](#)
 Type changed to: [CBPR_RestrictedFINXMax34Text on page 156](#)
- on [pacs.010.001.03/CreditInstruction/IntermediaryAgent2Account/Identification/Other/Identification](#)
 Type changed to: [CBPR_RestrictedFINXMax34Text on page 156](#)
- on [pacs.010.001.03/CreditInstruction/IntermediaryAgent3Account/Identification/Other/Identification](#)

Type changed to: [CBPR_RestrictedFINXMax34Text on page 156](#)

5.25.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[AccountScheme-Name1Choice_1](#)" on page 21 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		21
	Proprietary	<Prtry>	Or}	[1..1]		21

5.25.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 157

Usage Guideline details

- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgentAccount/Identification/Other/Issuer](#)
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAccount/Identification/Other/Issuer](#)
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on [pacs.010.001.03/CreditInstruction/CreditorAgentAccount/Identification/Other/Issuer](#)
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on [pacs.010.001.03/CreditInstruction/CreditorAccount/Identification/Other/Issuer](#)
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on [pacs.010.001.03/CreditInstruction/IntermediaryAgent1Account/Identification/Other/Issuer](#)
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on [pacs.010.001.03/CreditInstruction/IntermediaryAgent2Account/Identification/Other/Issuer](#)
 Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on [pacs.010.001.03/CreditInstruction/IntermediaryAgent3Account/Identification/Other/Issuer](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)

5.26 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]		91
	Issuer	<Issr>		[0..1]		91

Used in element(s)

"Other" on page 77, "Other" on page 81, "Other" on page 84, "Other" on page 88

5.26.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: ["Max35Text" on page 175](#)

5.26.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["FinancialIdentificationScheme-Name1Choice" on page 74](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		74
	Proprietary	<Prtry>	Or}	[1..1]		75

5.26.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 175

5.27 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		92
	Issuer	<Issr>		[1..1]		92
	SchemeName	<SchmeNm>		[0..1]		92

Used in element(s)

"Proprietary" on page 22

5.27.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 162

5.27.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 175

5.27.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max35Text" on page 175

5.28 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		93
	SchemeName	<SchmeNm>		[0..1]		93
	Issuer	<Issr>		[0..1]		93

Used in element(s)

"Other" on page 101

5.28.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 175

5.28.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 102 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		102
	Proprietary	<Prtry>	Or}	[1..1]		102

5.28.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 175

5.29 GenericPersonIdentification1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		94
	SchemeName	<SchmeNm>		[0..1]		94
	Issuer	<Issr>		[0..1]		94

Used in element(s)

"Other" on page 118

5.29.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 175

5.29.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationSchemeName1Choice](#)" on page 118 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		118
	Proprietary	<Prtry>	Or}	[1..1]		119

5.29.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 175

5.30 GroupHeader92__1

Definition: Set of characteristics shared by all individual transactions included in the message.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		95
	CreationDateTime	<CreDtTm>		[1..1]		95
	NumberOfTransactions	<NbOfTx>		[1..1]		96
	ControlSum	<CtrlSum>		[0..1]		96
	InstructingAgent	<InstgAgt>		[0..1]		96
	InstructedAgent	<InstdAgt>		[0..1]		96

Used in element(s)

"GroupHeader" on page 17

5.30.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- on pacs.010.001.03/GroupHeader/MessageIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 157

5.30.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: "CBPR_DateTime" on page 153

Usage Guideline details

- on pacs.010.001.03/GroupHeader/CreationDateTime
Type changed to: CBPR_DateTime on page 153

5.30.3 NumberOfTransactions

XML Tag: NbOfTxs

Presence: [1..1]

Definition: Number of individual transactions contained in the message.

Datatype: "Max15NumericText" on page 174

Usage Guideline details

- on pacs.010.001.03/GroupHeader/NumberOfTransactions
Single value: 1

5.30.4 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: "DecimalNumber" on page 161

Usage Guideline details

- This element(pacs.010.001.03/GroupHeader/ControlSum) is removed.

5.30.5 InstructingAgent

XML Tag: InstgAgt

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

The **InstgAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 23 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		23
	BranchIdentification	<BrnchId>		[0..1]		23

Usage Guideline details

- This element(pacs.010.001.03/GroupHeader/InstructingAgent) is removed.

5.30.6 InstructedAgent

XML Tag: InstdAgt

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

The **InstdAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 23 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		23
	BranchIdentification	<BrnchId>		[0..1]		23

Usage Guideline details

- This element(pacs.010.001.03/GroupHeader/InstructedAgent) is removed.

5.31 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		97
	Identification	<Id>		[1..1]		97

Used in element(s)

["MarketPractice"](#) on page 14

5.31.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "[Max350Text](#)" on page 175

5.31.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: ["Max2048Text" on page 174](#)

5.32 InstructionForCreditorAgent2

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		98
	InstructionInformation	<InstrInf>		[0..1]		98

Used in element(s)

["InstructionForCreditorAgent" on page 64](#)

5.32.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

Datatype: ["Instruction5Code" on page 172](#)

5.32.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

Datatype: ["Max140Text" on page 173](#)

5.33 LocalInstrument2Choice

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		99
	Proprietary	<Prtry>	Or}	[1..1]		99

Used in element(s)

"LocalInstrument" on page 114

5.33.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: "ExternalLocalInstrument1Code" on page 166

5.33.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: "Max35Text" on page 175

5.34 LocalInstrument2Choice__1

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		99
	Proprietary	<Prtry>	Or}	[1..1]		100

Used in element(s)

"LocalInstrument" on page 116

5.34.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: "ExternalLocalInstrument1Code" on page 166

5.34.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/PaymentTypeInformation/LocalInstrument/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 157

5.35 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]	🚫	100
	LEI	<LEI>		[0..1]	🚫	101
	Other	<Othr>		[0..*]	🚫	101

Used in element(s)

"OrganisationIdentification" on page 103

5.35.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 151

Usage Guideline details

- This element(pacs.010.001.03/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC) is removed.
- This element(pacs.010.001.03/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC) is removed.

5.35.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 173

Usage Guideline details

- This element(pacs.010.001.03/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/LEI) is removed.
- This element(pacs.010.001.03/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/LEI) is removed.

5.35.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericOrganisationIdentification1" on page 92 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		93
	SchemeName	<SchmeNm>		[0..1]		93
	Issuer	<Issr>		[0..1]		93

Usage Guideline details

- This element(pacs.010.001.03/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(pacs.010.001.03/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(pacs.010.001.03/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(pacs.010.001.03/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.

5.36 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		102
	Proprietary	<Prtry>	Or}	[1..1]		102

Used in element(s)

"SchemeName" on page 93

5.36.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 167

5.36.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 175

5.37 OtherContact1

Definition: Communication device number or electronic address used for communication.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanITp>		[1..1]		102
	Identification	<Id>		[0..1]		103

Used in element(s)

"Other" on page 50

5.37.1 ChannelType

XML Tag: ChanITp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 175

5.37.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 173

5.38 Party38Choice

Definition: Nature or use of the account.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		103
	PrivateIdentification	<PrvtId>	Or}	[1..1]	🚫	103

Used in element(s)

"Identification" on page 108

5.38.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29" on page 100 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]	🚫	100
	LEI	<LEI>		[0..1]	🚫	101
	Other	<Othr>		[0..*]	🚫	101

5.38.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrivtId** block contains the following elements (see datatype "[PersonIdentification13](#)" on page 117 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		117
	Other	<Othr>		[0..*]		118

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/From/OrganisationIdentification/Identification/PrivatIdentification) is removed.
- This element(pacs.010.001.03/.header/To/OrganisationIdentification/Identification/PrivatIdentification) is removed.
- This element(pacs.010.001.03/.header/From/OrganisationIdentification/Identification/PrivatIdentification) is removed.
- This element(pacs.010.001.03/.header/Related/To/OrganisationIdentification/Identification/PrivatIdentification) is removed.

5.39 Party44Choice

Definition: Identification of a person, an organisation or a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	104
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		105

Used in element(s)

"From" on page 34, "To" on page 34

5.39.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 106 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		107
	PostalAddress	<PstlAdr>		[0..1]		107
	Identification	<Id>		[0..1]		108
	CountryOfResidence	<CtryOfRes>		[0..1]		109
	ContactDetails	<CtctDtls>		[0..1]		109

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/From/OrganisationIdentification) is removed.
- This element(pacs.010.001.03/.header/Related/To/OrganisationIdentification) is removed.

5.39.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 23 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		23
	BranchIdentification	<BrnchId>		[0..1]		23

5.40 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		106
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		106

Used in element(s)

"From" on page 12, "To" on page 12

5.40.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 106 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		107
	PostalAddress	<PstlAdr>		[0..1]		107
	Identification	<Id>		[0..1]		108
	CountryOfResidence	<CtryOfRes>		[0..1]		109
	ContactDetails	<CtctDtls>		[0..1]		109

Usage Guideline details

- This element(pacs.010.001.03/.header/To/OrganisationIdentification) is removed.
- This element(pacs.010.001.03/.header/From/OrganisationIdentification) is removed.

5.40.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 24 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		24
	BranchIdentification	<BrnchId>		[0..1]		25

5.41 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]	🚫	107
	PostalAddress	<PstlAdr>		[0..1]	🚫	107
	Identification	<Id>		[0..1]	🚫	108
	CountryOfResidence	<CtryOfRes>		[0..1]	🚫	109
	ContactDetails	<CtctDtls>		[0..1]	🚫	109

Used in element(s)

"OrganisationIdentification" on page 104, "OrganisationIdentification" on page 106

5.41.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 173

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/To/OrganisationIdentification/Name) is removed.
- This element(pacs.010.001.03/.header/From/OrganisationIdentification/Name) is removed.
- This element(pacs.010.001.03/.header/To/OrganisationIdentification/Name) is removed.
- This element(pacs.010.001.03/.header/Related/From/OrganisationIdentification/Name) is removed.

5.41.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 119 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		120
	Department	<Dept>		[0..1]		120
	SubDepartment	<SubDept>		[0..1]		121
	StreetName	<StrtNm>		[0..1]		121
	BuildingNumber	<BldgNb>		[0..1]		121
	BuildingName	<BldgNm>		[0..1]		121
	Floor	<Flr>		[0..1]		121
	PostBox	<PstBx>		[0..1]		122
	Room	<Room>		[0..1]		122
	PostCode	<PstCd>		[0..1]		122
	TownName	<TwnNm>		[0..1]		122
	TownLocationName	<TwnLctnNm>		[0..1]		122
	DistrictName	<DstrctNm>		[0..1]		122
	CountrySubDivision	<CtrySubDvsn>		[0..1]		123
	Country	<Ctry>		[0..1]		123
	AddressLine	<AdrLine>		[0..7]		123

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/To/OrganisationIdentification/PostalAddress) is removed.
- This element(pacs.010.001.03/.header/To/OrganisationIdentification/PostalAddress) is removed.
- This element(pacs.010.001.03/.header/From/OrganisationIdentification/PostalAddress) is removed.
- This element(pacs.010.001.03/.header/Related/From/OrganisationIdentification/PostalAddress) is removed.

5.41.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice" on page 103 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		103
	PrivateIdentification	<PrvtId>	Or}	[1..1]		103

Usage Guideline details

- This element(pacs.010.001.03/.header/To/OrganisationIdentification/Identification) is removed.
- This element(pacs.010.001.03/.header/From/OrganisationIdentification/Identification) is removed.
- This element(pacs.010.001.03/.header/Related/To/OrganisationIdentification/Identification) is removed.

5.41.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 161

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/To/OrganisationIdentification/CountryOfResidence) is removed.
- This element(pacs.010.001.03/.header/Related/From/OrganisationIdentification/CountryOfResidence) is removed.
- This element(pacs.010.001.03/.header/To/OrganisationIdentification/CountryOfResidence) is removed.
- This element(pacs.010.001.03/.header/From/OrganisationIdentification/CountryOfResidence) is removed.

5.41.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 47 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		48
	Name	<Nm>		[0..1]		48
	PhoneNumber	<PhneNb>		[0..1]		48
	MobileNumber	<MobNb>		[0..1]		48
	FaxNumber	<FaxNb>		[0..1]		49
	EmailAddress	<EmailAdr>		[0..1]		49
	EmailPurpose	<EmailPurp>		[0..1]		49
	JobTitle	<JobTitl>		[0..1]		49
	Responsibility	<Rspnsblty>		[0..1]		49
	Department	<Dept>		[0..1]		49
	Other	<Othr>		[0..*]		50
	PreferredMethod	<PrefrdMtd>		[0..1]		50

Usage Guideline details

- This element(pacs.010.001.03/.header/Related/To/OrganisationIdentification/ContactDetails) is removed.
- This element(pacs.010.001.03/.header/To/OrganisationIdentification/ContactDetails) is removed.
- This element(pacs.010.001.03/.header/Related/From/OrganisationIdentification/ContactDetails) is removed.
- This element(pacs.010.001.03/.header/From/OrganisationIdentification/ContactDetails) is removed.

5.42 PaymentIdentification7__1

Definition: Provides further means of referencing a payment transaction.

⊘ Removed -
 ⊘ Partial Removed -
 ◇ Ignored -
 ◇ Partial Ignored -
 ▲ Details below -
 M Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionIdentification	<InstrId>		[0..1]	M ▲	111
	EndToEndIdentification	<EndToEndId>		[1..1]	▲	111
	TransactionIdentification	<TxId>		[0..1]	▲	112
	UETR	<UETR>		[0..1]	M	112
	ClearingSystemReference	<ClrSysRef>		[0..1]		112

Rules**R24 TransactionIdentificationPresenceRule**

TransactionIdentification or UETR must be present. Both may be present

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00420
- *Error Text:* No transaction identification is present

Used in element(s)

"PaymentIdentification" on page 68

5.42.1 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- **on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/PaymentIdentification/InstructionIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/PaymentIdentification/InstructionIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 157

5.42.2 EndToEndIdentification

XML Tag: EndToEndId

Presence: [1..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/PaymentIdentification/EndToEndIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 157

5.42.3 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/PaymentIdentification/TransactionIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 157

5.42.4 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 179

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/PaymentIdentification/UETR

This element is now mandatory, the minimum occurrence has been changed to : 1

5.42.5 ClearingSystemReference

XML Tag: ClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Datatype: "Max35Text" on page 175

5.43 PaymentTypeInformation28__1

Definition: Provides further details of the type of payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		113
	ClearingChannel	<ClrChanl>		[0..1]		113
	ServiceLevel	<SvcLvl>		[0..*]		114
	LocalInstrument	<LclInstrm>		[0..1]		114
	CategoryPurpose	<CtgyPurp>		[0..1]		114

Used in element(s)

"PaymentTypeInformation" on page 54

5.43.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: "Priority2Code" on page 178

5.43.2 ClearingChannel

XML Tag: ClrChanl

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: "ClearingChannel2Code" on page 159

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/PaymentTypeInformation/ClearingChannel) is removed.

5.43.3 ServiceLevel

XML Tag: SvcLvl

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype "[ServiceLevel8Choice](#)" on page 143 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		143
	Proprietary	<Prtry>	Or}	[1..1]		144

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/PaymentTypeInformation/ServiceLevel) is removed.

5.43.4 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype "[LocalInstrument2Choice](#)" on page 98 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		99
	Proprietary	<Prtry>	Or}	[1..1]		99

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/PaymentTypeInformation/LocalInstrument) is removed.

5.43.5 CategoryPurpose

XML Tag: Ctgypurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **Ctgypurp** block contains the following elements (see datatype "[CategoryPurpose1Choice__1](#)" on [page 42](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		42
	Proprietary	<Prtry>	Or}	[1..1]		42

5.44 PaymentTypeInformation28__2

Definition: Provides further details of the type of payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		115
	ClearingChannel	<ClrChanl>		[0..1]		115
	ServiceLevel	<SvcLvl>		[0..*]	R[0..3]	116
	LocalInstrument	<LclInstrm>		[0..1]		116
	CategoryPurpose	<Ctgypurp>		[0..1]		117

Used in element(s)

"[PaymentTypeInformation](#)" on [page 68](#)

5.44.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: "[Priority2Code](#)" on [page 178](#)

5.44.2 ClearingChannel

XML Tag: ClrChanl

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: "ClearingChannel2Code" on page 159

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Payment-TypeInformation/ClearingChannel) is removed.

5.44.3 ServiceLevel

XML Tag: SvcLvl

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype "ServiceLevel8Choice__1" on page 144 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		144
	Proprietary	<Prtry>	Or}	[1..1]	⚠	144

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/PaymentTypeInformation/ServiceLevel

This element has change repeatability, the maximum occurrence has been changed to : 3

5.44.4 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype "LocalInstrument2Choice__1" on page 99 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		99
	Proprietary	<Prtry>	Or}	[1..1]		100

5.44.5 CategoryPurpose

XML Tag: Ctgypurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **Ctgypurp** block contains the following elements (see datatype "[CategoryPurpose1Choice__1](#)" on page 42 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		42
	Proprietary	<Prtry>	Or}	[1..1]		42

5.45 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		117
	Other	<Othr>		[0..*]		118

Used in element(s)

"[PrivateIdentification](#)" on page 103

5.45.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1](#)" on page 66 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		66
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		66
	CityOfBirth	<CityOfBirth>		[1..1]		66
	CountryOfBirth	<CtryOfBirth>		[1..1]		67

5.45.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 93 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		94
	SchemeName	<SchmeNm>		[0..1]		94
	Issuer	<Issr>		[0..1]		94

5.46 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		118
	Proprietary	<Prtry>	Or}	[1..1]		119

Used in element(s)

"SchemeName" on page 94

5.46.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalPersonIdentification1Code" on page 167](#)

5.46.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 175](#)

5.47 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		120
	Department	<Dept>		[0..1]		120
	SubDepartment	<SubDept>		[0..1]		121
	StreetName	<StrtNm>		[0..1]		121
	BuildingNumber	<BldgNb>		[0..1]		121
	BuildingName	<BldgNm>		[0..1]		121
	Floor	<Flr>		[0..1]		121
	PostBox	<PstBx>		[0..1]		122
	Room	<Room>		[0..1]		122
	PostCode	<PstCd>		[0..1]		122
	TownName	<TwnNm>		[0..1]		122
	TownLocationName	<TwnLctnNm>		[0..1]		122
	DistrictName	<DstrctNm>		[0..1]		122
	CountrySubDivision	<CtrySubDvsn>		[0..1]		123
	Country	<Ctry>		[0..1]		123
	AddressLine	<AdrLine>		[0..7]		123

Used in element(s)

["PostalAddress" on page 32](#),
 ["PostalAddress" on page 76](#),
 ["PostalAddress" on page 107](#),
 ["PostalAddress" on page 80](#)

5.47.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "[AddressType3Choice](#)" on page 22 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		22
	Proprietary	<Prtry>	Or}	[1..1]		22

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/Creditor/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.010.001.03/CreditInstruction/CreditorAgent/BranchIdentification/PostalAddress/AddressType) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/BranchIdentification/PostalAddress/AddressType) is removed.

5.47.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "[Max70Text](#)" on page 176

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/BranchIdentification/PostalAddress/Department) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/BranchIdentification/PostalAddress/Department) is removed.
- This element(pacs.010.001.03/CreditInstruction/CreditorAgent/BranchIdentification/PostalAddress/Department) is removed.
- This element(pacs.010.001.03/CreditInstruction/Creditor/BranchIdentification/PostalAddress/Department) is removed.

5.47.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 176

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/CreditorAgent/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/BranchIdentification/PostalAddress/SubDepartment) is removed.
- This element(pacs.010.001.03/CreditInstruction/Creditor/BranchIdentification/PostalAddress/SubDepartment) is removed.

5.47.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max70Text" on page 176

5.47.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 174

5.47.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max35Text" on page 175

5.47.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 176

5.47.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 174

5.47.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 176

5.47.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 174

5.47.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 175

5.47.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 175

5.47.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 175

5.47.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 175

5.47.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 161

5.47.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 176

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/CreditorAgent/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/BranchIdentification/PostalAddress/AddressLine) is removed.
- This element(pacs.010.001.03/CreditInstruction/Creditor/BranchIdentification/PostalAddress/AddressLine) is removed.

5.48 PostalAddress24__1

Definition: Information that locates and identifies a specific address, as defined by postal services.

⊘ Removed - ⊘ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ▲ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	⊘	124
	Department	<Dept>		[0..1]		125

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SubDepartment	<SubDept>		[0..1]		125
	StreetName	<StrtNm>		[0..1]		125
	BuildingNumber	<BldgNb>		[0..1]		125
	BuildingName	<BldgNm>		[0..1]		125
	Floor	<Flr>		[0..1]		125
	PostBox	<PstBx>		[0..1]		126
	Room	<Room>		[0..1]		126
	PostCode	<PstCd>		[0..1]		126
	TownName	<TwnNm>		[0..1]	M 	126
	TownLocationName	<TwnLctnNm>		[0..1]		127
	DistrictName	<DstrctNm>		[0..1]		127
	CountrySubDivision	<CtrySubDvsn>		[0..1]		127
	Country	<Ctry>		[0..1]	M	127
	AddressLine	<AdrLine>		[0..7]	 R[0..2] R[0..2] R[0..2]	127

Used in element(s)

"PostalAddress" on page 83

5.48.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 22 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		22
	Proprietary	<Prtry>	Or}	[1..1]		22

Usage Guideline details

- This element(pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

- This element([pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.

5.48.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["Max70Text" on page 176](#)

5.48.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["Max70Text" on page 176](#)

5.48.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["Max70Text" on page 176](#)

5.48.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["Max16Text" on page 174](#)

5.48.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["Max35Text" on page 175](#)

5.48.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 176

5.48.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 174

5.48.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 176

5.48.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 174

5.48.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 157

Usage Guideline details

- **on pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/TownName**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/TownName**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/TownName**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/TownName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/TownName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/TownName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)

5.48.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["Max35Text" on page 175](#)

5.48.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["Max35Text" on page 175](#)

5.48.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["Max35Text" on page 175](#)

5.48.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 161](#)

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/Country
This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/Country

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/Country

This element is now mandatory, the minimum occurrence has been changed to : 1

5.48.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 158

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 158

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 158

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 158

5.49 PostalAddress24__2

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		129
	Department	<Dept>		[0..1]		130
	SubDepartment	<SubDept>		[0..1]		130
	StreetName	<StrtNm>		[0..1]		131
	BuildingNumber	<BldgNb>		[0..1]		131
	BuildingName	<BldgNm>		[0..1]		132
	Floor	<Flr>		[0..1]		132
	PostBox	<PstBx>		[0..1]		133
	Room	<Room>		[0..1]		134
	PostCode	<PstCd>		[0..1]		134
	TownName	<TwnNm>		[0..1]	 	135
	TownLocationName	<TwnLctnNm>		[0..1]		135
	DistrictName	<DstrctNm>		[0..1]		136
	CountrySubDivision	<CtrySubDvsn>		[0..1]		137
	Country	<Ctry>		[0..1]		137
	AddressLine	<AdrLine>		[0..7]	 R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2]	138

Used in element(s)

"PostalAddress" on page 87

5.49.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 22 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		22
	Proprietary	<Prtry>	Or}	[1..1]		22

Usage Guideline details

- This element([pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.

5.49.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 158](#)

Usage Guideline details

- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on [pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on [pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)

5.49.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 158](#)

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)

5.49.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 158](#)

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)

5.49.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 155

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)
- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)

5.49.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)

5.49.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 158](#)

Usage Guideline details

- on [pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/Floor](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/Floor](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on [pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Floor](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Floor](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)

5.49.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 155](#)

Usage Guideline details

- on [pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)
- on [pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/PostBox](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/PostBox](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)

5.49.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 158](#)

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 158](#)

5.49.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 155](#)

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/PostCode
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)

- on [pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/PostCode](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 155](#)

5.49.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 157](#)

Usage Guideline details

- on [pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/TownName](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/TownName](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on [pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/TownName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on [pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/TownName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on [pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownName](#)
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)

5.49.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/TownLocationName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)

5.49.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)

5.49.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)
- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 157](#)

5.49.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 161

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Country
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/Country
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/Country
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Country

This element is now mandatory, the minimum occurrence has been changed to : 1

5.49.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 158

Usage Guideline details

- **on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- **on pacs.010.001.03/CreditInstruction/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
 Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 158
- **on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
 Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 158
- **on pacs.010.001.03/CreditInstruction/Creditor/FinancialInstitutionIdentification/PostalAddress/AddressLine**
 Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 158
- **on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Debtor/FinancialInstitutionIdentification/PostalAddress/AddressLine**
 Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 158

5.50 ProxyAccountIdentification1__1

Definition: Information related to a proxy identification of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		139
	Identification	<Id>		[1..1]		140

Used in element(s)

"Proxy" on page 40

5.50.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "ProxyAccountType1Choice_1" on page 140 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		141
	Proprietary	<Prtry>	Or}	[1..1]		141

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1Account/Proxy/Type**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2Account/Proxy/Type**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3Account/Proxy/Type**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/CreditorAgentAccount/Proxy/Type**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/CreditorAccount/Proxy/Type**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAccount/Proxy/Type**
 This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgentAccount/Proxy/Type

This element is now mandatory, the minimum occurrence has been changed to : 1

5.50.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "CBPR_RestrictedFINXMax320Text_Extended" on page 156

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/CreditorAccount/Proxy/Identification
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 156
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgentAccount/Proxy/Identification
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 156
- on pacs.010.001.03/CreditInstruction/CreditorAgentAccount/Proxy/Identification
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 156
- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAccount/Proxy/Identification
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 156
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent1Account/Proxy/Identification
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 156
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent2Account/Proxy/Identification
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 156
- on pacs.010.001.03/CreditInstruction/IntermediaryAgent3Account/Proxy/Identification
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 156

5.51 ProxyAccountType1Choice__1

Definition: Specifies the scheme used for the identification of an account alias.

ⓧ Removed - ⓧ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		141
	Proprietary	<Prtry>	Or}	[1..1]	⚠	141

Used in element(s)

["Type" on page 139](#)

5.51.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalProxyAccountType1Code" on page 168](#)

5.51.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 157](#)

Usage Guideline details

- on **pacs.010.001.03/CreditInstruction/CreditorAccount/Proxy/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAccount/Proxy/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/DebtorAgentAccount/Proxy/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/CreditorAgentAccount/Proxy/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/IntermediaryAgent1Account/Proxy/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/IntermediaryAgent2Account/Proxy/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)
- on **pacs.010.001.03/CreditInstruction/IntermediaryAgent3Account/Proxy/Type/Proprietary**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 157](#)

5.52 Purpose2Choice__1

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		142
	Proprietary	<Prtry>	Or}	[1..1]		142

Used in element(s)

"Purpose" on page 73

5.52.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: "ExternalPurpose1Code" on page 169

5.52.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Purpose/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 157

5.53 RemittanceInformation2__1

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]	  R[1..1]	143

Used in element(s)

["RemittanceInformation" on page 74](#)

5.53.1 Unstructured

XML Tag: Ustrd

Presence: [0..*]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, for example, commercial invoices in an accounts' receivable system in an unstructured form.

Datatype: ["CBPR_RestrictedFINXMax140Text_Extended" on page 154](#)

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/RemittanceInformation/Unstructured

This element is now mandatory, the minimum occurrence has been changed to : 1

This element has change repeatability, the maximum occurrence has been changed to : 1

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/RemittanceInformation/Unstructured

Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 154](#)

5.54 ServiceLevel8Choice

Definition: Specifies the service level of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		143
	Proprietary	<Prtry>	Or}	[1..1]		144

Used in element(s)

["ServiceLevel" on page 114](#)

5.54.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: ["ExternalServiceLevel1Code" on page 170](#)

5.54.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: "Max35Text" on page 175

5.55 ServiceLevel8Choice__1

Definition: Specifies the service level of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		144
	Proprietary	<Prtry>	Or}	[1..1]		144

Used in element(s)

"ServiceLevel" on page 116

5.55.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: "ExternalServiceLevel1Code" on page 170

5.55.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 157

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/PaymentTypeInformation/ServiceLevel/Proprietary
 Type changed to: CBPR_RestrictedFINXMax35Text on page 157

5.56 SettlementDateTimeIndication1

Definition: Information on the occurred settlement time(s) of the payment transaction.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebitDateTime	<DbtDtTm>		[0..1]		145
	CreditDateTime	<CdtDtTm>		[0..1]		145

Used in element(s)

"SettlementTimeIndication" on page 55, "SettlementTimeIndication" on page 69

5.56.1 DebitDateTime

XML Tag: DbtDtTm

Presence: [0..1]

Definition: Date and time at which a payment has been debited at the transaction administrator. In the case of TARGET, the date and time at which the payment has been debited at the central bank, expressed in Central European Time (CET).

Datatype: "ISODatetime" on page 171

5.56.2 CreditDateTime

XML Tag: CdtDtTm

Presence: [0..1]

Definition: Date and time at which a payment has been credited at the transaction administrator. In the case of TARGET, the date and time at which the payment has been credited at the receiving central bank, expressed in Central European Time (CET).

Datatype: "ISODatetime" on page 171

5.57 SettlementTimeRequest2__1

Definition: Provides information on the requested settlement time(s) of the payment instruction.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CLSTime	<CLSTm>		[0..1]	⚠	146
	TillTime	<TillTm>		[0..1]	⚠	146
	FromTime	<FrTm>		[0..1]	⚠	146
	RejectTime	<RjctTm>		[0..1]	⚠	146

Used in element(s)

"SettlementTimeRequest" on page 70

5.57.1 CLSTime

XML Tag: CLSTm

Presence: [0..1]

Definition: Time by which the amount of money must be credited, with confirmation, to the CLS Bank's account at the central bank.

Usage: Time must be expressed in Central European Time (CET).

Datatype: "CBPR_Time" on page 158

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Settlement-TimeRequest/CLSTime

Type changed to: CBPR_Time on page 158

5.57.2 TillTime

XML Tag: TillTm

Presence: [0..1]

Definition: Time until when the payment may be settled.

Datatype: "CBPR_Time" on page 158

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Settlement-TimeRequest/TillTime

Type changed to: CBPR_Time on page 158

5.57.3 FromTime

XML Tag: FrTm

Presence: [0..1]

Definition: Time as from when the payment may be settled.

Datatype: "CBPR_Time" on page 158

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Settlement-TimeRequest/FromTime

Type changed to: CBPR_Time on page 158

5.57.4 RejectTime

XML Tag: RjctTm

Presence: [0..1]

Definition: Time by when the payment must be settled to avoid rejection.

Datatype: "CBPR_Time" on page 158

Usage Guideline details

- on pacs.010.001.03/CreditInstruction/DirectDebitTransactionInformation/Settlement-TimeRequest/RejectTime

Type changed to: CBPR_Time on page 158

5.58 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		147
	Envelope	<Envlp>		[1..1]		147

Rules

R8 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 19, "SupplementaryData" on page 65

5.58.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 175

5.58.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 ActiveCurrencyAndAmount

Definition: A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 149

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules

R20 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

"InterbankSettlementAmount" on page 68, "TotalInterbankSettlementAmount" on page 55

6.2 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Rules

R21 ActiveCurrency ✓

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Used in attribute(s)

"ActiveCurrencyAndAmount" on page 149

Restricts

"ParentCurrencyCode" on page 177

6.3 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Rules

R22 ActiveOrHistoricCurrency ✓

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Used in element(s)

"Currency" on page 39

Restricts

["ParentCurrencyCode" on page 177](#)

6.4 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["Code" on page 22](#)

Restricts

["AddressTypeCode" on page 151](#)

6.5 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 151](#)

6.6 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules**R7 AnyBIC ✓**

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

"AnyBIC" on page 100

6.7 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules**R6 BICFI ✓**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

"BICFI" on page 75, "BICFI" on page 78, "BICFI" on page 82, "BICFI" on page 85

6.8 BatchBookingIndicator

Definition: Identifies whether the sending party requests a single debit or credit entry per individual transaction or a batch entry for the sum of the amounts of all transactions.

Type: Indicator

Meaning When True: Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.

Meaning When False: Identifies that a single entry for each of the transactions in the batch or message is requested.

Used in element(s)

"BatchBooking" on page 54

6.9 CBPR_Date

Definition: This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Date

Format

pattern [0-9]{4}-[0-9]{2}-[0-9]{2}

Used in element(s)

"InterbankSettlementDate" on page 69

6.10 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm-m).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern `.*(\+|-)((0[0-9])|(1[0-4])):[0-5][0-9]`

Used in element(s)

["CreationDate" on page 36](#), ["CreationDateTime" on page 95](#)

6.11 CBPR_RestrictedFINXMax140Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	<code>[0-9a-zA-Z/\-!\?:(\)\.,\'+ !#\$%& ^_`{ }~";<>@[\\]]+</code>

Used in element(s)

["Name" on page 83](#), ["Name" on page 86](#), ["Unstructured" on page 143](#)

6.12 CBPR_RestrictedFINXMax16Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1

pattern [0-9a-zA-Z/\-!\?:\(\)\.,'\+]+

Used in element(s)

["CreditIdentification" on page 54](#)

6.13 CBPR_RestrictedFINXMax16Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'\+ !#\$%&*^_`{ }~";<>@[\]]+

Used in element(s)

["BuildingNumber" on page 131](#), ["PostBox" on page 133](#), ["PostCode" on page 134](#)

6.14 CBPR_RestrictedFINXMax210Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 210 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	210
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'\+]+

Used in element(s)

["InstructionForDebtorAgent" on page 73](#)

6.15 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+]+

Used in element(s)

"MemberIdentification" on page 46

6.16 CBPR_RestrictedFINXMax320Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 320 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	320
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*='^_`{ }~";<>@[\\]]+

Used in element(s)

"Identification" on page 140

6.17 CBPR_RestrictedFINXMax34Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 34 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . and disable the use of slash "/" at the beginning and end of line and double slash "/" within the line.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	34
minLength	1

pattern `(([0-9a-zA-Z\-\!\?:(\)\.,\'+ ]|([0-9a-zA-Z\-\!\?:(\)\.,\'+ ])*|([0-9a-zA-Z\-\!\?:(\)\.,\'+ ])?*))`

Used in element(s)

["Identification" on page 89](#)

6.18 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	<code>[0-9a-zA-Z\-\!\?:(\)\.,\'+]+</code>

Used in element(s)

["BusinessMessageIdentifier" on page 35](#), ["BusinessService" on page 36](#), ["EndToEndIdentification" on page 111](#), ["InstructionIdentification" on page 111](#), ["Issuer" on page 90](#), ["MessageDefinitionIdentifier" on page 35](#), ["MessageIdentification" on page 95](#), ["Proprietary" on page 42](#), ["Proprietary" on page 21](#), ["Proprietary" on page 41](#), ["Proprietary" on page 141](#), ["Proprietary" on page 144](#), ["Proprietary" on page 100](#), ["Proprietary" on page 142](#), ["TransactionIdentification" on page 112](#)

6.19 CBPR_RestrictedFINXMax35Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters `!#$%&*='^_`{|}~";<>@[\\]`

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	<code>[0-9a-zA-Z\-\!\?:(\)\.,\'+ !#\$%&*='^_`{ }~";<>@[\\]]+</code>

Used in element(s)

["BuildingName" on page 132](#), ["CountrySubDivision" on page 137](#), ["DistrictName" on page 136](#), ["Town-LocationName" on page 135](#), ["TownName" on page 126](#), ["TownName" on page 135](#)

6.20 CBPR_RestrictedFINXMax70Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'\+]+

Used in element(s)

"Name" on page 39

6.21 CBPR_RestrictedFINXMax70Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'\+ !#\$%&*='^_`{ }~";<>@[\\]]+

Used in element(s)

"AddressLine" on page 128, "AddressLine" on page 138, "Department" on page 130, "Floor" on page 132, "Room" on page 134, "StreetName" on page 131, "SubDepartment" on page 130

6.22 CBPR_Time

Definition: A particular point in the progression of time defined by a mandatory time component, expressed in local time with UTC offset format (hh:mm:ss.sss+/-hh:mm).

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: Time

Format

pattern `.*(\+|-)((0[0-9])|(1[0-4])):[0-5][0-9]`

Used in element(s)

["CLSTime" on page 146](#), ["FromTime" on page 146](#), ["RejectTime" on page 146](#), ["TillTime" on page 146](#)

6.23 ClearingChannel2Code

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Used in element(s)

["ClearingChannel" on page 113](#), ["ClearingChannel" on page 115](#)

Restricts

["ClearingChannelCode" on page 159](#)

6.24 ClearingChannelCode

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Is restricted by

"ClearingChannel2Code" on page 159

6.25 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

"CopyDuplicate" on page 37

Restricts

"CopyDuplicateCode" on page 160

6.26 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.

Code	Name	Definition
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

"CopyDuplicate1Code" on page 160

6.27 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules

R5 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

"Country" on page 123, "Country" on page 127, "Country" on page 137, "CountryOfBirth" on page 67, "CountryOfResidence" on page 109

6.28 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

fractionDigits 17
totalDigits 18

Used in element(s)

"ControlSum" on page 96

6.29 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

Used in element(s)

"Identification" on page 92

6.30 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 21

Restricts

"ExternalAccountIdentificationCode" on page 162

6.31 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalAccountIdentification1Code" on page 162

6.32 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 41

Restricts

"ExternalCashAccountTypeCode" on page 163

6.33 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCashAccountType1Code" on page 163

6.34 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 42](#)

Restricts

["ExternalCategoryPurposeCode" on page 164](#)

6.35 ExternalCategoryPurposeCode

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalCategoryPurpose1Code" on page 164](#)

6.36 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

["Code" on page 43](#)

Restricts

["ExternalClearingSystemIdentificationCode" on page 165](#)

6.37 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

["ExternalClearingSystemIdentification1Code" on page 164](#)

6.38 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 74](#)

Restricts

["ExternalFinancialInstitutionIdentificationCode" on page 165](#)

6.39 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 165

6.40 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Used in element(s)

"Code" on page 99, "Code" on page 99

Restricts

"ExternalLocalInstrumentCode" on page 166

6.41 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Is restricted by

"ExternalLocalInstrument1Code" on page 166

6.42 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 102](#)

Restricts

["ExternalOrganisationIdentificationCode" on page 167](#)

6.43 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalOrganisationIdentification1Code" on page 167](#)

6.44 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 118

Restricts

"ExternalPersonIdentificationCode" on page 168

6.45 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPersonIdentification1Code" on page 167

6.46 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 141

Restricts

"ExternalProxyAccountTypeCode" on page 169

6.47 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalProxyAccountType1Code" on page 168

6.48 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 142

Restricts

"ExternalPurposeCode" on page 169

6.49 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPurpose1Code" on page 169

6.50 ExternalServiceLevel1Code

Definition: Specifies the external service level code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 143, "Code" on page 144

Restricts

"ExternalServiceLevelCode" on page 170

6.51 ExternalServiceLevelCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalServiceLevel1Code" on page 170

6.52 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Format

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Rules

R23 IBAN ✓

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

["IBAN" on page 20](#)

6.53 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

["BirthDate" on page 66](#), ["InterbankSettlementDate" on page 55](#)

6.54 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

"CreditDateTime" on page 145, "DebitDateTime" on page 145

6.55 Instruction5Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

Code	Name	Definition
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

Used in element(s)

"Code" on page 98

Restricts

"InstructionCode" on page 172

6.56 InstructionCode

Definition: Specifies further instructions concerning the processing of a payment instruction.

Type: CodeSet

Code	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PBEN	PayTheBeneficiary	(Ultimate) creditor to be paid only after verification of identity.
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.

Code	Name	Definition
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.
TFRO	TimeFrom	Payment instruction will be valid and eligible for execution from the date and time stipulated.
TTIL	TimeTill	Payment instruction is valid and eligible for execution until the date and time stipulated. Otherwise, the payment instruction will be rejected.

Is restricted by

["Instruction5Code" on page 172](#)

6.57 LEIIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{18,18}[0-9]{2,2}

Used in element(s)

["LEI" on page 32](#), ["LEI" on page 76](#), ["LEI" on page 101](#), ["LEI" on page 79](#), ["LEI" on page 82](#), ["LEI" on page 86](#)

6.58 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength 128
minLength 1

Used in element(s)

["Identification" on page 103](#)

6.59 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

"InstructionInformation" on page 98, "Name" on page 32, "Name" on page 48, "Name" on page 76, "Name" on page 107, "Name" on page 79

6.60 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

"NumberOfTransactions" on page 96

6.61 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

"BuildingNumber" on page 121, "BuildingNumber" on page 125, "PostBox" on page 122, "PostBox" on page 126, "PostCode" on page 122, "PostCode" on page 126

6.62 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

["EmailAddress" on page 49](#), ["Identification" on page 97](#)

6.63 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

["PlaceAndName" on page 147](#), ["Registry" on page 97](#)

6.64 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

["BuildingName" on page 121](#), ["BuildingName" on page 125](#), ["CityOfBirth" on page 66](#), ["ClearingSystemReference" on page 112](#), ["CountrySubDivision" on page 123](#), ["CountrySubDivision" on page 127](#), ["DistrictName" on page 122](#), ["DistrictName" on page 127](#), ["EmailPurpose" on page 49](#), ["Identification" on page 32](#), ["Identification" on page 91](#), ["Identification" on page 93](#), ["Identification" on page 94](#), ["Issuer" on page 91](#), ["Issuer" on page 92](#), ["Issuer" on page 93](#), ["Issuer" on page 94](#), ["JobTitle" on page 49](#), ["MemberIdentification" on page 45](#), ["Proprietary" on page 43](#), ["Proprietary" on page 75](#), ["Proprietary" on page 99](#), ["Proprietary" on page 102](#), ["Proprietary" on page 119](#), ["Proprietary" on page 144](#), ["ProvinceOfBirth" on page 66](#), ["Responsibility" on page 49](#), ["SchemeName" on page 92](#), ["TownLocationName" on page 122](#), ["TownLocationName" on page 127](#), ["TownName" on page 122](#)

6.65 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

["ChannelType" on page 102](#)

6.66 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

["AddressLine" on page 123](#), ["Department" on page 49](#), ["Department" on page 120](#), ["Department" on page 125](#), ["Floor" on page 121](#), ["Floor" on page 125](#), ["Room" on page 122](#), ["Room" on page 126](#), ["StreetName" on page 121](#), ["StreetName" on page 125](#), ["SubDepartment" on page 121](#), ["SubDepartment" on page 125](#)

6.67 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

["NamePrefix" on page 48](#)

Restricts

["NamePrefixCode" on page 176](#)

6.68 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.

Code	Name	Definition
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

"NamePrefix2Code" on page 176

6.69 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern [A-Z]{3,3}

Is restricted by

"ActiveCurrencyCode" on page 149, "ActiveOrHistoricCurrencyCode" on page 150

6.70 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+\-]{1,30}

Used in element(s)

"FaxNumber" on page 49, "MobileNumber" on page 48, "PhoneNumber" on page 48

6.71 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 50](#)

Restricts

["PreferredContactMethodCode" on page 178](#)

6.72 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

["PreferredContactMethod1Code" on page 177](#)

6.73 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

["InstructionPriority" on page 113](#), ["InstructionPriority" on page 115](#), ["Priority" on page 37](#)

Restricts

["PriorityCode" on page 179](#)

6.74 Priority3Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Used in element(s)

["SettlementPriority" on page 69](#)

Restricts

["PriorityCode" on page 179](#)

6.75 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

["Priority2Code" on page 178](#), ["Priority3Code" on page 179](#)

6.76 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

Used in element(s)

"UETR" on page 112

6.77 UnicodeChartsCode

Definition: codelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R2 ValidationByTable

Error handling: Undefined

Used in element(s)

"CharacterSet" on page 34

6.78 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

"PossibleDuplicate" on page 37

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.