EXT: Simply Slideshow

Extension Key: simply_slideshow

Language: en

Keywords: forAdmins, forBeginners

Copyright 2000-2010, Henjo Hoeksma, <hphoeksma@stylence.nl>

This document is published under the Open Content License

available from http://www.opencontent.org/opl.shtml

The content of this document is related to TYPO3

- a GNU/GPL CMS/Framework available from www.typo3.org

Table of Contents

Introduction

What does it do?

– This extension gives you the possibility to add a plugin to your page where a slideshow can be selected.

– It is possible to use your own custom js to create the slideshow and to use the extension as nothing but a way for editors to add images, titles and links to the end product.

– Default it uses jQuery and the jQuery cycle plugin.

Users manual

– Editors can add a slideshow in the respective storage folder. Images can be added from within the slideshow.

– A plugin is used to put the slideshow on the page.

– Default it is possible to add multiple slideshows on 1 page.

– It is possible to add the plugin using typoscript as well.

Administration

- You can use TSConfig to hide the images and prevent the editor from adding images without being related to the slideshow.

- Code for this is – for example:

```
mod.web_list {
    allowedNewTables = tx_simplyslideshow_domain_model_slideshow
    hideTables = tx_simplyslideshow_domain_model_image
}
```

Configuration

– You will have to include the static templates (after you installed the extension using the Extension Manager)

– After this, set the constants to your liking.

– Add a plugin on a page using by going to 'General Plugins' and then select 'Slideshow'.

– Alternatively you can use TypoScript to add the plugin to your page like this:

```
10 = USER
10 {
    userFunc = tx_extbase_core_bootstrap->run
    pluginName = Pi1
    extensionName = SimplySlideshow
    switchableControllerActions {
        Slideshow {
            1 = show
        }
    }
    settings =< plugin.tx_simplyslideshow.settings
    settings.slideshow.current = 1
    persistence =< plugin.tx_simplyslideshow.persistence
    view =< plugin.tx_simplyslideshow.view
}
```

You can use current if you want to fetch it dynamically when using a FlexForm (with TemplaVoila for example) or substitute 'current = 1' with the uid of the slideshow.

Example DS for TemplaVoila:

```
<field_slider type="array">
    <tx_templavoila type="array">
        <title>Slider</title>
        <sample_data type="array">
                <numIndex index="0"></numIndex>
        </sample_data>
        <eType>ce</eType>
        <TypoScript><![CDATA[10 = USER
10 {
    userFunc = tx_extbase_core_bootstrap->run
    pluginName = Pi1
    extensionName = SimplySlideshow
    switchableControllerActions {
        Slideshow {
            1 = show
        }
    }
    settings =< plugin.tx_simplyslideshow.settings
    settings.slideshow.current = 1
    persistence =< plugin.tx_simplyslideshow.persistence
    view =< plugin.tx_simplyslideshow.view
}]]></TypoScript>
        <proc type="array">
                <HSC>0</HSC>
                <stdWrap></stdWrap>
                <int>0</int>
        </proc>
        <preview></preview>
        <oldStyleColumnNumber>0</oldStyleColumnNumber>
        <enableDragDrop>1</enableDragDrop>
    </tx_templavoila>
    <TCEforms type="array">
        <label>Slider</label>
        <config type="array">
                <type>group</type>
                <internal_type>db</internal_type>
                <allowed>tx_simplyslideshow_domain_model_slideshow</allowed>
                <size>1</size>
                <maxitems>1</maxitems>
                <minitems>0</minitems>
                <multiple>0</multiple>
                <show_thumbs>0</show_thumbs>
        </config>
    </TCEforms>
</field_slider>
```

Reference

– See the constants for this.

Tutorial

– Just the the preceding items and you'll be good to go!

Known problems

– None as far as I am aware of.

– Please email me if you think differently ;-)