


This article was downloaded by: [Aalborg University]

On: 10 May 2011

Access details: Access Details: [subscription number 912902584]

Publisher Taylor & Francis

Informa Ltd Registered in England and Wales Registered Number: 1072954 Registered office: Mortimer House, 37-41 Mortimer Street, London W1T 3JH, UK



International Journal of Computer Mathematics

Publication details, including instructions for authors and subscription information:

<http://www.informaworld.com/smpp/title~content=t713455451>

Algorithms For Computing Approximate Repetitions In Musical Sequences

Emilios Cambouropoulos^a; Maxime Crochemore^b; Costas Iliopoulos^{cd}; Laurent Mouchard^{de}; Yoan Pinzon^{cd}

^a Austrian Research Institute for Artificial Intelligence, Wien, Austria ^b Institut Gaspard Monge, Université de Marne-la-Vallée, Marne-la-Vallée CEDEX 2, France ^c Dept. Computer Science, King's College London, London, England ^d School of Computing, Curtin University of Technology, WA ^e LIFAR - ABISS, Université de Rouen, France

Online publication date: 15 September 2010

To cite this Article Cambouropoulos, Emilios , Crochemore, Maxime , Iliopoulos, Costas , Mouchard, Laurent and Pinzon, Yoan(2002) 'Algorithms For Computing Approximate Repetitions In Musical Sequences', International Journal of Computer Mathematics, 79: 11, 1135 – 1148

To link to this Article: DOI: 10.1080/00207160213939

URL: <http://dx.doi.org/10.1080/00207160213939>

PLEASE SCROLL DOWN FOR ARTICLE

Full terms and conditions of use: <http://www.informaworld.com/terms-and-conditions-of-access.pdf>

This article may be used for research, teaching and private study purposes. Any substantial or systematic reproduction, re-distribution, re-selling, loan or sub-licensing, systematic supply or distribution in any form to anyone is expressly forbidden.

The publisher does not give any warranty express or implied or make any representation that the contents will be complete or accurate or up to date. The accuracy of any instructions, formulae and drug doses should be independently verified with primary sources. The publisher shall not be liable for any loss, actions, claims, proceedings, demand or costs or damages whatsoever or howsoever caused arising directly or indirectly in connection with or arising out of the use of this material.

ALGORITHMS FOR COMPUTING APPROXIMATE REPETITIONS IN MUSICAL SEQUENCES

EMILIOS CAMBOUROPOULOS^{a,*,†}, MAXIME CROCHEMORE^{b,**},
COSTAS S. ILIOPOULOS^{c,***}, LAURENT MOUCHARD^{d,**}
and YOAN J. PINZON^c

^a*Austrian Research Institute for Artificial Intelligence, Schottengasse 3, 1010 Wien, Austria;*

^b*Institut Gaspard Monge, Université de Marne-la-Vallée, 77454 Marne-la-Vallée CEDEX 2, France;*

^c*Dept. Computer Science, King's College London, London WC2R 2LS, England,
and School of Computing, Curtin University of Technology, GPO Box 1987 U, WA;*

^d*LIFAR – ABISS, Université de Rouen, 76821 Mont Saint Aignan, France, and School
of Computing, Curtin University of Technology, GPO Box 1987 U, WA*

(Received 10 June 2001; In final form 16 June 2001)

Here we introduce two new notions of approximate matching with application in computer assisted music analysis. We present algorithms for each notion of approximation: for approximate string matching and for computing approximate squares.

Keywords: String algorithms; Approximate string matching; Dynamic programming; Computer-assisted music analysis

C. R. Categories: F.2.2, G.2.2, H.5.5, I.5.3

1 INTRODUCTION

This paper focuses on a set of string pattern-matching problems that arise in musical analysis, and especially in musical information retrieval. A musical score can be viewed as a string: at a very rudimentary level, the alphabet could simply be the set of notes in the chromatic or diatonic notation, or the set of intervals that appear between notes (*e.g.* pitch may be represented as MIDI numbers and pitch intervals as number of semitones). Approximate repetitions in one or more musical works play a crucial role in discovering similarities between different musical entities and may be used for establishing “characteristic signatures” (see

* Supported by the START programme Y99-INF, Austrian Federal Ministry of Science and Transport

** Partially supported by the C.N.R.S. Program “Génomes”

*** Partially supported by the EPSRC grant GR/J 17844.

† Address for correspondence: E-mail: emilios@ai.univie.ac.at; www.ai.univie.ac.at/~emilios

[6]). Such algorithms can be particularly useful for melody identification and musical retrieval.

Both exact and approximate matching techniques have been used for a variety of musical applications (see overviews in McGettrick [23]; Crawford *et al.* [6]; Rolland and Ganascia [28]; Cambouropoulos *et al.* [4]). The specific problem studied in this paper is pattern-matching for numeric strings where a certain tolerance is allowed during the matching procedure. This type of pattern-matching has been considered necessary for various musical applications and has been used by some researchers (see, for instance, Cope [5]). A number of efficient algorithms will be presented in this paper that tackle various aspects of this problem.

Most computer-aided musical applications adopt an absolute numeric pitch representation (most commonly MIDI pitch and pitch intervals in semitones; duration is also encoded in a numeric form). The absolute pitch encoding, however, may be insufficient for applications in tonal music as it disregards tonal qualities of pitches and pitch-intervals (*e.g.* a tonal transposition from a major to a minor key results in a different encoding of the musical passage and thus exact matching cannot detect the similarity between the two passages). One way to account for similarity between closely related but non-identical musical strings is to use what will be referred to as δ -approximate matching (and γ -approximate matching). In δ -approximate matching, equal-length patterns consisting of integers match if each corresponding integer differs by not more than δ —*e.g.* a C-major {60, 64, 65, 67} and a C-minor {60, 63, 65, 67} sequence can be matched if a tolerance $\delta = 1$ is allowed in the matching process (γ -approximate matching is described in the next section). Two simple musical examples that illustrate the usefulness of the proposed pattern-matching techniques are presented in Appendices I and II.

Exact repetitions have been studied extensively. The repetitions can be either concatenated with the original substring or they may overlap or they may not. Algorithms for finding non-overlapping repetitions in a given string can be found in [1, 8, 15, 18, 21, 26] and algorithms for computing overlapping repetitions can be found in [3, 13, 14, 25]. A natural extension of the repetitions problem is to allow the presence of errors; that is, the identification of substrings that are duplicated to within a certain tolerance k (usually edit distance or Hamming distance). Moreover, the repeated substring may be subject to other constraints: it may be required to be of at least a certain length, and certain positions in it may be required to be invariant.

Furthermore, efficient algorithms for computing the approximate repetitions are also directly applicable to molecular biology (see [11, 17, 24]) and in particular in DNA sequencing by hybridization [27], reconstruction of DNA sequences from known DNA fragments (see [29, 30]), in human organ and bone marrow transplantation as well as the determination of evolutionary trees among distinct species [29].

Another type of repetition that is used in computer assisted music analysis is that of finding evolutionary chains: given a string t (the “text”) and a pattern p (the “motif”), find whether there exists a sequence $u_1 = p, u_2, \dots, u_\ell$ occurring in the text t such that u_{i+1} occurs to the right of u_i in t and u_i and u_{i+1} are “similar” for $1 \leq i < \ell$ (*i.e.* they differ by a certain number of symbols). In [9] and [7] algorithms for overlapping and non-overlapping evolutionary chains were presented and several variants of the problem were studied: computing the longest chain, computing the chain with the least number of errors.

The paper is organised as follows. In the next section we present some basic definitions for strings and background notions for approximate matching. In Section 3 we present an algorithm for δ -approximate (the first notion of approximation) pattern matching. In Section 4 we present an algorithm for $\{\delta, \gamma\}$ -approximate (the second notion of approximation) pattern matching. In Section 5 we present algorithms for computing all δ and $\{\delta, \gamma\}$ -approximate squares in a given text. Finally, in Section 6 we present our conclusions and open problems.

2 BACKGROUND AND BASIC STRING DEFINITIONS

A *string* is a sequence of zero or more symbols from an alphabet Σ ; the string with zero symbols is denoted by ϵ . The set of all strings over the alphabet Σ is denoted by Σ^* . A string x of length n is represented by $x_1 \dots x_n$, where $x_i \in \Sigma$ for $1 \leq i \leq n$. A string w is a *substring* of x if $x = uwv$ for $u, v \in \Sigma^*$; we equivalently say that the string w occurs at position $|u| + 1$ of the string x . The position $|u| + 1$ is said to be the *starting position* of w in x and the position $|w| + |u|$ the *end position* of w in x . A string w is a *prefix* of x if $x = wu$ for $u \in \Sigma^*$. Similarly, w is a *suffix* of x if $x = uw$ for $u \in \Sigma^*$.

The string xy is a *concatenation* of two strings x and y . The concatenations of k copies of x is denoted by x^k . For two strings $x = x_1 \dots x_n$ and $y = y_1 \dots y_m$ such that $x_{n-i+1} \dots x_n = y_1 \dots y_i$ for some $i \geq 1$, the string $x_1 \dots x_{n-y_{i+1}} \dots y_m$ is a *superposition* of x and y . We say that x and y *overlap*.

Let x be a string of length n . A prefix $x_1 \dots x_p$, $1 \leq p < n$, of x is a *period* of x if $x_i = x_{i+p}$ for all $1 \leq i \leq n - p$. The *period* of a string x is the shortest period of x . A string y is a *border* of x if y is a prefix and suffix of x .

Let Σ be an alphabet of integers and δ an integer. Two symbols a, b of Σ are said to be δ -approximate, denoted $a =_\delta b$ if and only if

$$|a - b| \leq \delta$$

We say that two strings x, y are δ -approximate, denoted $x \stackrel{\delta}{=} y$, if and only if

$$|x| = |y|, \text{ and } x_i =_\delta y_i, \forall i \in \{1..|x|\} \quad (2.1)$$

Let γ be an integer. Two strings x, y are said to be γ -approximate, denoted $x \stackrel{\gamma}{=} y$ if and only if

$$|x| = |y|, \text{ and } \sum_1^{|x|} |x_i - y_i| < \gamma \quad (2.2)$$

Furthermore, we say that two strings x, y are $\{\gamma, \delta\}$ -approximate, denoted $x \stackrel{\gamma, \delta}{=} y$, if and only if x and y satisfy conditions (2.1) and (2.2).

3 δ -APPROXIMATE PATTERN MATCHING

The problem of *δ -approximate pattern matching* is formally defined as follows: given a string $t = t_1 \dots t_n$ and a pattern $p = p_1 \dots p_m$ compute all positions j of t such that

$$p \stackrel{\delta}{=} t[j..j + m - 1]$$

The algorithm is based on the $O(1)$ -time computation of the “Delta states” $DState_j, j \in \{1..n\}$ by using bit operations under the assumption that $m \leq w$, where w is the number of bits in a machine word. The basic steps of the algorithm are as follows:

1. First we compute the “Delta table” DT : we set $DT(\alpha) = r$, where α denotes a symbol occurring in t and $r = r_1 \dots r_m$ is a binary word with r_i equal to 1 if $|\alpha - p_i| \leq \delta$, otherwise r_i is equal to 0 for $i \in \{1..m\}$.

2. Let *LeftShift* be a bit-wise operation that shifts the bits of a binary word by one position to the left. We define

$$DState_j = (\text{LeftShift}(DState_{j-1}) \text{ OR } 1) \text{ AND } DT[t_j] \quad (3.1)$$

for $j = 1 \dots n$ and $DState_0 = 0$; hence this procedure is called “SHIFT-AND”. Once we have computed the DT table, we can use it to compute the $DState_j$ for $j = 1 \dots n$, using the recursive formula (3.1).

3. We say that there is a δ -approximate match (or simply δ -match) at position $j - m + 1$ if and only if the m th bit of $DState_j$ is 1 or equivalently if and only if $DState_j$ is greater or equal to 2^{m-1} when it is viewed as a decimal integer.

Example For $\Sigma = \{1, \dots, 9\}$ let us consider $p = 3, 4, 6, 2$, $t = 3, 4, 6, 2, 8, 2, 4, 5, 7, 1$ and $\delta = 1$. In the preprocessing table, $DT(x)$ denotes the position where $|\alpha - p_i| \leq \delta$. For example, $DT[3] = 1011$ because $|3 - p_i| \leq 1$ for $i = 1, 2, 4$.

The table below evaluates $DState_j$ using the relation (3.1). For example,

$$\begin{aligned} DState_4 &= (\text{LeftShift}(DState_3) \text{ OR } 1) \text{ AND } DT[t_4] \\ &= (\text{LeftShift}(0100) \text{ OR } 1) \text{ AND } DT[2] \\ &= (1000 \text{ OR } 1) \text{ AND } 1001 \\ &= 1001 \text{ AND } 1001 \\ &= 1001 \end{aligned}$$

which implies that there is a match starting at position 1 of t , since the 4th bit of $DState_4$ is 1.

A δ -approximate match occurs at position $j - m + 1$ of t if $[DState_j]_{10} \geq 2^{m-1}$, where $[DState_j]_{10}$ denotes the $DState_j$ as a decimal integer. Therefore, there is one match ending at position 4 of t ($\{3, 4, 6, 2\}$) and another one at position 10 of t ($\{4, 5, 7, 1\}$) since $\{DState_4, DState_{10}\} \geq 2^3$.

TABLE I The table DT for pattern $p = 2, 6, 4, 3$ and alphabet $\Sigma = \{1, \dots, 9\}$.

i	p_i	$DT[1]$	$DT[2]$	$DT[3]$	$DT[4]$	$DT[5]$	$DT[6]$	$DT[7]$	$DT[8]$	$DT[9]$
4	2	1	1	1	0	0	0	0	0	0
3	6	0	0	0	0	1	1	1	0	0
2	4	0	0	1	1	1	0	0	0	0
1	3	0	1	1	1	0	0	0	0	0

TABLE II Computing the $DStates$ and finding the δ -approximate matches.

j	1	2	3	4	5	6	7	8	9	10
t_j	3	4	6	2	8	2	4	5	7	1
$\text{LeftShift}(DState_{j-1}) \text{ OR } 1$	0001	0011	0111	1001	0011	0001	0011	0111	1101	1001
$DT[t_j]$	1011	0011	0100	1001	0000	1001	0011	0110	0100	1000
$DState_j$	0001	0011	0100	1001	0000	0001	0011	0110	0100	1000
$[DState_j]_{10}$	1	3	4	9	0	1	3	6	4	8

```

1.  procedure SHIFT-AND( $p, t, \delta$ )  {  $n = |t|, m = |p|$  }
2.  begin
3.     $DT_i[\alpha] \leftarrow \begin{cases} 1 & \text{if } |\alpha - p_i| \leq \delta \\ 0 & \text{otherwise} \end{cases} \quad \forall i \in \{1..m\}, \forall \alpha \in \Sigma$ 
4.     $DState_0 \leftarrow 0$ 
5.    for  $j \leftarrow 1$  to  $n$  do
6.       $DState_j \leftarrow (LeftShift(DState_{j-1}) \text{ OR } 1) \text{ AND } DT[t_j]$ 
7.      if  $DState_j \geq 2^{m-1}$  then write  $j-m+1$ 
8.    od
9.  end

```

FIGURE 1 The SHIFT-AND procedure.

3.1 Pseudo-Code

Figure 1 gives a complete specification of the algorithm. In line 3 we have the preprocessing phase which computes the DT table. In line 6 we use the recursive formula to compute the $DStates$. Finally, in line 7 we apply the matching criteria to see whether there is a δ -approximate match or not.

3.2 Running Time

Assuming that the pattern length is no longer than the memory word size of the machine (thus $O(1)$ size), the time complexity of the preprocessing phase is $O(n)$ (since we need to evaluate DT only for the symbols that occur in t) and the time complexity of the searching phase is $O(n)$. Figure 2 shows the timing¹ for different text sizes.

4 $\{\delta, \gamma\}$ -APPROXIMATE PATTERN MATCHING

The problem of $\{\delta, \gamma\}$ -approximate pattern matching is formally defined as follows: given a string $t = t_1 \dots t_n$ and a pattern $p = p_1 \dots p_m$ compute all positions j of t such that

$$p \stackrel{\delta, \gamma}{=} t[j..j+m-1]$$




FIGURE 2 Timing curves for the SHIFT-AND procedure.

¹ Using a SUN Ultra Enterprise 300MHz running Solaris Unix.

In order to solve this problem we first make use of the SHIFT-AND algorithm to find the δ -approximate matches of pattern p in t . Once we find a δ -approximate match we want to know whether it is also a γ -approximate match. To do so, we seek to compute successive “Delta States” $DState_j$ and “Gamma State” $GState_j$ in $O(1)$ time using bit operations under the assumption that $m \leq w$ where w is the number of bits in a machine word. The main steps of the algorithm are as follows:

1. We need to compute the “Delta Table” DT as we did before and the “Gamma Table” GT table; we set $GT(\alpha) = r$, where α denotes a symbol in the alphabet and $r = r_1 \dots r_m$ is a word with r_i equal to $|\alpha - p_i|$ if $|\alpha - p_i| \leq \delta$, otherwise r_i is equal to 0 for $i \in \{1..m\}$. Each $r_i, i \in \{1..m\}$ is stored as a binary number of d bits where $d = \lceil \log(\delta \times m) \rceil$.
2. Let $LeftShift$ be a bit-wise operation that shifts the bits of a binary word one position to the left and $RightShift$ shifts the bits of a binary word d positions to the right. Once we have computed the DT and GT tables, we can use them to compute the $DState_j$ and $GState_j$ for $j = 1 \dots n$, using the recursive formulas

$$DState_j = (LeftShift(DState_{j-1}) \text{ OR } 1) \text{ AND } DT[t_j] \quad (4.1)$$

$$GState_j = RightShift(GState_{j-1}, d) + GT[t_j] \quad (4.2)$$

We also need to define the seeds $DState_0 = 0$ and $GState_0 = 0$. We call this procedure “SHIFT-PLUS” because we use the “shift” and “plus” operators to compute a new state.

3. We say that there is a match ($\{\delta, \gamma\}$ -approximate match) at position $j - m + 1$ if and only if the m th bit of $DState_j$ is 1 and the m -th block of d bits taken as an integer is $\leq \gamma$.

Example. For our example, let $\Sigma = \{1, \dots, 9\}$, the pattern $p = 3, 4, 6, 2$, the text $t = 3, 4, 6, 2, 8, 2, 4, 5, 7, 1, \delta = 1$ and $\gamma = 3$. We will use blocks of size 3 ($d = 3$) to store the $|\alpha - p_i|$ value where $|\alpha - p_i| \leq \delta$. For example, $GT[3] = 00010000100$ because $|3 - p_i| \leq 1$ for $i = 1, 2, 4$ and the differences are 0, 1, 1 respectively (see left hand table of Table III).

TABLE III The left hand side table is the “Gamma Table” GT and the right hand side table is the table for finding $\{\gamma, \delta\}$ -approximate matches.

i	p_i	1	2	3	4	5	6	7	8	9
1	3	0	1	0	1	0	0	0	0	0
		0	0	0	0	0	0	0	0	0
		0	0	0	0	0	0	0	0	0
2	4	0	0	1	0	1	0	0	0	0
		0	0	0	0	0	0	0	0	0
		0	0	0	0	0	0	0	0	0
3	6	0	0	0	0	1	0	1	0	0
		0	0	0	0	0	0	0	0	0
		0	0	0	0	0	0	0	0	0
4	2	1	0	1	0	0	0	0	0	0
		0	0	0	0	0	0	0	0	0
		0	0	0	0	0	0	0	0	0

j	1	2	3	4	5	6	7	8	9	10
t_j	3	4	6	2	8	2	4	5	7	1
3	0	1	0	1	0	1	1	0	0	0
	0	0	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0	0	0
4	1	0	1	0	1	0	1	0	0	0
	0	0	0	0	0	0	0	1	0	0
	0	0	0	0	0	0	0	0	0	0
6	0	1	0	1	0	1	0	0	1	0
	0	0	0	0	0	0	0	1	1	0
	0	0	0	0	0	0	0	0	0	0
2	1	0	1	0	1	0	1	0	0	0
	0	0	0	0	0	0	0	0	1	0
	0	0	0	0	0	0	0	0	0	1

```

1.  procedure SHIFT-PLUS( $p, t, \delta, \gamma$ )  {  $n = |t|, m = |p|$  }
2.  begin
3.     $DT_i[\alpha] \leftarrow \begin{cases} 1 & \text{if } |\alpha - p_i| \leq \delta \\ 0 & \text{otherwise} \end{cases} \quad \forall i \in \{1..m\}, \forall \alpha \in \Sigma$ 
4.     $GT_{di-d...di-1}[\alpha] \leftarrow \begin{cases} |\alpha - p_i| & \text{if } DT_i[\alpha] = 1 \\ 0 & \text{otherwise} \end{cases} \quad \forall i \in \{1..m\}, \forall \alpha \in \Sigma$ 
5.     $DState_0 \leftarrow 0$ 
6.     $GState_0 \leftarrow 0$ 
7.    for  $j \leftarrow 1$  to  $n$  do
8.       $DState_j \leftarrow (LeftShift(DState_{j-1}) \text{ OR } 1) \text{ AND } DT[t_j]$ 
9.       $GState_j \leftarrow RightShift(GState_{j-1}, d) + GT[t_j]$ 
10.     if  $DState_j \geq 2^{m-1}$  AND  $GState_{dm-d...dm-1} \leq \gamma$  then write  $j-m+1$ 
11.   od
12. end

```

FIGURE 3 The SHIFT-PLUS algorithm.

The right hand table above shows the computation of the $DStates$ and the $GStates$ using (4.2). For example,

$$\begin{aligned}
 GState_9 &= RightShift(000010010000, 3) + 000000100000 \\
 &= 000000010010 + 000000100000 = 000000110010
 \end{aligned}$$

We already know that there are two δ -approximate matches ending at positions 4 and 10 of t . Now we can use the last three bits of $GState_4$, and $GState_{10}$ to find out the values of γ , which are 0 and 4 respectively (see right hand table of Table III).

4.1 Pseudo-Code

Figure 3 gives a complete description of the algorithm. In lines 3 and 4 are the preprocessing phase which computes the DT table and GT table respectively. In lines 8 and 9 we compute the next $DState$ and $GState$ respectively. Finally, in line 10 we apply the matching criteria to see whether there is a match or not.

4.2 Running Time

Assuming that $\delta \times m \leq 2^d - 1$ the time complexity of the preprocessing phase is $O(\delta \times m + |\Sigma|)$ and the time complexity of the searching phase is $O(n)$, thus independent from the alphabet size and the pattern length. Figure 4 shows the timing for different text sizes.




FIGURE 4 Timing curves for the SHIFT-PLUS algorithm.

5 COMPUTING APPROXIMATE SQUARES

The problem of computing all δ -approximate squares is formally defined as follows: given a string $t = t_1 \dots t_n$ and an integer δ , compute all positions j of t for which there exists a word u of length m such that

$$t[j..j+m] \overset{\delta}{=} u \text{ and } t[j+m+1..j+2m] \overset{\delta}{=} u$$

where u is said to be the *root* of the square.

The problem of computing all $\{\delta, \gamma\}$ -approximate squares is formally defined as follows: given a string $t = t_1 \dots t_n$ and two integers δ and γ , compute all positions j of t for which there exists a word u of length m such that

$$t[j..j+m] \overset{\delta, \gamma}{=} u \text{ and } t[j+m+1..j+2m] \overset{\delta, \gamma}{=} u$$

where u is said to be the *root* of the square.

When we look for a square we will run into two possibilities: the root does or does not occur necessarily in the square.

5.1 Consider an Approximate Square such that the Root Occurs in the Square

The diagonal $\text{diag}(i)$ corresponds to the pair of positions $(j, j+i)$ and therefore to the candidates for squares of length $2i$. There exists an approximate square of length $2i$ at position j if there exists a run of values not greater than δ of length at least i on the diagonal $\text{diag}(i)$ starting at position j .

For example, consider $\text{diag}(2)$ (see Table IV) and $\delta = 1$. We are trying to locate runs of length at least 2 containing only values not greater than $\delta = 1$. We obtain:

Position	Square	Roots
14	(2, 3, 1, 4)	(2, 3) or (1, 4)

TABLE IV Table for computing approximate squares.

	i	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	
		2	-3	-5	4	-1	-7	1	-5	-5	3	-3	1	1	2	3	1	4	5	7	
j																					
1	2	0	5	7	2	3	9	1	7	7	1	5	1	1	0	1	1	2	3	5	diag(18)
2	-3	—	0	2	7	2	4	4	2	2	6	0	4	4	5	6	4	7	8	10	diag(17)
3	-5	—	—	0	9	4	2	6	0	0	8	2	6	6	7	8	6	9	10	12	diag(16)
4	4	—	—	—	0	5	11	3	9	9	1	7	3	3	2	1	3	0	1	3	diag(15)
5	-1	—	—	—	—	0	6	2	4	4	4	2	2	2	3	4	2	5	6	8	diag(14)
6	-7	—	—	—	—	—	0	8	2	2	10	4	8	8	9	10	8	11	12	14	diag(13)
7	1	—	—	—	—	—	—	0	6	6	2	4	0	0	1	2	0	3	4	8	diag(12)
8	-5	—	—	—	—	—	—	—	0	8	2	6	6	6	7	8	6	9	10	12	diag(11)
9	-5	—	—	—	—	—	—	—	—	0	8	2	6	6	7	8	6	9	10	12	diag(10)
10	3	—	—	—	—	—	—	—	—	—	0	6	2	2	1	0	2	1	2	4	diag(9)
11	-3	—	—	—	—	—	—	—	—	—	—	0	4	4	5	6	4	7	8	10	diag(8)
12	1	—	—	—	—	—	—	—	—	—	—	—	0	0	1	2	0	3	4	6	diag(7)
13	1	—	—	—	—	—	—	—	—	—	—	—	—	0	1	2	0	3	4	6	diag(6)
14	2	—	—	—	—	—	—	—	—	—	—	—	—	—	0	1	1	2	3	5	diag(5)
15	3	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0	2	1	2	4	diag(4)
16	1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0	3	4	6	diag(3)
17	4	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0	1	3	diag(2)
18	5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0	2	diag(1)
19	7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0	diag(0)

For this example we only have a δ -approximate square starting at position 14 which root can be either (2,3) or (1,4). Note that the roots certainly occur in the square.

5.2 Consider an Approximate Square such that the Root does not Occur Necessarily in the String

We say that there exists an approximate square of length $2i$ at position j if there exists a run of values not greater than 2δ of length at least i on the diagonal $\text{diag}(i)$ starting at position j . In other words, we are using 2δ instead of δ .

For example, consider $\text{diag}(2)$ (see Table IV) and $\delta = 1$. We are trying to locate runs of length at least 2 containing only values not greater than $2\delta = 2$. We obtain:

Position	Square	Roots
5	(-1, -7, 1, -5)	(0, -6)
9	(-5, 3, -3, 1)	(-4, 2)
12	(1, 1, 2, 3)	(1, 2) or (2, 2)
13	(1, 2, 3, 1)	(2, 1) or (2, 2)
14	(2, 3, 1, 4)	(1, 3), (1, 4), (2, 3) or (2, 4)

Furthermore, consider $\text{diag}(3)$ and $\delta = 1$. We are trying to locate runs of length at least 3 containing only values not greater than $2\delta = 2$. We obtain:

Position	Square	Roots
1	(2, -3, -5, 4, -1, -7)	(3, -2, -6)
6	(-7, 1, -5, -5, 3, -3)	(-6, 2, -4)
12	(1, 1, 2, 3, 1, 4)	(2, 0, 3), (2, 1, 3) or (2, 2, 3)
13	(1, 2, 3, 1, 4, 5)	(0, 3, 4), (1, 3, 4) or (2, 3, 4)

In those cases where we want to consider a $\{\delta, \gamma\}$ -approximate square we just check each δ -approximate match to see if it is also a $\{\delta, \gamma\}$ -approximate square.

In the last example we will like to consider $\delta = 1$ and $\gamma = 4$. This means that we are trying to locate runs of length at least 2 containing only values not greater than $2\delta = 2$ but with $\gamma \leq 4$. We obtain:

Position	Square	Roots	γ
12	(1, 1, 2, 3, 1, 4)	(2, 0, 3), (2, 1, 3) or (2, 2, 3)	4
13	(1, 2, 3, 1, 4, 5)	(0, 3, 4), (1, 3, 4) or (2, 3, 4)	4

5.3 Pseudo-Code

Figure 5 gives the algorithm that solves the δ -approximation square problem. Figure 6 gives the algorithm that solves the $\{\delta, \gamma\}$ -approximation square problem.

5.4 Running Time

The complexity of these algorithms is easily seen to be $O(n^2)$. Figure 7 shows the timing for different text sizes.

```

1.  procedure DELTASQUARES( $t, \delta$ )  {  $n = |t|$  }
2.  begin
3.    for  $diag \leftarrow 2$  to  $n/2$  do
4.       $i \leftarrow 0$ ;  $dsum \leftarrow 0$ 
5.      for  $j \leftarrow diag$  to  $n$  do
6.         $diff \leftarrow |t[i] - t[j]|$ 
7.        if  $diff \leq \delta$  then  $dsum \leftarrow dsum + 1$ 
8.        else  $dsum \leftarrow 0$ 
9.        if  $dsum \geq diag$  then write  $j - 2 * diag + 2$ 
10.        $i \leftarrow i + 1$ 
11.     od
12.   od
13. end

```


FIGURE 5 The DELTASQUARES algorithm.

```

1.  procedure DELTAGAMMASQUARES( $t, \delta, \gamma$ )  {  $n = |t|$  }
2.  begin
3.    for  $diag \leftarrow 2$  to  $n/2$  do
4.       $i \leftarrow 0$ ;  $dsum \leftarrow 0$ ;  $gsum \leftarrow 0$ 
5.      for  $j \leftarrow diag$  to  $n$  do
6.         $diff \leftarrow |t[i] - t[j]|$ 
7.        if  $diff \leq \delta$  then
8.          begin
9.             $dsum \leftarrow dsum + 1$ 
10.            $gsum \leftarrow gsum + diff$ 
11.           if  $dsum > diag$  then  $gsum \leftarrow gsum - |t[i - diag] - t[j - diag]|$ 
12.         end
13.       else
14.         begin
15.            $dsum \leftarrow 0$ ;  $gsum \leftarrow 0$ 
16.         end
17.       if  $dsum \geq diag$  AND  $gsum \leq \gamma$  then write  $j - 2 * diag + 2$ 
18.        $i \leftarrow i + 1$ 
19.     od
20.   od
21. end

```

FIGURE 6 The DELTAGAMMASQUARES algorithm.

FIGURE 7 Timing curves for $\{\delta, \gamma\}$ -approximate squares.

6 CONCLUSION AND OPEN PROBLEMS

The running time of the computation of δ -approximate squares can be reduced to $O(n \log n)$; A theoretical algorithm is presented in [16] that shadows the Main and Lorentz algorithm [21].

The following two problems are still open:

Problem 1. Given a string $t = t_1 \dots t_n$ and two integers m and δ , compute all positions j of t , that there exists a string \hat{t} such that

$$\begin{aligned} t[j..j+m] &\stackrel{\delta}{=} \hat{t} \\ t[j+m+1..j+2m] &\stackrel{\delta}{=} \hat{t} \\ &\dots \\ t[j+\ell m+1..j+(\ell+1)m] &\stackrel{\delta}{=} \hat{t} \end{aligned}$$

Problem 2. Given a string $t = t_1 \dots t_n$ and three integers m , δ and γ , compute all positions j of t , that there exists a string \hat{t} such that

$$\begin{aligned} t[j..j+m] &\stackrel{\delta,\gamma}{=} \hat{t} \\ t[j+m+1..j+2m] &\stackrel{\delta,\gamma}{=} \hat{t} \\ &\dots \\ t[j+\ell m+1..j+(\ell+1)m] &\stackrel{\delta,\gamma}{=} \hat{t} \end{aligned}$$

References

- [1] Apostolico, A. and Preparata, F. P. (1983). Optimal off-line detection of repetitions in a string, *Theoretical Computer Science*, **22**(3), 297–315.
- [2] Baeza-Yates, R. A. and Gonnet, G. H. (1992). A new approach to text searching, *CACM*, **35**, 74–82.
- [3] Berkman, O., Iliopoulos, C. and Park, K. (1996). String covering, *Information and Computation*, **123**, 127–137.
- [4] Cambouropoulos, E., Crawford, T. and Iliopoulos, C. S. (1999). Pattern processing in melodic sequences: challenges, caveats and prospects, in *Proceedings of the AISB'99 Convention (Artificial Intelligence and Simulation of Behaviour)*, Edinburgh, U.K., pp. 42–47.
- [5] Cope, D. (1990). Pattern-matching as an engine for the computer simulation of musical style, in *Proceedings of the International Computer Music Conference*, Glasgow, pp. 288–291.
- [6] Crawford, T., Iliopoulos, C. S. and Raman, R. (1998). String matching techniques for musical similarity and melodic recognition, *Computing in Musicology*, **11**, 73–100.
- [7] Crawford, T., Iliopoulos, C. S., Winder, R. and Yu, H. (1999). Approximate musical evolution, in *Proceedings of the 1999 Artificial Intelligence and Simulation of Behaviour Symposium (AISB'99)*, G. Wiggins (Ed.), The Society for the Study of Artificial Intelligence and Simulation of Behaviour, Edinburgh, pp. 76–81.
- [8] Crochemore, M. (1981). An optimal algorithm for computing the repetitions in a word, *Information Processing Letters*, **12**, 244–250.
- [9] Crochemore, M., Iliopoulos, C. S. and Yu, H. (1998). Algorithms for computing evolutionary chains in molecular and musical sequences, *Proceedings of the 9th Australasian Workshop on Combinatorial Algorithms*, **6**, 172–185.
- [10] Czumaj, A., Ferragina, P., Gasieniec, L., Muthukrishnan, S. and Traeff, J. The architecture of a software library for string processing, presented at *Workshop on Algorithm Engineering*, Venice, September 1997.
- [11] Fischetti, V., Landau, G., Schmidt, J. and Sellers, P. (1992). Identifying periodic occurrences of a template with applications to protein structure, *Proc. 3rd Combinatorial Pattern Matching*, Lecture Notes in Computer Science, **644**, 111–120.
- [12] Galil, Z. and Park, K. (1990). An improved algorithm for approximate string matching, *SIAM Journal on Computing*, **29**, 989–999.
- [13] Iliopoulos, C. S. and Mouchard, L. (1999). An $O(n \log n)$ algorithm for computing all maximal quasiperiodic

- cities in strings, in *Proceedings of CATS'99: "Computing: Australasian Theory Symposium"*, Auckland, New Zealand, Lecture Notes in Computer Science, Springer Verlag, **21**(3), 262–272.
- [14] Iliopoulos, C. S., Moore, D. W. G. and Park, K. (1996). Covering a string, *Algorithmica*, **16**, 288–297.
- [15] Iliopoulos, C. S., Moore, D. W. G. and Smyth, W. F. (1996). A linear algorithm for computing the squares of a Fibonacci string, in *Proceedings CATS'96, "Computing: Australasian Theory Symposium"*, P. Eades and M. Moule (Eds), University of Melbourne, pp. 55–63.
- [16] Iliopoulos, C. S. and Pinzon, Y. J. An $O(n \log n)$ algorithm for computing squares in musical sequences, in preparation.
- [17] Karlin, S., Morris, M., Ghandour, G. and Leung, M.-Y. (1998). Efficient algorithms for molecular sequences analysis, *Proc. Natl. Acad. Sci., USA*, **85**, 841–845.
- [18] Landau, G. M. and Schmidt, J. P. (1993). An algorithm for approximate tandem repeats, in *Proc. Fourth Symposium on Combinatorial Pattern Matching*, Springer-Verlag Lecture Notes in Computer Science **648**, 120–133.
- [19] Landau, G. M. and Vishkin, U. (1988). Introducing efficient parallelism into approximate string matching and a new serial algorithm, in *Proc. Annual ACM Symposium on Theory of Computing*, ACM Press, pp. 220–230, 1986.
- [20] Landau, G. M. and Vishkin, U. (1988). Fast string matching with k differences, *Journal of Computer and Systems Sciences*, **37**, 63–78.
- [21] Main, G. and Lorentz, R. (1984). An $O(n \log n)$ algorithm for finding all repetitions in a string, *Journal of Algorithms*, **5**, 422–432.
- [22] Mongeau, M. and Sankoff, D. (1990). Comparison of musical sequences, *Computers and the Humanities*, **24**, 161–175.
- [23] McGettrick, P. (1997). MIDIMatch: musical pattern matching in real time. MSc Dissertation, York University, U.K.
- [24] Milosavljevic, A. and Jurka, J. (1993). Discovering simple DNA sequences by the algorithmic significance method, *Comput. Appl. Biosci.*, **9**, 407–411.
- [25] Moore, D. W. G. and Smyth, W. F. (1994). Computing the covers of a string in linear time, in *Proc. 5th ACM-SIAM Symposium on Discrete Algorithms*, 511–515.
- [26] Myers, E. W. and Kannan, S. K. (1993). An algorithm for locating non-overlapping regions of maximum alignment score, in *Proc. Fourth Symposium on Combinatorial Pattern Matching*, Springer-Verlag Lecture Notes in Computer Science **648**, 74–86.
- [27] Pevzner, P. A. and Feldman, W. (1993). Gray code masks for DNA sequencing by hybridization, *Genomics*, **23**, 233–235.
- [28] Rolland, P. Y. and Ganascia, J. G. (1999). Musical pattern extraction and similarity assessment, in *Readings in Music and Artificial Intelligence*, E. Miranda (Ed.), Harwood Academic Publishers (forthcoming).
- [29] Schmidt, J. P. (1994). All shortest paths in weighted grid graphs and its application to finding all approximate repeats in strings, in *Proc. of the Fifth Symposium on Combinatorial Pattern Matching CPM'94*, Lecture Notes in Computer Science.
- [30] Skiena, S. S. and Sundaram, G. (1995). Reconstructing strings from substrings, *J. Computational Biol.*, **2**, 333–353.
- [31] Wu, S. and Manber, U. (1992). Fast text searching allowing errors, *CACM*, **35**, 83–91.