CONFIDENTIAL — DRAFT — FOR DISCUSSION

Research first, claims last. One protocol, three gates, every thread under it.

The research question, precisely: *do engineered structures — a conditioned solid-state magnetic core, a Casimir cavity, a metal–insulator–metal junction — produce any repeatable, artifact-free electrical output whose energy accounting cannot be closed by known sources?* Expected answer, on the mainstream prior: no. EnergyWave exists to obtain that answer to a standard that survives independent review, and to publish it either way.

THE GATE PROTOCOL

Gate	Question	Pass	Kill
Gate 1 Characterize	Can the reported effects be reproduced, and are they artifacts?	Repeatable output above the fully characterized noise and artifact floor at ≥5σ in blinded runs, surviving every control.	Nothing above the floor, or output explained by a known source. Result published with data.
Gate 2 Conservation test	If something is there, where does the energy come from?	Net output whose closed-system energy balance cannot be closed by known sources, replicated by a second laboratory contracted in advance.	The balance closes, or replication fails. Effect retired publicly.
Gate 3 Extract or retire	Can it be engineered?	Independently validated, repeatable performance under third-party observation — the first point at which EnergyWave would ever state a number. The anti-tamper “paperweight test” is a Gate-3 deliverable.	Scaling, lifetime or stability fails.

Gate names follow the August 2026 white paper (Characterize / Conservation-test / Extract or retire); the September program documents number them Gate 1–3; the October deck shows them as Phases 0–3 with Phase 0 = this round. They are the same three decisions.

ENERGY ACCOUNTING — THE STANDARD EVERY THREAD IS HELD TO

> **$E_{\text{all inputs}} = E_{\text{load}} + E_{\text{heat and other outputs}} + \Delta U_{\text{device}}$** — where U includes everything stored in capacitors, batteries, magnetic and strain states and internal thermal reservoirs. DC input is ∫v(t)i(t)dt, never average V × average I. Timing deskew between voltage and current probes in a high-Q circuit can turn a true +50 mW dissipation into a false −75 mW “generation” reading at 1 MHz; calibration must cover the whole measurement chain. A null result bounds the tested configuration at its demonstrated sensitivity — it does not identify an origin. (Physical Architecture & Baseline Model v1.3, §§1–3; Claude review v2, §3.)

THE RESEARCH THREADS — KEPT SEPARATE, HELD TO THE SAME PROTOCOL

Thread	What it is	Evidence to date	Next step

A · Founder's solid-state module Sweet-lineage conditioned ferrite core	Floyd Sweet's vacuum triode amplifier as the named first module (Oct-13 deck). The physical nature of magnet "conditioning" is unestablished; three hypotheses are set out for test: finite stored-energy depletion, open-system environmental transduction, metrology phase skew.	No specimen selected, no hardware ordered, no measured result. Baseline model v1.3 proposes an unconditioned four-step characterization before any conditioning experiment. Specimen, magnetization, winding axis and conditioning procedure are inventor-defined and not yet on record. OPEN	Founder defines the specimen and conditioning; characterization plan with pass / kill criteria written with Chip Story.
B · Independent replication MIM diode under a Casimir cavity	Pre-registered replication of Moddel et al. 2021 with cavity / no-cavity twins from the same wafer, sign and magnitude vs. cavity thickness, blinded measurement.	Published claim: 1.4 pW maximum, one lab, >1,000 devices, unreplicated — *Claimed, not replicated*; Maclay 2024 predicts the opposite sign — *Disputed*. Proposed to the Army as an independent evaluation platform (xTech Search 10, submitted 9 Oct 2026).	Qualified independent lead; fabrication access; matched test articles; the artifact-exclusion bench commissioned on known-null samples.
C · The measurement platform Workstream 1B	Shielded isothermal enclosure; calorimetric accounting; lock-in electrical measurement to the picowatt level; blinded sample handling; open data pipeline. Published as a methods paper before any result is claimed.	Design only. Residual value if every thread fails: a credible nanoscale-measurement capability and its publications — stated once, not oversold.	Error budget for external review.

Which thread is first is the founder's decision (D2). The September program places the founder's own structure as workstream 1C under the same protocol as the replication; the October deck leads with it. Nothing on this page asserts a physical dependency between threads — none has been established — and no thread is described as feeding another.

EIGHT COMMITMENTS, WRITTEN IN FROM DAY ONE

- Pre-registration of every protocol, public and timestamped.
- Null results published, with data, every time.
- Replication budgeted and contracted before each gate, never assumed.
- External scientific advisory board with veto over any performance statement — at least one declared critic.
- No performance claim before Gate-3 third-party validation.
- Capital released by gate (escrowed tranches on the next round).
- Clean entity separation: EnergyWave, Inc. / McLean Companies LLC / GovThink.
- Open methods: bench design and error-budget methodology published.

WHY PHYSICISTS EXPECT "NO" — SAID HERE BEFORE AN INVESTOR'S PHYSICIST FRIEND SAYS IT

The vacuum is the ground state. Casimir energy is a difference of zero-point energies and the force is conservative, so whatever work it does closing the plates must be paid back to open them. A device delivering steady work from a single equilibrium reservoir is a perpetual-motion machine of the second kind (Brillouin 1950). Dynamical-Casimir photons are real, and the pump pays for them. Even the best-case single-use Casimir stack holds about 2 J/kg against ~9×10^5 J/kg in the lithium-ion cell a humanoid already carries. The program is designed so that if the prior is right, that is learned at Gate 1 for the price of the first tranche — and published.

TECHNICAL DOCUMENTS IN THIS FOLDER

File	Status	Note
EnergyWave_Physical_Architecture_and_Baseline_Model_v1.3_2026-10-05.pdf	VERIFIED	AI-reviewed working briefing (Antigravity & GPT/Codex; reviewed by Claude). §6 is a historical legal/corporate status table and is superseded by 04_Legal_and_IP.
2026-10-05_energywave-physics-review_claude_v2.md and three source notes	VERIFIED	Reservoir inventory; boundary language; Puthoff & Little assessed; Pais / Exodus / regauging checked; GR-coupling evaluation and its review.
EnergyWave_Technical_Prospectus_DRAFT_v1_2026-09-07.docx	HISTORICAL	The September program in full: §4 physics with labels, §6 Gate 1 design and artifact catalogue, §6.5 workstream 1C placeholder, §6.6 decision rule.
Key_Research_Facts_verified_2026-09-07.md	HISTORICAL	One-page corrections to common belief; energy figures used in the narrative.

Sources: Oct-13 deck slides 5–7, 9 (S-01); Technical Prospectus v1 §§4, 6–7 (M-05); Program_Summary_and_Gates.md and Key_Research_Facts (M-03b); DoD white paper v2.0 §3 (M-07); Physical Architecture & Baseline Model v1.3 (S-11/M-14); Claude physics review v2 and source notes (S-13, S-15–S-18); xTech white paper (M-10).