

# Constraint Programming

## An Appetizer

Christian Schulte  
schulte@imit.kth.se

Laboratory of Electronics and Computer Systems  
Institute of Microelectronics and Information Technology  
KTH – Royal Institute of Technology  
Stockholm, Sweden



## Constraint Programming

- Solving combinatorial problems

**start with a first toy problem**

2003-10-02 Christian Schulte, IMIT, KTH 2

## Send More Money (SMM)

- Find distinct digits for letters, such that

$$\begin{array}{r} \text{SEND} \\ + \text{MORE} \\ \hline = \text{MONEY} \end{array}$$

2003-10-02 Christian Schulte, IMIT, KTH 3

## Constraint Model for SMM

- Variables:  
 $S, E, N, D, M, O, R, Y \in \{0, \dots, 9\}$
- Constraints:
  - $\text{distinct}(S, E, N, D, M, O, R, Y)$
  - $1000 \times S + 100 \times E + 10 \times N + D$
  - $+ 1000 \times M + 100 \times O + 10 \times R + E$
  - $= 10000 \times M + 1000 \times O + 100 \times N + 10 \times E + Y$
  - $S \neq 0 \quad M \neq 0$

2003-10-02 Christian Schulte, IMIT, KTH 4

## Solving SMM

- Find values for variables

such that

**all constraints satisfied**

2003-10-02 Christian Schulte, IMIT, KTH 5

## Finding a Solution

- Enumerate assignments: poor!
- Constraint programming
  - compute with possible values
  - prune inconsistent values
  - constraint propagation
  - search
    - branch: define search tree
    - explore: explore search tree for solution

2003-10-02 Christian Schulte, IMIT, KTH 6

# Overview

## Overview

- Constraint propagation
- Search
- Summary: Applications & Principles
- Application examples
  - resource scheduling
  - instruction scheduling
- Constraint Programming 2G1515

2003-10-02

Christian Schulte, IMIT, KTH

8

# Constraint Propagation

## Important Concepts

- Constraint store
- Basic constraint
- Propagator
- Non-basic constraint
- Constraint propagation

2003-10-02

Christian Schulte, IMIT, KTH

10

## Constraint Store

$x \in \{3,4,5\} \quad y \in \{3,4,5\}$

- Stores basic constraints  
map variables to possible values

2003-10-02

Christian Schulte, IMIT, KTH

11

## Constraint Store

finite domain constraints

$x \in \{3,4,5\} \quad y \in \{3,4,5\}$

- Stores basic constraints  
map variables to possible values

2003-10-02

Christian Schulte, IMIT, KTH

12

## Constraint Store

$x \in \{3,4,5\} \quad y \in \{3,4,5\}$

- Stores basic constraints  
map variables to possible values
- Domains: finite sets, real intervals, trees, ...

2003-10-02

Christian Schulte, IMIT, KTH

13

## Propagators

- Implement non-basic constraints

$\text{distinct}(x_1, \dots, x_n)$

$x + 2xy = z$

2003-10-02

Christian Schulte, IMIT, KTH

14

## Propagators

$x \geq y$        $y > 3$

$x \in \{3,4,5\} \quad y \in \{3,4,5\}$

- Amplify store by constraint propagation

2003-10-02

Christian Schulte, IMIT, KTH

15

## Propagators

$x \geq y$        $y > 3$

$x \in \{3,4,5\} \quad y \in \{3,4,5\}$

- Amplify store by constraint propagation

2003-10-02

Christian Schulte, IMIT, KTH

16

## Propagators

$x \geq y$        $y > 3$

$x \in \{3,4,5\} \quad y \in \{4,5\}$

- Amplify store by constraint propagation

2003-10-02

Christian Schulte, IMIT, KTH

17

## Propagators

$x \geq y$        $y > 3$

$x \in \{3,4,5\} \quad y \in \{4,5\}$


- Amplify store by constraint propagation

2003-10-02

Christian Schulte, IMIT, KTH

18

## Propagators




- Amplify store by constraint propagation

2003-10-02

Christian Schulte, IMIT, KTH

19

## Propagators




- Amplify store by constraint propagation
- Disappear when done (entailed)
  - no more propagation possible

2003-10-02

Christian Schulte, IMIT, KTH

20

## Propagators




- Amplify store by constraint propagation
- Disappear when done (entailed)
  - no more propagation possible

2003-10-02

Christian Schulte, IMIT, KTH

21

## Computation Space



- Store with connected propagators

2003-10-02

Christian Schulte, IMIT, KTH

22

## Propagation for SMM

- Results in store

$S=9$     $E \in \{4, \dots, 7\}$     $N \in \{5, \dots, 8\}$     $D \in \{2, \dots, 8\}$   
 $M=1$     $O=0$     $R \in \{2, \dots, 8\}$     $Y \in \{2, \dots, 8\}$

- Propagation **alone** not sufficient!
  - create simpler sub-problems
  - branching

2003-10-02

Christian Schulte, IMIT, KTH

23

Search

## Important Concepts


- Branching
- Exploration
- Branching heuristics
- Best solution search

2003-10-02

Christian Schulte, IMIT, KTH

25

## Branching



- Yields spaces with additional constraints
- Enables further constraint propagation

2003-10-02

Christian Schulte, IMIT, KTH

26

## Branching Strategy


- Pick variable  $x$  with at least two values
- Pick value  $n$  from domain of  $x$
- Branch with
 
$$x=n \quad \text{and} \quad x \neq n$$
- Part of model

2003-10-02

Christian Schulte, IMIT, KTH

27

## Search




- Iterate propagation and branching
- Orthogonal: branching  $\rightleftharpoons$  exploration
- Nodes:
  - Unsolved
  - Failed
  - Succeeded

2003-10-02

Christian Schulte, IMIT, KTH

28

## SMM: Solution



$$\begin{array}{r}
 \text{SEND} \\
 + \text{ MORE} \\
 \hline
 = \text{ MONEY} \\
 9567 \\
 + 1085 \\
 \hline
 = 10652
 \end{array}$$

2003-10-02

Christian Schulte, IMIT, KTH

29

## Heuristics for Branching

- Which variable
  - least possible values (first-fail)
  - application dependent heuristic
- Which value
  - minimum, median, maximum
 
$$x=m \quad \text{or} \quad x \neq m$$
  - split with median  $m$ 


$$x < m \quad \text{or} \quad x \geq m$$
- Problem specific

2003-10-02

Christian Schulte, IMIT, KTH

30

## SMM: Solution With First-fail



$$\begin{array}{r}
 \text{SEND} \\
 + \text{ MORE} \\
 \hline
 = \text{ MONEY} \\
 \\
 9567 \\
 + 1085 \\
 \hline
 = 10652
 \end{array}$$

2003-10-02

Christian Schulte, IMIT, KTH

31

## Send Most Money (SMM++)

- Find distinct digits for letters, such that

$$\begin{array}{r}
 \text{SEND} \\
 + \text{ MOST} \\
 \hline
 = \text{ MONEY}
 \end{array}$$

and MONEY maximal

2003-10-02

Christian Schulte, IMIT, KTH

32

## Best Solution Search


- Naïve approach:
  - compute all solutions
  - choose best
- Branch-and-bound approach:
  - compute first solution
  - add "betterness" constraint to open nodes
  - next solution will be "better"
  - prunes search space

2003-10-02

Christian Schulte, IMIT, KTH

33

## Branch-and-bound Search




- Find first solution

2003-10-02

Christian Schulte, IMIT, KTH

34

## Branch-and-bound Search




- Explore with additional constraint

2003-10-02

Christian Schulte, IMIT, KTH

35

## Branch-and-bound Search




- Explore with additional constraint

2003-10-02

Christian Schulte, IMIT, KTH

36

## Branch-and-bound Search




- Guarantees better solutions

2003-10-02

Christian Schulte, IMIT, KTH

37

## Branch-and-bound Search




- Guarantees better solutions

2003-10-02

Christian Schulte, IMIT, KTH

38

## Branch-and-bound Search




- Last solution best

2003-10-02

Christian Schulte, IMIT, KTH

39

## Branch-and-bound Search



- Proof of optimality

2003-10-02

Christian Schulte, IMIT, KTH

40

## Modelling SMM++


- Constraints and branching as before
- Order among solutions with constraints
  - so-far-best solution S, E, N, D, M, O, T, Y
  - current node S, E, N, D, M, O, T, Y
  - constraint added
 
$$10000 \times M + 1000 \times O + 100 \times N + 10 \times E + Y < 10000 \times M + 1000 \times O + 100 \times N + 10 \times E + Y$$

2003-10-02

Christian Schulte, IMIT, KTH

41

## SMM++: Branch-and-bound




2003-10-02

Christian Schulte, IMIT, KTH

42

## SMM++: All Solution Search



2003-10-02

Christian Schulte, IMIT, KTH

43

## Summary

### Summary

#### ■ Modeling

- variables with domain
- constraints to state relations
- branching strategy
- solution ordering

#### ■ Solving

- constraint propagation
- constraint branching
- search tree exploration

applications

principles

2003-10-02

Christian Schulte, IMIT, KTH

45

### Application Areas

- Timetabling
- Scheduling
- Crew rostering
- Resource allocation
- Workflow planning and optimization
- Gate allocation at airports
- Sports-event scheduling
- Railroad: track allocation, train allocation, schedules
- Automatic composition of music
- Genome sequencing
- Frequency allocation
- ...

2003-10-02

Christian Schulte, IMIT, KTH

46

### Application Examples

#### ■ Scheduling resources

- machines, personal, ...
- constraint programming showcase

#### ■ Instruction scheduling

- used in compilation
- for modern microprocessors with latencies

2003-10-02

Christian Schulte, IMIT, KTH

47

### Principles

#### ■ Models for constraint propagation

- properties and guarantees

#### ■ Strong constraint propagation

- global constraints with strong algorithmic methods
- mantra: search kills, search kills, search k...

#### ■ Branching strategies

#### ■ Exploration strategies


2003-10-02

Christian Schulte, IMIT, KTH

48



## SMM: Strong Propagation


$$\begin{array}{r} \text{SEND} \\ + \text{MORE} \\ \hline = \text{MONEY} \\ 9567 \\ + 1085 \\ \hline = 10652 \end{array}$$

2003-10-02

Christian Schulte, IMIT, KTH

49

## Used Techniques

- Artificial intelligence
- Operations research
- Algorithms
- Programming languages

2003-10-02

Christian Schulte, IMIT, KTH

50

## Why Does CP Matter?

- Middleware for combining smart algorithmic components
  - scheduling
  - graphs
  - flows
  - ...
- plus
  - essential extra constraints

2003-10-02

Christian Schulte, IMIT, KTH

51

## Significance

- Constraint programming identified as a strategic direction in computer science research  
[ACM Computing Surveys, December 1996]
- Applications are ubiquitous
  - knowledgeable people are not!

2003-10-02

Christian Schulte, IMIT, KTH

52

## Relation to Logic Programming

- Logic programming
  - horn clauses + trees with unification
- Constraint logic programming
  - horn clauses + constraint domain
- Constraint programming
  - X + constraint domain
    - with focus on constraints
    - refined search language

2003-10-02

Christian Schulte, IMIT, KTH

53

## Scheduling Resources

- Modeling
- Propagation
- Strong propagation

## Scheduling Resources: Given

- Tasks
  - duration
  - resource
- Precedence constraints
  - determine order among two tasks
- Resource constraints
  - at most one task per resource


[disjunctive, non-preemptive scheduling]

2003-10-02

Christian Schulte, IMIT, KTH

55

## Scheduling: Bridge Example



2003-10-02

56

## Scheduling: Solution

- Start time for each task
- All constraints satisfied
- Earliest completion time
  - minimal make-span

2003-10-02

Christian Schulte, IMIT, KTH

57

## Scheduling: Model

- Variable for start-time of task  $a$   
 $\text{start}(a)$
- Precedence constraint:  $a$  before  $b$   
 $\text{start}(a) + \text{dur}(a) \leq \text{start}(b)$

2003-10-02

Christian Schulte, IMIT, KTH

58

## Propagating Precedence

$a$  before  $b$



$\text{start}(a) \in \{0, \dots, 7\}$   
 $\text{start}(b) \in \{0, \dots, 5\}$

2003-10-02

Christian Schulte, IMIT, KTH

59

## Propagating Precedence

$a$  before  $b$



$\text{start}(a) \in \{0, \dots, 7\}$   
 $\text{start}(b) \in \{0, \dots, 5\}$

$\text{start}(a) \in \{0, \dots, 2\}$   
 $\text{start}(b) \in \{3, \dots, 5\}$

2003-10-02

Christian Schulte, IMIT, KTH

60

## Scheduling: Model

- Variable for start-time of task  $a$   
 $start(a)$
- Precedence constraint:  $a$  before  $b$   
 $start(a) + dur(a) \leq start(b)$
- Resource constraint:  
 $a$  before  $b$   
or  
 $b$  before  $a$

2003-10-02

Christian Schulte, IMIT, KTH

61

## Scheduling: Model

- Variable for start-time of task  $a$   
 $start(a)$
- Precedence constraint:  $a$  before  $b$   
 $start(a) + dur(a) \leq start(b)$
- Resource constraint:  
 $start(a) + dur(a) \leq start(b)$   
or  
 $b$  before  $a$

2003-10-02

Christian Schulte, IMIT, KTH

62

## Scheduling: Model

- Variable for start-time of task  $a$   
 $start(a)$
- Precedence constraint:  $a$  before  $b$   
 $start(a) + dur(a) \leq start(b)$
- Resource constraint:  
 $start(a) + dur(a) \leq start(b)$   
or  
 $start(b) + dur(b) \leq start(a)$

2003-10-02

Christian Schulte, IMIT, KTH

63

## Reified Constraints

- Use control variable  $b \in \{0,1\}$   
 $c \leftrightarrow b=1$
- Propagate
 

■ $c$ holds	$\Rightarrow$	propagate $b=1$
■ $\neg c$ holds	$\Rightarrow$	propagate $b=0$
■ $b=1$ holds	$\Rightarrow$	propagate $c$
■ $b=0$ holds	$\Rightarrow$	propagate $\neg c$

2003-10-02

Christian Schulte, IMIT, KTH

64

## Reified Constraints

- Use control variable  $b \in \{0,1\}$   
 $c \leftrightarrow b=1$
- Propagate
 

■ $c$ holds	$\Rightarrow$	propagate $b=1$
■ $\neg c$ holds	$\Rightarrow$	propagate $b=0$
■ $b=1$ holds	$\Rightarrow$	propagate $c$
■ $b=0$ holds	$\Rightarrow$	propagate $\neg c$

2003-10-02

Christian Schulte, IMIT, KTH

65

## Reification for Disjunction

- Reify each precedence  
 $[start(a) + dur(a) \leq start(b)] \leftrightarrow b_0=1$   
 and  
 $[start(b) + dur(b) \leq start(a)] \leftrightarrow b_1=1$
- Model disjunction  
 $b_0 + b_1 \geq 1$

2003-10-02

Christian Schulte, IMIT, KTH

66

## Model Is Too Naïve

- Local view
  - individual task pairs
  - $O(n^2)$  propagators for  $n$  tasks
- Global view
  - all tasks on resource
  - single propagator
  - smarter algorithms possible

2003-10-02

Christian Schulte, IMIT, KTH

67

## Edge Finding

- Find ordering among tasks ("edges")
- For each subset of tasks  $\{a\} \cup B$ 
  - assume:  $a$  before  $B$ 
    - deduce information for  $a$  and  $B$
  - assume:  $B$  before  $a$ 
    - deduce information for  $a$  and  $B$
  - join computed information
  - can be done in  $O(n^2)$

2003-10-02

Christian Schulte, IMIT, KTH

68

## Summary

- Modeling
  - easy but not always efficient
  - constraint combinators (reification)
  - global constraints
  - smart heuristics
- More on constraint-based scheduling
  - Baptiste, Le Pape, Nuijten. Constraint-based Scheduling, Kluwer, 2001.

2003-10-02

Christian Schulte, IMIT, KTH

69

## Instruction Scheduling

## Instruction Scheduling

- Optimized object code by compiler
  - Minimum length instruction schedule
    - precedence
    - latency
    - resources
- per basic block


Best paper CP 2001, Peter van Beek and Kent Wilken, Fast Optimal Scheduling for Single-issue Processors with Arbitrary Latencies, 2001.

2003-10-02

Christian Schulte, IMIT, KTH

71







## Problem



2003-10-02

Christian Schulte, IMIT, KTH

72



## Model

- All issue times must be distinct
  - use single distinct constraint (as in SMM)
  - is resource constraint or unit duration
- Latency constraints
  - precedence constraints (as before)
  - difference: duration  $\rightleftharpoons$  latency

2003-10-02

Christian Schulte, IMIT, KTH

79

## Making It Work

- Only propagate bounds information
  - relevant for distinct
- Add redundant constraints
  - regions: additional structure in DAG
  - successor and predecessor constraints [special case of edge-finding]

2003-10-02

Christian Schulte, IMIT, KTH

80

## Results

- Tested with gcc
- SPEC95 FP
- Large basic blocks
  - up to 1000 instructions
- Optimally solved
  - less than 0.6% compile time increase
  - limited static improvement ( $< 0.1\%$ )
  - better dynamic impact (loops)
- Far better than ILP approach

2003-10-02

Christian Schulte, IMIT, KTH

81



2G1515

## Course Overview 2G1515

- As to be expected, no surprises:
  - applications
  - principles
  - pragmatics
  - limitations

2003-10-02

Christian Schulte, IMIT, KTH

83

## Organization

- 12 lectures
- Assignments (practical + principles)
- Exam
- Material
  - to be developed as we go...
  - with some textbook excerpts + research papers

2003-10-02

Christian Schulte, IMIT, KTH

84

## More Info

- Check my webpage frequently...

`www.imit.kth.se/~schulte/`