

Lab4 NAT

宁晨然 17307130178

一、实验目的

了解网络抓包中的信息。

二、实验过程

1. What is the IP address of the client?

Time	Source	Destination	Protocol	Length	Info
7 1.208040	192.168.1.100	74.125.91.113	HTTP	1035	POST /safebrowsing/
11 1.274062	74.125.91.113	192.168.1.100	HTTP	853	HTTP/1.1 200 OK (a

IP 地址是 192.168.1.100

2. The client actually communicates with several different Google servers in order to implement “safe browsing.” (See extra credit section at the end of this lab). The main Google server that will serve up the main Google web page has IP address 64.233.169.104. In order to display only those frames containing HTTP messages that are sent to/from this Google, server, enter the expression “http && ip.addr ==64.233.169.104” (without quotes) into the Filter: field in Wireshark .

http && ip.addr ==64.233.169.104					
No.	Time	Source	Destination	Protocol	Length Info
56	7.109267	192.168.1.100	64.233.169.104	HTTP	689 GET / HTTP/1.1
60	7.158797	64.233.169.104	192.168.1.100	HTTP	814 HTTP/1.1 200 OK (text/html)
62	7.281399	192.168.1.100	64.233.169.104	HTTP	719 GET /intl/en_ALL/images/logo.gif HTTP/1.1
73	7.349451	64.233.169.104	192.168.1.100	HTTP	226 HTTP/1.1 200 OK (GIF89a)
75	7.370185	192.168.1.100	64.233.169.104	HTTP	809 GET /extern_js/f/CgJlbhICdXMrMAo4NUAILCsw
92	7.448649	64.233.169.104	192.168.1.100	HTTP	648 HTTP/1.1 200 OK (text/javascript)
94	7.492324	192.168.1.100	64.233.169.104	HTTP	695 GET /extern_chrome/ee36edbd3c16a1c5.js HT
100	7.537353	64.233.169.104	192.168.1.100	HTTP	870 HTTP/1.1 200 OK (text/html)
107	7.652836	192.168.1.100	64.233.169.104	HTTP	712 GET /images/nav_logo7.png HTTP/1.1
112	7.682361	192.168.1.100	64.233.169.104	HTTP	806 GET /csi?v=3&s=webhp&action=&tran=undefin
119	7.685786	64.233.169.104	192.168.1.100	HTTP	1359 HTTP/1.1 200 OK (PNG)
122	7.709490	192.168.1.100	64.233.169.104	HTTP	670 GET /favicon.ico HTTP/1.1
124	7.737783	64.233.169.104	192.168.1.100	HTTP	269 HTTP/1.1 204 No Content
127	7.763501	64.233.169.104	192.168.1.100	HTTP	1204 HTTP/1.1 200 OK (image/x-icon)

3. Consider now the HTTP GET sent from the client to the Google server (whose IP address is IP address 64.233.169.104) at time 7.109267. What are the source and destination IP addresses and TCP source and destination ports on the IP datagram carrying this HTTP GET?

Time	Source	Destination	Protocol	Length	Info
56 7.109267	192.168.1.100	64.233.169.104	HTTP	689	GET / HTTP/1.1

IP source address = 192.178.1.100/ IP destination address = 64.233.169.104

Transmission Control Protocol, Src Port: 4335, Dst Port: 80, Seq: 1, Ack: 1, Len: 635
Source Port: 4335
Destination Port: 80

TCP source port = 4335 ; TCP destination port = 80

4. At what time is the corresponding 200 OK HTTP message received from the Google server? What are the source and destination IP addresses and TCP source and destination ports on the IP datagram carrying this HTTP 200 OK message?

60 7.158797	64.233.169.104	192.168.1.100	HTTP	814	HTTP/1.1 200 OK (text/html)
-------------	----------------	---------------	------	-----	-----------------------------

Transmission Control Protocol, Src Port: 80, Dst Port: 4335, Seq: 2861, Ack: 636, Len: 760

IP source = 64.233.169.104 ; destination = 192.168.1.100

TCP source port = 80 ; destination port = 4335

5. Recall that before a GET command can be sent to an HTTP server, TCP must first set up a connection using the three-way SYN/ACK handshake. At what time is the client-to-server TCP SYN segment sent that sets up the connection used by the GET sent at time 7.109267? What are the source and destination IP addresses and source and destination ports for the TCP SYN segment? What are the source and destination IP addresses and source and destination ports of the ACK sent in response to the SYN. At what time is this ACK received at the client? (Note: to find these segments you will need to clear the Filter expression you entered above in step 2. If you enter the filter “tcp”, only TCP segments will be displayed by Wireshark).

53	7.075657	192.168.1.100	64.233.169.104	TCP	66	4335 → 80 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=4 SACK_PERM=1
54	7.108986	64.233.169.104	192.168.1.100	TCP	66	80 → 4335 [SYN, ACK] Seq=0 Ack=1 Win=5720 Len=0 MSS=1430 SACK_PERM=1 WS=64
55	7.109053	192.168.1.100	64.233.169.104	TCP	54	4335 → 80 [ACK] Seq=1 Ack=1 Win=260176 Len=0
56	7.109267	192.168.1.100	64.233.169.104	HTTP	689	GET / HTTP/1.1

三次握手如上图，第一次客户-服务器的 SYN 段信息在 7.075657 时间发送的。

IP source address = 192.168.1.100 ; destination = 64.233.169.104

ACK: IP source = 64.233.169.104 ; destination = 192.168.1.100; 时间 7.108986

6. In the NAT_ISP_side trace file, find the HTTP GET message was sent from the client to the Google server at time 7.109267 (where t=7.109267 is time at which this was sent as recorded in the NAT_home_side trace file). At what time does this message appear in the NAT_ISP_side trace file? What are the source and destination IP addresses and TCP source and destination ports on the IP datagram carrying this HTTP GET (as recording in the NAT_ISP_side trace file)? Which of these fields are the same, and which are different, than in your answer to question 3 above?

http && ip.addr ==64.233.169.104						
No.	Time	Source	Destination	Protocol	Length	Info
85	6.069168	71.192.34.104	64.233.169.104	HTTP	689	GET / HTTP/1.1
Transmission Control Protocol, Src Port: 4335, Dst Port: 80, Seq: 1, Ack: 1, Len: 635						
Source Port: 4335						
Destination Port: 80						

time = 6.069168; destination IP = 64.233.169.104 ; source IP = 71.192.34.104

TCP source port = 4335; destination port = 80

时间不同，源地址和目标地址不同，TCP 端口相同。

7. Are any fields in the HTTP GET message changed? Which of the following fields in the IP datagram carrying the HTTP GET are changed: Version, Header Length , Flags , Checksum . If any of these fields have changed, give a reason (in one sentence) stating why this field needed to change.

Internet Protocol Version 4, Src: 71.192.34.104, Dst: 64.233.169.104	Internet Protocol Version 4, Src: 192.168.1.100, Dst: 64.233.169.104
0100 = Version: 4	0100 = Version: 4
.... 0101 = Header Length: 20 bytes (5) 0101 = Header Length: 20 bytes (5)
> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)	> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 675	Total Length: 675
Identification: 0xa2ac (41644)	Identification: 0xa2ac (41644)
> Flags: 0x4000, Don't fragment	> Flags: 0x4000, Don't fragment
Time to live: 127	Time to live: 128
Protocol: TCP (6)	Protocol: TCP (6)
Header checksum: 0x022f [validation disabled]	Header checksum: 0xa94a [validation disabled]
[Header checksum status: Unverified]	[Header checksum status: Unverified]
Source: 71.192.34.104	Source: 192.168.1.100
Destination: 64.233.169.104	Destination: 64.233.169.104

左图是 ISPside，右图是 homeside。对比发现，除了上一题中提到的 ip src/dst 变化外，time tolive 变化，header checksum 变化。因为 header checksum 是 ip 头部的校验位，所以头部信息变化自然 checksum 也会变化。

8. In the NAT_ISP_side trace file, at what time is the first 200 OK HTTP message received from the Google server?. What are the source and destination IP addresses and TCP source and destination ports on the IP datagram carrying this HTTP 200 OK message? Which of these fields are the same, and which are different than your answer to question 4 above?

90	6.117570	64.233.169.104	71.192.34.104	HTTP	814 HTTP/1.1 200 OK (text/html)
Transmission Control Protocol, Src Port: 80, Dst Port: 4335, Seq: 2861, Ack: 636, Len: 760					
Source Port: 80					
Destination Port: 4335					

time = 6.117570

ip source = 64.233.169.104 ; dst = 71.192.34.104

TCP source port = 80; dst port = 4335

time 和目的 ip 地址不同。

9. In the NAT_ISP_side trace file, at what time were the client-to-server TCP SYN segment and the server-to-client TCP ACK segment corresponding to the segments in question 5 above captured? What are the source and destination IP addresses and source and destination ports for these two segments? Which of these fields are the same, and which are different than your answer to question 5 above?

82	6.035475	71.192.34.104	64.233.169.104	TCP	66 4335 → 80 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=4 SACK_PERM=1
83	6.067775	64.233.169.104	71.192.34.104	TCP	66 80 → 4335 [SYN, ACK] Seq=0 Ack=1 Win=5720 Len=0 MSS=1430 SACK_PERM=1 WS=64
84	6.068754	71.192.34.104	64.233.169.104	TCP	60 4335 → 80 [ACK] Seq=1 Ack=1 Win=260176 Len=0
85	6.069168	71.192.34.104	64.233.169.104	HTTP	689 GET / HTTP/1.1

client-to-server TCP SYN time = 6.035475; server-to-client TCP ACK time = 6.067775

source ip = 71.192.34.104 -> dst = 64.233.169.104; 第二个反过来

发送 TCP 的源地址 ip 不同，其他都相同。