

# Statistical mechanical models for stabiliser codes subject to correlated noise

Joint work with Steve Flammia (USyd/Yale)  
Christopher Chubb

Centre for Engineered Quantum Systems  
University of Sydney

TQC 2018

`christopher.chubb@sydney.edu.au`

`christopherchubb.com`



THE UNIVERSITY OF  
SYDNEY



EQUIS

# Quantum error correction

Two important questions about quantum codes:

- How do I decode?
- What is the threshold?

The statistical mechanical mapping allows us to address both questions for stabiliser codes subject to Pauli noise.

# Quantum error correction

Two important questions about quantum codes:

- How do I decode **optimally**?
- What is the threshold?

The statistical mechanical mapping allows us to address both questions for stabiliser codes subject to Pauli noise.

# Quantum error correction

Two important questions about quantum codes:

- How do I decode optimally?
- What is the **fault-tolerant** threshold?

The statistical mechanical mapping allows us to address both questions for stabiliser codes subject to Pauli noise.

# Quantum error correction

Two important questions about quantum codes:

- How do I decode optimally?
- What is the fault-tolerant threshold?

The statistical mechanical mapping allows us to address both questions for stabiliser codes subject to Pauli noise.

# Statistical mechanical mapping

Stabiliser code  
& iid Pauli noise



Disordered statistical  
mechanical model

Error-correcting  
threshold



Quenched phase  
transition

Maximum likelihood  
decoding



Calculating partition  
functions/free energies

Allows us to reappropriate techniques for studying stat. mech. systems to study quantum codes.

# Statistical mechanical mapping

Stabiliser code & iid Pauli noise	$\longrightarrow$	Disordered statistical mechanical model
Error-correcting threshold	$\longleftrightarrow$	Quenched phase transition
Maximum likelihood decoding	$\longleftrightarrow$	Calculating partition functions/free energies

Allows us to reappropriate techniques for studying stat. mech. systems to study quantum codes.

# Statistical mechanical mapping

Stabiliser code & iid Pauli noise	$\longrightarrow$	Disordered statistical mechanical model
Error-correcting threshold	$\longleftrightarrow$	Quenched phase transition
Maximum likelihood decoding	$\longleftrightarrow$	Calculating partition functions/free energies

Allows us to reappropriate techniques for studying stat. mech. systems to study quantum codes.



# Our results

- Generalise mapping correlated noise for arbitrary codes
- Numerically show that mild correlations can lower the threshold of the toric code considerably
- Show how to apply our mapping to circuit noise via the history code
- Show that the stat. mech. mapping gives tensor network maximum likelihood decoders which generalise the MPS decoder of Bravyi, Suchara and Vargo

# Our results

- Generalise mapping correlated noise for arbitrary codes
- Numerically show that mild correlations can lower the threshold of the toric code considerably
- Show how to apply our mapping to circuit noise via the history code
- Show that the stat. mech. mapping gives tensor network maximum likelihood decoders which generalise the MPS decoder of Bravyi, Suchara and Vargo

# Our results

- Generalise mapping correlated noise for arbitrary codes
- Numerically show that mild correlations can lower the threshold of the toric code considerably
- Show how to apply our mapping to circuit noise via the history code
- Show that the stat. mech. mapping gives tensor network maximum likelihood decoders which generalise the MPS decoder of Bravyi, Suchara and Vargo

# Our results

- Generalise mapping correlated noise for arbitrary codes
- Numerically show that mild correlations can lower the threshold of the toric code considerably
- Show how to apply our mapping to circuit noise via the history code
- Show that the stat. mech. mapping gives tensor network maximum likelihood decoders which generalise the MPS decoder of Bravyi, Suchara and Vargo

# Independent case

Let  $\llbracket A, B \rrbracket$  be the scalar commutator of two Paulis,  $AB =: \llbracket A, B \rrbracket BA$ .

For a stabiliser code generated by  $\{S_k\}_k$ , and an error Pauli  $E$ ,

$$H_E(\vec{s}) := - \sum_i \sum_{\sigma \in \mathcal{P}_i} \overbrace{J_i(\sigma)}^{\text{Coupling Disorder}} \overbrace{\llbracket \sigma, E \rrbracket}^{\text{Disorder}} \overbrace{\prod_{k: \llbracket \sigma, S_k \rrbracket = -1} s_k}^{\text{DoF}}$$

for  $s_k \in \{\pm 1\}$ , and couplings  $J_i(\sigma) \rightarrow \mathbb{R}$ .

Take-aways:

- Ising-type, with interactions corresponding to single-site Paulis  $\sigma$
- Disorder  $E$  flips some interactions (Ferro  $\leftrightarrow$  Anti-ferro)
- Local code  $\implies$  local stat. mech. model
- Stat. mech. model has a symmetry:  $s_j \rightarrow -s_j$  and  $E \rightarrow ES_j$

# Independent case

Let  $\llbracket A, B \rrbracket$  be the scalar commutator of two Paulis,  $AB =: \llbracket A, B \rrbracket BA$ .

For a stabiliser code generated by  $\{S_k\}_k$ , and an error Pauli  $E$ ,

$$H_E(\vec{s}) := - \sum_i \sum_{\sigma \in \mathcal{P}_i} \overbrace{J_i(\sigma)}^{\text{Coupling}} \overbrace{\llbracket \sigma, E \rrbracket}^{\text{Disorder}} \overbrace{\prod_{k: \llbracket \sigma, S_k \rrbracket = -1} s_k}^{\text{DoF}}$$

for  $s_k \in \{\pm 1\}$ , and couplings  $J_i(\sigma) \rightarrow \mathbb{R}$ .

Take-aways:

- Ising-type, with interactions corresponding to single-site Paulis  $\sigma$
- Disorder  $E$  flips some interactions (Ferro  $\leftrightarrow$  Anti-ferro)
- Local code  $\implies$  local stat. mech. model
- Stat. mech. model has a symmetry:  $s_j \rightarrow -s_j$  and  $E \rightarrow ES_j$

# Independent case

Let  $\llbracket A, B \rrbracket$  be the scalar commutator of two Paulis,  $AB =: \llbracket A, B \rrbracket BA$ .

For a stabiliser code generated by  $\{S_k\}_k$ , and an error Pauli  $E$ ,

$$H_E(\vec{s}) := - \sum_i \sum_{\sigma \in \mathcal{P}_i} \overbrace{J_i(\sigma)}^{\text{Coupling}} \overbrace{\llbracket \sigma, E \rrbracket}^{\text{Disorder}} \overbrace{\prod_{k: \llbracket \sigma, S_k \rrbracket = -1} s_k}^{\text{DoF}}$$

for  $s_k \in \{\pm 1\}$ , and couplings  $J_i(\sigma) \rightarrow \mathbb{R}$ .

Take-aways:

- Ising-type, with interactions corresponding to single-site Paulis  $\sigma$
- Disorder  $E$  flips some interactions (Ferro  $\leftrightarrow$  Anti-ferro)
- Local code  $\implies$  local stat. mech. model
- Stat. mech. model has a symmetry:  $s_j \rightarrow -s_j$  and  $E \rightarrow ES_j$

# Independent case

Suppose we have an independent error model

$$\Pr(E) = \prod_i p_i(E_i).$$

Nishimori condition: 
$$\beta J_i(\sigma) = \frac{1}{4} \sum_{\tau \in \mathcal{P}} \log p_i(\tau) \llbracket \sigma, \tau \rrbracket,$$

Using the Fourier-like orthogonality relation  $\frac{1}{4} \sum_{\sigma} \llbracket \sigma, \tau \rrbracket = \delta_{\tau, I}$  we get that

$$e^{-\beta H_E(\vec{1})} = \Pr(E).$$

Together with the previous symmetry,

$$Z_E = \sum_{\vec{s}} e^{-\beta H_E(\vec{s})} = \sum_S e^{-\beta H_{ES}(\vec{1})} = \sum_S \Pr(ES) = \Pr(\bar{E}).$$



# Independent case

Suppose we have an independent error model

$$\Pr(E) = \prod_i p_i(E_i).$$

Nishimori condition: 
$$\beta J_i(\sigma) = \frac{1}{4} \sum_{\tau \in \mathcal{P}} \log p_i(\tau) \llbracket \sigma, \tau \rrbracket,$$

Using the Fourier-like orthogonality relation  $\frac{1}{4} \sum_{\sigma} \llbracket \sigma, \tau \rrbracket = \delta_{\tau, I}$  we get that

$$e^{-\beta H_E(\vec{I})} = \Pr(E).$$

Together with the previous symmetry,

$$Z_E = \sum_{\vec{s}} e^{-\beta H_E(\vec{s})} = \sum_S e^{-\beta H_{ES}(\vec{I})} = \sum_S \Pr(ES) = \Pr(\bar{E}).$$

# Error correction threshold as a quenched phase transition

Consider the free energy cost of a logical operator  $L$ ,

$$\Delta_E(L) = -\frac{1}{\beta} \log Z_{EL} + \frac{1}{\beta} \log Z_E = \frac{1}{\beta} \log \frac{\Pr(\bar{E})}{\Pr(\bar{EL})}.$$

For a fixed error  $E$

	Quantum code	Stat. mech. system
Below threshold	$\{\Pr(\bar{EL})\}_L$ peaked	$\Delta(L) \rightarrow \infty$ (in mean)
Above threshold	$\{\Pr(\bar{EL})\}_L$ flat	$\Delta(L) \rightarrow 0$ (in prob.)

# Error correction threshold as a quenched phase transition

Consider the free energy cost of a logical operator  $L$ ,

$$\Delta_E(L) = -\frac{1}{\beta} \log Z_{EL} + \frac{1}{\beta} \log Z_E = \frac{1}{\beta} \log \frac{\Pr(\bar{E})}{\Pr(\bar{EL})}.$$

For a fixed error  $E$

	Quantum code	Stat. mech. system
Below threshold	$\{\Pr(\bar{EL})\}_L$ peaked	$\Delta(L) \rightarrow \infty$ (in mean)
Above threshold	$\{\Pr(\bar{EL})\}_L$ flat	$\Delta(L) \rightarrow 0$ (in prob.)

# Error correction threshold as a quenched phase transition

Consider the free energy cost of a logical operator  $L$ ,

$$\Delta_E(L) = -\frac{1}{\beta} \log Z_{EL} + \frac{1}{\beta} \log Z_E = \frac{1}{\beta} \log \frac{\Pr(\bar{E})}{\Pr(\bar{EL})}.$$

For a fixed error  $E$

	Quantum code	Stat. mech. system
Below threshold	$\{\Pr(\bar{EL})\}_L$ peaked	$\Delta(L) \rightarrow \infty$ (in mean)
Above threshold	$\{\Pr(\bar{EL})\}_L$ flat	$\Delta(L) \rightarrow 0$ (in prob.)

# Error correction threshold as a quenched phase transition

Consider the free energy cost of a logical operator  $L$ ,

$$\Delta_E(L) = -\frac{1}{\beta} \log Z_{EL} + \frac{1}{\beta} \log Z_E = \frac{1}{\beta} \log \frac{\Pr(\bar{E})}{\Pr(\bar{EL})}.$$


For a fixed error  $E$

	Quantum code	Stat. mech. system
Below threshold	$\{\Pr(\bar{EL})\}_L$ peaked	$\Delta(L) \rightarrow \infty$ (in mean)
Above threshold	$\{\Pr(\bar{EL})\}_L$ flat	$\Delta(L) \rightarrow 0$ (in prob.)

# Independent examples


## Toric code

Bit-flip  $\rightarrow$  Random-bond Ising<sup>1</sup>  
Indep.  $X$  &  $Z \rightarrow 2 \times$  Random-bond Ising  
Depolarising  $\rightarrow$  Random 8-vertex model<sup>2</sup>



## Color code

Bit-flip  $\rightarrow$  Random 3-spin Ising  
Phase-flip  $\rightarrow$  Random 3-spin Ising  
Depolarising  $\rightarrow$  Random interacting 8-vertex<sup>2</sup>




<sup>1</sup>Dennis et.al., JMP 2002, doi:10/cs2mtf, arXiv:quant-ph/0110143

<sup>2</sup>Bombin et.al., PRX 2012, doi:10/crz5, arXiv:1202.1852

# Independent examples


## Toric code

Bit-flip  $\rightarrow$  Random-bond Ising<sup>1</sup>  
Indep.  $X$ & $Z$   $\rightarrow$   $2 \times$  Random-bond Ising  
Depolarising  $\rightarrow$  Random 8-vertex model<sup>2</sup>



## Color code

Bit-flip  $\rightarrow$  Random 3-spin Ising  
Phase-flip  $\rightarrow$  Random 3-spin Ising  
Depolarising  $\rightarrow$  Random interacting 8-vertex<sup>2</sup>




<sup>1</sup>Dennis et.al., JMP 2002, doi:10/cs2mtf, arXiv:quant-ph/0110143

<sup>2</sup>Bombin et.al., PRX 2012, doi:10/crz5, arXiv:1202.1852

# Independent examples


## Toric code

Bit-flip  $\rightarrow$  Random-bond Ising<sup>1</sup>  
Indep.  $X$  &  $Z \rightarrow 2 \times$  Random-bond Ising  
Depolarising  $\rightarrow$  Random 8-vertex model<sup>2</sup>



## Color code

Bit-flip  $\rightarrow$  Random 3-spin Ising  
Phase-flip  $\rightarrow$  Random 3-spin Ising  
Depolarising  $\rightarrow$  Random interacting 8-vertex<sup>2</sup>



<sup>1</sup>Dennis et.al., JMP 2002, doi:10/cs2mtf, arXiv:quant-ph/0110143


<sup>2</sup>Bombin et.al., PRX 2012, doi:10/crz5, arXiv:1202.1852



# Independent examples


## Toric code

Bit-flip  $\rightarrow$  Random-bond Ising<sup>1</sup>  
Indep. X&Z  $\rightarrow$  2 $\times$ Random-bond Ising  
Depolarising  $\rightarrow$  Random 8-vertex model<sup>2</sup>



## Color code

Bit-flip  $\rightarrow$  Random 3-spin Ising  
Phase-flip  $\rightarrow$  Random 3-spin Ising  
Depolarising  $\rightarrow$  Random interacting 8-vertex<sup>2</sup>



<sup>1</sup>Dennis et.al., JMP 2002, doi:10/cs2mtf, arXiv:quant-ph/0110143

<sup>2</sup>Bombin et.al., PRX 2012, doi:10/crz5, arXiv:1202.1852

# Correlated case

The key point independence gave us was the ability to factor our noise model

$$\Pr(E) = \prod_i p_i(E_i).$$

We can generalise this to correlated models:

## Factored distribution

An error model factors over regions  $\{R_j\}_j$  if there exist  $\phi_j : \mathcal{P}_{R_j} \rightarrow \mathbb{R}$  such that

$$\Pr(E) = \prod_j \phi_j(E_{R_j})$$

This model includes many probabilistic graphical models, such as Bayesian Networks and Markov Random Fields.

# Correlated case

The key point independence gave us was the ability to factor our noise model

$$\Pr(E) = \prod_i p_i(E_i).$$

We can generalise this to correlated models:

## Factored distribution

An error model factors over regions  $\{R_j\}_j$  if there exist  $\phi_j : \mathcal{P}_{R_j} \rightarrow \mathbb{R}$  such that

$$\Pr(E) = \prod_j \phi_j(E_{R_j})$$

This model includes many probabilistic graphical models, such as Bayesian Networks and Markov Random Fields.

# Correlated case

The construction works pretty much the same as before, changing  $\sigma \in \mathcal{P}_i$  to  $\sigma \in \mathcal{P}_{R_j}$ :

$$H_E(\vec{s}) := - \sum_j \sum_{\sigma \in \mathcal{P}_{R_j}} J_j(\sigma) \llbracket \sigma, E \rrbracket \prod_{k: \llbracket \sigma, S_k \rrbracket = -1} s_k$$

Nishimori condition: 
$$\beta J_j(\sigma) = \frac{1}{|\mathcal{P}_{R_j}|} \sum_{\tau \in \mathcal{P}_{R_j}} \log \phi_j(\tau) \llbracket \sigma, \tau \rrbracket,$$

As before we get that  $Z_E = \Pr(\bar{E})$ , and so the threshold manifests as a phase transition.

# Correlated case

The construction works pretty much the same as before, changing  $\sigma \in \mathcal{P}_i$  to  $\sigma \in \mathcal{P}_{R_j}$ :


$$H_E(\vec{s}) := - \sum_j \sum_{\sigma \in \mathcal{P}_{R_j}} J_j(\sigma) \llbracket \sigma, E \rrbracket \prod_{k: \llbracket \sigma, S_k \rrbracket = -1} s_k$$

Nishimori condition: 
$$\beta J_j(\sigma) = \frac{1}{|\mathcal{P}_{R_j}|} \sum_{\tau \in \mathcal{P}_{R_j}} \log \phi_j(\tau) \llbracket \sigma, \tau \rrbracket,$$

As before we get that  $Z_E = \Pr(\bar{E})$ , and so the threshold manifests as a phase transition.


# Correlated example

**Toric code with correlated bit-flips**  
Correlations induce longer-range interactions




# Correlated example

**Toric code with correlated bit-flips**  
Correlations induce longer-range interactions



# Correlated example


**Toric code with correlated bit-flips**  
Correlations induce longer-range interactions







# Correlated example

**Toric code with correlated bit-flips**  
Correlations induce longer-range interactions



# Monte Carlo simulations



## Thresholds

Indep.<sup>1</sup>:  $p_{th} = 10.94(2)\%$


Corr.:  $p_{th} = 10.04(6)\%$

<sup>1</sup>Dennis et.al., JMP 2002, doi:10/cs2mtf, arXiv:quant-ph/0110143

# Circuit noise


Noise followed by ideal measurements is unrealistic. In reality, circuits will be faulty.

Applying measurement circuits will tend to spread around and correlate noise:



# Circuit noise

We will consider measurement circuits of the form




where  $U$  is a Clifford and  $M$  is a Pauli.

For convenience we only consider independent noise on each circuit. We also will push noise through until after the unitary:




# Circuit noise

We will consider measurement circuits of the form




where  $U$  is a Clifford and  $M$  is a Pauli.


For convenience we only consider independent noise on each circuit. We also will push noise through until after the unitary:




# Circuit noise



# Circuit noise




# Circuit noise






# Circuit noise




# Circuit noise




$$\Pr(\text{Error history}) = \prod_i \Pr(\text{Error after meas. } i \mid \text{Error before meas. } i)$$

# Circuit noise




$$\Pr(\text{Error history}) = \prod_i \Pr(\text{Error after meas. } i \mid \text{Error before meas. } i)$$

# Circuit noise



$$\Pr(\text{Error history}) = \prod_i \Pr(\text{Error after meas. } i \mid \text{Error before meas. } i)$$


# History code



History code:

- Qubits placed at points in space-time (including ancillae)
  - Stabilizers correspond to measurements and stabilisers at final time
  - Logicals correspond to logicals at final time
- 
- Circuit noise on original code = Spatially correlated noise on history code
  - FT decoding of original code = Decoding the history code
  - FT threshold of original code = Threshold of history code

# History code



History code:

- Qubits placed at points in space-time (including ancillae)
- Stabilizers correspond to measurements and stabilisers at final time
- Logicals correspond to logicals at final time
- Circuit noise on original code = Spatially correlated noise on history code
- FT decoding of original code = Decoding the history code
- FT threshold of original code = Threshold of history code

# Conclusions and further work

- Extended the stat. mech. mapping to correlated models
- Can apply stat. mech. mapping to circuit noise via the history code
- Stat. mech. mapping gives tensor network maximum likelihood decoders
- Can we apply this to experimentally relevant correlated models?
- Can we use the decoders to understand to better understand the connection between correlation and the threshold (ongoing work).