

## 1 Introduction

This document provides an overall introduction to the DSP including system architecture, file organization, DSP-related toolchain, and so on. This document helps with the overall understanding of the DSP-related code. Currently, the DSP is used to decode and encode audio streams on the i.MX 8QXP, 8QuadMax, 8M Plus, and 8ULP platforms.

The current DSP framework can support several clients. They support these codecs:

Decoder:

- AAC-LC
- AAC plus(HE-AAC/HE-AACv2)
- BSAC
- DAB+
- MP2
- MP3
- DRM
- SBC
- OGG
- AMR-NB
- AMR-WB
- WMA
- WAV
- OPUS

Encoder:

- SBC

## 2 System Architecture

[Figure 1](#) and [Figure 2](#) provide the overall system architecture of the DSP-related code.

### Contents

1	Introduction.....	1
2	System Architecture.....	1
3	File Organization.....	5
4	Building DSP Framework on Linux OS.....	6
5	Building DSP Framework on Windows OS.....	10
6	Building DSP Wrapper and Unit Test .....	15
7	Usage of DSP Binary Files.....	16
8	Building Codec Wrapper and Codec Library.....	17
9	Revision History.....	18
A	Memory Allocation for DSP.....	19
B	NatureDSP Library Support.....	21
	Legal information.....	22







Figure 1. Software architecture for Cortex-A cores running Linux OS



**Figure 2. Software architecture for DSP processor**

The DSP-related code includes the DSP framework, DSP remoteproc driver, DSP wrapper, unit test, DSP codec wrapper, and DSP codec.

- The DSP framework is a firmware code which runs on the DSP core. The DSP driver is used to load the DSP firmware into the memory and transfer messages between the user space and the DSP framework.
- The remoteproc and RPMmsg framework is used to transfer messages between the Cortex-A cores and the DSP cores. The Message Unit (MU) is used to trigger interrupts between the Cortex-A cores and DSP cores when messages are placed into the vring buffer.

- The DSP wrapper and the unit test are the application code in the user space, which uses the `rpmsg_char` interface to transfer messages between the DSP remoteproc driver and the user space. In addition, the DSP wrapper is used to provide unified interfaces for the GStreamer.
- The DSP codec provides the actual decoding and encoding functions.
- The DSP codec wrapper is a wrapping code for the DSP codec and provides unified interfaces for the DSP framework.

## 2.1 Remote processor start

To start the firmware, use the following command.

```
Board $> echo start >/sys/class/remoteproc/remoteprocX/state
```

## 2.2 Remote processor stop

To stop the firmware, use the following command.

```
Board $> echo stop >/sys/class/remoteproc/remoteprocX/state
```

## 2.3 Resource table example

```
#define NUM_VRINGS 0x02

/* Place resource table in special ELF section */
__attribute__((section(".resource_table")))

const struct remote_resource_table resources = {
/* Version */
1,

/* Number of table entries */
NO_RESOURCE_ENTRIES,
/* reserved fields */
{
0,
0,
},

/* Offsets of rsc entries */
{
offsetof(struct remote_resource_table, user_vdev),
},

/* SRTM virtio device entry */
{
RSC_VDEV,
7,
0,
RSC_VDEV_FEATURE_NS,
0,
0,
0,
NUM_VRINGS,
{0, 0},
},

/* Vring rsc entry - part of vdev rsc entry */
```

```
{VDEV0_VRING_DA_BASE, VRING_ALIGN, RL_BUFFER_COUNT, 0, 0},  
{VDEV0_VRING_DA_BASE + VRING_SIZE, VRING_ALIGN, RL_BUFFER_COUNT, 1, 0},  
};
```

## 3 File Organization

The DSP framework, DSP wrapper, and unit test code are in the <https://github.com/NXP/imx-audio-framework> repository. Use the following command to clone the Git repository and check out the branch matching with the Linux release:

```
git clone https://github.com/NXP/imx-audio-framework.git --recursive
```

The DSP remoteproc driver code belongs to the Linux OS kernel.

DSP codecs originated from Cadence are license-restricted: A license authorization is required from NXP Marketing to access them in binary format.

### 3.1 DSP remoteproc driver

The driver is under the remoteproc framework. The remote processor (RPROC) framework allows the different platforms/architectures to control (power on, load firmware, power off) remote processors while abstracting the hardware differences. For more details, refer to the below link.

<https://www.kernel.org/doc/Documentation/remoteproc.txt>

The DSP remoteproc driver code is in the Linux OS kernel. It includes the following files:

- *drivers/remoteproc/imx\_dsp\_rproc.c*
- *drivers/rpmsg/rpmsg\_char.c*
- *drivers/rpmsg/rpmsg\_ctrl.c*
- *drivers/rpmsg/rpmsg\_ns.c*

### 3.2 DSP framework

The DSP framework code is in this folder:

- *imx-audio-framework/dsp\_framework*
- *imx-audio-framework/dsp\_framework/rpmsg-lite*

The rpmsg-lite code is copied from <https://github.com/NXPmicro/rpmsg-lite>.

### 3.3 DSP wrapper and unit test

The DSP wrapper and unit test are in these folders:

- *imx-audio-framework/dsp\_wrapper*
- *imx-audio-framework/unit\_test*

### 3.4 Interface header files

The DSP-related code includes these four interface header files:

- *imx-audio-framework/include/mxc\_dsp.h*
- *imx-audio-framework/dsp\_framework/plugins/audio\_codec/dsp\_codec\_interface.h*
- *imx-audio-framework/dsp\_wrapper/include/uni\_audio/fsl\_unia.h*
- *imx-audio-framework/dsp\_wrapper/include/uni\_audio/fsl\_types.h*

The *mx\_c\_dsp.h* file is the same as the header file in the Linux OS kernel. This file includes the interfaces and command definitions that are used by the DSP wrapper and unit test. The *dsp\_codec\_interface.h* file wraps the DSP codec's header files. It includes unified interfaces and command definitions which can be used by the DSP framework. The *fsl\_unia.h* and *fsl\_types.h* header files include the interfaces and command definitions which can be used by GStreamer.

## 4 Building DSP Framework on Linux OS

Before you compile the DSP-related code, set up the DSP-related toolchains. The DSP framework, DSP codec wrapper, and DSP codec use Xtensa development toolchain.

### 4.1 Installing Xtensa development toolchain

The Xtensa development toolchain consists of two components, which are installed separately in the Linux OS, including:

- Configuration-independent Xtensa Tool
- Configuration-specific core files and Xtensa Tool

The configuration-independent Xtensa Tool is released by Cadence. For the current code, the version of the tool is *XtensaTools\_RI\_2020\_4\_linux.tgz*, which is updated from *XtensaTools\_RF\_2016\_4\_linux.tgz*. The two versions are compatible. You can download this package from the Xtensa Explorer.

The configuration-specific core files and the Xtensa Tool are released by NXP. The following are the packages for each platform:

- i.MX 8QuadMax and i.MX 8QuadXPlus:

```
— hifi4_nxp_v4_3_1_prod_linux.tgz
```

```
— hifi4_nxp_v4_3_1_prod_win32.tgz
```

These packages can also be obtained from <https://tensilicatools.com/platform/imx8qm/> or <https://tensilicatools.com/platform/imx8qxp/>.

- i.MX 8M Plus:

```
— hifi4_mscale_v1_0_2_prod_linux.tgz
```

```
— hifi4_mscale_v1_0_2_prod_win32.tgz
```

These packages can also be obtained from <https://tensilicatools.com/platform/i-mx8mp/>.

- i.MX 8ULP:

```
— hifi4_nxp2_s7_v1_1a_prod_linux.tgz
```

```
— hifi4_nxp2_s7_v1_1a_prod_win32.tgz
```

When you have these two components, you can set up the toolchain as follows:

- Open the *imx-audio-framework* folder and execute these commands:

```
mkdir -p ./imx-audio-toolchain/Xtensa_Tool/tools mkdir -p ./imx-audio-toolchain/Xtensa_Tool/builds
```

- Set up the configuration-independent Xtensa Tool:

```
cd imx-audio-toolchain/Xtensa_Tool
tar zxvf XtensaTools_RI_2020_4_linux.tgz -C ./tools
```

- Set up the configuration-specific core files and the Xtensa Tool:

```
cd imx-audio-toolchain/Xtensa_Tool
tar zxvf hifi4_nxp_v4_3_1_prod_linux.tgz -C ./builds
```

- Install the Xtensa development toolchain:

```
cd imx-audio-toolchain/Xtensa_Tool
./builds/RI-2020.4-linux/hifi4_nxp_v4_3_1_prod/install --xtensa-tools ./tools/RI-2020.4-linux/XtensaTools --registry ./tools/RI-2020.4-linux/XtensaTools/config
```

- Set the PATH environment variable:

```
export PATH=./imx-audio-toolchain/Xtensa_Tool/tools/RI-2020.4-linux/XtensaTools/bin:$PATH
```

- Set the LM\_LICENSE\_FILE environment variable.

The Xtensa development tools use FLEXlm for license management. The FLEXlm licensing is required for tools such as the Xtensa Explorer, TIE Compiler, and Xtensa C and C++ compiler. If you want to use a floating license, install the FLEXlm license manager and set the LM\_LICENSE\_FILE environment variable. If there is any problem, you can find useful information in the *Xtensa Development Tools Installation Guide User's Guide.doc* document provided by Cadence.

After the above steps, the Xtensa development toolchain is set up successfully. In addition, the Xtensa Tools and additional tools are provided as 32-bit (x86) binaries. They are supported on 32-bit (x86) systems, and also on recent 64-bit (x86-64) systems that have appropriate 32-bit compatibility packages installed. If you use a 64-bit system (for example; Ubuntu 16.04), install the 32-bit compatibility packages first. Use these commands:

```
sudo apt-get install lib32ncurses5 lib32z1 sudo dpkg --add-architecture i386
```

```
sudo apt-get install libc6:i386 libstdc++6:i386
```

## 4.2 Building DSP framework

After installing the DSP-related toolchains on your Linux OS server, you can compile the DSP framework. Execute the “make” command in the *imx-audio-framework* folder to compile the DSP framework. This way also builds the DSP wrapper and unit test. If you want to compile the DSP framework separately, see the README file in the *imx-audio-framework* folder. After the compiling process, you can find the binary files in the *imx-audio-framework/release* folder.

For the DSP framework, different commands generate different frameworks for different platforms:

- *imx-audio-framework/release/hifi4\_imx8mqxp.bin*
- *imx-audio-framework/release/hifi4\_imx8mp.bin*
- *imx-audio-framework/release/hifi4\_imx8ulp.bin*

By default, the command generates the *hifi4\_imx8mqxp.bin* file. With the “PLATF=imx8m” attribute, it generates the *hifi4\_imx8mp.bin* file. With the “PLATF= imx8ulp” attribute, it generates the *hifi4\_imx8ulp* file. With the “DEBUG=1” attribute, it generates the firmware with the debug information. You can see the debug information using UART. For details, see [Section DSP DEBUG](#).

## 4.3 DSP DEBUG

Building the DSP framework with the extra “DEBUG=1” attribute, the DSP can print the debug information using the UART console. To enable this feature, do some changes in the kernel and in the DSP side. For a different platform, prepare a different board and different changes. The following sections describe what need to change for different platforms.

### 4.3.1 Enabling DSP debug on i.MX 8M Plus

Enable the UART for DSP print debug information in the i.MX 8M Plus board and add the UART clock in the DTS file and the UART module driver in the DSP.

1. Add the UART clock and pinctrl in the DTS.

Add the UART clock and pinctrl in the DSP node as follows:

```
&dsp {
compatible = "fsl,imx8mp-dsp-v1"; memory-region = <&dsp_reserved>; reg = <0x0 0x3B6E80000x0
0x88000>;
pinctrl-0 = <&pinctrl_uart4>;
clocks = <&audiomix_clk IMX8MP_CLK_AUDIOMIX_OCRAMA_IPG>,
...
...
<&audiomix_clk IMX8MP_CLK_AUDIOMIX_ASRC_IPG>,
<&clk IMX8MP_CLK_UART4_ROOT>,
<&clk IMX8MP_CLK_UART4_ROOT>;
clock-names =
"ocram", "audio_root", "audio_axi", "core", "debug", "mu2", "sdma_root", "sai_ipg",
"sai_mclk", "asrc_ipg", "uart_ipg", "uart_per";
...
fsl,dsp-firmware = "imx/dsp/hifi4.bin"; status = "okay";
};
```

Then generate the DTB file, replacing the old one.

## 2. Add the UART driver in the DSP.

By default, the DSP side already supports enabling the UART. Build the DSP firmware with the “DEBUG=1” attribute to generate the *hifi4\_imx8mp.bin* file, rename it to *hifi4.bin*, and copy it to the board.

## 3. Run the DSP and print the debug information.

Run one instance and the following debug information is printed on the fourth serial COM port:

```
DSP Start.....
core initialized
Response queue: write = 0x0 / read = 0x0 Command queue: write = 0x10001 / read = 0x0 ext_msg:
[client:0]:(80008004,4,1000) Response queue: write = 0x0 / read = 0x0 Command queue: write =
0x10001 / read
= 0x10001
alloc size out: 943feff8 4104 avail mem: 16773104 Response queue: write = 0x0 / read = 0x0
Response[client: 0]:(80048000,4,1000)
Command queue: write = 0x10001 / read = 0x10001 Response queue: write = 0x10001 / read = 0x10001
Command queue: write = 0x20002 / read = 0x10001 ext_msg: [client: 0]:(80008004,80000001,15)
Response
queue: write = 0x10001 / read = 0x10001
```

### 4.3.2 Enabling DSP DEBUG on i.MX QuadXPlus

To enable the DSP DEBUG on the i.MX QuadXPlus platform, you need only one base board, as shown in [Figure 3](#).






Figure 3. i.MX8-8X-BB

Connect the RS-232 to a PC and connect the base board to the i.MX QuadXPlus board.

1. Add the UART clock and pinctrl in the DTS.

Add the UART clock and pinctrl in the DSP node as follows:

```
dsp: dsp@596e8000 {
    compatible = "fsl,imx8qxp-dsp"; reg = <0x596e8000 0x88000>;
    clocks = ...
    <&uart2_lpcg 1>, <&uart2_lpcg 0>; clock-names = ... "uart_ipg", "uart_per";
    assigned-clocks = <&clk IMX_SC_R_UART_2 IMX_SC_PM_CLK_PER>; assigned-clock-rates = <80000000>;
    ...
    status = "disabled";
};
```

Then build the image instead of the old one.

2. Modify the DSP side.

The DSP supports the LPUART driver in the *dsp\_framework/arch/peripheral.c* file. Change the LPUART\_BASE from 0x5a090000 to 0x5a080000:

```
diff --git a/dsp_framework/arch/board.h b/dsp_framework/arch/board.h
index 9e04e64e821c..75a15fd09f0d 100644
--- a/dsp_framework/arch/board.h
```

```

+++ b/dsp_framework/arch/board.h

@@ -138,7 +138,7 @@ enum {

#define MUB_BASE (MU_PADDR)

#define SYSTEM_CLOCK (600000000UL)

-#define LPUART_BASE (0x5a090000)
+#define LPUART_BASE (0x5a080000)

#define UART_CLK_ROOT (80000000)

#endif /*PLATF_8ULP */

```

Then build the DSP with “DEBUG=1” and copy it to the board.

### 3. Run the DSP and print the debug information.

This part is the same as on the i.MX 8M Plus board. Select the proper serial COM port and you will see the debug information. The debug information cannot print on the i.MX 8QuadMax board, because the UART is taken.

## 5 Building DSP Framework on Windows OS

The DSP framework can be built also on Windows OS. The Xplorer software can be used to build the DSP framework on Windows OS. This chapter explains how to use Xplorer to build the DSP framework. First, install the Xtensa Xplorer IDE. You can download the Xplorer IDE and Xplorer license form Cadence.

### NOTE

Log into the XPG Cadence website to download installers for the Xplorer IDE, Xtensa tools, and so on. For NXP internal use, contact the DSP owner to get the NXP common XPG login credentials. The Xplorer 7.0.8 version is used as an example and its default installation folder is C:\usr\xtensa.

### 5.1 Adding new configuration packages

Currently, the *hifi4\_nxp\_v4\_3\_1\_prod\_win32.tgz* configuration package, which is updated from the *hifi4\_nxp\_v3\_3\_1\_prod\_win32.tgz* configuration package, is used to build the DSP framework on Windows OS. Add this configuration package into Xplorer before building the code. You can get this configuration package and the corresponding memory map linker files from NXP. The required files are as following:

- *hifi4\_nxp\_v4\_3\_1\_prod\_win32.tgz*
- *memmap/mainsim folder*

When you have the DSP configuration package, you can add a new configuration package into Xplorer as follows:

- Download and install Xtensa Tools for Xplorer.

If you do not have the Xtensa Tools, you shall download and install it using Xplorer. Currently, the Xtensa Tool that we use is *XtensaTools\_RI\_2020\_4\_win32.tgz*. You can first open the Xplorer software and click the “RI-2020.4” option in the “XPG View” panel and select the “tools->Xtensa Tools->Xtensa Tools 14.04 for Windows” option. After you select it, you can click the download button to start the downloading process.




Figure 4. "XPG View" panel

After the download finishes, right-click the "Xtensa Tools 14.04 for Windows" option and select the "Install Xtensa Tools..." option in the new dialog. The installing process takes some time.

The Xtensa Tool is installed successfully after this step. You can see this folder in the Xplorer's installing folder if everything is OK:

*C:\usr\xtensa\XtDevTools\install\tools\RI-2020.4-win32*

- Add the configuration package into Xplorer.

When you have the *hifi4\_nxp\_v4\_3\_1\_prod\_win32.tgz* package from NXP, you can add it into Xplorer. The first thing to do is to create a folder called *build* in Xplorer's installing path if the *build* folder is not created already. The total path after this operation is as follows:

*C:\usr\xtensa\XtDevTools\downloads\RI-2020.4\build*

- Place the *hifi4\_nxp\_v4\_3\_1\_prod\_win32.tgz* package into the new *build* folder.

*C:\usr\xtensa\XtDevTools\downloads\RI-2020.4\build\hifi4\_nxp\_v4\_3\_1\_prod\_win32.tgz*

- After you have performed the above steps, you can click the refresh button in the "XPG View" panel and find the "build" option in this panel.




Figure 5. The "build" option

- Right-click the *build->hifi4\_nxp\_v4\_3\_1\_prod\_win32.tgz* package and click the "Install Build..." option in the new dialog to start the installing process. This takes some time. You can see the following folder in the Xplorer's installing folder if everything is OK.

*C:\usr\xtensa\XtDevTools\install\builds\RI-2020.4-win32\hifi4\_nxp\_v4\_3\_1\_prod*

- Add the new memmap linker files into Xplorer.

After you add the *hifi4\_nxp\_v4\_3\_1\_prod\_win32.tgz* configuration package into Xplorer, you can add the new memmap linker files.

After you complete the above three steps, the new configuration package is successfully added into Xplorer.

## 5.2 Creating the DSP framework Xplorer project

The DSP framework project must be created before using Xplorer to build it. The DSP framework code is in the *imx-audio-framework* package:

- *imx-audio-framework\dsp\_framework*

You can create the DSP framework as follows:

- Open Xplorer and click the “File->New->Xtensa C/C++ project” option in the menu bar. You will see this dialog:




Figure 6. New Xtensa project

- Enter the project name and import DSP framework source code into the “New Xtensa C/C++ Project” dialog. Then click the “Finish” button.




Figure 7. The “Finish” button

After the above two steps, the DSP framework project is successfully created. You can see the project in [Figure 7](#).



Figure 8. DSP framework project

### 5.3 Building DSP framework

When you created the DSP framework project, you can build its code. Choose the *memmap* linker files before the building process.

- Right-click the name of the DSP framework project in the “Project Explorer” panel and choose the “Build Properties...” option. You will see the “Build Properties for dsp\_framework” dialog. The dialog is shown in [Figure 9](#).




Figure 9. "Build Properties" dialog

- Click the "Addl" compiler to add options. Add the "-DPLATF\_8M" attribute to build the firmware for i.MX 8M Plus. Add the "-DPLATF\_8ULP" attribute to build the firmware for i.MX 8ULP. Add the "-DDEBUG" attribute to build the firmware with the print debug information.
- Click the "Linker" option and configure the custom LSP path as shown in Figure 10. Click the "OK" button to finish this process.




Figure 10. "Linker" option

- When you configured the *memmap* linker files, you can choose the *dsp\_framework* project and the required DSP configuration to start the building process. The configuration is as follows:




Figure 11. Build process configuration

- Click the “Build Active->Build Active” option to start building the DSP framework. This takes some time.

#### NOTE

You must remove the file `rpmsg_queue.c` and directory porting in `rpmsg_lite` in project explorer window (not from disk); otherwise it reports error.

- After performing the above steps, you get the binary file called *dsp\_framework* (which is the firmware of the DSP) in the following folder.

`C:\usr\Xtensa\Xplorer-8.0.13-workspaces\workspace\dsp_framework\bin\hifi4_nxp_v4_3_1_prod\Debug\dsp_framework`

If you want to use this binary file to run on a real board, rename the *dsp\_framework* binary file as

*hifi4.bin* and place it to a right place of “rootfs”.

## 6 Building DSP Wrapper and Unit Test

Before you compile the DSP wrapper and the unit test, set up the related toolchain. The DSP wrapper and the unit test use the Linaro compiler toolchain for the Yocto platform.

### 6.1 Installing Linaro compiler toolchain

Currently, the Yocto toolchain is used to compile the DSP wrapper and the unit test's code for the Yocto platform. Use `source environment-setup-armv8a-poky-linux` to set up the yocto gcc toolchain. If you want to successfully build the code, you can get more information from the *Makefile* file of the DSP wrapper and the unit test.

### 6.2 Building the code

When the Linaro toolchain is successfully installed on your server, you can compile the DSP-related code. You can execute the “make” command in the *imx-audio-framework* folder to compile the DSP wrapper and the unit test. If you want to compile them separately, see the *README* file in the *imx-audio-framework* folder. After the compiling process, you can find the binary files in the *imx-audio-framework/release* folder.

For the DSP wrapper:

- imx-audio-framework/release/wrapper/lib\_dsp\_wrap\_arm\_elinux.so*

For the unit test:



- *imx-audio-framework/release/exe/dsp\_test*

## 7 Usage of DSP Binary Files

### 7.1 Getting DSP binary files

You can get the DSP binary files of the DSP framework, DSP wrapper, and unit test directly from NXP or compile the source code to produce them yourself. You can also obtain DSP codec binary files directly from NXP. DSP codecs originated from Cadence are license-restricted: A license authorization is required from NXP Marketing to access them.

The location for all prebuilt binaries not requiring any NXP Marketing authorization is on the Yocto mirror server.

### 7.2 Binary files in Linux OS rootfs

To run these binary files, place them into the Linux OS rootfs. The location of the DSP framework is determined by the DSP remoteproc driver, so you shall keep it in the specified place. The location of the DSP wrapper is determined by the GStreamer and you shall keep it in the specified place. You can change the location of the unit test. The binary files are in these folders:

- The unit test is here (default path):

*/unit\_tests/DSP/dsp\_test.out*

- The DSP framework is here:

*/lib/firmware/imx/dsp/hifi4.bin*

- The DSP wrapper is here:

*/usr/lib/imx-mm/audio-codec/wrap/lib\_dsp\_wrap\_arm\_elinux.so*

- You can keep the DSP codec wrapper and the DSP codec in these folders of the Linux OS rootfs (These libraries require authorization from NXP Marketing):

*/usr/lib/imx-mm/audio-codec/dsp/lib\_dsp\_codec\_wrap.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_dsp\_mp3\_dec.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_dsp\_aac\_dec.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_dsp\_bsac\_dec.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_dsp\_dabplus\_dec.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_dsp\_drm\_dec.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_dsp\_mp2\_dec.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_dsp\_sbc\_dec.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_dsp\_sbc\_enc.so*

- Add DSP NXP codec wrapper library (WMA10 library requires authorization from NXP Marketing, others are on the Yocto Mirror Server):

*/usr/lib/imx-mm/audio-codec/dsp/lib\_mp3d\_wrap\_dsp.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_aacd\_wrap\_dsp.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_vorbisd\_wrap\_dsp.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_wma10d\_wrap\_dsp.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_nbamrd\_wrap\_dsp.so*

*/usr/lib/imx-mm/audio-codec/dsp/lib\_wbamrd\_wrap\_dsp.so*



## 7.3 Unit test and playing

### 7.3.1 dsp\_test

After placing the binary files into the correct location of the rootfs, you can decode or encode audio streams directly using the unit test binary file. To decode one \*.mp3 file, use this command:

```
./dsp_test -f1 -dl6 -itest.mp3 -otest.pcm

dsp_test.out -f3 -r32 -t49 -dl6 -ithetest_48000ps_chbr32.nac -othetest_48000ps_chbr32.pcm dsp_test.out -f4
-il12-fl111.mp2 -ol2-fl111.pcm
```

For more information about the dsp\_test, use this command:

```
./dsp_test
```

To play one music file using the GStreamer and DSP wrapper, use this command:

```
gplay-1.0 test.mp3
```

The dsp\_test also supports compress playback. This feature is now usable on i.MX 8MP board, after this change the dtb filename is: imx8mp-evk-dsp.dtb, you can hear the sound by running the command:

```
./dsp_test -f1 -c33 -dl6 -isyz.mp3
```

## 8 Building Codec Wrapper and Codec Library

The library of the DSP codec wrapper and DSP codec is the loadable library. This chapter describes how to make the loadable library for the DSP.

The DSP loadable library is available as two different types: a fixed-location overlay and a position-independent library.

- For a fixed-location overlay, you can load the code into a predetermined location in the memory.
- For a position-independent library, you can load the code at an address determined during runtime.

You can link the loadable library using a special LSP named “pload” or “pisplitload” (see the *Xtensa Linker Support Packages (LSPs) Reference Manual*). The binary files that are used by the DSP framework belong to the position-independent library, so this chapter briefly discusses how to generate the position-independent library. For more detailed information, see Chapter 4 of the *Xtensa System Software Reference Manual*.

A position-independent library can be loaded and run at any address that supports both code and data, like a normal system RAM. Alternatively, you can use the “pisplitload” LSP to load the code and data into separate memory blocks located in local RAMs. The library location must be decided before the runtime.

The Xtensa development toolchain must be installed before making a loadable library. After that, you can follow the steps below.

### 8.1 Finding custom LSPs

The loadable libraries must be linked to a custom linker support package. For the position-independent libraries, you do not have to generate or edit an LSP. Instead, you must link your position-independent library using the standard “pisplitload” LSP that is provided as a part of your configuration.

### 8.2 Source code modifying and compiling

The API only allows the main program to directly access a single symbol in the library, the “\_start” symbol. The library cannot access any symbols in the main program directly. Any other symbol’s address must be passed to or from the library as an argument to the “\_start” function. This code is an example:

```
#include <stdio.h>

/* declare a printf function pointer */ int (*printf_ptr)(const char *format, ...);

/* replace all calls to printf with calls through the pointer */ #define printf printf_ptr
```

```

/* This is the function provided by the library */ char * interface_func(unsigned int input)
{
printf("executing function interface_func\n"); 13
return "this is string returned from interface_func";
}

void * _start(int (*printf_func)(const char *format, ...))
{
printf_ptr = printf_func;

/* The main application wants to call the function interface_func, but can't directly reference it.
Therefore, this function returns a pointer to it, and the main application will be able to call it via this
pointer. */

return interface_func;
}

```

The main application calls the “\_start” function, passes a pointer to “printf”, and takes a pointer to *interface\_func()* in return. If the library and the main program must communicate a value of more than one symbol, then the “\_start” function call can return arrays of pointers, rather than single pointers.

After finishing your source code, you can use “xt-xcc” of the Xtensa development toolchain to compile the code. Because the position-independent libraries can be loaded at any address, make sure that the code in the library is position-independent using the “-fpic” flag along with your normal compile options, as shown here:

```
xt-xcc -O3 -o library.o -c library.c
```

### 8.3 Linking the library code

In this step, link the library code into a loadable library using the appropriate LSP. For position-independent library, you can use this command:

```
xt-xcc -mlsp=plsplitload -Wl,--shared-pagesize=128 -Wl,-pie -lgcc -lc -o library.so library.o
```

After this command, you can get a position-independent library with the code and data loadable separately. If you want to get a contiguous position-independent library, you can use this command.

```
xt-xcc -mlsp=piload -Wl,--shared-pagesize=128 -Wl,-pie -lgcc -lc -o library.so library.o
```

After the linking stage, you can get a loadable library which can be loaded by the DSP framework. The current DSP framework only supports loading the code and data sections separately.

## 9 Revision History

The following table provides the revision history for this document.

Table 1. Revision history

Revision number	Date	Substantive changes
0	06/2018	Initial release
1	01/2019	Added details about using the sound card feature that allows users to play mp3 files over ALSA compressed interface.

*Table continues on the next page...*

Table 1. Revision history (continued)

Revision number	Date	Substantive changes
2	05/2020	Updated sections <a href="#">Introduction</a> , <a href="#">Building DSP framework</a> , and <a href="#">Binary files in Linux OS rootfs</a> .
3	09/2020	Added support for the i.MX8 MP board. Added support for *.wav files playback by the ALSA compressed interface. Added details about DSP framework building.
4	01/2021	Updated the version of the toolchain. Added details about the firmware generation and the LPA.
5	09/2021	<ul style="list-style-type: none"> <li>• Added 8ulp support</li> <li>• Removed the cplay and LPA support</li> <li>• Added <a href="#">Remote processor start</a>, <a href="#">Remote processor stop</a>, and <a href="#">Resource table example</a></li> <li>• Updated <a href="#">System Architecture</a>, <a href="#">DSP framework</a>, <a href="#">DSP remoteproc driver</a>, <a href="#">Enabling DSP debug on i.MX 8M Plus</a>, <a href="#">Enabling DSP DEBUG on i.MX QuadXPlus</a>, and <a href="#">Memory Allocation for DSP</a></li> <li>• Updated <a href="#">Figure 1</a></li> <li>• Added <a href="#">Figure 2</a></li> <li>• Changed "DSP driver" to "DSP remoteproc driver" in <a href="#">File Organization</a></li> </ul>
6	11/2021	<ul style="list-style-type: none"> <li>• Added OPUS decoder in <a href="#">Introduction</a></li> <li>• Updated <a href="#">Figure 10</a></li> <li>• Added note in <a href="#">Building DSP framework</a></li> <li>• Added compress playback feature for i.MX 8MP board in <a href="#">dsp_test</a></li> <li>• Removed the path of configurable memory map file from <a href="#">Installing Xtensa development toolchain</a></li> </ul>
LF5.10.72_2.2.0	12/2021	This document is published with the Linux software document package from this release.
LF5.15.5_1.0.0	03/2022	Updated the Section "File organization" and added Appendix B.
LF5.15.32_2.0.0	06/2022	Upgraded to the 5.15.32 kernel, U-Boot 2022.04, and Kirkstone Yocto

## A Memory Allocation for DSP

The DSP firmware is loaded into the memory by the DSP remoteproc driver. The loading address is defined by the memory map linker files of the Xtensa development toolchain. You may change the loading address based on the memory map list of i.MX 8QuadXPlus, as shown in [Table 2](#).

**Table 2. Memory allocation on i.MX8 QXP**

Cortex-A35/Cortex-M4	DSP	Content
—	0x80000000 - 0x806FFFFF	Reserved (cannot be used)
0x59700000 - 0x5971FFFF	0x80700000 - 0x8071FFFF	DSP OCRAM-system RAM
0x59720000 - 0x5973FFFF	0x80720000 - 0x8073FFFF	DSP OCRAM-system ROM
—	0x80740000 - 0x80FFFFFF	Reserved (cannot be used)
0x80700000 - 0x8073FFFF	—	Linux OS kernel (not visible from DSP)
0x81000000 - 0x9FFFFFFF	0x81000000 - 0x9FFFFFFF	SDRAM

Currently, the Linux OS kernel reserves the memory for the DSP in the SDRAM separately. The range of the reserved memory is 0x92400000 ~ 0x943ffff (32 MB). You may set this reserved memory by changing the *imx8x-mek.dtsi* file in the *linux-kernel/arch/arm64/boot/dts/freescale* folder.

```

reserved-memory {
    .....
    dsp_reserved: dsp@92400000 {
        reg = <0 0x92400000 0 0x1000000>;
        no-map;
    };
    dsp_reserved_heap: dsp_reserved_heap {
        reg = <0 0x93400000 0 0xef0000>;
        no-map;
    };
    dsp_vdev0vring0: vdev0vring0@942f0000 {
        reg = <0 0x942f0000 0 0x8000>;
        no-map;
    };
    dsp_vdev0vring1: vdev0vring1@942f8000 {
        reg = <0 0x942f8000 0 0x8000>;
        no-map;
    };
    dsp_vdev0buffer: vdev0buffer@94300000 {
        compatible = "shared-dma-pool";
        reg = <0 0x94300000 0 0x100000>;
        no-map;
    };
    .....
}

```

The DSP remoteproc driver splits the current reserved memory into five parts. One part is used to store the DSP firmware and the other part is a scratch memory for the DSP framework. The detailed information about these five parts is shown in [Table 3](#).

**Table 3. Five memory parts**

0x92400000 - 0x933FFFFF	DSP firmware (16 MB)
0x93400000 - 0x942EFFFFF	Scratch memory (16 MB)
0x942F0000 - 0x942F7FFF	vdev0vring0

*Table continues on the next page...*

**Table 3. Five memory parts (continued)**

0x942F8000 - 0x942FFFFF	vdev0vring1
0x94300000 - 0x943FFFFF	vdev0buffer

**NOTE**

If you make changes in the memory map linker files of the Xtensadevelopment toolchain, make the related changes for the DSP remoteproc driver.

## B NatureDSP Library Support

NatureDSP Library is an extensive library, containing the most commonly used signal processing functions: FFT, FIR, vector, matrix, and common mathematics. API and programming guide is in [hifi4\\_library/doc/NatureDSP\\_Signal\\_Library\\_Reference\\_HiFi4.pdf](#), and performance data is in [hifi4\\_library/doc/NatureDSP\\_Signal\\_Library\\_Performance\\_HiFi4.pdf](#).

NatureDSP Library package is license restricted on the i.MX platform. License authorization is required from the NXP marketing for the users to access the source code.

NatureDSP Library supported on the i.MX platform uses the same architecture as DSP framework. It is a separate firmware.

**Firmware location:** rootfs: /lib/firmware/imx/dsp/ hifi4\_naturedsp.bin

**Unit test location:** rootfs: /unit\_tests/DSP/naturedsp\_test

**How to test:**

Find the remoteproc instance for DSP, because we may have other remoteproc for the Cortex-M core

```
root@imx8ulpevk:~# cat /sys/class/remoteproc/remoteproc1/name
imx-dsp-rproc
```

**Change the default firmware for DSP**

```
root@imx8ulpevk:~# echo imx/dsp/hifi4_naturedsp.bin > /sys/class/remoteproc/remoteproc1/firmware
```

**Run unit test:**

```
root@imx8ulpevk:~# /unit_tests/DSP/naturedsp_test -func
root@imx8ulpevk:~# /unit_tests/DSP/naturedsp_test -mips
```

# Legal information

## Definitions

**Draft** — A draft status on a document indicates that the content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included in a draft version of a document and shall have no liability for the consequences of use of such information.

## Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

**Terms and conditions of commercial sale** — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Suitability for use in non-automotive qualified products** — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

**Translations** — A non-English (translated) version of a document, including the legal information in that document, is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

**Security** — Customer understands that all NXP products may be subject to unidentified vulnerabilities or may support established security standards or specifications with known limitations. Customer is responsible for the design and operation of its applications and products throughout their lifecycles to reduce the effect of these vulnerabilities on customer's applications and products. Customer's responsibility also extends to other open and/or proprietary technologies supported by NXP products for use in customer's applications. NXP accepts no liability for any vulnerability. Customer should regularly check security updates from NXP and follow up appropriately.

Customer shall select products with security features that best meet rules, regulations, and standards of the intended application and make the ultimate design decisions regarding its products and is solely responsible for compliance with all legal, regulatory, and security related requirements concerning its products, regardless of any information or support that may be provided by NXP.

NXP has a Product Security Incident Response Team (PSIRT) (reachable at [PSIRT@nxp.com](mailto:PSIRT@nxp.com)) that manages the investigation, reporting, and solution release to security vulnerabilities of NXP products.

## Trademarks

Notice: All referenced brands, product names, service names, and trademarks are the property of their respective owners.

**NXP** — wordmark and logo are trademarks of NXP B.V.

**AMBA, Arm, Arm7, Arm7TDMI, Arm9, Arm11, Artisan, big.LITTLE, Cordio, CoreLink, CoreSight, Cortex, DesignStart, DynamIQ, Jazelle, Keil, Mali, Mbed, Mbed Enabled, NEON, POP, RealView, SecurCore, Socrates, Thumb, TrustZone, ULINK, ULINK2, ULINK-ME, ULINK-PLUS, ULINKpro, µVision, Versatile** — are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved.

**Airfast** — is a trademark of NXP B.V.

**Bluetooth** — the Bluetooth wordmark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by NXP Semiconductors is under license.

**Cadence** — the Cadence logo, and the other Cadence marks found at [www.cadence.com/go/trademarks](http://www.cadence.com/go/trademarks) are trademarks or registered trademarks of Cadence Design Systems, Inc. All rights reserved worldwide.

**CodeWarrior** — is a trademark of NXP B.V.

**ColdFire** — is a trademark of NXP B.V.

**ColdFire+** — is a trademark of NXP B.V.

**EdgeLock** — is a trademark of NXP B.V.

**EdgeScale** — is a trademark of NXP B.V.

**EdgeVerse** — is a trademark of NXP B.V.

**eIQ** — is a trademark of NXP B.V.

**FeliCa** — is a trademark of Sony Corporation.

**Freescale** — is a trademark of NXP B.V.

**HITAG** — is a trademark of NXP B.V.

**ICODE and I-CODE** — are trademarks of NXP B.V.

**Immersiv3D** — is a trademark of NXP B.V.

**I2C-bus** — logo is a trademark of NXP B.V.

**Kinetis** — is a trademark of NXP B.V.

**Layerscape** — is a trademark of NXP B.V.

**Mantis** — is a trademark of NXP B.V.

**MIFARE** — is a trademark of NXP B.V.

**NTAG** — is a trademark of NXP B.V.

**Processor Expert** — is a trademark of NXP B.V.

**QorIQ** — is a trademark of NXP B.V.

**SafeAssure** — is a trademark of NXP B.V.

**SafeAssure** — logo is a trademark of NXP B.V.

**Synopsys** — Portions Copyright © 2021 Synopsys, Inc. Used with permission. All rights reserved.

**Tower** — is a trademark of NXP B.V.

**UCODE** — is a trademark of NXP B.V.

**VortiQa** — is a trademark of NXP B.V.



---

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

---

© NXP B.V. 2018-2021.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

Date of release: 30 June 2022  
Document identifier: IMXDSPUG