Ex.No.6	Develop a customized ping command to test the server connectivity
DATE:	

6.1 Customized ping command to test the server connectivity

Aim:

To develop a customized ping command to test the server connectivity.

Algorithm for Program1: Customized ping command to test the server connectivity:

1. Start.
2. Import the `socket` and `time` modules.
3. Specify the server name, port number, and number of attempts.
4. Create a TCP socket.
5. Set the timeout period.
6. Record the start time.
7. Connect to the server.
8. Record the end time.
9. Calculate and display the response time.
10. If the connection fails, display "Request timed out".
11. Repeat Steps 4–10 for the specified number of attempts.
12. Stop.

PROGRAM 1:


Customized ping command to test the server connectivity:

```
import socket
import time
host = "google.com"
port = 80
count = 4
for i in range(count):
    try:
        # Create a socket
        s = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
        # Set timeout (optional)
        s.settimeout(3)
        # Record start time
        start = time.time()
        # Connect to the server
        s.connect((host, port))
      # Record end time
        end = time.time()
        # Close the socket
        s.close()
        print(f"Reply from {host}: time={(end - start) * 1000:.2f} ms")
    except Exception:
        print("Request timed out")
```

Sample Output:

Reply from google.com: time=18.52 ms
Reply from google.com: time=17.84 ms
Reply from google.com: time=19.03 ms
Reply from google.com: time=18.26 ms

OUTPUT



RESULT:

Thus, the customized ping command was executed successfully to test server connectivity, and the connectivity status was verified by receiving replies from the server.