



*Flying Operations*

**C-130H MAFFS OPERATIONS LOADMASTER CHECKLIST**

**COMPLIANCE WITH THIS PUBLICATION IS MANDATORY**

**ACCESSIBILITY:** Publications and forms are available for downloading or ordering on the e-Publishing website at [www.e-Publishing.af.mil](http://www.e-Publishing.af.mil)

**RELEASABILITY:** Military and U.S. Government

OPR: HQ AMC/A3V

Supersedes: AFI 11-2C-130V3 ADD B CL-2

Date: 1 August 2018

Number of Pages: 17

Certified by: HQ USAF/A3T

(Maj Gen Scott F. Smith)

This checklist establishes procedures for employing the Modular Airborne Fire Fighting System (MAFFS) on C-130 aircraft employed by Mobility Air Forces (MAF) to accomplish their worldwide mission. This checklist complements AFMAN 11-2C-130HV3, *Operations Procedures*, and is printed on standard 8 ½" x 11" bond paper, and trimmed to fit the standard plastic aircrew checklist binders. This checklist is intended to provide MAFFS certified crewmembers quick reference to procedures required for the safe execution of MAFFS ground and flight operations. All MAFFS certified C-130 loadmasters will carry this annex. Refer recommended changes and questions about this publication to the Office of Primary Responsibility (OPR) using the AF IMT 847, Recommendation for Change of Publication; route AF IMT 847s from the field through the appropriate chain of command.

**TABLE OF CONTENTS**

<b>Checklist</b>	<b>Page</b>
<b>PART ONE – NORMAL PROCEDURES.....</b>	<b>2</b>
<b>MAFFS PRE-FLIGHT CHECKLIST .....</b>	<b>3</b>
<b>ELECTRICAL PRE-FLIGHT CHECKLIST .....</b>	<b>4</b>
<b>MAFFS RETARDANT/WATER/FOAM SERVICING</b>	
<b>PROCEDURES.....</b>	<b>6</b>
<b>MAFFS GROUND AIR SERVICING PROCEDURES .....</b>	<b>7</b>
<b>MAFFS BEFORE TAKEOFF CHECKLIST .....</b>	<b>8</b>
<b>MAFFS AFTER TAKEOFF CHECKLIST .....</b>	<b>9</b>
<b>SLOWDOWN CHECKLIST.....</b>	<b>10</b>
<b>ONE MINUTE ADVISORY .....</b>	<b>10</b>
<b>RELEASE POINT CHECKLIST .....</b>	<b>11</b>
<b>COMPLETION OF DROP CHECKLIST .....</b>	<b>12</b>
<b>MAFFS WEIGHT TABLES.....</b>	<b>13</b>
<b>MAFFS BEFORE LANDING CHECKLIST.....</b>	<b>14</b>
<b>MAFFS AFTER LANDING CHECKLIST .....</b>	<b>14</b>
<b>RETARDANT DE-SERVICING PROCEDURES .....</b>	<b>14</b>
<b>SYSTEM DE-ARMING CHECKLIST .....</b>	<b>15</b>
<b>BEFORE LEAVING AIRPLANE .....</b>	<b>15</b>

## TABLE OF CONTENTS (Cont.)

<b>Checklist</b>	<b>Page</b>
<b>PART TWO – EMERGENCY PROCEDURES.....</b>	<b>16</b>
<b>EMERGENCY DROP.....</b>	<b>16</b>
<b>EMERGENCY SHUTDOWN .....</b>	<b>17</b>

## NOTE

**MAFFS CHECKLIST PROCEDURES:** Items on the MAFFS BEFORE TAKEOFF, AFTER TAKEOFF, BEFORE LANDING, and AFTER LANDING CHECKLISTS will be accomplished following completion of the normal checklist items from T.O. 1C-130(K)H-1CL-4. The CL-4 checklists will not be called complete for MAFFS missions until items of the MAFFS checklist are accomplished. The loadmaster will verbalize the setting of the Compressor Enable Switch and the pressure of the MAFFS hydraulic system (Before Takeoff) when calling the CL-4 checklist complete. As always, these checklists and instructions are not substitutes for sound judgment and special circumstances may require modifications of these procedures.

## WARNING

Ensure the Drop Control Pendant is not dropped or impacted, is readily available during critical phases of flight, and properly secured to minimize the likelihood of being dropped.

## **PART ONE – NORMAL PROCEDURES**

### **CAUTION**

Do not operate galley equipment when MAFFS equipment is in use. Operation of galley equipment during MAFFS compressor operations may exceed maximum generator loads

### **CAUTION**

Do not operate the MAFFS compressors if use of propeller de-icing is expected. Operation of the MAFFS compressors in icing conditions may exceed maximum generator loads. If icing conditions are anticipated, ensure Compressor Enable switch is in the OFF position. The loadmaster will obtain a verbal confirmation from the pilot prior to enabling compressors

### **MAFFS PRE-FLIGHT CHECKLIST**

1. Left & Right Hand Locks - Checked; Right Hand Locks Set to 4.0
2. Tie down Chains – Connected
3. Support Struts (4) – Connected
4. Foam Tank Manual Shutoff Valve (V29) – CLOSED (If foam tank is installed but not used)
5. High Pressure Tanks – Checked
6. MAFFS Hydraulic Quantities – Checked
7. MAFFS Hydraulic System – Depressurized
  - a. Slowly open Main hydraulic valve to vertical position
  - b. After depressurization, return Main valve to CLOSED position (horizontal)
8. Main System Accumulator – Pre-charge (1500 PSI +/- 100 PSI)
9. Emergency Accumulator – Pre-charge (1500 PSI +/- 100 PSI)
10. Main Tank Purge Valve – CLOSED
11. High Pressure Air Reservoir Purge Valve – CLOSED

**ELECTRICAL PRE-FLIGHT CHECKLIST**

1. AC and DC Power Hook Up (FWD Pallet) – Completed
2. Emergency Battery Cable Connected (FWD Pallet) - Completed
3. Circuit Breakers (FWD Pallet) - Checked IN
4. Energy Level Test Switch – Press – Battery OK Light “ON”
5. EMER STOP (FWD Pallet) – OUT
6. 28 VDC Power Switch (FWD Pallet) – ENABLE
7. Hydraulic Pump Switch (FWD Pallet) – ENABLE
8. Test Lamps Button (Cabin Control Box) – (PRESS TO TEST/CHECKED)
  - a. Power: ON
  - b. Armed: ON
  - c. Compressors Armed: ON
  - d. System fail: ON
  - e. Reservoir Pressure: ON
  - f. Tank Pressure: ON
  - g. E-Dump Electrical: ON
  - h. Hydraulic Pressure: ON
  - i. Nozzle Open: ON
  - j. Compressor Oil: 2 lights – ON
  - k. Compressor Hot: 2 lights – ON
  - l. Main Tank Quantity Indicator Lights – ON
  - m. Foam Tank Quantity Indicator Lights – ON
  - n. Foam Control Panel Lights (Armed/Inject) - ON
9. Lamp Test Button (Vent Valve Box) – (PRESS TO TEST/CHECKED)
  - a. Vent Valve Closed – ON
  - b. Vent Valve Open – ON

10. Air/Ground Mode Power Switch – AIR MODE

11. Arming Switch – ARM (As Required)

**CAUTION**

Prior to Arming the system ensure the Retardant Fill  
Line Handle is Closed

**NOTE**

If high pressure reservoirs are pressurized, pressure loss  
will occur during Arming/Disarming sequence

- a. Cabin Control Box Armed Light – ON
- b. Drop Control Assemblies Armed Lights – ON/FLASHING
- c. Nozzle Strobe Light – ON/FLASHING

12. Arming Switch – DISARM

**MAFFS RETARDANT/WATER/FOAM SERVICING  
PROCEDURES**

1. 28 VDC Power Switch (FWD Pallet) – ENABLE
2. Arming Switch – DISARM (Tank pressure should read zero)
3. Vent Valve – OPEN

**NOTE**

If NOZZLE OPEN light remains illuminated, place NOZZLE switch to CLOSE position after charging Hydraulic System. To charge Hydraulic System, follow the “CHARGING THE MAFFS SYSTEM USING EXTERNAL GROUND POWER” procedure

4. Nozzle Open Light – OFF

**CAUTION**

If electrical power fails during filling operations, shut off the retardant fill line handle immediately and determine the problem

**CAUTION**

Monitor tank quantity indicator while filling and shut off retardant fill line handle when desired quantity is reached

**DO NOT OVERFILL**

5. Retardant GROUND & SYSTEM Fill Line Handles – Open
6. Place Float Switch to Spare then back to Primary Position to check volume indicator – Verify filled to correct quantity
7. Retardant Fill Line Handle – Closed
8. Ground Nozzle – Disconnected and Cap On
9. Right Hand Fill Line – Retract and Secure
10. Vent valve – CLOSED
11. If a foam drop is planned, service foam system:
  - a. After foam tank filled, filler cap replaced – CHECK
  - b. Foam Tank Manual Shutoff Valve (V29) – OPEN
12. 28 VDC Power Switch (FWD Pallet) – DISABLE (As required)

**MAFFS GROUND AIR SERVICING PROCEDURES**

**CHARGING THE MAFFS SYSTEM USING EXTERNAL HIGH PRESSURE COMPRESSOR**

1. High Pressure line – Connect to fill port
2. Monitor High Pressure Reservoir Gauge and charge system to 1150 - 1200 PSI
3. High Pressure line – Disconnect from fill port

**CHARGING THE MAFFS SYSTEM USING EXTERNAL GROUND POWER**

1. Compressor Enable Switch – OFF
2. Connect AC and DC cables to Ground Electrical Connectors, J104 & J105
3. 28 VDC Power Switch (FWD Pallet) – ENABLED
4. Hydraulic Pump Switch (FWD Pallet) – ENABLED
5. Power Switch – GROUND MODE
6. Compressor Enable Switch – ON

**NOTE**

Compressor will automatically shut off at 1150 - 1200 PSI

7. Compressor Enable Switch – OFF
8. Hydraulic Pump Switch (FWD Pallet) – DISABLE
9. 28 VDC Power Switch (FWD Pallet) – DISABLE (As required)
10. Disconnect AC and DC cables from Ground Electrical Connectors

**MAFES BEFORE TAKEOFF CHECKLIST**

1. Paratroop Door Plug Latches – Locked
2. Power Switch – AIR MODE
3. Compressor Enable Switch – OFF
4. Circuit Breakers (FWD Pallet) – Checked IN
5. 28 VDC Power Switch (FWD Pallet) – ENABLE

**WARNING**

Emergency Hydraulic system must be pressurized to accomplish an emergency drop

6. Hydraulic Pump Switch (FWD Pallet) – ENABLE (Only after all 4 engines are at normal ground idle.)

**NOTE**

If normal/emergency pressure is between 1900 and 2500 PSI, depressurization is required before pressurizing main tank because of system logic. Depressurize by slowly opening only the Main hydraulic valve to vertical position. After depressurization, return valve to CLOSED (horizontal) position

7. Normal/Emergency Hydraulic System – Pressurized (2500 – 2900 PSI)
8. Vent Valve Switch – CLOSED
9. Compressor Enable Switch – “**SET**” (State setting) (LM)

**NOTE**

If Compressor does not start, turn Compressor Enable Switch to “OFF”. After verifying that Hydraulic System is pressurized (2500 – 2900 PSI), turn Compressor Enable Switch to “ON”

10. Drop Selection Switch – SET to Coverage Level 8/ALL
11. Seat belt and shoulder harness – Fastened, unlocked
12. Seat Position – As Required



**MAFFS AFTER TAKEOFF CHECKLIST**

**WARNING**

Do not depressurize/cycle emergency accumulator system IN FLIGHT or EMERGENCY DUMP capability may be lost

**NOTE**

If Compressor does not come on and tank pressure is above 600 PSI, you must press Compressor Start buttons on FWD pallet within 45 seconds of placing the Compressor Enable Switch to "ON." Once compressors are running, set both Compressor Start Switches to the extended (disabled) position

1. Compressor Enable Switch – **"SET"** (State setting) (LM)
2. Compressor Armed Light – Verify ON (As required)

**PRE-SLOWDOWN CHECKLIST**

1. **"ACKNOWLEDGED"** (LM)
2. Helmets – ON (As required)
3. Left and Right Hand Locks – Checked
4. Tie Down Chains – Checked
5. Support Struts (4) – Checked
6. PRE-SLOWDOWN CHECKS **"COMPLETE"** (LM, E)

### **SLOWDOWN CHECKLIST**

1. **“ACKNOWLEDGED”** (LM)
2. Compressor Enable Switch – **“OFF”** (LM)
3. Arming Switch – ARM (Pistol Grip Armed Light Illuminated)
4. Drop Selection Switch – **“SET”** (state setting) (LM)

#### **NOTE**

If a foam drop is planned the following steps must also be accomplished

- a. Foam Switch – ON
  - b. Foam Tank Armed Light – ON
  - c. Foam Tank Pressure – 125 PSI +/- 15 PSI
  - d. Foam Mix – **“SET”** (state setting) (LM)
5. System Status – **“ARMED”** (LM)

#### **NOTE**

The Armed light on the drop control assembly will flash when the arming cycle is initiated. The light will be on and steady when the system is fully armed. The system takes approximately 30 seconds to complete the arming cycle.

6. SLOWDOWN CHECKS – **“COMPLETE”** (LM, E)

### **ONE MINUTE ADVISORY**

1. **“ACKNOWLEDGED, ARMED,** Coverage level/quantity – **“SET”** (State setting) (LM)
2. Seat belt and shoulder harness – Fastened, unlocked
3. SEAT POSITION - As Required

## **RELEASE POINT CHECKLIST**

1. Status of Load – **“LOAD CLEAR”** (Or condition) (LM)

### **NOTE**

If multiple drops are planned in the immediate area, crews may re-accomplish checklists starting with the ONE MINUTE ADVISORY. If multiple drops are accomplished outside the immediate area but the system remains armed, re-accomplish checklists starting with the SLOWDOWN CHECKLIST. If the system is de-armed, re-accomplish checklists beginning with the AFTER TAKOFF (LM), and PRE-SLOWDOWN, (Cockpit Crew) checklists

### **NOTE**

For multiple drop sorties, drops may be accomplished with the reservoir pressure light and main tank pressure light on the cabin control unit illuminated, provided adequate pressure is indicated in the main tank. If adequate pressure is not indicated, disarm the system, charge the high pressure tanks and proceed with the SLOWDOWN checklist

## **COMPLETION OF DROP CHECKLIST**

### **NOTE**

If multiple drops are not planned, the Copilot's "Flaps" call on the Release Point Checklist initiates the Completion of Drop Checklist

1. Arming Switch – DISARM (Only after the last drop)
2. Foam Switch – OFF (As required after last drop)

### **NOTE**

If NOZZLE OPEN light remains illuminated, close NOZZLE switch

3. Compressor Enable Switch – **"SET"** (State setting) (LM)

### **NOTE**

If Compressor does not come on and tank pressure is above 600 PSI, you must press Compressor Start buttons on FWD pallet within 45 seconds of placing the Compressor Enable Switch to "ON." Once compressors are running, set both Compressor Start Switches to the extended (disabled) position

4. DROP CHECKS – **"COMPLETE"** (LM, E)

**MAFFS WEIGHT TABLES**

<b>MAFFS Weight Chart</b> (thousands of pounds)				
<b>Quantity</b>	<b>Retardant</b>	<b>Retardant (Foam Tank Removed)</b>	<b>Water and Foam</b>	<b>Water Only</b>
<b>Empty</b>	<b>15.1</b>	<b>14.8</b>	<b>15.1</b>	<b>15.1</b>
<b>1/6</b>	<b>19.6</b>	<b>19.3</b>	<b>19.5</b>	<b>19.3</b>
<b>1/3</b>	<b>24.1</b>	<b>23.8</b>	<b>23.9</b>	<b>23.4</b>
<b>1/2</b>	<b>28.6</b>	<b>28.3</b>	<b>28.2</b>	<b>27.6</b>
<b>2/3</b>	<b>33.1</b>	<b>32.8</b>	<b>32.6</b>	<b>31.7</b>
<b>5/6</b>	<b>37.6</b>	<b>37.3</b>	<b>37.0</b>	<b>35.9</b>
<b>FULL</b>	<b>42.1</b>	<b>41.8</b>	<b>41.4</b>	<b>40.0</b>
<b>NO WATER, FULL FOAM TANK</b>			<b>16.5</b>	

<b>Fluid Weights</b> (pounds per gallon)		
<b>Retardant (typical)</b>	<b>Water</b>	<b>Foam</b>
<b>9.0</b>	<b>8.3</b>	<b>8.5</b>

<b>System Capacity</b> (gallons)	
<b>Main Tank</b>	<b>Foam Tank</b>
<b>3000</b>	<b>160</b>

**NOTE**

Weights provided above are rounded estimates for planning purposes and actual weights must be verified. Actual weight of a MAFFS II unit can be found in the weight and balance section of the maintenance documentation specific to each unit

### **MAFFS BEFORE LANDING CHECKLIST**

1. Compressor Enable Switch – “**SET**” (State setting) (LM)
2. Vent Valve – CLOSED (If landing with water/retardant in tank)

### **WARNING**

Prior to an emergency landing, if conditions permit, depressurize high pressure tanks 1 and 2 to reduce risks associated with pressure vessel breach during impact. Opening the high pressure jettison valve (V10) will depressurize both tanks

3. Seat belt and shoulder harness – Fastened, unlocked
4. Seat Position – As Required

### **MAFFS AFTER LANDING CHECKLIST**

1. 28 VDC Power Switch (FWD Pallet) – DISABLED (As required)
2. Main Hydraulic System Pressure – Depressurized (As required)

### **RETARDANT DE-SERVICING PROCEDURES**

### **NOTE**

Use the following procedures to transfer the retardant from the tank into the ground storage tank

1. Right Retardant Fill Line Cap – REMOVED
2. 28 VDC Power Switch (FWD Pallet) – ENABLE
3. Vent Valve – OPEN
4. Retardant Fill Line Handle – OPEN
5. Tank Quantity – EMPTY
6. Retardant Fill Line Handle – CLOSED
7. Ground Fill Line – DISCONNECTED
8. Retardant Fill Line Cap – ON

**SYSTEM DE-ARMING CHECKLIST**

**NOTE**

After the system has been armed, use the following checklist prior to landing

1. Arming Switch – DISARM (hold until the Arming light goes out)
2. Tank Pressure – Zero PSI and Main Tank Pressure light goes out
3. Vent Valve – CLOSED
4. System De-Arming Checklist - COMPLETE (LM)

**BEFORE LEAVING AIRPLANE**

1. Compressor Enable Switch – OFF
2. Hydraulic Pump Switch (FWD Pallet) – DISABLE
3. 28 VDC Power Switch (FWD Pallet) – DISABLE
4. Emergency battery circuit breaker (CB1 on battery, FWD Pallet) – PULLED (Last flight of the day or as required)
5. Main Tank Purge Valve – OPEN
6. High Pressure Air Reservoir Purge Valve – As required
7. Main Hydraulic System Pressure – Depressurized
8. Emergency Hydraulic System – Depressurized
9. Before Leaving Airplane Checklist – COMPLETE

## **PART TWO – EMERGENCY PROCEDURES**

### **EMERGENCY DROP**

1. Emergency Drop – **“CLEARED TO DROP”** (P)
2. Emergency Drop Switch – Lift Guard and Toggle (LM, CP)

### **WARNING**

If nozzle fails to open after both the pilot and loadmaster select E-Dump, ensure the system is not in an armed state and move the NOZZLE switch on the cabin control unit to OPEN. If the system is in the armed state the NOZZLE switch on the cabin control unit will not actuate the nozzle position

3. Status of Load – **“LOAD CLEAR”** (Or condition) (LM)
4. Nozzle – CLOSED

### **NOTE**

The nozzle can only be closed by placing the NOZZLE switch to the CLOSE position. This function is not available for 90 seconds after the pintle is retracted

5. EMERGENCY DROP CHECKS – **“COMPLETE”** (LM, CP)



## **EMERGENCY SHUTDOWN**

To stop both compressors and all hydraulic pumps from the MAFFS loadmaster station:

1. Power Switch – GROUND MODE (LM)
2. EMER STOP (FWD Pallet) – IN (E/LM)
3. 28 VDC Power Switch (FWD Pallet) – DISABLE (E/LM)

If conditions dictate complete removal of power to the MAFFS unit:

4. Generators 1, 3, and 4 – **“OFF”** (E)
5. 6 MAIN TR circuit breakers – **“PULLED”** (E)
6. DC MAIN BUS GND CONT circuit breaker - **"PULLED"** (E)

When Conditions Permit:

7. MAFFS Power Cables – **“REMOVED”** (E/LM)
8. MAFFS Battery Breaker – **“PULLED”** (E/LM)

## **WARNING**

Once the MAFFS unit power cables are disconnected from the aircraft, pulling the MAFFS battery circuit breaker will remove all power from the MAFFS unit including power required for an emergency dump. Pulling this circuit breaker is only recommended if you have already dropped and the MAFFS DC system is suspected of causing smoke or fire

9. MAIN TR Circuit Breakers – **“RESET”** (E)
10. DC MAIN BUS GND CONT circuit breaker – **"RESET"** (E)
11. Generators 1, 3, and 4 – **“ON”** (E)
12. Emergency Shutdown Checks – **“COMPLETE”** (E, LM)