

Propeller-Assisted Robust 3D Hopping Robot with Hierarchical Force Allocation

Chuhan Zhang^{1,2,3}, Hongbo Zhang¹, Yanlin Chen^{1,4}, Yunxi Tang^{1,4}, Yun-Hui Liu¹, Mingyi Liu^{2,3}, and Xiangyu Chu^{1,4}

Presenter: Chuhan Zhang - Johns Hopkins University, M.S.E. Robotics czhang.daniel@gmail.com ■ chuhandanielzhang.github.io

¹The Chinese University of Hong Kong ■ ²Guangdong Technion-Israel Institute of Technology ■ ³Technion-Israel Institute of Technology ■ ⁴Multiscale Medical Robotics Centre




SCAN: DEMO VIDEO
PAPER + ARXIV



2026 IEEE 22nd International Conference on Automation Science and Engineering (CASE)
17-21 AUGUST 2026
SHENYANG, CHINA
IEEE Robotics & Automation Society

1. Problem - hybrid dynamics create an authority gap



Stance
Ground reaction force exists only during a short contact interval.


Flight
No contact: attitude becomes underactuated.

Disturbance
Impacts and pushes inject attitude and horizontal momentum.

Control authority disappears exactly when attitude can keep drifting.

Design question: how should leg contact force and rotor thrust be coordinated across stance and flight?

2. First proof- stable on 30° grass



Propellers off
After asymmetric contact, attitude error grows. With no flight-phase actuator, the robot falls.


Propellers on
Differential thrust remains available through flight and restores attitude before the next landing.

What this establishes
Residual authority in stance.
Primary attitude authority in flight.
Faster recovery from uneven impacts.

Not primary lift: the rotors close the attitude-authority gap.

Propellers off: attitude diverges and the robot falls. **Propellers on:** it remains upright and keeps hopping.

3. Platform- hardware built for leg-first hopping




3-RSR parallel leg
Three RSR chains meet at one foot: fast 3-DoF omnidirectional placement, only **0.35 kg** moving mass.

Computational hub
Batteries and electronics near the hip: low center of mass, low inertia.

Y-layout tri-rotor
Continuous attitude authority; **10 N** per rotor, total **0.82 mg**: a hopper, not a drone.

3.75 kg total ■ 9.2% leg mass ■ 20 Nm / leg motor ■ 500 Hz control

4. Model- one rigid body, two actuator sets



Net wrench = leg contact + three rotors

$$\begin{bmatrix} \mathbf{F}_{net} \\ \boldsymbol{\tau}_{net} \end{bmatrix} = \begin{bmatrix} \mathbf{f}_c \\ \mathbf{r}_c \times \mathbf{f}_c \end{bmatrix} + \sum_{i=1}^3 \begin{bmatrix} \mathbf{d}_i \\ \mathbf{r}_i \times \mathbf{d}_i \end{bmatrix} t_i$$

Newton-Euler dynamics of the CoM

$$m\mathbf{a} = \mathbf{F}_{net} + m\mathbf{g}, \quad \dot{\boldsymbol{\omega}} = \mathbf{I}^{-1}(\mathbf{R}^\top \boldsymbol{\tau}_{net} - \boldsymbol{\omega} \times \mathbf{I}\boldsymbol{\omega})$$

Contact force $\mathbf{f}_c$ and thrusts $t_{1,2,3}$ produce the body wrench.


Symbols (values used in all experiments)

$\mathbf{f}_c$ ground reaction force (world)
 $\mathbf{r}_c, \mathbf{r}_i$ arms: CoM $\rightarrow$ contact, rotor i
 $t_i \in [0, 10]$ N thrust along $\mathbf{d}_i = \mathbf{R}\mathbf{e}_3$
 $\mathbf{F}_{net}, \boldsymbol{\tau}_{net}$ net force, moment

$m=3.75$ kg; $\mathbf{g}$ gravity; $\mathbf{I}$ inertia
 $\mathbf{R} \in \text{SO}(3)$ attitude; $\boldsymbol{\omega}$ body rate
 $\mathbf{J}$ leg Jacobian; $\tau_{max}=20$ Nm limit
 $\mu=0.4$ friction coefficient

$p_z, \dot{p}_z$ CoM height, velocity; $h_{des}=0.664$ m
 l leg length; $l_0=0.464$ m; Δ_{ld} threshold
 k_z, b_z, k_E vertical, k_v, k_r Raibert gains
 $\mathbf{K}_R, \mathbf{K}_\omega$ attitude PD gains

5. Onehop- event-driven authority handoff




Touchdown: $l \leq l_0 - \Delta_{ld}$
Leg absorbs impact; energy law drives the next apex.

Lift-off: $l \geq l_0$
Contact wrench vanishes; rotors primary for attitude.

Handoff
Events switch authority; no hardware or gain change.

Leg authority exists only in stance; rotor attitude authority is continuous through the full hop.

6. Control- leg-priority hierarchical force allocation



500 Hz architecture: commands + feedback $\rightarrow$ planner $\rightarrow$ two-stage allocator $\rightarrow$ leg torques + rotor thrusts.

A. Vertical energy hopping (stance)

$$E_{sys} = \frac{1}{2} m \dot{p}_z^2 + m g p_z, \quad E_{des} = m g h_{des}$$

$$f_{c,z}^{des} = \max(0, k_z(h_{des} - p_z) - b_z \dot{p}_z + k_E(E_{des} - E_{sys}))$$

Injects push-off energy, absorbs impact.

B. SO(3) attitude PD (both phases)

$$\mathbf{e}_R = \frac{1}{2} (\mathbf{R}_{des}^\top \mathbf{R} - \mathbf{R}^\top \mathbf{R}_{des})^\vee$$

$$\boldsymbol{\tau}_b^{des} = -\mathbf{K}_R \mathbf{e}_R + \mathbf{K}_\omega (\boldsymbol{\omega}^{des} - \boldsymbol{\omega})$$

Roll/pitch only; yaw left free. $\boldsymbol{\tau}^{des} = \mathbf{R} \boldsymbol{\tau}_b^{des}$.

C. Leg first- constrained least squares

$$\mathbf{f}_{c,xy}^{cmd} = \arg \min_{\mathbf{f}_{xy}} \|(\mathbf{r}_c \times \mathbf{f}_c)_{rp} - (\boldsymbol{\tau}_{res}^{cmd})_{rp}\|_2^2$$

s.t. $\|\mathbf{f}_{xy}\|_2 \leq \mu f_{c,z}^{des}, \quad \|\mathbf{J}^\top (-\mathbf{R}^\top \mathbf{f}_c)\|_\infty \leq \tau_{max}$
The leg realizes all it can under friction and torque limits.

D. Rotors take only the residual

$$\boldsymbol{\tau}_{res}^{cmd} = \boldsymbol{\tau}^{des} - \mathbf{r}_c \times \mathbf{f}_{c,xy}^{cmd}$$

$$\delta \mathbf{t}^{cmd} = \arg \min_{\delta \mathbf{t}} \|(\mathbf{M}_t \delta \mathbf{t})_{rp} - (\boldsymbol{\tau}_{res}^{cmd})_{rp}\|_2^2$$


s.t. thrust bounds; $\mathbf{t}^{cmd} = \frac{T_{base}}{3} \mathbf{1}_3 + \delta \mathbf{t}^{cmd}, T_{base} = 0.02$ mg.

E. Flight- rotors primary for attitude; Raibert foot placement

$$\mathbf{f}_c = 0; \quad \text{rotors track } (\boldsymbol{\tau}^{des})_{rp}; \quad \text{leg tracks } \mathbf{r}_{ld,xy}^{des} = k_v \mathbf{v}_{xy} - k_r \mathbf{v}_{xy}^{des}$$


By construction the rotors can only add to - never replace - the leg's contact action.

7. Validation- indoor tracking




17 hops - 1.6 and 0.94 m/s commands - bounded attitude error through every impact.

8. Validation- grass to wood



23 hops - same controller - no terrain model - no gain retuning.

9. Validation- push recovery



Rotor-arm hit: attitude recovers in 1-2 hops. Main-body hit: lateral velocity recovers in three hops.