VCC 2020 reference design & its application in Mandarin VC

Sian-Yi Chen

Advisor: Tay-Jyi Lin and Chingwei Yeh


Outline

Action item

● 將 ASR 與 TTS 英文轉換模型更換成中文轉換模型

Status report

- Before :
 - VCC2020 baseline 為英文轉換模型,使用的皆為 ESPnet (End-to-end speech processing toolkit) 所提供的預訓練模型,如今目標為更換為中文轉換模型,ESPnet 提供各種語言所訓練的預訓練模型,因此 ASR、TTS model 我打算使用與 baseline 相同架構 (Transformer) 不同語料的預訓練模型做替換
- Now:
 - 語料:使用碩一 IASoC 錄製的語料,明祥的語料作為 source、竣尹的語料作為 target
 - 替換步驟:
 - 1. 使用 ASR model 辨識,輸出文字 (**進行中**)
 - 2. 使用 target 語料微調 TTS 模型,並接續 ASR model 辨識結果完成轉換,輸出 mel-filterbank sequence
 - 3. 訓練 vocoder 並合成語音
- After:
 - 在使用 ASR 中文模型辨識時,在特徵提取的部分出錯
 - 解決方案:原先急著要輸出成果,因此除了將 ASR model 換成中文模型之外,還將語料換成中文
 - 使用原語料 (英文),驗證成功將英文模型替換成中文模型再做更換 input 的動作 (可能輸入格式不正確、也可能替換過程有部分檔案缺失)




■附錄

1. The VCC 2020 Rules

- Dataset relationship
- Evaluation methodology
- 2. How Baseline (ASR+TTS) Work
 - Transfer learning and fine-tuning
 - Training and conversion process
- 3. Strategy to win
 - Why change vocoder from non-autoregressive to autoregressive
- 4. Its application in Mandarin VC
 - ASR and TTS Mandarin pretraining model detail
 - Replacement method


The VCC 2020 Rules




Same language conversion in task1



Conversion system




Total: 16 systems



Evaluation methodology


Transfer learning and fine-tuning

- The more dataset, the higher accuracy, but the longer training time.
- 70 sentences corpus approximately 5 minutes is not enough to train a good model.
- A pre-trained model is a model created by some one else to solve a similar problem.
- Advantages of the pre-training model can save a lot of computing time and resources, and can avoid some training risks.




How Baseline Works

- Task1: voice conversion within the same language.
- A naive approach for VC is a cascade of an automatic speech recognition (ASR) model and a text-to-speech (TTS) model, and both model are using pre-training model.
- ASR models are usually trained with a multi-speaker dataset, thus speaker-independent in nature.
- TTS model output was the mel filterbank sequence extracted from the waveform and was also the input of the vocoder.



Pre-training model	Language	Dataset	speakers	Hours
ASR	English	LibriSpeech	Over 2000	960
TTS	English	LibriTTS	Over 2000	250






Strategy to win

- Baseline adopted a non-AR neural vocoder (Parallel WaveGAN (PWG)) for fast generation.
- Change vocoder from non-autoregressive to autoregressive, e.g., change from Parallel WaveGAN (PWG) to WaveNet.
- Voice conversion = VC model + Vocoder

parallel"

The champion in the VCC2020 use a AR neural vocoder (WaveNet).



previously generated output"

<u>Auto-regressive decoding vs non -autoregressive decoding | by Mithilesh kumar singh | Medium</u>

Its application in Mandarin VC

• The AST and TTS model used in the Baseline are provided by ESPnet.

Lang.	ASR pre-training model	Dataset	Dataset summary	Speake r	Hours	Test set corr.	
Mandarin	Conformer + SpecAugment	aidatatang_200zh	speech data	600	200	95.2	similar
		AISHELL	recording	400	178	95.0	
	Conformer	aidatatang_200zh	speech data	600	200	94.1	
	Transformer	aidatatang_200zh	speech data	600	200	93.6	J
		AISHELL	recording	400	178	93.4	
		AISHELL2	recording	1991	1000	91.8	
		HKUST	telephone speech	無標示	約200	79.1	

Lang.	TTS pre-training model	Dataset	Speaker	Hours	Sample sentence	Audio
Mandarin	FastSpeech	CSMSC 女聲	1	12	這場抗議活動究竟是如何發展演變	
Mandann	Transformer	CSINISC 文賞	'	12	的,又究竟是誰傷害了誰	

TTS samples

TTS pre-training model	Sample sentence	Audio
FastSpeech	在雨中,張明寶悔恨交加寫了一份懺悔書	
	今天快遞員拿著一個快遞在辦公室喊·秦 王是哪個有他快遞	
	李東王表示自己當時在法庭上發表了一次 獨特的供訴意見	Z 3002
	接下來,紅娘要求記者交費,記者表示不 知表姊身分證號碼	
	小明搖搖頭說,不是,我只是美女看多了, 想換個口味而已	
Transformer	在雨中,張明寶悔恨交加寫了一份懺悔書	
	今天快遞員拿著一個快遞在辦公室喊·秦 王是哪個有他快遞	
	李東王表示自己當時在法庭上發表了一次 獨特的供訴意見	
	接下來,紅娘要求記者交費,記者表示不 知表姊身分證號碼	
	小明搖搖頭說,不是,我只是美女看多了, 想換個口味而已	