

Práctica #13. Secuencias en Oracle

1.-

```
CREATE SEQUENCE dept_deptid_seq
INCREMENT BY 10
START WITH 300
MAXVALUE 9999
NOCACHE
NOCYCLE;
```

[2026-03-02 11:25:12] completed in 19 ms
[2026-03-02 11:25:12] HR> CREATE SEQUENCE dept_deptid_seq
INCREMENT BY 10
START WITH 300
MAXVALUE 9999
NOCACHE
NOCYCLE
[2026-03-02 11:25:12] completed in 74 ms

2.-

```
INSERT INTO departments(department_id, department_name,
                        location_id)
VALUES ( DEPARTMENT_ID dept_deptid_seq.NEXTVAL, DEPARTMENT_NAME 'Support', LOCATION_ID 2500);
```

Output HR.DEPARTMENTS
[2026-03-02 11:30:54] 2/ rows retrieved starting from 1 in 684 ms (execution: 55 ms, retrieval: 629 ms)
[2026-03-02 11:31:38] HR> INSERT INTO departments(department_id, department_name, location_id)
VALUES (dept_deptid_seq.NEXTVAL, 'Support', 2500)
[2026-03-02 11:31:38] 1 row affected in 23 ms
[2026-03-02 11:31:42] HR> INSERT INTO departments(department_id, department_name, location_id)
VALUES (dept_deptid_seq.NEXTVAL, 'Support', 2500)

3.-

```
SELECT * FROM DEPARTMENTS
WHERE department_name = 'Support';
```

Output HR.DEPARTMENTS x
DEPARTMENT_ID DEPARTMENT_NAME MANAGER_ID LOCATION_ID
1 300 Support <null> 2500

4.-

The screenshot shows the SQL Developer interface. The SQL Editor contains the query: `SELECT dept_deptid_seq.currval FROM DUAL;`. The left sidebar shows the database structure with 'hr' selected. The 'console_2' session is active, showing a duration of 529 ms. The 'DEPT50' table is highlighted. The right sidebar shows the 'Output' tab with 'currval:INTEGER' selected. Below the output, a table displays the result: a single row with the value 310.

```
SELECT dept_deptid_seq.currval
FROM DUAL;
```

CURRVAL
310

5.-

The screenshot shows the SQL Developer interface. The SQL Editor contains the command: `ALTER SEQUENCE dept_deptid_seq INCREMENT BY 20 MAXVALUE 9999999 NOCACHE NOCYCLE;`. The left sidebar shows the database structure with 'hr' selected. The 'console_2' session is active, showing a duration of 94 ms. The 'DEPT50' table is highlighted. The right sidebar shows the 'Session' tab with 'currval:INTEGER' selected. The 'Output' tab shows the execution log: `[2026-03-02 11:40:40] completed in 47 ms` and `[2026-03-02 11:41:59] HR> ALTER SEQUENCE dept_deptid_seq INCREMENT BY 20 MAXVALUE 9999999 NOCACHE NOCYCLE [2026-03-02 11:41:59] completed in 11 ms`.

```
ALTER SEQUENCE dept_deptid_seq
INCREMENT BY 20
MAXVALUE 9999999
NOCACHE
NOCYCLE;
```

6.-

The screenshot shows the SQL Developer interface. The SQL Editor contains the command: `DROP SEQUENCE dept_deptid_seq;`. The left sidebar shows the database structure with 'hr' selected. The 'console_2' session is active, showing a duration of 147 ms. The 'DEPT50' table is highlighted. The right sidebar shows the 'Session' tab with 'currval:INTEGER' selected. The 'Output' tab shows the execution log: `[2026-03-02 11:41:59] completed in 11 ms`, `[2026-03-02 11:46:10] HR> DROP SEQUENCE dept_deptid_seq`, and `[2026-03-02 11:46:10] completed in 88 ms`.

```
DROP SEQUENCE dept_deptid_seq;
```