日進電線股份有限公司 NIZING ELECTRIC CO., LTD.

GREEN WIRE FOR OUR EARTH

新北市新莊區三泰路11之15號 11-15 Santai Rd, Hsinchuang, New Taipei City, Taiwan, R.O.C.

Tel: (02)29016164. 29087519 Fax: 886-2-29050644 E-mail: kelven33033@nizing.com.tw

WIRE/CABLE SPECIFICATION (線材規格書)

Sta	ndard	WIRE/CABLE SPECIFICA 不鏽鋼感液線 PVC 16A	X		' 105°C 600V	
Sundard		Item (項目)	Unit (單位)	Specification (規格值)		Tolerance (容差)
General Specification (線種規格)			AWG	16	26	
No. of Inner Cords (芯線數)			PCs	2	2	
芯線結構	Conductor 導體	Material (材質)		Bare Copper	Stainless steel	
		Structure(結構)	No.×mm	26 / 0.254	1 / 0.4	
		Stranded Diameter(絞線外徑)	mm	1.50	0.40	±0.05
	Insulation 絕緣	Material (材質)		PVC		
		Average Thickness (平均厚度)	mm	0.79		±0.05
		Color (顏色)		Black		
				White		
	Braid 編織	Material (材質)			Polyester Gold 0.2	
		Color (顏色)				
		Wall Thickness (壁厚)	mm			±0.02
	Inner wire Diameter(芯線完成外徑)		mm	3.1	0.8	±0.10
總集合	Inner w	ires stranding diameter (總絞合外徑)	mm	5.65		±0.20
Electric Characters 電氣特性		Rated Temperature (額定溫度)	°C	105		
		Rated Voltage(額定電壓)	V-AC	600		
		Resistance of Insulation (水中常溫絕緣阻抗,20℃)	MΩ/km	50		
		Withstand Voltage Spark (火花試驗)	KV/Sec	2		
Marking			N/A			-
Certification		N/A				



Specification Documented By *Engineering Department* of Nizing Electric Co., LTD.


日進電線股份有限公司 NIZING ELECTRIC CO., LTD.

GREEN WIRE FOR OUR EARTH

新北市新莊區三泰路11之15號 11-15 Santai Rd, Hsinchuang, New Taipei City, Taiwan, R.O.C. Tel: (02)29016164. 29087519 Fax: 886-2-29050644 E-mail: kelven33033@nizing.com.tw

Standard

Structural Configuration (結構圖):



Bare Copper Wire (裸銅導體)

Product sectional view (產品剖面圖):

